

SAP → API Connectivity Troubleshooting

Resolving `NIECONN_REFUSED(-10)` when connecting to `digitisationapi.jpmpgroup.co.in:443`

Date: 06 Jul 2026 **For:** SAP BASIS / Network team **Ref:** Template sync pull feed

1 Current verified status (checked 06 Jul 2026)

✓ **The API is up and reachable from the public internet.** Verified today: `digitisationapi.jpmpgroup.co.in` resolves publicly to `150.241.244.161` ; TLS handshake on **443** succeeds; `GET /health` returns **HTTP 200** — “**server is running and ok**”.

Why the error is not an API-side block: `NIECONN_REFUSED(-10)` is a **TCP-level** refusal — the connection is rejected before HTTPS, certificates, or the `x-api-key` are ever evaluated. The API has **no IP whitelist**: any client that reaches it receives an HTTP response (e.g. `401` for a wrong key). A refused TCP connection therefore means the request is being stopped *inside the network path between the SAP server and the API* — by definition, a refused connection never reaches the application at all.

2 Two tests to run on the SAP server (OS shell, not SAPGUI)

```
nslookup digitisationapi.jpmpgroup.co.in

curl -v https://digitisationapi.jpmpgroup.co.in/health
```

Please share both outputs. The result identifies the root cause directly:

3 Diagnosis table — result → cause → fix

Test result on SAP server	Root cause	Fix (network / BASIS)
<code>nslookup</code> returns anything other than <code>150.241.244.161</code> (e.g. a private <code>10.x</code> / <code>192.168.x</code> address)	Split / internal DNS — inside the plant network the domain points to an internal host that does not serve port 443	Correct the internal DNS record to <code>150.241.244.161</code> , or add a hosts entry on the SAP server: <code>150.241.244.161 digitisationapi.jpmpgroup.co.in</code>
<code>nslookup</code> is correct, but <code>curl</code> cannot connect	Egress firewall / proxy-only policy — outbound 443 from the SAP host is blocked for direct connections	Allow outbound TCP 443 from the SAP server to <code>150.241.244.161</code> , or configure the corporate web proxy in the SM59 destination (Proxy host / port / user). The SAP error text “ Direct connect ... failed” indicates the destination currently bypasses any proxy.
<code>curl</code> works (returns “server is running and ok”) but SAP still fails	SM59 destination configuration	SM59 → RFC destination type G : Target host <code>digitisationapi.jpmpgroup.co.in</code> , Service No. <code>443</code> , SSL Active , certificate list containing the imported CA, path prefix <code>/api/v1/sync/templates</code> . Re-run “Connection Test”.

4 Final verification (run from the SAP server once TCP connects)

```
curl "https://digitisationapi.jpmpgroup.co.in/api/v1/sync/templates/pending-count" \
-H "x-api-key: <the sync API key already shared with your team>"
```

Expected: `HTTP 200` with `{"success":true, ...}` . When this returns 200 from the SAP host, connectivity is fully resolved — only standard SM59/ABAP consumption remains.

Endpoint summary for the integration: pull feed `GET /api/v1/sync/templates (+ /pending-count )`, authenticated by the `x-api-key` header. HTTPS on port 443 only; no VPN or IP registration is required on the API side.