


NFA -> DFA Example



NFA to DFA. Remark


- An NFA may be in many states at any time
- How many different states ?
- If there are N states, the NFA must be in some subset of those N states
- How many non-empty subsets are there?
 - $2^N - 1 =$ finitely many, but exponentially many



Implementation

- A DFA can be implemented by a 2D table T
 - One dimension is “states”
 - Other dimension is “input symbols”
 - For every transition $S_i \xrightarrow{a} S_k$ define $T[i,a] = k$
- DFA “execution”
 - If in state S_i and input a , read $T[i,a] = k$ and skip to state S_k
 - Very efficient

Table Implementation of a DFA




	0	1
S	T	U
T	T	U
U	T	U

Implementation (Cont.)

- NFA \rightarrow DFA conversion is at the heart of tools such as lex, flex or jflex
- But, DFAs can be huge
- In practice, lex-like tools trade off speed for space in the choice of NFA and DFA representations



Lexical Analyzer Generator - Lex



Structure of Lex programs

declarations

%%

translation rules

%%

auxiliary functions



Pattern {Action}

Example

```
%{
/* definitions of manifest constants
LT, LE, EQ, NE, GT, GE,
IF, THEN, ELSE, ID, NUMBER, RELOP */
%}

/* regular definitions
delim      [ \t\n]
ws         {delim}+
letter[A-Za-z]
digit [0-9]
id         {letter}({letter}|{digit})*
number     {digit}+(\.{digit}+)?(E[+-]?{digit}+)?

%%
{ws} { /* no action and no return */}
if      {return(IF);}
then {return(THEN);}
else {return(ELSE);}
{id} {yylval = (int) installID(); return(ID); }
{number} {yylval = (int) installNum(); return(NUMBER);}
```

```
int installID() { /* funtion to install the
lexeme, whose first character is
pointed to by yytext, and whose
length is yyleng, into the symbol
table and return a pointer thereto
*/
}
```

```
int installNum() { /* similar to
installID, but puts numerical
constants into a separate table */
}
```



Conclusion

- Words of a language can be specified using regular expressions
- NFA and DFA can act as acceptors
- Regular expressions can be converted to NFA
- NFA can be converted to DFA
- Automated tool lex can be used to generate lexical analyser for a language





NPTEL ONLINE CERTIFICATION COURSES

**Thank
you!**

Compiler Design

Syntax Analysis

Santanu Chattopadhyay


Electronics and Electrical Communication Engineering



- ☐ Role of Parsers
- ☐ Context Free Grammars
- ☐ Top-Down Parsing
- ☐ Bottom-Up Parsing
- ☐ Parser Generators
- ☐ Conclusion



The role of parser



Grammar

- A 4-tuple $G = \langle V_N, V_T, P, S \rangle$ of a language $L(G)$
 - V_N is a set of nonterminal symbols used to write the grammar
 - V_T is the set of terminals (set of words in the language $L(G)$)
 - P is a set of production rules
 - S is a special symbol in V_N , called the start symbol of the grammar
- Strings in language $L(G)$ are those derived from S by applying the production rules from P
- Examples:

$E \rightarrow E + T \mid T$
 $T \rightarrow T * F \mid F$
 $F \rightarrow (E) \mid \text{id}$

$E \rightarrow TE'$
 $E' \rightarrow +TE' \mid \epsilon$
 $T \rightarrow FT'$
 $T' \rightarrow *FT' \mid \epsilon$
 $F \rightarrow (E) \mid \text{id}$

