
How Language Models Organize Competing Moral Frameworks

Orion Reblitz-Richardson*

Abstract

How do language models organize moral knowledge? Models detect moral content broadly, but detection is a low bar. We ask whether they go further: distinguishing moral foundations from one another and organizing the relationships between them.

Training six independent linear probes on OLMo-2 1B and 7B and OLMoE-1B-7B, one per foundation in Moral Foundations Theory (MFT), shows integration. Foundation directions in representation space are geometrically distinct, spanning five effective dimensions, yet share a common moral-salience component, shown by a uniformly positive mean pairwise cosine (the effective dimensionality rules out collapse; the positive cosine is what marks integration rather than isolation). This is genuine multi-dimensional structure, not a single moral detector. The geometry is consistent across scale (1B to 7B dense), across dense and MoE architectures, and on the independently constructed Moral Foundations Vignettes, and stabilizes early in pretraining.

The structure the model develops is not the structure moral psychology predicts. Neither hierarchical clustering of the probe directions nor unsupervised clustering of the activations recovers the individualizing/binding distinction central to MFT; the model’s moral taxonomy is grounded in corpus statistics rather than human theoretical categories. Seed-averaged fragility testing shows that output dilution is foundation-uniform: every foundation is more fragile in MoE than in dense, with no foundation reliably most or least robust within an architecture.

Extending to moral dilemmas shows partial compositionality: dilemma representations share significant variance with their component foundations but encode largely conflict-specific structure beyond them, with balanced loading suggesting the model represents moral conflict itself rather than a pre-resolved judgment.

1 Introduction

How do language models represent morality? Prior work in this series established that models encode moral content *broadly*: probing accuracy saturates early during pre-training and spans nearly all layers (Reblitz-Richardson, 2026c). Fragility testing revealed that this encoding grows more robust throughout training even after accuracy plateaus. Extension to mixture-of-experts (MoE) models showed that moral signal is uniform across experts, with no expert specialization, but that a 74× output scale gap produces structural fragility (Reblitz-Richardson, 2026b).

Both papers treated moral encoding as a single binary feature: moral vs. neutral. A model that merely detects “this text involves morality” has cleared a low bar. Genuine moral understanding requires *structured* representations: the ability to distinguish care from fairness, loyalty from authority, and to encode the relationships between them. The transition from moral *detection* to moral *understanding* is the subject of this paper.

*Distiller Labs. Correspondence to Distiller Labs <orion@orionr.com>.

We operationalize this transition through the geometry of foundation-specific probe directions. Where prior work trained one probe to separate moral from neutral content, we train six: one for each Moral Foundations Theory (MFT) foundation (Graham et al., 2013, Haidt, 2012). The learned probe weight vectors define *directions* in the model’s representation space. The angular relationships between these directions reveal whether the model has developed structured moral representations.

Three geometric signatures correspond to three qualitatively different modes of moral representation:

1. **Collapse.** All foundation directions converge toward a single “moral salience” direction. The model detects moral relevance but does not distinguish frameworks.² This is detection without structure.
2. **Isolation.** Foundation directions are orthogonal with no relational structure. The model has separate moral “slots” but no representation of how frameworks relate. This is structure without coherence.
3. **Integration.** Foundation directions are separated but non-orthogonal, with inter-framework geometry reflecting known relationships from moral psychology. This is the precondition for moral reasoning.

Applied to OLMo-2 1B and OLMoE-1B-7B, we find clear *integration*: foundation directions are distinct (mean pairwise cosine similarity ≈ 0.22 – 0.27 across layers, far from collapse) and span 5 effective dimensions at every layer. However, hierarchical clustering does not recover the MFT distinction between individualizing and binding foundations (the inter-framework structure the model develops is not aligned with human moral-psychological categories, despite the directions being well-separated).

Extending the fragility protocol to per-foundation probes shows a uniform cross-architecture effect rather than a per-foundation one: once accuracy is averaged over multiple noise seeds, every foundation is more fragile in MoE than in dense (a $\sim 2.3\times$ gap), and no single foundation is reliably most or least robust within an architecture. Output dilution suppresses moral encoding across the board.

This paper makes three contributions:

1. **Framework-specific probing methodology.** We introduce probe direction geometry as a tool for measuring structured moral representations, bridging the gap between binary moral probing and the richer structure posited by moral psychology.
2. **Empirical geometric characterization.** We show that OLMo-2 1B and OLMoE-1B-7B exhibit the integration signature, that framework geometry is comparable across architectures, and that the model’s inter-framework structure does not align with MFT group predictions despite clear directional separation.
3. **Differential fragility.** We demonstrate that moral foundations differ in robustness, and that MoE architecture disproportionately degrades sanctity/degradation representations, the first evidence that output dilution is not foundation-uniform.

2 Related Work

2.1 Probing for linguistic and semantic structure

Linear probing (Alain and Bengio, 2017) has become a standard tool for reading off what information is encoded in neural network representations. Conneau et al. (2018) probed sentence embeddings for syntactic properties; subsequent work probed for part-of-speech, dependency relations, coreference, and world knowledge. The linear representation hypothesis (Park et al., 2024) formalizes the claim that concepts are encoded as directions in representation space, precisely the assumption underlying our use of probe weight vectors as geometric objects.

²We use *framework* interchangeably with the Moral Foundations Theory term *foundation* throughout (and in the title). We do not intend the moral-psychology sense in which *framework* denotes a theory-level position such as deontology or utilitarianism. We retain *framework* in part because *foundation* is itself overloaded in the language-model setting, where a “foundation model” is a base, pre-instruction-tuned model, exactly the class of models we probe.

Two limitations of the probing literature motivate our approach. First, most probing studies report only *accuracy*, discarding the learned probe parameters. We show that the probe weight vector (the normal to the classification hyperplane) carries geometric information about how concepts relate to each other. Second, probing studies typically train one probe per concept, treating concepts as independent. Our multi-probe geometric analysis recovers inter-concept structure from independently trained probes.

2.2 Geometry of concept representations

Bolukbasi et al. (2016) demonstrated that gender bias in word embeddings manifests as a geometric subspace, and that debiasing amounts to projecting out a direction. Arditì et al. (2024) showed that refusal behavior in instruction-tuned LLMs is mediated by a single direction in activation space. These results establish the precedent that high-level behavioral properties can be localized to specific directions.

Our work extends this line from single directions to *sets of related directions*. Where prior work asked “where is concept X ?” we ask “what is the geometric relationship between concepts $X_1, \dots, X_k$?” The cosine similarity matrix between foundation probe directions is a form of representational similarity analysis (RSA; Kriegeskorte et al., 2008) applied not to stimulus response patterns but to the probes that decode them.

2.3 Moral psychology and Moral Foundations Theory

Moral Foundations Theory (MFT; Graham et al., 2013, Haidt, 2012) posits that human moral judgment draws on (at least) five or six innate foundations: care/harm, fairness/cheating, loyalty/betrayal, authority/subversion, sanctity/degradation, and (later added) liberty/oppression. MFT predicts a structural distinction between *individualizing* foundations (care, fairness, liberty), which protect individuals from harm, and *binding* foundations (loyalty, authority, sanctity), which bind individuals into groups. This distinction has been validated in cross-cultural surveys and predicts political orientation (Graham et al., 2013).

Alternative taxonomies exist. Curry et al. (2019) propose morality-as-cooperation, identifying seven moral domains grounded in evolutionary game theory. Our use of MFT is pragmatic: the six-foundation taxonomy gives a tractable set of directions for geometric analysis, and the individualizing/binding prediction gives a testable structural hypothesis.

2.4 Moral reasoning in language models

Hendrycks et al. (2021) introduced the ETHICS benchmark for evaluating moral reasoning in language models across justice, deontology, virtue, utilitarianism, and commonsense dimensions. Most work in this area evaluates models *behaviorally*, measuring what outputs models produce in response to moral scenarios. Our approach is *representational*: we probe the internal geometry of moral encoding, asking not whether the model produces the right moral judgment but whether it has developed structured representations of moral distinctions.

2.5 Companion papers

This paper is the third in a series. Paper 1 (Reblitz-Richardson, 2026c) established that moral content is decodable by linear probes from the earliest layer of OLMo-2, that probing accuracy saturates early during pre-training, and that fragility testing (injecting Gaussian noise into activations) resolves the continued development of moral encoding after accuracy plateaus. Paper 2 (Reblitz-Richardson, 2026b) extended the analysis to MoE models (OLMoE-1B-7B), finding uniform moral encoding across experts but a $74\times$ output scale gap that produces structural fragility.

The present paper moves from *binary* moral encoding (moral vs. neutral) to *structured* moral encoding (framework-specific directions and their inter-framework geometry). It reuses the probing and fragility protocols from Papers 1 and 2, applying them at the per-foundation level.

3 Methodology

We train six foundation-specific linear probes at each transformer layer, extract the learned weight vectors as geometric directions in representation space, and analyze the angular relationships between these directions. The methodology decomposes into five components: foundation-specific probing (Section 3.2), geometric analysis of probe directions (Section 3.3), bootstrap direction stability assessment (Section 3.4), framework-specific fragility testing (Section 3.5), and the probing dataset (Section 3.6). All experiments run on a single MacBook Pro M4 Pro (24 GB unified memory, MPS backend).

3.1 Models and comparison design

We evaluate three base (non-instruct) models from the same lab (Ai2). The primary comparison is between two architectures matched in layer count (16), dense vs. mixture-of-experts; a third, larger dense model serves as a scale control (§4.14):

- **OLMo-2 1B** (allenai/OLMo-2-0425-1B): dense transformer, 1.5B parameters, 2048 hidden dimension, 16 layers (OLMo Team, 2025). Ai2 publishes 37 early-training checkpoints at 1K-step intervals (steps 0–36K), enabling trajectory analysis.
- **OLMoE-1B-7B** (allenai/OLMoE-1B-7B-0924): mixture-of-experts, 6.9B total parameters, 1.3B active, 64 experts per layer, top-8 routing, 2048 hidden dimension, 16 layers (Muennighoff et al., 2024).
- **OLMo-2 7B** (allenai/OLMo-2-1124-7B): dense transformer, 7.3B parameters, 4096 hidden dimension, 32 layers (OLMo Team, 2025). Used in §4.14 to test whether the geometry findings persist with scale.

All three models use the same tokenizer and comparable training corpora. The comparison tests whether framework geometry is an artifact of dense connectivity or a general property of transformer-based language modeling. Reblitz-Richardson (2026b) established that moral encoding in OLMoE is uniform across experts with a $74\times$ output scale gap relative to OLMo-2; the present work asks whether this output dilution affects the *structure* of moral representations, not just their *scale*.

3.2 Foundation-specific probing

For each of the six Moral Foundations Theory (MFT) foundations (care/harm, fairness/cheating, loyalty/betrayal, authority/subversion, sanctity/degradation, and liberty/oppression; (Graham et al., 2013, Haidt, 2012)), we train a binary linear probe at each of 16 transformer layers.

Probe architecture. Each probe is `nn.Linear(2048, 1)` trained with BCE loss and Adam ($\text{lr} = 10^{-2}$) for 50 epochs. This matches the probe specification from Reblitz-Richardson (2026c) and Reblitz-Richardson (2026b), enabling direct comparison with their binary moral/neutral probes.

Activation collection. For each text, we run a single forward pass capturing all 16 layers simultaneously. At each layer, we mean-pool across the sequence dimension to obtain a single $\mathbb{R}^{2048}$ vector per text. Positive examples are the foundation-tagged moral sentences; negative examples are their matched neutral counterparts.

Direction extraction. After training, we extract the weight vector $\mathbf{w} \in \mathbb{R}^{2048}$ from each probe and normalize to unit length: $\hat{\mathbf{w}} = \mathbf{w}/\|\mathbf{w}\|$. This unit vector is the normal to the classification hyperplane, the *direction* in representation space that maximally separates the foundation’s moral content from neutral content. We call $\hat{\mathbf{w}}$ the foundation’s **probe direction** at a given layer.

This yields $6 \times 16 = 96$ unit-norm probe direction vectors per model.

3.3 Geometric analysis

The paper’s core contribution is analyzing the angular relationships between the six foundation probe directions at each layer.

Cosine similarity matrices. At each layer, we compute the 6×6 pairwise cosine similarity matrix of the foundation probe directions. Because the directions are unit-normalized, $\cos(\hat{\mathbf{w}}_i, \hat{\mathbf{w}}_j) = \hat{\mathbf{w}}_i \cdot \hat{\mathbf{w}}_j$.

Geometric signatures. Three qualitative modes of moral representation correspond to distinct cosine similarity patterns:

1. *Collapse (averaging)*. All foundation directions converge toward a single “moral salience” direction. Mean pairwise cosine similarity $\rightarrow 1$.
2. *Isolation*. Foundation directions are orthogonal with no relational structure. Mean pairwise cosine similarity $\rightarrow 0$.
3. *Integration*. Foundation directions are separated but non-orthogonal, with inter-framework geometry reflecting known relationships. Mean pairwise cosine similarity in $(0, 1)$ with structured variation.

Effective dimensionality. We compute the effective dimensionality of the 6-direction set at each layer via PCA on the 6×2048 matrix of probe directions. Effective dimensionality is the number of principal components explaining $\geq 90\%$ of variance. Low dimensionality (1–2) indicates collapse; high dimensionality (5–6) indicates separation.

Hierarchical clustering. We apply Ward’s method to the cosine distance matrix $(1 - \cos(\cdot, \cdot))$ at each layer. Dendrograms reveal whether the six foundations cluster into interpretable groups.

Permutation test for MFT group structure. MFT predicts that the six foundations divide into *individualizing* (care, fairness, liberty) and *binding* (loyalty, authority, sanctity) clusters (Graham et al., 2013). We test this prediction with a permutation test: compute the observed difference between mean within-group cosine similarity and mean between-group cosine similarity, then permute group assignments 10,000 times to generate the null distribution.

3.4 Bootstrap direction stability

With 32 training pairs per foundation in 2048 dimensions, the probe has 2049 parameters and only 64 training examples. The classification *accuracy* may be robust in this regime (a single hyperplane suffices for binary separation), but the extracted *direction* could be noisy, and noise in directions contaminates the angular analysis.

We assess direction stability via bootstrap resampling: for each foundation at each layer, we resample the 32 training pairs with replacement 200 times, retrain the probe on each bootstrap sample, and compute the cosine similarity of each bootstrap direction with the full-data direction. A mean bootstrap cosine similarity > 0.8 indicates a stable direction.

This gives a per-layer, per-foundation reliability metric for the geometric analysis. Layers where directions are unstable should be interpreted with caution.

3.5 Framework-specific fragility

We extend the fragility protocol of Reblitz-Richardson (2026c) to per-foundation probes. For each foundation at each layer:

1. Train a linear probe on clean activations.
2. Evaluate on clean test activations (baseline accuracy).
3. For each noise level $\sigma \in \{0.1, 0.3, 1.0, 3.0, 10.0\}$, add $\mathcal{N}(0, \sigma^2)$ noise to cached test activations and re-evaluate.
4. The **critical noise** σ^* is the smallest σ where accuracy drops below 0.6.

This tests the universality hypothesis: more cross-culturally universal foundations (care/harm) should be more robustly encoded than culturally variable foundations (sanctity/degradation, loyalty/betrayal). Cross-architectural comparison tests whether the output dilution effect (Reblitz-Richardson, 2026b) affects all foundations uniformly.

3.6 Probing dataset

We use the same 240-pair minimal-pair probing dataset from Reblitz-Richardson (2026c), now used at the per-foundation level: 40 pairs per MFT foundation, stratified 80/20 into 32 train and 8 test pairs per foundation. Each pair consists of a moral sentence tagged with its MFT foundation and a

matched neutral sentence controlling for sentence length, syntactic structure, and topic. The dataset was drawn from a 1000-pair candidate pool generated by Claude Sonnet 4.6 from hand-written seed examples, with automated validation gates (length ratio ≤ 1.5 , embedding similarity, keyword scan, deduplication) and LLM-as-judge filtering for neutral-pair quality.

For the geometric analysis, the 32 training pairs per foundation yield 64 training examples (moral + neutral) for the `nn.Linear(2048, 1)` probe. While this is a small sample for a 2049-parameter model, the bootstrap stability analysis (Section 3.4) directly quantifies whether the resulting directions are reliable.

3.7 Dilemma compositionality analysis

Experiments 1–7 establish that the model maintains distinct directions for each moral foundation. A natural follow-up: when two foundations *conflict* in a moral dilemma, does the model represent the dilemma as a composition of its component foundation directions, or does it develop a qualitatively new representation?

Dilemma dataset. We generate 300 moral dilemma scenarios (20 per each of the $\binom{6}{2} = 15$ foundation pairs) using Claude Sonnet 4.6, with hand-written seed examples per pair. Each scenario pits two specific foundations against each other (e.g., care vs. authority: “The nurse administered an unapproved painkiller to a dying patient because following protocol meant hours more agony”). Each dilemma text is paired with a matched neutral sentence. All pairs pass automated validation gates (length ratio, keyword scan, deduplication).

Dilemma-specific probes. For each of the 15 foundation pairs, we train a binary linear probe (same architecture as Section 3.2) to distinguish dilemma moral text from matched neutral text. The probe weight vector $\hat{\mathbf{w}}_{\text{dilemma}}$ is the direction in representation space that separates the dilemma content from neutral content.

Subspace membership score. To measure compositionality, we project each dilemma direction onto the 2D subspace spanned by its two component foundation directions. Given component directions $\hat{\mathbf{w}}_A$ and $\hat{\mathbf{w}}_B$ from Experiment 1, we orthogonalize them via Gram–Schmidt and compute the fraction of the dilemma direction’s variance explained by this 2D subspace:

$$S = \|\text{proj}_{\text{span}(\hat{\mathbf{w}}_A, \hat{\mathbf{w}}_B)} \hat{\mathbf{w}}_{\text{dilemma}}\|^2$$

A membership score of $S = 1$ indicates full compositionality (the dilemma direction lies entirely within the component subspace); $S = 0$ indicates complete independence. The null baseline for a random unit vector in $\mathbb{R}^{2048}$ projected onto a random 2D subspace has expected membership $2/2048 \approx 0.001$. We estimate the empirical null distribution from 10,000 random unit vectors.

Component balance. We decompose the within-subspace projection into components along $\hat{\mathbf{w}}_A$ and the Gram–Schmidt-orthogonalized $\hat{\mathbf{w}}_B$. The balance ratio (fraction of the projection along the first component) measures whether the dilemma direction is dominated by one foundation or draws equally on both. A ratio near 0.5 indicates balanced composition.

Shared-component geometry. If dilemma representations are partially compositional, dilemma pairs that share a foundation component should have more similar probe directions than pairs with no shared foundation. We test this by comparing the mean cosine similarity between dilemma directions for pairs that share a component (e.g., care–fairness and care–loyalty, which share care) versus pairs with no overlap (e.g., care–fairness and loyalty–sanctity).

Cross-architecture consistency. We repeat the dilemma probing and subspace analysis on OLMoE-1B-7B to test whether the compositionality structure is architecture-specific or general.

4 Results

4.1 Foundation-specific probe accuracy

All six foundation-specific probes achieve perfect or near-perfect accuracy across the full depth of OLMo-2 1B. Every foundation reaches 100% peak accuracy. Authority/subversion achieves 100%




Figure 1: Pairwise cosine similarity between foundation probe directions at layer 7 (bootstrap-stable; all six foundations exceed the 0.8 stability threshold at this layer; Section 4.6), OLMo-2 1B. Mean off-diagonal cosine = 0.262. See Appendix C for matrices at layers 0 and 15.

at all 16 layers; the remaining foundations show minor fluctuations at individual layers (minimum 87.5% for care/harm at layer 1). The onset threshold (0.6) is exceeded at layer 0 for all foundations.

These results confirm that moral foundation content is linearly separable from the earliest layer, consistent with the “immediate onset” finding of Reblitz-Richardson (2026c) for the pooled binary moral/neutral probe. The per-foundation decomposition shows no qualitative difference in *detectability* across foundations: all are equally easy to decode. The interesting variation is not in accuracy but in the *geometry* of the probe directions that achieve this accuracy.

On OLMoE-1B-7B, all foundations similarly reach 100% peak accuracy, with the lowest early-layer values at 81.25% (layers 0–1). The accuracy profiles are essentially indistinguishable between architectures.

These peak accuracies are maxima over 16 layers on small held-out sets (8–16 examples per foundation), so they should be read as “easily decodable” rather than as precise point estimates: the exact binomial 95% confidence interval on a perfect 16/16 still reaches down to ~ 0.79 . The geometric analysis below, not these saturated accuracies, carries the paper’s claims.

4.2 Framework geometry: integration, not collapse

The headline finding: foundation probe directions are *separated*, not collapsed. Across bootstrap-stable layers (6–15, where all six directions exceed the 0.8 stability threshold; Section 4.6, with the single exception of authority at layer 8, 0.792), mean pairwise cosine similarity ranges from **0.232 to 0.274**, far below the collapse threshold (> 0.95) and below the intermediate zone (0.8–0.95).




Figure 2: Layer-wise geometric metrics for OLMo-2 1B. (a) Mean pairwise cosine similarity is relatively flat across layers. (b) Effective dimensionality remains constant at 5 across all layers. (c) MFT group structure: mean cosine within the individualizing group, within the binding group, and between groups track together across layers, so the directions do not separate into the predicted individualizing/binding clusters.




Figure 3: Hierarchical clustering (Ward’s method) of foundation probe directions at layer 7 (bootstrap-stable), OLMo-2 1B. The first split does not recover the MFT individualizing/binding distinction.

Figure~1 shows the representative pattern at layer 7 (mean cosine 0.262). The peak-separation layer (layer 0, mean cosine 0.216) is below the bootstrap stability threshold for all foundations and is reported in Appendix~C.

The cosine similarities are uniformly *positive* at all layers (range 0.14–0.35), indicating that the foundation directions share a common component. This is the *integration* signature from our trichotomy: the directions are separated but non-orthogonal, consistent with a shared moral-salience subspace from which foundation-specific directions deviate.

Effective dimensionality. The six foundation directions span 5 effective dimensions (the number of PCs explaining $\geq 90\%$ of variance) at every layer, confirming that the directions are geometrically distinct and do not collapse into a lower-dimensional subspace. Effective dimensionality alone does not establish *integration*, however: six random directions in this hidden space also span ~ 5 effective dimensions (Section 4.8), so a near-maximal eff-dim is equally consistent with the isolation regime. The integration signal is carried by two statistics that random directions do not reproduce: the uniformly positive mean pairwise cosine (0.26, vs. ~ 0 for random directions), and the concentration of variance on a shared leading axis. The first principal component of the six unit directions captures **0.379** of their variance averaged over the stable layers 6–15, more than double the **0.179** expected for six random unit vectors in 2048 dimensions ($\approx 1/6$). Both reflect the shared moral-salience component; the effective dimensionality only rules out collapse.

4.3 Dendrogram structure does not recover MFT groups

Hierarchical clustering of the six foundation directions does *not* recover the MFT individualizing/binding distinction at any layer. At layer 7, loyalty and authority merge first, liberty joins them, then care and fairness merge separately, then sanctity joins the loyalty–authority–liberty cluster. No layer produces the predicted {care, fairness, liberty} vs. {loyalty, authority, sanctity} partition.

The most consistent clustering pattern across layers is a care–sanctity pairing: these two foundations appear in the same cluster at 10 of 16 layers. This crosses the MFT boundary (care is individualizing, sanctity is binding) but has a plausible semantic interpretation: both foundations concern protection of vulnerable entities (persons from harm, sacred things from degradation). The loyalty–authority pairing at layer 7 is within the binding group, but liberty (individualizing) joins this cluster before grouping with the other individualizing foundations (care, fairness), further mixing MFT categories.

The permutation test for the individualizing/binding distinction does not reach significance at any layer (minimum $p = 0.32$; median $p = 0.53$). With only 6 items and 20 unique 3–3 partitions, statistical power is limited, but the consistently high p -values combined with the absence of MFT-aligned dendrograms at any layer indicate that the model’s inter-framework geometry does not reflect the MFT group structure on this dataset.

4.4 Layer-wise geometric development

The geometric structure is relatively stable across layers. Mean pairwise cosine similarity is lowest at layer 0 (0.216), rises modestly to a peak of 0.274 at layer 6, then returns to 0.232 at layer 13 before a slight increase at layer 15 (0.262). The variation is small (range 0.06) compared to the distance from collapse, indicating that framework separation is a consistent property of the representation space rather than an emergent late-layer phenomenon.

Effective dimensionality remains constant at 5 across all layers, meaning the rank of the direction set does not change even as the pairwise angles shift. The geometric structure is a rotation of the direction set within a fixed-rank subspace, not a dimensionality change.

4.5 Dense vs. MoE framework geometry

Framework geometry is remarkably similar between architectures. OLMoE-1B-7B shows mean pairwise cosine similarity ranging from 0.219 to 0.287, compared to OLMo-2 1B’s 0.217 to 0.282. Effective dimensionality is 5 at all layers for both models. The overall degree of framework separation is consistent across dense and MoE architectures in our comparison.

Neither architecture produces MFT-aligned dendrogram structure at any layer. Both models show the care–sanctity pairing as the most stable clustering feature, suggesting that inter-framework geometry is driven by semantic relationships in the training corpus rather than by architectural properties. The permutation test for MFT group structure is non-significant at all layers for both models (all $p > 0.25$).

This finding extends [Reblitz-Richardson \(2026b\)](#): output dilution affects moral encoding *scale* ($74\times$ signal gap) but not framework *structure*. The geometric organization of moral foundations is preserved across architectures.

4.6 Direction stability under bootstrap

Bootstrap resampling (200 iterations) shows a stability gradient across layers. Early layers (0–5) show borderline stability (mean cosine similarity with the full-data direction: 0.74–0.80, below the 0.8 threshold for most foundations). Middle and late layers (6–15) are stable (mean cosine > 0.80). Sanctity/degradation is the most stable foundation (13/16 layers stable); care/harm the least (10/16 stable).

This gradient has two implications. First, the geometric analysis at early layers, including the peak separation layer (layer 0), should be interpreted with caution, as the specific pairwise cosine values may shift under resampling. Second, the stability gradient itself is informative: probe directions become more determined as representations become more specialized, paralleling the lexical-to-compositional gradient from [Reblitz-Richardson \(2026c\)](#).




Figure 4: Mean critical noise σ^* per foundation for OLMo-2 1B (left) and OLMoE-1B-7B (right), seed-averaged with cap-at-max and bootstrap 95% CIs over noise seeds. Every foundation is more fragile in MoE than in dense (the cross-architecture dilution effect); within each architecture the per-foundation CIs overlap and the ordering is not statistically separable.

The headline geometric findings (separation not collapse; effective dimensionality = 5) are confirmed at layers 6–15 where directions are stable.

4.7 Differential fragility across frameworks

We measure per-foundation critical noise σ^* with the standard fragility protocol, averaging accuracy over 10 noise seeds and censoring never-fragile layers at the grid maximum (the cap-at-max convention of Reblitz-Richardson (2026c)); bootstrap 95% CIs are over the noise seeds. Seed-averaging is necessary here: a single noise draw makes per-layer σ^* unstable.

The result is between architectures, not between foundations. Every foundation is more fragile in OLMoE than in OLMo-2: dense σ^* runs 3.8–5.6 across the six foundations (mean 5.0), MoE σ^* runs 1.2–3.8 (mean 2.2), a per-foundation architecture gap of $\sim 2.3\times$. This is the same direction as, and smaller than, the $4.2\times$ pooled gap reported by Reblitz-Richardson (2026b); the pooled probe trains on 192 pairs versus 32 per foundation here, so it has more statistical power and a cleaner separation. Output dilution suppresses moral encoding across the board.

Within an architecture, foundations are not reliably separable. The per-foundation σ^* values have wide, overlapping bootstrap CIs (dense: e.g. sanctity 5.50, CI [3.6, 8.6]; care 4.81, CI [3.5, 8.0]. MoE: sanctity 2.33, CI [1.3, 5.3]; care 3.76, CI [0.9, 6.7]), and no foundation is robustly most or least fragile. The binding-vs-individualizing group difference is not significant in either model and reverses sign between them (dense: binding – individualizing = +0.58, exact permutation $p = 0.40$; MoE: -0.41 , $p = 0.70$). We therefore make no per-foundation or MFT-group fragility claim; the supported finding is the uniform cross-architecture dilution.

4.8 Geometric trajectory during training

Framework geometry develops rapidly and stabilizes early. Tracking mean pairwise cosine similarity (averaged over stable layers 5–14) across 20 OLMo-2 1B checkpoints from step 0 to step 35,000:

- **Step 0.** Mean cosine similarity is 0.007; the six foundation directions are effectively orthogonal, as expected for probes trained on random representations. Mean accuracy is 0.510 (chance).
- **Step 1000.** Cosine similarity jumps to 0.176. Accuracy reaches 0.734. The model has already begun developing shared moral-salience structure.




Figure 5: Geometric trajectory during OLMo-2 1B pre-training. (a) Mean cosine similarity stabilizes by step 2000. (b) Effective dimensionality remains at 5 throughout. (c) Accuracy continues climbing after geometry plateaus.

- **Step 2000.** Cosine similarity reaches 0.382, within 5% of its final value. Accuracy is 0.873, still 10 points below its peak.
- **Steps 3000–15,000.** Cosine similarity plateaus at 0.38–0.40. Accuracy continues climbing from 0.922 to 0.970.
- **Steps 20,000–35,000.** Cosine similarity drifts slightly downward (0.382 to 0.367). Accuracy stabilizes at 0.975–0.979.

Effective dimensionality remains constant at 5 from step 0 onward. This is expected: random unit vectors in $\mathbb{R}^{2048}$ are nearly orthogonal with high probability, so even at initialization the six probe directions span 5 effective dimensions. The informative signal is cosine similarity, which transitions from ≈ 0 (random) to ≈ 0.4 (mature structure) during the first 2000 training steps.

The temporal dissociation (framework geometry stabilizing at step 2000 while accuracy continues improving through step 25,000) extends the two-phase pattern identified by [Reblitz-Richardson \(2026c\)](#): accuracy saturates early, but fragility continues resolving. Here we add a third metric: inter-framework *structure* also stabilizes before inter-framework *discriminability* finishes developing. The model discovers the geometric layout of moral concepts early and then spends the remainder of training strengthening the representations within that fixed layout.

4.9 Dilemma compositionality: partial but structured

We now ask whether the model’s representation of moral *dilemmas* (scenarios where two foundations conflict) can be decomposed in terms of the single-foundation directions from Experiment 1.

Dilemma probes achieve high accuracy. All 15 dilemma-specific probes achieve $\geq 75\%$ peak test accuracy (mean 94.2%), with 13 of 15 pairs at $\geq 87.5\%$. The model reliably distinguishes dilemma moral content from matched neutral text.

Subspace membership: partial compositionality. The mean peak subspace membership score across all 15 pairs is **0.099**, approximately $100\times$ the null baseline of 0.001 ($p_{95} = 0.003$; $p_{99} = 0.004$). Every pair exceeds the 99th percentile of the null distribution at its peak layer. However, 0.099 is far from 1.0: on average, only $\sim 10\%$ of each dilemma direction’s variance is explained by its component foundation subspace. The remaining $\sim 90\%$ (mean residual norm = 0.949) lies in directions orthogonal to both component foundations.

Component balance is near-equal. The mean component balance ratio is 0.486 (perfect balance = 0.5). In 14 of 15 pairs, the balance falls within [0.40, 0.58], indicating that both component foundations contribute approximately equally to the within-subspace projection. The exception is fairness–sanctity (balance = 0.335), where the sanctity component dominates. When two foundations *do* compose, they compose symmetrically rather than one foundation dominating the representation.

Shared-component structure. Dilemma pairs that share a foundation component have consistently higher cosine similarity than pairs with no shared foundation. At the peak effect layer (layer 13), the mean cosine similarity between shared-component pairs is **0.269** versus **0.195** for non-sharing pairs (difference = 0.074). This difference is positive at every layer, indicating that the compositional structure is not layer-specific but a general property of the dilemma direction geometry.




Figure 6: Subspace membership scores for 15 dilemma probe directions across 16 layers. Each cell shows the fraction of a dilemma direction’s variance explained by the 2D subspace of its component foundation directions. Liberty–sanctity shows the strongest compositional signal.

Hierarchical clustering. The 21-direction dendrogram (6 foundation + 15 dilemma directions) at layer 13 shows two features. First, the six foundation directions form a distinct cluster separate from the dilemma directions. Second, within the dilemma cluster, pairs sharing a component foundation tend to merge at lower distances, consistent with the shared-component analysis above.

The categorical foundation/dilemma separation initially appears to undercut the compositionality narrative: if dilemmas were purely compositional, they would cluster near their component foundations, not in a separate region. However, this separation is driven by register features, not moral content. Projecting all 21 directions into the 5D moral subspace (spanned by the six foundation directions) and re-clustering dissolves the separation entirely: foundations now cluster with their related dilemmas (e.g., sanctity with fairness–sanctity and care–sanctity). The first-order separation in the full-space dendrogram reflects the $\sim 90\%$ extra-moral residual (likely text-register differences between declarative single-foundation sentences and narrative dilemma scenarios), while the second-order structure within each cluster reflects genuine moral content relationships.

Full moral subspace projection. The 2D subspace analysis above uses only the two component foundations per dilemma. To test whether dilemma representations are compositional over the *full* moral vocabulary, we project each dilemma direction onto the 5D subspace spanned by all six foundation directions (5D because the six directions have effective dimensionality 5). Averaging across all layers and pairs, the mean 5D membership is **0.093**, only modestly above the layer-averaged 2D membership of 0.078 (ratio $1.19\times$). (The higher value of 0.099 reported above is the mean of per-pair *peak* values; 0.078 is the cross-layer average, used here for an apples-to-apples comparison with the 5D statistic.) Both exceed their respective null baselines (5D: $38\times$ null; 2D: $81\times$ null), confirming genuine moral content in the dilemma representations. However, the small gain from 2D to 5D indicates that the $\sim 90\%$ residual is not explained by *any* foundation direction: it is genuinely extra-moral, likely encoding conflict-specific features such as trade-off framing and tension that lie outside the moral subspace entirely.

Scale replication. The partial-compositionality result reproduces on OLMo-2~7B. Mean peak subspace membership is 0.091 (9.1%, vs. 9.9% at 1B), with all 15 pairs exceeding the null 95th




Figure 7: Mean subspace membership across layers (red), with ± 1 SD band. The null baseline (gray) is ~ 0.001 . Membership is relatively flat at $\sim 8\%$ across all layers.




Figure 8: Component balance at each pair's peak subspace membership layer. Values near 0.5 (dashed line) indicate balanced contribution from both foundations. Fairness–sanctity (red) is the only pair with substantial imbalance.

percentile; mean residual norm is 0.953 (vs. 0.949); and component balance is 0.455 (vs. 0.486, where 0.5 is perfect balance). The 7B model decomposes moral dilemmas the same way the 1B model does: a small, significant projection onto the component foundations, a large conflict-specific residual, and near-balanced loading on the two foundations in tension.

4.10 Dilemma direction stability

Bootstrap resampling (50 iterations) of the 15 dilemma probe directions across 16 layers yields 240 direction–layer combinations. Of these, **239 are stable** (mean cosine with full-data direction > 0.7), with the single exception at liberty–loyalty, layer 0. The relaxed threshold (0.7 vs. 0.8 for foundation probes) reflects the smaller sample size (16 training pairs vs. 32 for foundations), but the results




Figure 9: Distribution of pairwise cosine similarities between dilemma directions at layer 13, split by whether the pairs share a component foundation. Shared-component pairs (blue, $n = 60$) have higher mean similarity (0.269) than non-sharing pairs (red, $n = 45$, mean 0.195).




Figure 10: Hierarchical clustering of all 21 directions (6 foundation in blue, 15 dilemma in red) at layer 13. Foundation directions cluster separately from dilemma directions.

indicate that the dilemma probe directions, and therefore the subspace analysis built on them, are reliable.

4.11 Complexity–fragility gradient

We compare fragility across three levels of moral complexity: single-foundation probes (from Experiment 7), pooled binary dilemma probes (all 300 dilemma pairs pooled), and per-type dilemma probes (15 separate probes, 20 pairs each).

All three are measured under the same convention (seed-averaged, cap-at-max). The mean critical noise follows a **complexity–fragility gradient**: single-foundation probes are most robust ($\sigma^* = 5.02$), followed by the pooled dilemma probe ($\sigma^* = 3.81$), with per-type dilemma probes least robust




Figure 11: Mean critical noise for probes at three complexity levels. Single-foundation probes (Exp. 7) are most robust; per-type dilemma probes are least robust. Higher values indicate greater noise tolerance.

($\sigma^* = 3.55$). This ordering is consistent with the hypothesis that more specific moral distinctions are encoded with less redundancy and are therefore more vulnerable to perturbation.

The gradient’s direction matters: the pooled dilemma probe is *less* robust than single-foundation probes, not more. This argues against the possibility that dilemma probes are simply detecting a generic “morally complex” feature with high redundancy. Instead, the dilemma direction captures genuinely more specific information that is correspondingly more fragile.

4.12 MoE architecture preserves compositionality

The dilemma probing and subspace analysis on OLMoE-1B-7B produces results consistent with the dense model. Mean peak accuracy is 95.8% (vs. 94.2% on OLMo-2), and mean peak subspace membership is **0.092** (vs. 0.099). The $\sim 7\%$ difference in membership scores is within the variation across individual foundation pairs. The partial compositionality structure (statistically significant but low absolute membership, with high residual) is a property of the representation geometry, not a dense-architecture artifact.

4.13 Robustness to direction-finding method

The geometric findings reported above rely on probe weight vectors as foundation directions. To test whether the geometry is an artifact of discriminative probe training, we extract directions using two alternative methods and compare.

Mean-difference directions. For each foundation, we compute $\mathbf{d}_f = \bar{\mathbf{a}}_{\text{moral}} - \bar{\mathbf{a}}_{\text{neutral}}$ (the normalized difference of class-conditional activation means), requiring no optimization. These training-free directions replicate the core geometric findings: effective dimensionality is 5 at all layers. Like the probe-weight directions, the mean-diff dendrogram does not recover the MFT individualizing/binding split at any layer, and the permutation test is non-significant throughout. Per-foundation cosine similarity between probe-weight and mean-difference directions ranges from 0.67 to 0.72 (mean across layers), indicating related but non-identical directions: the probe-weight method finds more foundation-specific discriminative signal, while the mean-difference method captures more of the shared moral-salience component (mean pairwise cosine 0.41 vs. 0.22 at layer 0).

Representation-engineering directions. We also test paired-difference PCA (Zou et al., 2023): for each pair i , compute $\mathbf{d}_i = \mathbf{a}_{\text{moral},i} - \mathbf{a}_{\text{neutral},i}$ and take the first principal component. This method performs poorly: the first PC explains only 8–11% of variance (barely above chance in $\mathbb{R}^{2048}$), and the resulting directions show low alignment with probe-weight directions ($|\cos| = 0.07\text{--}0.26$).




Figure 12: Foundation direction cosine similarity for OLMo-2 1B (layer 7/16) and 7B (layer 14/32), at matched relative depth. Mean off-diagonal cosine is 0.262 (1B) and 0.240 (7B) at these display layers; both sit in the integration range. Effective dimensionality is 5 for both (Figure 13).

and weak classification accuracy. With ~ 32 pairs per foundation in 2048 dimensions, the $p \gg n$ regime prevents PCA from isolating the concept direction. This negative result validates that the convergent probe-weight and mean-difference findings are not trivially recoverable; they depend on direction-finding methods with appropriate inductive bias for small datasets.

Cross-register transfer. Both probe-weight and mean-difference directions transfer to narrative dilemma text with $> 90\%$ mean pair accuracy across foundations (the fraction of pairs where the direction projects the moral text higher than the neutral text). Probe-weight directions achieve $> 95\%$ for all foundations; the mean-difference method drops to $\sim 91\%$ for authority/subversion, the foundation with weakest directional stability. The transfer gap between same-register (declarative test pairs) and cross-register (dilemma pairs) averages under 4 percentage points, with authority/subversion showing the largest gap (~ 9 pp for mean-difference; §5.5).

4.14 Scale validation: geometry persists from 1B to 7B

We replicate the core geometric findings on OLMo-2~7B (the 1124 release, 32 layers, hidden dimension 4096), a dense model with 7.3B parameters, versus 1.5B for OLMo-2~1B. The integration signature holds. Mean pairwise cosine similarity ranges from **0.193 to 0.244** across layers (1B: 0.217–0.282), positive everywhere and far below the collapse threshold. Effective dimensionality is **5 at every one of the 32 layers**, identical to the 1B and MoE models. Foundation directions are geometrically distinct, sharing a common moral-salience component, at both scales.

Direction stability. Bootstrap resampling (200 iterations) places 110 of 192 foundation–layer combinations above the 0.8 stability threshold, with the remainder in the 0.72–0.80 borderline band. Sanctity/degradation is again the most stable foundation (29/32 layers), fairness/cheating the least (7/32). The per-layer cosine range (0.72–0.85) is comparable to the 1B model; the larger model’s directions are no less determined.

MFT is not recovered at 7B either. Hierarchical clustering does not produce the individualizing/binding split at any layer, and the permutation test for MFT group structure is non-significant throughout ($p = 0.49$ –0.78). The model’s inter-framework geometry is not MFT-aligned at either scale.

Fragility. Seed-averaged per-foundation fragility at 7B uses the extended noise grid (Section 4.7), which censors only 1 of 192 foundation–layer cells at the cap. As at 1B, the per-foundation σ^* values have wide, overlapping bootstrap CIs and no foundation is reliably most or least robust (7B mean σ^* : loyalty 14.7, authority 13.5, care 10.1, sanctity 10.0, liberty 8.4, fairness 6.9, all with overlapping CIs). The binding-vs-individualizing group difference is again not significant ($+4.2$, exact $p = 0.20$). What the 7B run does add is a clean scale effect: the dense model is uniformly more robust at 7B




Figure 13: Layer-wise geometry across scale on normalized depth. (a) Mean pairwise cosine for both models stays in the integration band. (b) Effective dimensionality is constant at 5 for both 1B and 7B.




Figure 14: Per-foundation mean critical noise σ^* for OLMo-2 1B and 7B (dense), seed-averaged with bootstrap 95% CIs. The 7B model is uniformly more robust (scale effect); within each model the per-foundation CIs overlap and no foundation is reliably most robust.

than at 1B (mean $\sigma^* \approx 10.6$ vs. 5.0). The robust fragility findings are therefore the cross-architecture dilution (Section 4.7) and this dense scale effect, not any per-foundation ordering.

4.15 The model’s data-driven taxonomy does not recover MFT

Sections 4.3 and 4.14 show that hierarchical clustering of the six probe *directions* does not recover MFT groups. We test the stronger question directly: cluster the moral-positive *activations* themselves, without reference to foundation labels, and ask whether the discovered groups align with the foundations.

K-means and spectral clustering (k selected by silhouette score, $k = 2\text{--}8$) on OLMo-2~7B moral activations produce clusters that barely align with MFT foundations. Adjusted mutual information between the discovered clusters and the foundation labels peaks at **0.032** (layer 11) and is near zero or slightly negative at most layers; silhouette scores stay low (0.06–0.08), indicating weak cluster structure. A clustering that recovered the foundations would give AMI near 1.

This is consistent with integration. Foundations are linearly *decodable*: supervised probes separate them with near-perfect accuracy and span 5 effective dimensions. But they are not the dominant axis of variation in the raw activations, so unsupervised clustering recovers the shared moral-salience




Figure 15: Discovered clusters (rows) against MFT foundations (columns) at the most foundation-aligned layer (11) of OLMo-2 7B. Cells are pair counts; row-normalized shading. The clusters do not map onto foundations (AMI = 0.032).

structure rather than the foundation distinctions. The model represents the foundations as distinct directions without organizing its moral activations around them.

4.16 External replication on the Moral Foundations Vignettes

To test whether the integration geometry is a property of the model rather than of our probing dataset, we recompute foundation directions from the Moral Foundations Vignettes (Clifford et al., 2015), an independently constructed set of 30 validated moral scenarios (5 per foundation). Directions are estimated by mean difference against a shared neutral baseline, the same estimator applied to both datasets for a fair comparison.

The integration signature replicates. The six MFV directions span **5 effective dimensions at every layer** of OLMo-2~7B, identical to the directions derived from our dataset. Mean pairwise cosine is higher for MFV (0.50–0.72) than for the matched mean-difference directions on our data (0.42 at the display layer), an expected small-sample effect given five vignettes per foundation. Because absolute cosine is inflated by the five-per-foundation sample, the cross-dataset claim rests on the sign and structure of the geometry rather than the cosine magnitude: both datasets show uniformly positive mean cosine with variance concentrated on a shared leading axis (the integration signature), spanning the same 5 effective dimensions. Effective dimensionality by itself does not separate integration from isolation (random directions also span ~ 5 dimensions); the positive mean cosine carries that distinction, and it replicates in sign across the two datasets.

Cross-dataset direction alignment. Foundation directions estimated from the two independent datasets are positively aligned ($|\cos| = 0.14\text{--}0.43$ per foundation at layer 12), with individualizing foundations aligning more strongly (care 0.30, fairness 0.36, liberty 0.43) than binding foundations (loyalty 0.14, authority 0.19, sanctity 0.29). That directions estimated from independently authored




Figure 16: MFV external replication on OLMo-2 7B. (a) Cosine similarity among the six MFV foundation directions. (b) Mean cosine and effective dimensionality vs depth for MFV and for matched mean-difference directions on our dataset. (c) Per-foundation alignment between MFV and our directions.

stimuli agree at all is evidence that the foundation directions reflect the model’s representations rather than artifacts of any single dataset.

5 Discussion

5.1 Integration as the default geometric mode

The central finding, that foundation probe directions exhibit integration rather than collapse or isolation, has a straightforward interpretation: language models develop structured moral representations from distributional statistics alone. The training corpus does not label texts with MFT foundations, yet the model learns representations in which moral foundations occupy distinct directions that share a positive common component (mean cosine ≈ 0.22 at peak separation, ≈ 0.26 at stable mid-network layers). This is genuine multi-dimensional moral structure, not a single “moral salience” detector.

The fact that effective dimensionality is 5 (near-maximal for 6 directions) throughout the network rules out the possibility that the model has learned a single “this text is moral” feature and then adds minor perturbations per foundation. The foundation directions are geometrically distinct objects that happen to share a common moral-salience component.

This holds across scale, architecture, and dataset. Effective dimensionality is 5 at every layer of OLMo-2~1B, OLMo-2~7B, and OLMoE-1B-7B, and on the independently constructed Moral Foundations Vignettes (§4.14, §4.16). Integration is the default geometric mode for moral representations in these models, not a property of one scale, architecture, or probing dataset.

Dataset sensitivity. The mean cosine similarity is sensitive to neutral-pair quality: neutrals that inadvertently carry moral content inflate the shared moral-salience component, producing higher cosine values. The quality-gated dataset used here (Section 3.6) minimizes this inflation, and we interpret the ≈ 0.22 – 0.27 range as a lower bound on the true integration signal. All qualitative conclusions (integration signature, effective dimensionality of 5, absence of MFT dendrogram structure) are robust to dataset construction choices, but the quantitative sensitivity highlights the importance of neutral-pair quality for geometric analyses. The replication on the Moral Foundations Vignettes (§4.16), where directions estimated from independently authored stimuli reproduce the 5-dimensional integration geometry, shows that the qualitative signature does not depend on our dataset.

The model’s moral taxonomy is not MFT. The inter-framework structure that emerges does not align with MFT’s predicted individualizing/binding distinction: hierarchical clustering does not recover this partition at any layer, and the permutation test is non-significant throughout. Instead, the most consistent clustering feature is a care–sanctity pairing that crosses MFT groups. Both care and sanctity involve protection (of persons from harm, of sacred things from degradation), sharing distributional signatures that the model detects. The care–sanctity pairing is itself robust to dataset construction choices: it persists across different neutral-pair generation methods and quality thresholds, arguing against a dataset artifact explanation. The model’s moral taxonomy is thus empirically grounded in corpus statistics rather than aligned with any a priori grouping from moral

psychology, which is itself evidence of genuine structure learning (the model discovers which moral concepts are distributionally related) rather than surface keyword matching.

A data-driven test sharpens this point. Clustering the moral activations themselves, without foundation labels, recovers the foundations only weakly (adjusted mutual information 0.03 at best; §4.15). Even the model’s own unsupervised grouping of moral content is not MFT-structured, which is the expected consequence of integration: the foundations are linearly decodable but are not the dominant axis of variation, so unsupervised methods find the shared moral-salience structure instead.

5.2 Per-foundation fragility is not separable

Within an architecture, the moral foundations are not reliably distinguishable by fragility. With 10 noise seeds and the cap-at-max convention (Section 4.7), per-foundation σ^* values carry wide, overlapping bootstrap CIs in all three models, and no foundation is reliably most or least robust. Sanctity sits mid-pack everywhere (dense 1B 5.50, MoE 2.33, dense 7B 10.0, fourth of six), and the binding-vs-individualizing group difference is not significant in any model (dense 1B $p = 0.40$, MoE $p = 0.70$, dense 7B $p = 0.20$) and reverses sign between dense and MoE. Per-foundation σ^* is sensitive to single-draw noise, so we make no per-foundation or MFT-group fragility claim.

The fragility result that does hold is between architectures, not between foundations: every foundation is more fragile in MoE than in dense (a $\sim 2.3\times$ per-foundation gap, the same direction as the pooled $4.2\times$ of Reblitz-Richardson (2026b)), and dense robustness rises with scale from 1B to 7B. Output dilution suppresses moral encoding uniformly across foundations rather than singling any one out.

5.3 Framework geometry stabilizes before accuracy saturates

The trajectory analysis shows a temporal dissociation: framework geometry (mean cosine similarity between foundation directions) reaches its mature value by approximately step 2000–3000, while probing accuracy continues climbing through step 10000 and beyond. This extends the “accuracy saturates but fragility resolves” finding of Reblitz-Richardson (2026c) to a third metric: the *structure* of moral representations stabilizes before the *strength* of moral representations finishes developing.

This pattern is consistent with a two-phase account of moral representation learning. In the first phase (steps 0–2000), the model discovers the geometric layout (which moral concepts are related and how). In the second phase (steps 2000+), it strengthens these representations, improving the discriminability of each foundation without changing the inter-framework relationships.

Effective dimensionality is 5 from step 0 onward, indicating that even random initialization produces probe directions that span 5 dimensions. This is expected: random unit vectors in $\mathbb{R}^{2048}$ are nearly orthogonal with high probability. The informative signal is not dimensionality but cosine similarity, which jumps from ≈ 0 (random) to ≈ 0.38 (mature structure) during the first 2000 training steps.

5.4 Partial compositionality of moral dilemmas

When two moral foundations conflict in a dilemma scenario, the model’s representation is partially compositional: the dilemma probe direction shares statistically significant overlap with the 2D subspace spanned by its component foundation directions (mean membership $S = 0.099$, $100\times$ the null baseline of 0.001), yet $\sim 90\%$ of the dilemma direction lies outside this subspace.

This partial compositionality has two complementary interpretations. First, the model recognizes moral dilemmas as involving their component foundations (the $\sim 10\%$ subspace membership is not an artifact), as confirmed by permutation testing and by the shared-component structure (dilemma pairs that share a foundation have higher cosine similarity, $\Delta = 0.074$ at layer 13). Second, the model represents something beyond the sum of parts: the $\sim 90\%$ residual captures conflict-specific features (tension, trade-off framing, or contextual modulation) that single-foundation probes do not isolate.

The near-balanced component loading ($\bar{\alpha} = 0.486$) is notable. If dilemma representations were dominated by one foundation (e.g., always prioritizing care over authority), we would expect strongly asymmetric projections. Instead, both conflicting foundations contribute roughly equally to the within-subspace component, consistent with the model encoding the *conflict itself* rather than a pre-resolved moral judgment. This is an “understanding before choice” mode of representation: the model maintains both competing moral claims in tension rather than collapsing to a resolution,

suggesting that moral comprehension (the capacity to represent the structure of ethical disagreement) may precede and be separable from moral judgment. This pattern is scale-stable: OLMo-2~7B reproduces the partial-compositionality profile (9.1% subspace membership, 0.95 residual, 0.46 component balance; §4.9), so the conflict-as-tension representation is not an artifact of the smaller model’s capacity.

The complexity–fragility gradient (single-foundation $\sigma^* = 4.72 >$ pooled dilemma $\sigma^* = 3.12 >$ per-type dilemma $\sigma^* = 2.90$) shows that representational complexity trades off against robustness. Dilemma representations sit in a higher-dimensional space and are correspondingly more fragile under Gaussian noise. This is consistent with the residual component encoding subtle contextual features that require higher precision to maintain.

5.5 Register sensitivity: directions transfer, thresholds do not

Foundation-specific probes trained on declarative minimal pairs do not fully generalize to narrative dilemma text *as classifiers*. In the dilemma verification experiment, authority and loyalty probes showed near-chance transfer (Youden’s $J < 0.2$), while care and fairness probes transferred well. This asymmetry is not a model-capacity issue: testing on OLMo-2 7B (32 layers, 4096 hidden dim) yielded comparable transfer failure (54.0% vs. 61.3% for the 1B model).

Directions vs. thresholds. The probe engineering analysis (§4.13) resolves this concern by separating two components of cross-register transfer: the *direction* (probe weight vector) and the *threshold* (bias term). When evaluated by pair accuracy (the fraction of pairs where the direction projects the moral text higher than the neutral text, requiring no threshold), both probe-weight and mean-difference directions achieve $> 90\%$ mean pair accuracy on narrative dilemma text (probe-weight $> 95\%$ for all foundations; mean-difference drops to $\sim 91\%$ for authority/subversion). The Youden’s J failure is therefore a threshold miscalibration effect: the absolute projection scale shifts between registers, invalidating the fixed decision boundary learned on declarative text. The directional structure itself, the subspace in which moral content is encoded, transfers robustly.

This distinction matters for the geometric findings. Cosine similarity, effective dimensionality, and dendrogram clustering depend only on direction vectors, not on classification thresholds. Since the directions transfer across registers, the geometric findings are not register-bound.

Threshold vs. direction transfer. The register sensitivity is specific to threshold transfer, not direction transfer. Both individualizing and binding directions transfer across registers with high pair accuracy ($> 90\%$); what shifts across register is the decision threshold, not the direction itself. Authority and loyalty show the largest threshold gaps (Appendix B.2), so their register sensitivity reflects a calibration shift rather than a change in the underlying moral direction.

Implications for the geometric findings. The 21-direction dendrogram analysis (§4.9) gives direct evidence that register features drive part of the representation geometry: projecting all directions into the 5D moral subspace dissolves the categorical foundation/dilemma separation, confirming that the separation is carried by extra-moral (register) features. This is consistent with the threshold miscalibration account: foundation and dilemma directions occupy the same moral subspace (their projections overlap), but differ in extra-moral dimensions that carry register information and shift the activation scale.

5.6 Limitations

Small probing dataset. The 32 training pairs per foundation are sufficient for classification (near-perfect accuracy) but limit the precision of direction estimation. Bootstrap analysis (Section 4.6) confirms that directions at layers 0–5 are borderline unstable, and all geometric claims are qualified to the bootstrap-stable core, layers 6–15 (the lone exception being authority at layer 8, 0.792). A larger dataset would tighten direction estimates, but the current dataset is deliberately minimal to demonstrate that structured geometry is recoverable even from small samples.

Permutation test power. With 6 foundations divided into two groups of 3, the permutation space contains only 20 unique partitions. The permutation test for the individualizing/binding distinction cannot reach $p < 0.05$ unless the effect is very large. The dendrogram structure gives qualitative support, but the formal statistical test is underpowered.

One model family. The three configurations span scale (1B and 7B dense) and architecture (dense and MoE), and the integration signature and MFT-mismatch hold across all of them and on the independently constructed MFV stimuli (§4.14–4.16). The models are still all from Ai2’s OLMo family, trained on comparable corpora, so generalization to models trained on substantively different data mixtures remains open. The architectural and scale comparisons are well-controlled because the models share training data, at the cost of corpus diversity.

Linear probes. The entire analysis assumes that moral foundations are encoded as linear directions. If some foundations are encoded nonlinearly (e.g., as curved manifolds or distributed across multiple directions), the cosine similarity analysis would understate the true geometric richness. The near-perfect accuracy of linear probes suggests that linear decoding captures the dominant signal, but does not rule out additional nonlinear structure.

Causal status. Probe directions are read off the representation: on their own they identify *where* foundation information is readable, not whether that information is *used* during generation. Companion work (Reblitz-Richardson, 2026a) addresses this with direction ablation and steering, and our 7B foundation directions show the same pattern: ablating a foundation’s direction selectively perturbs that foundation’s continuations, and injecting it produces a dose-response shift (Appendix~F). Full causal localization across layers is left to that companion paper; the geometry reported here is descriptive of the representation, with this initial causal evidence that the directions are functionally implicated.

6 Conclusion

Language models develop structured moral representations that go beyond mere moral detection. By training independent linear probes for each of six Moral Foundations Theory foundations and analyzing the geometry of their weight vectors, we find that OLMo-2 1B and OLMoE-1B-7B exhibit the *integration* signature: foundation directions are distinct (effective dimensionality = 5, which rules out collapse) yet share a common moral-salience component, shown by a uniformly positive mean pairwise cosine (≈ 0.22 – 0.27) and a leading principal component that captures ~ 0.38 of the directions’ variance (vs. ~ 0.18 for random directions). The positive cosine, not the effective dimensionality, is what distinguishes integration from isolation. This geometric structure is consistent across the two architectures tested (dense vs. MoE), emerges early in pre-training, and stabilizes before probing accuracy saturates. However, the inter-framework structure does not align with MFT’s predicted individualizing/binding grouping, indicating that the model’s moral taxonomy is empirically grounded in corpus statistics rather than organized along human-theoretical lines.

Framework-specific fragility testing shows that the output dilution effect is foundation-uniform: every foundation is more fragile in MoE than in dense (a $\sim 2.3\times$ per-foundation gap), with no foundation reliably most or least robust within an architecture and no significant binding/individualizing group difference.

Extending this geometric lens to moral dilemmas (scenarios where two foundations conflict) shows partial compositionality: dilemma representations share $\sim 10\%$ of their variance with the subspace spanned by component foundation directions ($100\times$ the null baseline), with near-balanced loading across both conflicting foundations. The remaining $\sim 90\%$ residual and the complexity–fragility gradient (σ^* : $5.02 \rightarrow 3.81 \rightarrow 3.55$) indicate that dilemma representations encode conflict-specific structure beyond their component foundations. This compositionality pattern is preserved across architectures (dense and MoE).

The probe direction geometry methodology introduced here is general. Any set of related concepts that can be isolated by binary linear probes can be analyzed for inter-concept structure via the same cosine similarity and clustering techniques. We anticipate applications to other taxonomies of human values, to political orientation, and to the internal organization of safety training in instruction-tuned models.

Acknowledgments and Disclosure of Funding

This work made extensive use of Anthropic’s Claude (the Claude Code agent on Opus 4.6, 4.7, and 4.8) for code scaffolding, experimental scripts, and prose drafting. The author retains responsibility for experimental design, all scientific claims, and final wording.

References

- Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*, 2017. URL <https://arxiv.org/abs/1610.01644>.
- Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *arXiv preprint arXiv:2406.11717*, 2024. URL <https://arxiv.org/abs/2406.11717>.
- Tolga Bolukbasi, Kai-Wei Chang, James Zou, Venkatesh Saligrama, and Adam Kalai. Man is to computer programmer as woman is to homemaker? Debiasing word embeddings. *Advances in Neural Information Processing Systems*, 29, 2016.
- Scott Clifford, Vijeth Iyengar, Roberto Cabeza, and Walter Sinnott-Armstrong. Moral foundations vignettes: A standardized stimulus database of scenarios based on moral foundations theory. *Behavior Research Methods*, 47(4):1178–1198, 2015.
- Alexis Conneau, Germán Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. What you can cram into a single $\$ \& ! \# *$ vector: Probing sentence embeddings for linguistic properties. *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pages 2126–2136, 2018.
- Oliver Scott Curry, Daniel Austin Mullins, and Harvey Whitehouse. Is it good to cooperate? Testing the theory of morality-as-cooperation in 60 societies. *Current Anthropology*, 60(1):47–69, 2019.
- Jesse Graham, Jonathan Haidt, Sena Koleva, Matt Motyl, Ravi Iyer, Sean P. Wojcik, and Peter H. Ditto. Moral foundations theory: The pragmatic validity of moral pluralism. In *Advances in Experimental Social Psychology*, volume 47, pages 55–130. Academic Press, 2013.
- Jonathan Haidt. *The Righteous Mind: Why Good People Are Divided by Politics and Religion*. Vintage Books, 2012.
- Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. Aligning AI with shared human values. *arXiv preprint arXiv:2008.02275*, 2021. URL <https://arxiv.org/abs/2008.02275>.
- Nikolaus Kriegeskorte, Marieke Mur, and Peter Bandettini. Representational similarity analysis — connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, 2:4, 2008.
- Niklas Muennighoff, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Jacob Morrison, Sewon Min, Weijia Shi, Pete Walsh, Oyvind Tafjord, Nathan Lambert, Yuling Gu, Shane Arora, Akshita Bhagia, Dustin Schwenk, David Wadden, Alexander Wettig, Binyuan Hui, Tim Dettmers, Douwe Kiela, Ali Farhadi, Noah A. Smith, Pang Wei Koh, Amanpreet Singh, and Hannaneh Hajishirzi. OLMoE: Open mixture-of-experts language models. *arXiv preprint arXiv:2409.02060*, 2024. URL <https://arxiv.org/abs/2409.02060>.
- OLMo Team. 2 OLMo 2 furious. *arXiv preprint arXiv:2501.00656*, 2025. URL <https://arxiv.org/abs/2501.00656>.
- Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models. *arXiv preprint arXiv:2311.03658*, 2024. URL <https://arxiv.org/abs/2311.03658>.
- Orion Reblitz-Richardson. Causal validation and behavioral grounding of moral representation directions in language models. *arXiv preprint*, 2026a. Companion paper, in preparation.

Orion Reblitz-Richardson. Output dilution in MoE models: Redundant encoding, fragile representations. *arXiv preprint*, 2026b. Companion paper.

Orion Reblitz-Richardson. When probing accuracy saturates, fragility resolves: A complementary metric for LLM pre-training analysis. *arXiv preprint*, 2026c. Companion paper.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to ai transparency. *arXiv preprint arXiv:2310.01405*, 2023. URL <https://arxiv.org/abs/2310.01405>.

Appendices

Supplementary material.

A Per-Foundation Probe Accuracy Tables

A.1 OLMo-2 1B

Table 1: Per-foundation probe accuracy across layers, OLMo-2 1B. Each cell shows test accuracy (16 test examples per foundation). All foundations exceed 0.6 at every layer.

Layer	Care	Fairness	Liberty	Loyalty	Authority	Sanctity
0	1.000	1.000	1.000	0.938	1.000	0.938
1	0.875	0.938	0.938	0.938	1.000	0.938
2	0.938	0.938	0.938	0.938	1.000	0.938
3	0.938	0.938	0.938	0.938	1.000	0.938
4	1.000	0.938	1.000	0.938	1.000	0.938
5	1.000	0.938	1.000	1.000	1.000	1.000
6	1.000	0.938	1.000	1.000	1.000	0.938
7	1.000	1.000	1.000	1.000	1.000	0.938
8	1.000	1.000	1.000	1.000	1.000	1.000
9	1.000	0.938	1.000	1.000	1.000	0.938
10	1.000	0.938	1.000	1.000	1.000	0.938
11	1.000	0.938	1.000	0.938	1.000	0.938
12	1.000	0.938	1.000	0.938	1.000	1.000
13	1.000	0.938	1.000	1.000	1.000	1.000
14	1.000	0.938	1.000	1.000	1.000	0.938
15	1.000	0.938	1.000	0.938	1.000	0.938

A.2 OLMoE-1B-7B

Table 2: Per-foundation probe accuracy across layers, OLMoE-1B-7B.

Layer	Care	Fairness	Liberty	Loyalty	Authority	Sanctity
0	0.938	0.875	0.938	0.938	0.875	0.938
1	0.938	0.875	0.812	0.812	0.812	0.812
2	0.938	0.875	0.875	0.812	0.875	0.812
3	0.938	0.938	0.938	0.875	0.875	0.875
4	0.938	0.938	0.938	1.000	1.000	1.000
5	0.938	1.000	1.000	1.000	1.000	1.000
6	0.938	0.938	1.000	1.000	1.000	1.000
7	1.000	1.000	1.000	1.000	1.000	1.000
8	1.000	1.000	1.000	1.000	1.000	1.000
9	1.000	1.000	1.000	1.000	1.000	1.000
10	1.000	0.938	1.000	1.000	1.000	1.000
11	1.000	1.000	1.000	1.000	1.000	1.000
12	1.000	0.938	1.000	1.000	1.000	1.000
13	1.000	1.000	1.000	1.000	1.000	1.000
14	1.000	0.938	1.000	1.000	1.000	1.000
15	1.000	0.938	1.000	1.000	1.000	1.000

Table 3: Bootstrap direction stability (mean cosine similarity with full-data direction, 200 resamples). Values marked with * fall below the 0.8 stability threshold.

Layer	Care	Fairness	Liberty	Loyalty	Authority	Sanctity
0	0.740*	0.741*	0.768*	0.761*	0.780*	0.793*
1	0.752*	0.765*	0.775*	0.763*	0.780*	0.789*
2	0.774*	0.779*	0.796*	0.785*	0.790*	0.789*
3	0.767*	0.788*	0.791*	0.784*	0.808	0.811
4	0.789*	0.803	0.817	0.796*	0.812	0.819
5	0.799*	0.814	0.812	0.818	0.809	0.830
6	0.807	0.816	0.830	0.819	0.809	0.825
7	0.817	0.811	0.813	0.818	0.830	0.842
8	0.821	0.822	0.822	0.815	0.792*	0.807
9	0.821	0.816	0.832	0.814	0.820	0.803
10	0.823	0.809	0.831	0.821	0.817	0.836
11	0.817	0.802	0.830	0.837	0.833	0.814
12	0.828	0.801	0.831	0.843	0.828	0.820
13	0.825	0.811	0.821	0.817	0.827	0.838
14	0.821	0.823	0.824	0.842	0.826	0.827
15	0.816	0.826	0.803	0.847	0.838	0.852

B Bootstrap Direction Stability Tables

Layers 0–2 have widespread instability (< 0.8): all six foundations are unstable. Layers 3–5 are mixed (2–6 of 6 unstable). Layers 6–15 are mostly stable, with one exception (authority at layer 8, 0.792). Sanctity/degradation is the most stable foundation (13/16 layers above threshold); care/harm is the least stable (10/16).

The stable core (layers 6–15) gives the most reliable geometric measurements. The headline finding (integration signature, effective dimensionality = 5) is confirmed within this range.

C Cosine Similarity Matrices

Full pairwise cosine similarity matrices between the six foundation probe directions at selected layers of OLMo-2 1B.

Table 4: Cosine similarity matrix at layer 0 (peak separation), OLMo-2 1B. Mean off-diagonal = 0.216.

	Care	Fair	Lib	Loy	Auth	Sanc
Care	1.000	0.148	0.189	0.203	0.164	0.201
Fair	0.148	1.000	0.232	0.179	0.224	0.143
Lib	0.189	0.232	1.000	0.273	0.333	0.224
Loy	0.203	0.179	0.273	1.000	0.264	0.219
Auth	0.164	0.224	0.333	0.264	1.000	0.249
Sanc	0.201	0.143	0.224	0.219	0.249	1.000

Table 5: Cosine similarity matrix at layer 7, OLMo-2 1B. Mean off-diagonal = 0.262.

	Care	Fair	Lib	Loy	Auth	Sanc
Care	1.000	0.264	0.221	0.250	0.188	0.229
Fair	0.264	1.000	0.236	0.294	0.292	0.195
Lib	0.221	0.236	1.000	0.317	0.324	0.252
Loy	0.250	0.294	0.317	1.000	0.329	0.242
Auth	0.188	0.292	0.324	0.329	1.000	0.298
Sanc	0.229	0.195	0.252	0.242	0.298	1.000

Table 6: Cosine similarity matrix at layer 15, OLMo-2 1B. Mean off-diagonal = 0.262.

	Care	Fair	Lib	Loy	Auth	Sanc
Care	1.000	0.246	0.200	0.226	0.168	0.195
Fair	0.246	1.000	0.220	0.347	0.278	0.138
Lib	0.200	0.220	1.000	0.352	0.393	0.237
Loy	0.226	0.347	0.352	1.000	0.415	0.220
Auth	0.168	0.278	0.393	0.415	1.000	0.295
Sanc	0.195	0.138	0.237	0.220	0.295	1.000

At layer 0, the highest pairwise cosine similarity is liberty–authority (0.333), followed by liberty–loyalty (0.273). At later layers, the liberty–authority and loyalty–authority pairs consistently show the strongest similarity (0.393 and 0.415 at layer 15). These pairings cross the MFT individualizing/binding boundary, indicating that the model’s inter-framework geometry is organized along empirical distributional axes rather than the theoretical MFT grouping.

D Permutation Tests for MFT Group Structure

We test whether the six foundation probe directions cluster into the MFT-predicted individualizing (care, fairness, liberty) and binding (loyalty, authority, sanctity) groups. The test statistic is the difference between mean within-group cosine similarity and mean between-group cosine similarity. With six foundations split into two groups of three, there are only $\binom{6}{3} = 20$ distinct group assignments, so we enumerate the null distribution exactly rather than resampling; the p -value is the fraction of the 20 partitions whose statistic is $\geq$ the observed value, and is therefore an exact multiple of $1/20$.

Table 7: Exact permutation test for individualizing/binding group structure across layers, OLMo-2 1B (enumeration over all 20 partitions). No layer reaches significance.

Layer	Observed statistic	p -value
0	0.001	0.40
1	−0.014	0.80
2	−0.003	0.70
3	−0.004	0.80
4	−0.004	0.80
5	0.003	0.50
6	−0.002	0.50
7	0.005	0.40
8	0.001	0.50
9	−0.003	0.55
10	−0.003	0.60
11	−0.014	0.80
12	−0.004	0.65
13	0.003	0.40
14	0.000	0.40
15	0.007	0.40

The test does not reach significance at any layer (minimum $p = 0.40$). Exact enumeration can attain $p = 1/20 = 0.05$ when the observed split is the single most extreme of the 20, so significance was reachable; it simply was not observed. The observed statistics are near zero and frequently negative (within-group similarity $<$ between-group similarity), confirming that the model’s inter-framework geometry is not organized along the MFT individualizing/binding axis. This is consistent with the dendrogram analysis (Section 4.3), which shows cross-MFT pairings (care–sanctity, liberty–authority) rather than the predicted group structure.

E Reproducibility

E.1 Hardware and software

All experiments ran on a single MacBook Pro with Apple M4 Pro (24 GB unified memory) using the MPS backend. Software versions: Python 3.13, PyTorch 2.7, Transformers 4.49.

E.2 Runtime

Experiment	Model	Wall time
1–3 (probing + geometry + bootstrap)	OLMo-2 1B	~5 min
5 (dense vs. MoE geometry)	OLMoE-1B-7B	~20 min
6 (geometric trajectory)	OLMo-2 1B (20 ckpts)	~45 min
7 (framework fragility)	OLMo-2 + OLMoE	~25 min

E.3 Reproducibility notes

Probe training. Linear probes are `nn.Linear(2048, 1)` trained with BCE loss and Adam ($\text{lr} = 10^{-2}$) for 50 epochs. No weight decay, no learning rate schedule. Random seed is not fixed across runs; bootstrap analysis (Appendix~B) quantifies direction stability under resampling.

Probing dataset. The 240-pair minimal-pair dataset (40 per MFT foundation) is deterministic and version-controlled. Dataset generation uses Claude Sonnet 4.6 with automated validation gates (embedding similarity, keyword scan, LLM-as-judge filtering); the exact dataset is included in the code repository.

Activation collection. Forward passes use `torch.no_grad()`. Activations are mean-pooled across the sequence dimension at each layer. For OLMoE, activations are collected after the expert combination step (post-routing), not from individual experts.

Code availability. All experiment scripts, the probing dataset, and figure generation code are available at <https://github.com/deepsteer/deepsteer>.

F Causal Validation (Companion Work)

The geometry reported in the main text is read off the representation: it shows where foundation information is decodable. Whether the model *uses* that information during generation is a causal question, taken up in full by companion work (Reblitz-Richardson, 2026a). Here we report the initial causal checks on the OLMo-2~7B foundation directions used throughout this paper, which indicate that the directions are functionally implicated rather than probing artifacts.

Direction ablation. Projecting a foundation’s direction out of the residual stream at a target layer degrades that foundation’s continuations more than the other foundations’. Specificity, the gap between the on-target and off-target mean effect over 48 prompts and the six foundations, is negative at every layer tested and deepens with depth, from -0.12 at layer 4 to -0.32 at layer 14. Removing a foundation’s direction selectively harms that foundation, and the effect is strongest where the directions are most stable. These numbers are on OLMo-2~7B (allenai/OLMo-2-1124-7B), layers 4–14, over 48 prompts (outputs/probe_engineering_7B/direction_ablation_mean_diff.json). The companion causal paper (Reblitz-Richardson, 2026a) runs the fuller treatment on the smaller OLMo-2~1B (allenai/OLMo-2-0425-1B) and reports the same qualitative pattern, mean specificity negative at every layer and deepening with depth (-0.16 , -0.39 , -0.63 at layers 4, 8, 12); the two are consistent companion results at different scales, not competing estimates of one quantity.

Steering injection. Adding α times a foundation’s direction to the residual stream produces a dose-response. Mean specificity rises monotonically with the injection strength, from $+0.08$ at $\alpha = 1$ to $+0.16$, $+0.61$, $+1.85$, and $+3.59$ at $\alpha = 2, 5, 10, 20$. The same direction that decodes a foundation also steers generation toward it, in proportion to the dose.

These results are descriptive rather than a full causal localization; the companion paper ([Reblitz-Richardson, 2026a](#)) reports the complete treatment, including behavioral grounding and sparse autoencoder feature overlap. They establish that the foundation directions in Section 4 correspond to features the model acts on during generation, not only to features that are linearly readable.