

Algorithms for Solving the Minimum Vertex Cover Problem

ALEXANDER WINKLES, DEEPTHI VENKITARAMANAN, and JUNLIN LIU

ACM Reference Format:

Alexander Winkles, Deepthi Venkitaramanan, and Junlin Liu. 2017. Algorithms for Solving the Minimum Vertex Cover Problem. 1, 1, Article 1 (November 2017), 8 pages. <https://doi.org/0000000.0000000>

1 INTRODUCTION

The Minimum Vertex Cover (MVC) problem seeks to find a subset of vertices for a given graph G such that all the said vertices touch all edges of the graph. This is a well known NP Complete problem that has many real world applications including finding phylogenetic trees based on protein domain information [1] or finding where to place bunkers to cover all cities. For this project, our group was tasked with solving the MVC problem using three different approaches: branch-and-bound, local search, and approximation.

1.1 Approximation Algorithm

The approximation approach is one that sacrifices accuracy of the result in favor of speed. Generally, approximation algorithms have a provable guarantee that they will be no worse than $p(n) \times OPT$, where $p(n)$ is some value greater than or equal to 1 that may depend on the size of the problem and OPT is the optimal solution. For the MVC problem, the approximation approach involves arbitrarily picking an edge in the given graph, then removing it and all neighboring edges from the graph. Then a new edge is arbitrarily picked from the remaining ones and the process is repeated until all the edges have been removed. The vertex cover will then be the nodes corresponding to all the arbitrarily picked edges.

1.2 Local Search

In addition to the traditional hill climbing approach, the local search I algorithm has options such as forward stopping when the optimal vertex count is reached, remembering the best solution obtaining so far, growing and shrinking (either direction traversal). The local search approach begins with an initial solution and then tries to obtain the global minima by choosing neighbours and moving to the neighbour with the best eval function. The eval function for the local search approach is the number of edges incident on the vertex that is to be added to the current set of vertices in our current search iteration.

1.3 Branch and Bound

Branch and bound algorithm derives from backtracking strategy for decision problems, which iterates through all the possible solutions in the search space and eliminates some unpromising alternatives from consideration. Branch and bound further refines this idea for optimization problems. It keeps the best solution found so far and computes a lower bound based on this solution. When a solution node for a sub-problem is worse than the lower bound, we consider it as an unpromising solution node and prune it and all its child nodes. Although

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

© 2017 Association for Computing Machinery.

XXXX-XXXX/2017/11-ART1 \$15.00

<https://doi.org/0000000.0000000>

branch and bound algorithm is a general idea for NP-complete problems, how to compute the lower bound has to be customized for each individual application. This strategy reduces the time consumption on searching for solutions and a global optimal solution is guaranteed, but the worst case is still exponential. Therefore, this algorithm can be useful only when the instances are small.

2 PROBLEM

Consider a graph $G = (V, E)$. Formally, a vertex cover V' is a subset of V such that for each $(u, v) \in E$ it follows that either $u \in V'$ or $v \in V'$. This set V' is said to cover the edges of G . For the project at hand, this problem is further complicated by searching for the smallest possible V' that satisfies the above definition. The MVC problem is known to be NP Complete, and as such it requires specialized algorithms such as local search and approximation in order to be solved.

3 RELATED WORK

TBC

4 ALGORITHMS

4.1 Approximation Algorithm

As mentioned above, the approximation algorithm works by arbitrarily picking an edge in the graph, adding its nodes to the solution, then removing the edge and all of its neighboring edges from the graph, and repeating this process until all edges have been removed. In pseudocode, this looks like the following:

ALGORITHM 1: MVC Approx(G)

```

 $C = \{\};$ 
 $E' = E;$ 
while  $E'$  is not empty do
    remove  $e$  in  $E'$  and add its nodes to  $C$ ;
    remove all edges neighboring  $e$  from  $E'$ ;
end
return  $C$ ;

```

This algorithm is inspired by that found in CLRS Chapter 35. The algorithm works by choosing an edge arbitrarily, then adding its nodes to the solution and removing all edges neighboring said nodes. This is done because the nodes added to the solution now cover all the edges, so they do not need to be considered. By repeating this process until every edge has been removed from the graph, this guarantees that the solution will cover all edges in the graph by design. This algorithm is provably a 2-approximation algorithm, which means that any solution found will be no worse than twice the size of the optimal solution.

Because of its structuring, it is not particularly complex and thus fast compared to the other algorithm options. But it also does not give exact solutions except for particular cases, which can be disadvantageous depending on the application of it. As seen in the table below, the approximation algorithm runs extremely quickly, but has high relative error.

4.2 Local Search Algorithm I: Initial Solution and approach

The local search is capable of traversing two ways:

- (1) When the vertices in the current search iteration form a vertex cover, we try to remove a vertex so as to see if a lesser size vertex cover is possible

- (2) When the vertices in current search iteration do not form a vertex cover, we try to add a maximum impact vertex from a random uncovered edge and perform the check for vertex cover once again.

ALGORITHM 2: LocalSearch(G , no_of_iterations, k)

Input: graph $G = (V, E)$, no_of_iterations

Output: vertex cover of G if k = no of vertices **else** optimal vertex coverage obtained so far

gain(v) := no of edges for each vertex $v \in G$;

Circ_deque_len = circular deque of length 100;

$C := \text{ConstructVC}(k)$ // constructs list of size k with vertices sorted according to no of edges incident on them;

while no_of_iterations **do**

 no_of_iterations <- no_of_iterations - 1;

 Edge_set = set of edges covered by C ;

if Edge_set == total_no_of_edges **then**

 Circ_deque_len.append(C .length);

if length of C is the minimum length in Circ_deque_len **then**

 Optimal_soln = C ;

end

 remove a random Vertex from C ;

 Continue;

end

U, V = vertices of a random uncovered edge ;

 Append either U/V to C depending on the number of edges incident on U, V ;

 Return Optimal_soln or C if Optimal_soln is empty;

end

Here the maximum impact vertex is the vertex with most edges incident on it. Random uncovered edge is chosen from the set of edges in the graph that do not have any of its vertices on the current iteration of VC. In order to get a guaranteed VC, we can start with initial solution equal to the total number of vertices and the minimum impact vertices are removed. However, for large graphs this can be quite time consuming - for each VC of specific length almost all other possible permutations are tried. Thus the rate at which the VC size decreases is very low. The optimal strategy is to begin with $\frac{|V|}{2}$ vertices which have the maximum impact which is done in the method ConstructVC. The current iteration vertices list will grow to add more vertices if a VC is not currently found.

4.3 Local Search Algorithm II: Simulated Annealing with random restart

Neighbourhood choice: Choosing a vertex with more number of edges incident to them does not necessarily ensure edge coverage. The second approach allows us to add the vertex with lesser number of edges incident on them with a specific probability. With Simulated Annealing, we can allow exploration at lower temperatures (more chances of adding vertices with lesser vertices incident on them) and at higher temperature, there is more exploitation of the gradient. Thus the probability of choosing a vertex with lesser number of edges incident on them is:

$$P(C, n) = \frac{1}{1 + e^{\frac{\Delta E}{T}}} \quad (1)$$

Where n is the next vertex to be added to current VC vertices. ΔE is the number of edges additionally covered by adding n . T is temperature.

ALGORITHM 3: Local Search II

```

T <- very - high;
C <- random_initial_soution;
while T do
  Monotonically decrease T;
  n <- random_neigh(C);
  Evaluate  $\Delta E$ ;
  Evaluate  $P(C, n)$ ;
  Add n to C with probability  $P(C, n)$ ;
end

```

4.4 Branch and Bound

Branch and bound algorithm keeps the best solution found so far and computes a lower bound based on this solution. When a solution node for a sub-problem is worse than the lower bound, we consider it as an unpromising solution node and prune it and all its child nodes. The solution tree represents all the possible solutions. A sample solution tree for a graph with 4 vertices is given below. When we scan through all the nodes, a lower bound is calculated to determine whether a node and its branch is promising or not. If it is not a potential solution, we will skip this branch and continue our scan.




Fig. 1. Sample solution tree for a graph with four vertices

5 EMPIRICAL EVALUATION

5.1 Approximation Algorithm

See Table 1 for comprehensive evaluation for approximation algorithm.

ALGORITHM 4: Branch and bound

```

Bnb(): //main body;
if len of result + lowerbound() >= len of min so far then
    return;
end
if it is a better global solution then
    Record it as min so far;
    Return;
else
    for all the left items do
        Add it in the solution;
        Call Bnb();
        Remove it in the solution;
    end
end
Lower bound(): //function to compute the lower bound;
LB = 0;
while True do
    Randomly remove two nodes in the same edge;
    LB ++;
    if G has no edge left then
        return LB;
    end
end

```

Table 1. Comprehensive evaluation table for approximation algorithm

Graph	OPT	Approx.	Time (s)	Error
Jazz	158	186	0.094	0.18
Karate	14	22	0.00071	0.57
Football	94	110	0.016	0.17
as-22july06	3303	6026	142.5	0.82
hep-th	3926	5784	51.21	0.47
Star	6909	10536	268.7	0.52
Star2	4542	6786	508.59	0.49
Net Science	899	1224	1.53	0.36
Email	594	834	1.17	0.4
Delaunay	703	960	1.03	0.37
Power	2203	3788	16.96	0.72

5.2 Local Search

See Table 2 for comprehensive evaluation for local search algorithms. We can see from Table 2 that VC can be obtained by increasing the number of iterations for larger graphs if $k = \frac{|V|}{2}$.

Table 2. Comprehensive evaluation table for local search I

Instance	For $K = V /2$				For $K= V $		
	Iters No.	Time	VC	Quality if VC not obtained in <1000 iters	Iters No.	Time	VC
karate	937	0.36	14	Obtained	983	0.38	14
football	952	3.04	99	Obtained	1000	3.12	101
					2000	6.94	99
					3000	10.36	97
jazz	973	10.78	164	Obtained	1000	11.67	182
					2000	24.91	175
					3000	37.15	175
					4000	51.93	170
					5000	65.99	169
delaunay_n10	1000	125.32	720	2996/3056	1000	100.32	972
	2000	244.21	774	3046/3056	2000	250.99	963
	3000	374.3	783	3053/3056	3000	394.77	946
	4000	511.85	787	3055/3056	4000	523.76	934
	5000	620.9	785	3055/3056	5000	633.29	929
	5533	678.46	784	Obtained	6000	797.72	920

5.3 Branch and Bound

See Table 3 for comprehensive evaluation for branch and bound algorithms.

Table 3. Comprehensive evaluation table for branch and bound algorithm

instance ^a	OPT	Time	VC Value	relErr
jazz.graph	158	434.79	165	0.044303797
karate.graph	14	13.46	14	0
football.graph	94	69.73	101	0.074468085
netscience.graph	899	18.77	899	0
email.graph	594	13.5	668	0.124579125
delaunay_n10.graph	703	68.38	798	0.135135135

^aNo result got in 10 mins for other larger graphs.

6 DISCUSSION

6.1 Branch and Bound

For branch and bound algorithm, time consumption varies with lower bounds, scan orders, and coding strategies and many other characteristics. Analysis of different features are listed below:

6.1.1 Lower Bound. Up till now, we have tried three different lower bounds.

- (1) This lower bound uses the idea of approximation algorithm that computes the maximal matching of the graph. Randomly pick one edge from the graph and join the two end nodes of the edge in a set until it becomes a solution for the sub vertex cover problem. The number of nodes in the set is counted as the lower bound. This strategy is easy to code, but it is fairly slow to compute and the bound is also not tight.
- (2) This lower bound computes the maximum matching of the graph. We use networkx API to implement this strategy. Although the lower bound is quite tight compared with Lower Bound 1, it turned out to consume much longer time to compute it in our tests. We cannot afford to compute this lower bound for every solution node. Therefore, this strategy is abandoned.
- (3) Here we designed our own lower bound without referring to the project instructions. First compute the node number difference n of our sub-problem solution and the best solution so far, which means we have to cover the sub-graph with n nodes left or we are done. Then compare the number of edges left and the degree summation of the n nodes left that have the largest degree. If there are more edges than the total degree, then we know this branch is not possible to produce an optimal solution. This lower bound has about the same effect as Lower Bound 1, but it is much faster to compute. Therefore, we will use this lower bound in our final code and the following tests and evaluations are all based on this lower bound. It is also possible to ignore the lower bound. Though it will not waste time on calculating the lower bound, the loss outweighs the gain.

6.1.2 Scan Order. We also tried different scan orders. Scan order matters because we have to prune our solution branches based on current best solution. If we find a relatively good solution earlier, we can dispose more trash solutions earlier. The scan orders that we tested are listed as follows.

- (1) We simply use the number order to scan in the first place and tested with karate.graph. Then we compared the result with the reverse number order. Amazingly, we found that the number order took about 570 seconds while the reverse order took 350 seconds. As the degree of each vertex is randomly distributed, this result implies that the number order has a huge influence on the whole scan process.
- (2) Inspired by the tests for Scan Order 1, here we first sort all the vertices with their degrees and then put the numbers in the solution tree in this order, as the node with larger degree is more likely to appear in the final optimal solution. There is also a benefit for this scan order: when the program cannot reach the optimal solution due to time limitation, this strategy is most likely to provide a satisfying solution. As a result, this scan order is the default order in our code.
- (3) As can be seen in the sample graph, the solution tree is not balanced, which means we can whether scan from the “heavy” end or the “light” end. With tests on karate.graph, scanning from the “heavy” end takes about 570 seconds while starting from the “light” end takes about 1080 seconds. We have not reached a reasonable explanation on this result and all our following tests will scan from the “heavy” end. One possibility is that scanning from the “heavy” end will guarantee to reach a rough solution that can work as a criterion for pruning in the very beginning, while scanning from the “light” end will result in scanning through every solution without pruning anything at the start.

6.1.3 Coding Strategies. TBC (Further report will concentrate on analysis about different coding strategies. We have implement the branch and bound algorithm in three ways, say, DFS with recursion, DFS with stack, and iteration. Any other implementation and analysis depend on the workload in our final season.)

6.1.4 miscellaneous. TBC

7 CONCLUSION

TBC

REFERENCES

- [1] Faisal N Abu-Khzam, Rebecca L Collins, Michael R Fellows, Michael A Langston, W Henry Suters, and Christopher T Symons. 2004. Kernelization Algorithms for the Vertex Cover Problem: Theory and Experiments. *ALENEX/ANALC* 69 (2004).
- [2] Shaowei Cai. 2015. Balance between Complexity and Quality: Local Search for Minimum Vertex Cover in Massive Graphs.. In *IJCAI*. 747–753.

Received November 2017; revised November 2017; accepted December 2017