

Active Directory onboarding in SailPoint

The Real Enterprise Workflow (Simulated)

Instead of using a local hypervisor, you can sign up for a Free Tier account on AWS or Azure. This perfectly mimics a real production setup where identity infrastructure is hosted in a cloud data center.

Here is exactly how the process flows in an organization, mapped out step-by-step:

1. Set up the Corporate Cloud Network: Phase 1.

In AWS or Azure, you create a virtual network (VPC/VNet). This mimics the company's internal server network. You will configure security groups (firewalls) to allow the VA to talk to AD on ports like 389 (LDAP) or 636 (LDAPS).

2. Deploy the Domain Controller: Phase 2.

Spin up a lightweight Windows Server cloud instance (like an AWS t2.micro which fits into the free tier). You log in via Remote Desktop, install Active Directory, and create a fake enterprise domain (e.g., corp.local) with standard test OUs and users.

3. Deploy the SailPoint VA Image: Phase 3.

In an enterprise, you download the VA image (.ova or .vhd) from the SailPoint portal. In AWS/Azure, you launch SailPoint's pre-built machine image into your cloud network.

4. The: Phase 4.

You SSH into the newly booted VA using terminal software (like PuTTY or Git Bash) from your laptop. You will run a command to set a secure console password and enter a Pairing Code generated from your SailPoint Identity Security Cloud (ISC) browser console. This links the cloud infrastructure securely to the SailPoint control plane.

5. The Connection (AD Onboarding): Phase 5.

You log into the SailPoint browser console, go to Sources, and create an Active Directory source. You point it to your cloud VA cluster, type in the private IP address of your Windows cloud server, provide an AD service account credential, and hit Test Connection.

Phase 1 Set up the Corporate Cloud Network

Step 1: Setting up the Corporate Cloud Network in Azure

In a production environment, you never just spin up virtual machines blindly. You must establish a secure Virtual Network (VNet) first. We need a network layout where our Windows AD Domain Controller and our SailPoint Virtual Appliance can safely talk to one another over a private back-channel.

Here is how we will configure the fundamental network components via the Azure Portal.

1. Create the Virtual Network (VNet)

Think of the VNet as your dedicated corporate data center slice inside Azure.

Resource Group: Create a brand new one called rg-sailpoint-lab (keeping everything in one group makes it clean and easy to delete later so you don't get surprise charges).

Name: vnet-corporate-prod

Region: Choose a cost-effective region close to you (e.g., East US or South India).

IP Address Space: Give it a standard corporate CIDR block: 10.0.0.0/16.

2. Segmenting with Subnets

An identity team will always segment infrastructure. We will break our 10.0.0.0/16 block into two distinct subnets:

By default, Azure automatically creates a subnet called default with the range 10.0.0.0/24. We want to modify and add to this to build our structured enterprise network.

Delete the default subnet:

Look at the table under the 10.0.0.0/16 block. You will see the row for default.

Click the Trash Can icon (delete) on the far right of that default row. This clears the slate.

Add Subnet 1 (Active Directory):

Click the + Add a subnet link right above that box.

A side panel will slide out from the right.

Name: Type snet-active-directory

Starting address: It will likely default to 10.0.1.0. Ensure it says 10.0.1.0.

Size: Select /24 (256 addresses) from the dropdown.

Click Add at the bottom of that side panel.

Add Subnet 2 (SailPoint VA):

Click the + Add a subnet link once more.

Name: Type snet-sailpoint-va

Starting address: Change this one to 10.0.2.0.

Size: Select /24 (256 addresses) from the dropdown.

Click Add.

Once you complete these steps, your screen will update to show both snet-active-directory (10.0.1.0/24) and snet-sailpoint-va (10.0.2.0/24) listed neatly under your 10.0.0.0/16 space.

Once those look good, click the Review + create tab at the top to let Azure provision your enterprise network skeleton

Go ahead and click that Create button at the very bottom of the page! Let's finish Phase 1 by creating the Network Security Group (NSG).

Step-by-Step: Creating the Corporate Firewall (NSG)

Search for NSG: Go to the top search bar in the Azure Portal, type in Network security groups, and click on it.

Create a new NSG: Click the + Create button.

Configure Basics:

Subscription: (Leave as default)

Resource Group: Select rg-sailpoint-lab from the dropdown (keep it in the same family!).

Name: Type nsg-identity-tier

Region: Ensure it matches the same region as your VNet (Central India).

Review + Create: Click Review + create at the bottom, and then click Create.

Once that deploys successfully (usually takes less than 10 seconds), click Go to resource.

look at the main overview page of your new nsg-identity-tier, and we will write the explicit enterprise firewall rules to bridge SailPoint and Active Directory!

Right now, you can see the default rules listed under Inbound Security Rules. Note rule 65500: DenyAllInbound. This means that by default, your network is completely locked down from the outside world.

To allow yourself to log into the VMs later and to let SailPoint communicate with Active Directory, we need to add two custom inbound rules, and then associate this firewall with your subnets.

the inbound rules

Step 1: Add the RDP & SSH Management Rule

This rule ensures you can connect to your Windows VM and the SailPoint VA from your laptop.

On the left-hand menu, under Settings, click on Inbound security rules.

Click + Add at the top.

Fill in the panel exactly like this:

Source: Any (Tip: In a real enterprise, this would be restricted to the company VPN IP, but for a lab, Any is fine).

Source port ranges: *

Destination: Any

Service: Custom

Destination port ranges: 3389, 22 (This opens 3389 for Windows Remote Desktop and 22 for Linux/VA terminal access).

Protocol: TCP

Action: Allow

Priority: 100

Name: Allow-Management-RDP-SSH

Click Add at the bottom.

Don't worry about the little orange warning triangle next to it—Azure is just reminding you that opening management ports (3389 and 22) to Any source IP is a security risk, which is completely expected and normal for a sandbox learning lab.

Step 2: Add the SailPoint to AD Rule (The Enterprise Core)

This rule specifically allows the SailPoint VA to read, write, and manage accounts inside Active Directory.

Click + Add again.

Fill in the panel exactly like this:

Source: IP Addresses

Source IP addresses/CIDR ranges: 10.0.2.0/24 (This targets the exact subnet where your SailPoint VA lives).

Source port ranges: *

Destination: IP Addresses

Destination IP addresses/CIDR ranges: 10.0.1.0/24 (This targets your Active Directory subnet).

Service: Custom

Destination port ranges: 389, 636 (Standard LDAP port 389 and Secure LDAPS port 636).

Protocol: TCP

Action: Allow

Priority: 110

Name: Allow-SailPointVA-to-AD-LDAP

Click Add

Once that rule is added, you will see both priority 100 and priority 110 in your table. Final step for Phase 1: wrapping this firewall around your subnets!

Now, we have one final, crucial action to complete Phase 1: Set up the Corporate Cloud Network. Right now, this Network Security Group (nsg-identity-tier) is sitting out in space—it isn't actually attached to our subnets yet. We need to lock down our subnets with it.

Look at the left-hand menu on your current screen under the Settings section. You will see a setting option called Subnets.

Click on Subnets in that left-hand menu.

Click the + Associate button at the top of the page.

In the side panel that slides out:

Virtual network: Select vnet-corporate-prod from the dropdown.

Subnet: Select snet-active-directory.

Click OK at the bottom.

Click the + Associate button one more time.

In the side panel:

Virtual network: Select vnet-corporate-prod.

Subnet: This time, select snet-sailpoint-va.

Click OK.

Phase 1 Is complete! ■

Once both rows show up in your Subnets grid, you have officially completed the network design.

Your infrastructure skeleton perfectly mimics an enterprise environment: you have an isolated network, an identity target zone, a governance zone, and explicit firewall rules ensuring SailPoint can communicate with Active Directory while allowing you to manage both securely.

Explicit

What is explicit? What is the difference between implicit and explicit.

In IT, engineering, and architecture, the difference between explicit and implicit comes down to whether you are stating something directly or letting it happen automatically.

Here is the easiest way to understand the difference:

1. Explicit (Direct and Intentional)

When something is explicit, it means it is clearly stated, intentionally defined, and leaving absolutely no room for doubt.

In your lab right now: You just created an explicit firewall rule for SailPoint (Priority 110). You directly told Azure: "I want traffic from exactly 10.0.2.0/24 to hit 10.0.1.0/24 on ports 389 and 636." You manually wrote it out, gave it a name, and specified the exact numbers.

2. Implicit (Automatic and Hidden)

When something is implicit, it means it is implied, hidden beneath the surface, or happening automatically without you having to spell it out.

In your lab right now: Look back at your NSG screenshot from earlier. Remember rule 65500: DenyAllInbound? That is an implicit rule built into Azure by default. You didn't create it, but it's implied that if you don't write a rule to allow traffic, the system will automatically block it.

A Quick Comparison Table

Why "Explicit" matters for SailPoint

When an identity platform like SailPoint provisions a user into Active Directory, we always prefer explicit configurations. For example, we explicitly map the First Name attribute in SailPoint to the givenName attribute in AD. We don't want the system guessing (implicitly) where the data should go!

Phase 2: Create VM 1 (The Active Directory Domain Controller).

In an enterprise environment, your domain controllers are the keys to the kingdom, so they are built with stability in mind. Since you are on a Pay-As-You-Go subscription, we are going to choose a specific VM size that balances performance with extremely low hourly costs.

Step-by-Step: Provisioning the Windows Server VM

Search for Virtual Machines: At the top search bar of the Azure portal, type Virtual machines and select it.

Create New VM: Click + Create and choose Azure virtual machine.

Basics Tab Configurations:

Resource Group: Select your existing rg-sailpoint-lab.

Virtual machine name: Type vm-corp-dc01 (Enterprise naming standard: Virtual Machine - Corporate - Domain Controller 01).

Region: Central India (Keep it in the exact same region as your network!).

Availability options: Select No infrastructure redundancy required.

Security type: Select Standard.

Image: Select Windows Server 2022 Datacenter: Azure Edition - x64 Gen2 (or standard Windows Server 2019/2022 Datacenter).

Size: Click See all sizes and select B2s (2 vCPUs, 4 GiB memory).

■ Cost Tip: The B2s size costs only a few cents per hour and has just enough RAM to run Active Directory comfortably for a lab.

Administrator Account:

Username: Create a local admin user (e.g., labadmin). Avoid using generic names like "administrator" or "root".

Password: Create a strong password and save it somewhere secure. You will need this to log into the VM.

Inbound Port Rules:

Public inbound ports: Select None.

Why? We already explicitly configured our Network Security Group (nsg-identity-tier) to handle our security. We don't want Azure overriding it here.

6. Networking Tab (CRITICAL STEP)

Click the Next: Disks > then Next: Networking > button at the bottom. Do not skip this, as we must place the VM in the correct subnet we built!

Virtual network: Ensure vnet-corporate-prod is selected.

Subnet: Select snet-active-directory (10.0.1.0/24).

Public IP: Leave it on Create new (it will auto-name it vm-corp-dc01-ip). We need this public IP temporarily so you can RDP into it from your laptop.

NIC network security group: Select Advanced, and in the dropdown below it, pick the nsg-identity-tier firewall we already made.

Step 1: Connect to your VM via Remote Desktop (RDP)

On your local laptop, open the Remote Desktop Connection app (built into Windows, or downloadable as "Microsoft Remote Desktop" if you are on a Mac).

Look at your Azure screenshot for the Public IP address. Type 20.207.202.91 into the Computer field and click Connect.

When prompted for credentials, use the local admin account details you set up earlier:

Username: labadmin (or whatever custom name you provided)

Password: [Your Secret Password]

If a security warning pops up asking about an untrusted certificate, click Yes to proceed. Your virtual server's desktop will load up!

Step 2: Install Active Directory Domain Services (AD DS)

Once the Windows desktop loads, a program called Server Manager will automatically open up. If it doesn't, click the Start menu and open it manually.

In the top-right corner of Server Manager, click Manage ➡ Add Roles and Features.

Click Next continuously through the prompts until you hit the Server Roles tab.

In the list of roles, check the box for Active Directory Domain Services. A popup will appear; click Add Features to confirm.

Click Next through the rest of the default tabs, and finally click Install.

Wait a minute or two for the blue progress bar to finish.

Step 1: Log Back In via RDP

Open your Remote Desktop Connection client again.

Connect to the same public IP address: 20.207.202.91

When the login screen prompts you for credentials, you need to tell Windows explicitly to look at your new domain instead of the local machine. Change the username formatting to this:

Username: CORP\labadmin (or labadmin@corp.local)

Password: [Your Secret Password]

Click Connect.

■■■ Note: The first login after promoting a Domain Controller takes a bit longer than usual (around 2–4 minutes) because Windows is building the NTDS database structures and preparing your new roaming administrator profile. Don't worry if it sits on a "Applying computer settings..." screen for a moment.

Step 2: The Success Verification Check

Once your desktop loads up, open up Server Manager (it usually opens automatically).

Look at the left-hand navigation pane. If the installation was successful, you will see two brand-new services listed in that column:

AD DS (Active Directory Domain Services)

DNS (Domain Name System)

Your corporate Domain Controller is officially alive, healthy, and ready for action.

Now we get to perform the actual Identity Engineering work. Before SailPoint can manage or read anything from Active Directory, we need a clean structure inside our directory, along with a few test employee accounts to pull into our governance lifecycle.

Let's build a clean, enterprise-standard directory structure using Organizational Units (OUs).

Step 1: Open Active Directory Users and Computers (ADUC)

Inside your RDP session, look at the top right corner of Server Manager.

Click on Tools ➡■■ select Active Directory Users and Computers.

A new window will pop open. In the left-hand column, click the little arrow next to your domain name (corp.local) to expand it.

Step 2: Create Your Corporate OUs (The Identity Target)

In an enterprise environment, we never leave corporate users floating in the default "Users" folder. We group them into explicit OUs so that SailPoint can target them cleanly.

Let's create a main corporate container and two sub-containers:

Right-click on corp.local ➡■■ select New ➡■■ Organizational Unit.

Name: Type Corporate

Click OK.

Now, right-click on your brand-new Corporate OU folder ➡■■ select New ➡■■ Organizational Unit.

Name: Type Employees (This is where our standard staff accounts will sit).

Click OK.

Right-click on the Corporate OU folder one more time ➡■■ select New ➡■■ Organizational Unit.

Name: Type Service Accounts (This is where we will store the special account that SailPoint uses to log into AD).

Click OK.

Step 3: Create the SailPoint Service Account

SailPoint needs a standard domain user account to act as its "hands and eyes" inside your network.

Click on your newly created Service Accounts OU.

Right-click in the empty white space on the right side of the screen ➡■■ select New ➡■■ User.

Fill out the details:

First name: SailPoint

Last name: Service

User logon name: svc-sailpoint

Click Next.

Set a strong password for it.

Crucial Enterprise Settings:

☐ Uncheck: User must change password at next logon (Since it's an automated service account, it shouldn't expire).

☒ Check: Password never expires.

Click Next and then click Finish.

Created as below shown in the picture (all highlighted in yellow are created)

Users are created in each folder under Employee.. example shown below

Once employee is created in OU we will move to Phase 3: Deploying the SailPoint Virtual Appliance Skeleton inside your governance subnet! Phase 2 is fully complete.

Phase 3: Deploying the SailPoint Virtual Appliance Skeleton

SailPoint Identity Security Cloud (ISC) uses a lightweight Linux-based Virtual Appliance that acts as an on-premises bridge. It dials outbound to the SailPoint cloud control plane over HTTPS (443) and talks inbound to your Active Directory domain controllers over LDAP/LDAPS (389/636).

Step-by-Step: Provisioning the SailPoint VA Replica

Navigate back to Azure: In your browser tab outside the RDP session, head back to the main Azure Portal.

Search for Virtual Machines: Go to the top search bar, type Virtual machines, and select it.

Create New VM: Click + Create ➡ Azure virtual machine.

Basics Tab Configurations:

Resource Group: Select your existing rg-sailpoint-lab.

Virtual machine name: Type vm-sailpoint-va01.

Region: Central India (Keep it uniform!).

Availability options: No infrastructure redundancy required.

Security type: Select Standard.

Image: Select Ubuntu Server 24.04 LTS - x64 Gen1 (or 22.04 LTS).

Size: Select the same stable D2s_v3 size from the list.

Administrator Account:

Authentication type: Select Password (This makes it much easier to log in and troubleshoot via our RDP jump box later instead of messing with SSH keys).

Username: labadmin (or match your DC name).

Password: [Your Secret Password].

Inbound Port Rules:

Public inbound ports: Select None.

Networking Tab (CRITICAL SEGMENTATION STEP)

Click Next: Disks > then Next: Networking >. We must drop this VM into its designated governance zone!

Virtual network: Ensure vnet-corporate-prod is selected.

Subnet: Change the dropdown to snet-sailpoint-va (10.0.2.0/24).

Public IP: Select None.

NIC network security group: Select Advanced, and pick our existing nsg-identity-tier from the dropdown.

Step 3 Validation Check

Click Review + create at the bottom. Once the green validation pass banner appears, click Create.

It will take a minute or two for Azure to deploy this internal Linux appliance block. Let me know when the deployment finishes successfully, and we will hop back into your Windows Server to perform the ultimate enterprise engineering test: verifying the isolated firewall tunnel between SailPoint and Active Directory!

Feature	Explicit	Implicit
What it means	Clearly defined and spelled out.	Assumed, automatic, or hidden.
Who sets it	You (the engineer).	The System (Azure default settings).
Example	Writing a rule to open port 3389.	Azure blocking everything else by default.

Reference Screenshots

Create virtual network ...

Basics Security Address space Tags Review + create

Virtual network address space

Define the address space of your virtual network with one or more IPv4 or IPv6 address ranges. Create subnets to segment the virtual network address space into smaller ranges for use by your applications. When you deploy resources into a subnet, Azure assigns the resource an IP address from the subnet. [Learn more](#)

☐ Allocate using IP address pools. [Learn more](#)

+ Add a subnet

10.0.0.0/16

Delete address space

Starting address

Size

10.0.0.0

/16

10.0.0.0 - 10.0.255.255

65,536 addresses

Subnets	IP address range	Size	NAT gateway
default	10.0.0.0 - 10.0.0.255	/24 (256 addresses)	-

Add IPv4 address space

Advertised address prefixes

+ Add IPv4 address prefix + Add IPv6 address prefix

Create virtual network ...

Basics Security Address space Tags Review + create

Virtual network address space

Define the address space of your virtual network with one or more IPv4 or IPv6 address ranges. Create subnets to segment the virtual network address space into smaller ranges for use by your applications. When you deploy resources into a subnet, Azure assigns the resource an IP address from the subnet. [Learn more](#)

☐ Allocate using IP address pools. [Learn more](#)

+ Add a subnet

10.0.0.0/16

Delete address space

Starting address

Size

10.0.0.0

/16

10.0.0.0 - 10.0.255.255

65,536 addresses

Subnets	IP address range	Size	NAT gateway
default	10.0.0.0 - 10.0.0.255	/24 (256 addresses)	-

Add IPv4 address space

Advertised address prefixes

+ Add IPv4 address prefix + Add IPv6 address prefix

Create virtual network ...

Basics Security Address space Tags Review + create

Virtual network address space

Define the address space of your virtual network with one or more IPv4 or IPv6 address ranges. Create subnets to segment the virtual network address space into smaller ranges for use by your applications. When you deploy resources into a subnet, Azure assigns the resource an IP address from the subnet. [Learn more](#)

☐ Allocate using IP address pools. [Learn more](#)

+ Add a subnet

10.0.0.0/16

Delete address space

Starting address

Size

10.0.0.0

/16

10.0.0.0 - 10.0.255.255

65,536 addresses

Subnets	IP address range	Size	NAT gateway
---------	------------------	------	-------------

Add a subnet



Select an address space and configure your subnet. You can customize a default subnet or select from subnet templates if you plan to add select services later. [Learn more](#)

Subnet purpose ⓘ Default ▼

Name * ⓘ snet-active-directory

IPv4

Include an IPv4 address space ☒

IPv4 address range ⓘ 10.0.0.0/16 ▼
10.0.0.0 - 10.0.255.255

Starting address * ⓘ 10.0.1.0 ▼ ▲

Size ⓘ /24 (256 addresses) ▼

Subnet address range ⓘ 10.0.1.0 - 10.0.1.255

IPv6

Include an IPv6 address space ☐ This virtual network has no IPv6 address ranges.

Private subnet

Private subnets enhance security by not providing default outbound access. To enable outbound connectivity for virtual machines to access the internet, it is necessary to explicitly grant outbound access. A NAT gateway is the recommended way to provide outbound connectivity for virtual machines in the subnet. [Learn more](#)

Enable private subnet (no default outbound access) ☐

i After March 31, 2026, private subnet will be the default selection for new virtual networks. [Learn more](#)

Security

Simplify internet access for virtual machines by using a network address translation gateway. Filter subnet traffic using a network security group. [Learn more](#)

NAT gateway ⓘ None ▼
[Create new](#)

Select an address space and configure your subnet. You can customize a default subnet or select from subnet templates if you plan to add select services later. [Learn more](#)

Subnet purpose ⓘ Default ▼

Name * ⓘ snet-sailpoint-va

IPv4

Include an IPv4 address space ☒

IPv4 address range ⓘ 10.0.0.0/16 ▼
10.0.0.0 - 10.0.255.255

Starting address * ⓘ 10.0.2.0 ▼ ▲

Size ⓘ /24 (256 addresses) ▼

Subnet address range ⓘ 10.0.2.0 - 10.0.2.255

IPv6

Include an IPv6 address space ☐ This virtual network has no IPv6 address ranges.

Private subnet

Private subnets enhance security by not providing default outbound access. To enable outbound connectivity for virtual machines to access the internet, it is necessary to explicitly grant outbound access. A NAT gateway is the recommended way to provide outbound connectivity for virtual machines in the subnet. [Learn more](#)

Enable private subnet (no default outbound access) ☐

i After March 31, 2026, private subnet will be the default selection for new virtual networks. [Learn more](#)

Security

Simplify internet access for virtual machines by using a network address translation gateway. Filter subnet traffic using a network security group. [Learn more](#)

NAT gateway ⓘ None ▼
[Create new](#)

Create virtual network ...

Basics Security Address space Tags Review + create

☐ Allocate using IP address pools. [Learn more](#)

+ Add a subnet

10.0.0.0/16

Delete address space

Starting address

Size

10.0.0.0

/16

10.0.0.0 - 10.0.255.255

65,536 addresses

Subnets	IP address range	Size	NAT gateway
snet-active-directory	10.0.1.0 - 10.0.1.255	/24 (256 addresses)	-
snet-sailpoint-va	10.0.2.0 - 10.0.2.255	/24 (256 addresses)	-

Add IPv4 address space |

Advertised address prefixes

+ Add IPv4 address prefix + Add IPv6 address prefix

Advertised gateway prefixes let you control route advertisements by specifying which IP address ranges Azure gateways advertise to on premises networks, instead of advertising all virtual network and spoke CIDRs.

Create virtual network ...

 Validation passed

- Basics
- Security
- Address space
- Tags
- Review + create

[View automation template](#)

Basics

Subscription	Trialing
Resource Group	rg-sailpoint-lab
Name	vnet-corporate-prod
Region	Central India

Security

Azure Bastion	Disabled
Azure Firewall	Disabled
Azure DDoS Network Protection	Disabled

Address space

Address space	10.0.0.0/16 (65,536 addresses)
Subnet	snet-active-directory (10.0.1.0/24) (256 addresses)
Subnet	snet-sailpoint-vb (10.0.2.0/24) (256 addresses)

Tags

Home > Network foundation

Network foundation | Network security groups

Check security rule conflicts across network security groups

Suggest a firewall SKU for my network topology

Search

+ Create Manage view Refresh Export to CSV Open query Assign tags Add to service group

Overview

Virtual network

Virtual Network overview

Virtual networks

NAT gateways

Public IP addresses

Network interfaces

Network security groups

Application security groups

Bastions

Route tables

Route servers

Private Link

DNS

Monitoring and management

Filter for any field...

Subscription equals all

Resource Group equals all

Location equals all

Add filter

No network security groups to display

Create a network security group with rules to filter inbound traffic to, and outbound traffic from, virtual machines and subnets.

Create

Learn more

Create network security group

 Running final validation...

Basics Tags Review + create

Basics

Subscription	Trialing
Resource group	rg-sailpoint-lab
Region	Central India
name	nsg-identity-tier

Tags

None

nsg-identity-tier

Network security group

☆

...

How do I create an alert to track firewall metric failures

×

Search

→ Move

🗑️ Delete

🔄 Refresh

🗨️ Give feedback

Overview

Activity log

Access control (IAM)

Tags

Diagnose and solve problems

Resource visualizer

Settings

Monitoring

Automation

Help

Essentials

Resource group (move) : rg-salpoint-lab

Location : Central India

Subscription (move) : Training

Subscription ID : f672ed5d-007b-42ff-b24d-dc78ccbea4fb

Tags (edit) : Add tags

Custom security rules : 0 inbound, 0 outbound

Associated with : 0 subnets, 0 network interfaces

JSON View

Filter by name

Port == all

Protocol == all

Source == all

Destination == all

Action == all

Priority ↑↓	Name ↑↓	Port ↑↓	Protocol ↑↓	Source ↑↓	Destination ↑↓	Action ↑↓	
Inbound Security Rules							
65000	AllowVnetInBound	Any	Any	VirtualNetwork	VirtualNetwork	✔️ Allow	🗑️
65001	AllowAzureLoadBalancerInBound	Any	Any	AzureLoadBalancer	Any	✔️ Allow	🗑️
65500	DenyAllInBound	Any	Any	Any	Any	❌ Deny	🗑️
Outbound Security Rules							
65000	AllowVnetOutBound	Any	Any	VirtualNetwork	VirtualNetwork	✔️ Allow	🗑️
65001	AllowInternetOutBound	Any	Any	Any	Internet	✔️ Allow	🗑️
65500	DenyAllOutBound	Any	Any	Any	Any	❌ Deny	🗑️

Destination IP addresses/CIDR ranges * ⓘ

10.0.1.0/24



Service ⓘ

Custom



Destination port ranges * ⓘ

389,636

Protocol

☐

Any

☒

TCP

☐

UDP

☐

ICMPv4

☐

ICMPv6

Action

☒

Allow

☐

Deny

Priority * ⓘ

110



Name

Allow-SailPointVA-to-AD-LDAP

Description



nsg-identity-tier | Subnets



Network security group

Search



Associate



Overview



Activity log



Access control (IAM)



Tags



Diagnose and solve problems



Resource visualizer



Settings



Inbound security rules



Outbound security rules



Network interfaces



Subnets



Properties



Locks



Search subnets

Name

No results.

Associate subnet



nsg-identity-tier

Virtual network ⓘ

vnet-corporate-prod (rg-sailpoint-lab)▼

Subnet ★ ⓘ

snet-active-directory▼

Associate subnet



nsg-identity-tier

Virtual network ⓘ

vnet-corporate-prod (rg-sailpoint-lab)▼

Subnet ★ ⓘ

snet-sailpoint-va▼

Search



+ Associate

- Overview
- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems

Search subnets	
Name	↑↓ Address range
snet-active-directory	10.0.1.0/24
snet-sailpoint-va	10.0.2.0/24

vm-corp-dc01

Virtual machine

Help me copy this VM in any region

Manage this VM with Azure CLI

Search

Connect

Start

Restart

Stop

Hibernate

Capture

Delete

Refresh

Scale

Open in mobile

Feedback

CLI / PS

Overview

Activity log

Access control (IAM)

Tags

Diagnose and solve problems

Monitor

Resource visualizer

Connect

Networking

Settings

Availability + scale

Security

Backup + disaster recovery

Operations

Monitoring

Automation

Help

Essentials

Resource group (mouse)

Status

Location

Subscription (mouse)

Subscription ID

Operating system

Size

Primary NIC public IP

Virtual network/subnet

DNS name

Health state

Time created

Tags (edit)

Add tags

Properties

Monitoring

Capabilities (8)

Recommendations

Tutorials

Virtual machine

Computer name

Operating system

VM generation

VM architecture

Agent status

Agent version

Hibernation

Host group

Host

Proximity placement group

Colocation status

Networking

Public IP address

Public IP address (IPv6)

Private IP address

Private IP address (IPv6)

Virtual network/subnet

DNS name

Size

Size

vCPUs

vm-corp-dc01 - 20.207.202.91:3389 - Remote Desktop Connection

Server Manager

Add Roles and Features Wizard

Installation progress

Before You Begin

Installation Type

Server Selection

Server Roles

Features

AD DS

Confirmation

Results

View installation progress

Feature installation

Installation started on vm-corp-dc01

Active Directory Domain Services

Group Policy Management

Remote Server Administration Tools

Role Administration Tools

AD DS and AD LDS Tools

Active Directory module for Windows PowerShell

AD DS Tools

Active Directory Administrative Center

AD DS Snap-Ins and Command-Line Tools

You can close this wizard without interrupting running tasks. View task progress or open this page again by clicking Notifications in the command bar, and then Task Details.

Export configuration settings

< Previous

Next >

Close

Cancel

Servers

1

Availability

Events

Performance

BPA results

6/21/2026 11:18 AM

Saved Queries		
CompanyCorp.local		
Builtin		
Computers		
Domain Controllers		
ForeignSecurityPrincipals		
Managed Service Accounts		
Users		
Corporate		
Europe		
Employees		
IT		
HR		
Finance		
Service Accounts		
USA		
Asia		
Employees		
IT		
HR		
Finance		
Service Accounts		

Name	Type	Description
Sailpoint Service	User	

Active Directory Users and Computers

File Action View Help

Saved Queries		
CompanyCorp.local		
Builtin		
Computers		
Domain Controllers		
ForeignSecurityPrincipals		
Managed Service Accounts		
Users		
Corporate		
Europe		
Employees		
IT		
HR		
Finance		
Service Accounts		
USA		
Asia		
Employees		
IT		
HR		
Finance		
Service Accounts		

Name	Type	Description
Priya Reddy	User	
Amit Sharma	User	



nsg-identity-tier | Inbound security rules



Network security group



[+ Add](#) [Hide default rules](#) [Refresh](#) [Delete](#) [Give feedback](#)

Overview

Activity log

Access control (IAM)

Tags

Diagnose and solve problems

Resource visualizer

Settings

Inbound security rules

Outbound security rules

Network interfaces

Network security group security rules are evaluated by priority using the combination of source, source ports, destination, destination ports, and protocol. [Learn more](#)

Port == all

Protocol == all

Sc

Priority ↑↓	Name ↑↓	Port ↑↓
☐ 65000	AllowVnetInBound	Any
☐ 65001	AllowAzureLoadBalancerInBound	Any
☐ 65500	DenyAllInBound	Any

Source ⓘ

IP Addresses

Source IP addresses/CIDR ranges * ⓘ

10.0.2.0/24

Source port ranges * ⓘ

*

Destination ⓘ

IP Addresses

Destination IP addresses/CIDR ranges * ⓘ

10.0.1.0/24

Service ⓘ

Custom

Destination port ranges * ⓘ

389,636

Protocol

☐ Any

☒ TCP

☐ UDP

☐ ICMPv4

☐ ICMPv6

Action

☒ Allow

☐ Deny

 nsg-identity-tier | Inbound security rules

☆ ...



 Search

◦ << + Add  Hide default rules  Refresh  Delete  Give feedback

- Overview
- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems
- Resource visualizer
- Settings
 - Inbound security rules**
 - Outbound security rules
 - Network interfaces
 - Subnets
 - Properties
 - Links

Network security group security rules are evaluated by priority using the combination of source, source port, destination, destination port, and protocol to allow or deny the traffic. A security rule can't have the same priority and direction as an existing rule. You can't delete default security rules, but you can override them with rules that have a higher priority. [Learn more](#) 

 Filter by name

Port == **all** Protocol == **all** Source == **all** Destination == **all** Action == **all**

Priority ↑↓	Name ↑↓	Port ↑↓	Protocol ↑↓	Source ↑↓	Destination ↑↓	Action ↑↓
☐ 100	 Allow-Management-RDP-SSH	3389,22	TCP	Any	Any	 Allow
☐ 65000	AllowVnetInBound	Any	Any	VirtualNetwork	VirtualNetwork	 Allow
☐ 65001	AllowAzureLoadBalancerInBound	Any	Any	AzureLoadBalancer	Any	 Allow
☐ 65500	DenyAllInBound	Any	Any	Any	Any	 Deny