

## CST8259 Web Programming Language II

### Lab 3

#### Objective

- Use .NET utility XSD.EXE and .NET XML serialization classes to process XML files.


#### Due Date

See Brightspace posting for the due date of this lab. To earn 5 points, you are required:

1. Complete the lab as required.
2. Submit your lab work to the Brightspace before the due date.
3. Demo your lab work during the lab session after the due date.

#### Requirements

- Use **XSD.EXE** to generate classes from the XML schema you created in Lab 2, **restaurant\_review.xsd** file. Copy the generated C# file **restaurant\_review.cs** into a folder, say, **Data**, of the ASP.NET MVC Core web application project created below.
- Create an ASP.NET MVC Core web application which has the following functionality
  - 1) On start the page displays the overviews of all restaurants in the XML file **restaurant\_review.xml**:



Restaurant	Food Type	Rating (best=5)	Cost (most expensive=5)	City	Province	
Giovanni's Italia Fine Dinning	Italian	4.00	5.00	Toronto	ON	<a href="#">Edit</a>
Gong's Asian Cuisine	Asian	5.00	2.50	Montreal	QC	<a href="#">Edit</a>
Baker Street TexMex Grill	Mexican	3.00	2.50	Ottawa	ON	<a href="#">Edit</a>

Hints:

- a. Create a view model class for this view:

```
public class RestaurantOverviewViewModel
{
    public int Id { get; set; }

    [Display(Name = "Rataurant")]
    public string Name { get; set; }

    [Display(Name = "Food Type")]
    public string FoodType { get; set; }


    [Display(Name = "Rating (best=5)")]
    public decimal Rating { get; set; }

    [Display(Name = "Cost (most expensive=5)")]
    public decimal Cost { get; set; }

    [Display(Name = "City")]
    public string City { get; set; }

    [Display(Name = "Province")]
    public string ProvinceState { get; set; }
}
```

- b. In Visual Studio, generate a view binding to list of above view model objects:



The screenshot shows the 'Add Razor View' dialog box. The 'View name' field contains 'Index'. The 'Template' dropdown is set to 'List'. The 'Model class' dropdown is set to 'RestaurantOverviewViewModel (Lab3.Models)'. Under the 'Options' section, the 'Create as a partial view' checkbox is unchecked, while 'Reference script libraries' and 'Use a layout page' are checked. There is a text box for a layout page name and a button to browse. At the bottom are 'Add' and 'Cancel' buttons.

- c. Create a list of **RestaurantOverviewViewModel** with the data retrieved from **restaurant\_review.xml**. You can use the sequence of a restaurant in the XML file as the value of **Id** property or you can use the id attribute if the restaurants in your XML have this attribute.

You can use `Path.GetFullPath(...)` method to get a full path of your **restaurant\_review.xml** file from its relative path to the root of the website, for example:

```
string xmlFilePath = Path.GetFullPath("Data/restaurant_review.xml");
```

when **restaurant\_review.xml** is inside the **Data** folder under application root.

- d. Pass the list as the model object when showing the view
- e. Edit link can have the restaurant's Id as the value of attribute **asp-route-id**

```
<a asp-action="Edit" asp-route-id="@item.Id">Edit</a>
```

- 2) For each restaurant, there is an **"Edit"** link which leads the user to a view to edit the data of the restaurant (for simplicity, we only edit a few data items):

The screenshot shows a web browser window titled 'Edit - Lab3' with the address bar displaying 'localhost:50324/Home/Edit/0'. The page has a navigation bar with 'Lab3', 'Home', and 'Privacy' links. The main heading is 'Edit'. Below it, there is a form with the following fields:

- Restaurant Name: Giovanni's Italia Fine Dinning
- Street Address: 2100 Lakeview Road
- City: Toronto
- Province: ON (dropdown menu)
- Postal Code: K1K 1K1
- Summary: Giovanni's Italia Fine Dinning is a completely restored Victorian stone house and offers a warm and elegant atmosphere and gracious service
- Rating (1 to 5): 4.00

A blue 'Save' button is located at the bottom left of the form.

## Hints:

- a) Create an action method take the restaurant id as its parameter:

```
public IActionResult Edit(int? id)
{ ... }
```

Use **id** as the index to find the restaurant in the object deserialized from your **restaurant\_review.xml** file. Set the property values of the view model object defined next with the data of the found restaurant.

- b) Create a view model for this view:

```
public class RestaurantEditViewModel
{
    public int Id { get; set; }

    [Display(Name="Restaurant Name")]
    public string Name { get; set; }

    [Required]
    [Display(Name = "Street Address")]
    public string StreetAddress { get; set; }

    [Required]
    [Display(Name = "City")]
    public string City { get; set; }
    [Display(Name = "Province")]
    public StateProvinceType ProvinceState { get; set; }

    [Required]
    [RegularExpression(@"^[a-zA-Z]\d[a-zA-Z](\s)*\d[a-zA-Z]\d$",
        ErrorMessage = "Must be in the form of A1A 1A1")]
    [Display(Name = "Postal Code")]
    public string PostalZipCode { get; set; }

    [Required]
    [Display (Name="Summary")]
    public string Summary { get; set; }

    [Required]
    [Range(1, 5)]
    [Display(Name = "Rating (1 to 5)")]
    public decimal Rating { get; set; }
}
```

**StateProvinceType** above is an **enum** generated by XSD.EXE from my restaurant\_review.xsd schema. Replace it with the **enum** for provinces generated from your **restaurant\_review.xsd** schema.

- c) Generate a view binding to the view model. Change the input field for the Id to hidden, the input field for Summary to text area and the input field for Province to dropdown.
- d) For simplicity, the Province dropdown in the view only shows the Simples of the provinces, not the full names of the provinces. You can populate the dropdown from an **enum** and bind the selected provinces as:

```
<select asp-for="ProvinceState"
        asp-items="Html.GetEnumSelectList<StateProvinceType>()"
        class="form-control">
</select>
```

- 3) After click save button, the application saves the changes made to the restaurant and back to the overview page reflecting the modified data of the restaurant:

Overview - Lab3

localhost:50324

Update

Lab3 Home Privacy

Restaurants Overview

Rataurant	Food Type	Rating (best=5)	Cost (most expensive=5)	City	Province	
Giovanni's Italia Fine Dinning	Italian	4.00	5.00	Toronto	MB	<a href="#">Edit</a>
Asian Cuisine	Asian	3.00	2.50	Montreal	QC	<a href="#">Edit</a>
Baker Street TexMex Grill	Mexican	3.00	2.50	Ottawa	ON	<a href="#">Edit</a>

## Hints

- a) Create a [HttpPost] annotated action method which takes a `RestaurantEditViewModel` object as its parameter:

```
[HttpPost]
public IActionResult Edit(RestaurantEditViewModel rsVM)
{... ...}
```

- b) Use Id property of the view model object as the index to find the restaurant being edited.
- c) After completion, my Visual Studio solution have the following structure, yours may be slightly different:

