



AQUA FILTRATION SYSTEM

GSTIN: 06DMUPS2289L1ZZ | Since 2017

Our Online Brand




WTPeSTORE™

ZeroScale

EFFLUENT TREATMENT PLANTS

PRODUCT CATALOGUE — ETP SERIES



WTPeSTORE

ES 40 kld ETP PLANT
model no - ZS-ETP-40KLD



WTPeSTORE | Premium Water Solutions

ZS-ETP-05KLD • ZS-ETP-10KLD • ZS-ETP-20KLD • ZS-ETP-30KLD • ZS-ETP-40KLD

Powered by **AQUA FILTRATION SYSTEM** | Faridabad (HR) | Since 2017

Advertisement by **WTPeSTORE™** — www.wtpestore.co.in



ABOUT ZEROSCALE ETP SYSTEMS

ZeroScale Effluent Treatment Plants (ETP Series) are biological wastewater treatment systems that reduce BOD, COD, and suspended solids from domestic and light-industrial effluent before discharge or reuse. Extended aeration, MBBR, and SBR technologies are matched to each capacity, with sludge dewatering and optional tertiary treatment for higher-quality output. The ETP series covers five capacities — from 5 KLD for small establishments to 40 KLD for large industrial units and townships — so every daily effluent volume is matched to the right plant.

POWERED BY AQUA FILTRATION SYSTEM

Aqua Filtration System has been supplying water treatment equipment — RO plants, water softeners, DM plants, and dosing systems — from Faridabad, Haryana since 2017. Every ZeroScale unit is manufactured, installed, and serviced under the Aqua Filtration System quality and after-sales network.

WHY CHOOSE A ZEROSCALE ETP?

- ✓ Biological treatment (EASP/MBBR/SBR) matched to each capacity for consistent BOD/COD reduction
- ✓ Corrosion-free RCC/FRP tank construction rated for continuous duty
- ✓ Diffused aeration blowers sized for reliable oxygen transfer at every scale
- ✓ Sludge drying bed or filter press dewatering, scaled to daily sludge load
- ✓ Optional tertiary treatment (PSF + ACF + chlorination) for reuse-grade output
- ✓ Scales from 5 KLD (small establishments) to 40 KLD (large industrial units/townships)
- ✓ Backed by Aqua Filtration System's installation and after-sales service network

CONTENTS

- 1. ZS-ETP-05KLD** — Compact ETP for Small Hotels & Housing Societies
- 2. ZS-ETP-10KLD** — ETP for Mid-Size Hotels & Apartment Complexes
- 3. ZS-ETP-20KLD** — ETP for Large Housing Societies, Hospitals & Malls
- 4. ZS-ETP-30KLD** — ETP for Large Institutions & Townships
- 5. ZS-ETP-40KLD** — High-Capacity ETP for Large Industrial Units & Townships



MODEL ZS-ETP-05KLD

Compact ETP for Small Hotels, Hostels & Small Housing Societies



Description

The ZeroScale ZS-ETP-05KLD is a compact effluent treatment plant sized for small hotels, hostels, and small housing societies that need to treat domestic/light-industrial wastewater before discharge or reuse. Extended aeration biological treatment breaks down organic load, and a settling stage separates treated water from sludge, delivering effluent that meets standard discharge norms.

Rated Capacity: 5 KLD

Technical Specifications

Rated Capacity	5 KLD (Kilolitres Per Day)
Treatment Technology	Extended Aeration Activated Sludge Process (EASP)
Raw Effluent BOD (Inlet)	Up to 300 mg/l
Treated Water BOD (Outlet)	< 30 mg/l (tertiary treatment for further reduction)
Raw Effluent COD (Inlet)	Up to 800 mg/l
Treated Water COD (Outlet)	< 250 mg/l
TSS Removal Efficiency	> 90%
Retention Time (Aeration)	18 – 24 Hours
Aeration System	1 HP Air Blower with Diffused Aeration
Tank Construction	RCC / FRP Prefab Skid
Sludge Management	Sludge Drying Bed
Tertiary Treatment	Pressure Sand Filter + Activated Carbon Filter (optional)
Control Panel	Semi-Automatic
Recommended Use	Small Hotels, Hostels, Small Housing Societies, Small Factories

Installation, commissioning & annual maintenance by Aqua Filtration System, Faridabad • Mob: 9910646950



MODEL ZS-ETP-10KLD

ETP for Mid-Size Hotels, Schools & Apartment Complexes



Description

The ZeroScale ZS-ETP-10KLD steps up blower and aeration capacity to treat higher daily effluent volumes from mid-size hotels, schools, and apartment or commercial complexes. The extended aeration process holds BOD and COD reduction steady even as inflow patterns vary through the day.

Rated Capacity: 10 KLD

Technical Specifications

Rated Capacity	10 KLD (Kilolitres Per Day)
Treatment Technology	Extended Aeration Activated Sludge Process (EASP)
Raw Effluent BOD (Inlet)	Up to 300 mg/l
Treated Water BOD (Outlet)	< 30 mg/l (tertiary treatment for further reduction)
Raw Effluent COD (Inlet)	Up to 800 mg/l
Treated Water COD (Outlet)	< 250 mg/l
TSS Removal Efficiency	> 90%
Retention Time (Aeration)	16 – 20 Hours
Aeration System	2 HP Air Blower with Diffused Aeration
Tank Construction	RCC / FRP Prefab Skid
Sludge Management	Sludge Drying Bed / Filter Press (optional)
Tertiary Treatment	Pressure Sand Filter + Activated Carbon Filter (optional)
Control Panel	Semi-Automatic
Recommended Use	Mid-Size Hotels, Schools, Apartments, Commercial Complexes

Installation, commissioning & annual maintenance by Aqua Filtration System, Faridabad • Mob: 9910646950



MODEL ZS-ETP-20KLD

ETP for Large Housing Societies, Hospitals & Malls



Description

The ZeroScale ZS-ETP-20KLD is built for large housing societies, hospitals, and malls generating higher and more variable effluent loads. A PLC-based semi-automatic panel and filter-press sludge dewatering keep the plant running with minimal manual intervention.

Rated Capacity: 20 KLD

Technical Specifications

Rated Capacity	20 KLD (Kilolitres Per Day)
Treatment Technology	EASP / MBBR (Moving Bed Biofilm Reactor)
Raw Effluent BOD (Inlet)	Up to 350 mg/l
Treated Water BOD (Outlet)	< 30 mg/l (tertiary treatment for further reduction)
Raw Effluent COD (Inlet)	Up to 700 mg/l
Treated Water COD (Outlet)	< 250 mg/l
TSS Removal Efficiency	> 92%
Retention Time (Aeration)	14 – 18 Hours
Aeration System	3 HP Air Blower with Diffused Aeration
Tank Construction	RCC (Civil Constructed)
Sludge Management	Filter Press
Tertiary Treatment	Pressure Sand Filter + Activated Carbon Filter + Chlorination
Control Panel	PLC-Based Semi-Automatic
Recommended Use	Large Housing Societies, Hospitals, Malls, Institutions

Installation, commissioning & annual maintenance by Aqua Filtration System, Faridabad • Mob: 9910646950



MODEL ZS-ETP-30KLD

ETP for Large Institutions, Industrial Units & Townships



Description

The ZeroScale ZS-ETP-30KLD is engineered for large institutions, industrial units, and townships with high daily effluent volumes. MBBR/SBR biological treatment, automatic filter-press sludge dewatering, and a fully automatic PLC panel deliver reliable, low-maintenance operation at scale.

Rated Capacity: 30 KLD

Technical Specifications

Rated Capacity	30 KLD (Kilolitres Per Day)
Treatment Technology	MBBR / SBR (Sequential Batch Reactor)
Raw Effluent BOD (Inlet)	Up to 350 mg/l
Treated Water BOD (Outlet)	< 30 mg/l (tertiary treatment for further reduction)
Raw Effluent COD (Inlet)	Up to 700 mg/l
Treated Water COD (Outlet)	< 250 mg/l
TSS Removal Efficiency	> 92%
Retention Time (Aeration)	12 – 16 Hours
Aeration System	5 HP Air Blower with Diffused Aeration
Tank Construction	RCC (Civil Constructed)
Sludge Management	Automatic Filter Press
Tertiary Treatment	Pressure Sand Filter + Activated Carbon Filter + Chlorination
Control Panel	PLC-Based Fully Automatic
Recommended Use	Large Institutions, Industrial Units, Townships, Large Commercial Complexes

Installation, commissioning & annual maintenance by Aqua Filtration System, Faridabad • Mob: 9910646950



MODEL ZS-ETP-40KLD

High-Capacity ETP for Large Industrial Units, Townships & Commercial Complexes



Description

The ZeroScale ZS-ETP-40KLD is the flagship of the ETP range, built for large industrial units, townships, and commercial complexes generating the highest daily effluent volumes in the series. A larger MBBR/SBR biological stage, higher-duty aeration blower, and automatic filter-press dewatering keep the plant running steadily under continuous high-load conditions with minimal operator intervention.

Rated Capacity: 40 KLD

Technical Specifications

Rated Capacity	40 KLD (Kilolitres Per Day)
Treatment Technology	MBBR / SBR (Sequential Batch Reactor)
Raw Effluent BOD (Inlet)	Up to 350 mg/l
Treated Water BOD (Outlet)	< 30 mg/l (tertiary treatment for further reduction)
Raw Effluent COD (Inlet)	Up to 700 mg/l
Treated Water COD (Outlet)	< 250 mg/l
TSS Removal Efficiency	> 92%
Retention Time (Aeration)	10 – 14 Hours
Aeration System	7.5 HP Air Blower with Diffused Aeration
Tank Construction	RCC (Civil Constructed)
Sludge Management	Automatic Filter Press
Tertiary Treatment	Pressure Sand Filter + Activated Carbon Filter + Chlorination
Control Panel	PLC-Based Fully Automatic
Recommended Use	Large Industrial Units, Townships, Group Housing Societies, Large Commercial Complexes

Installation, commissioning & annual maintenance by Aqua Filtration System, Faridabad • Mob: 9910646950



AQUA FILTRATION SYSTEM


GSTIN: 06DMUPS2289L1ZZ | Since 2017

Our Online Brand



WTPeSTORE™

SHOP ONLINE



WTPeSTORE™

Powered by Aqua Filtration System

[Water Treatment Products Online](#) | [RO Plants](#) | [Water Softeners](#) | [Sand Filters](#) | [Spares](#)

www.wtpestore.co.in

CONTACT & COMPANY DETAILS

Aqua Filtration System

B-198, Royal Plaza, Near Domino's, Green Field, Faridabad – 121001 (Haryana)

Phone: 0129-4340856 | Mob: 9910646950 | WhatsApp: 9899193589

Email: info@aquafiltrationsystem.in | GSTIN: 06DMUPS2289L1ZZ

Websites: aquafiltrationsystem.in | zeroscale.co.in | wtpestore.co.in