

```

⟨program⟩ → [⟨metas⟩] ⟨object⟩ EOF
⟨metas⟩ → ⟨meta⟩ { EOF ⟨meta⟩ } EOP
⟨comment⟩ → ⟨commentary⟩ EOL
⟨commentoptional⟩ → { ⟨comment⟩ }
⟨object⟩ → (⟨commentoptional⟩ ⟨masterbody⟩)
| ⟨bound⟩
⟨bound⟩ → ⟨commentoptional⟩ (⟨application⟩ | ((⟨method⟩ | ⟨just⟩) (⟨onameortname⟩ | ⟨aphi⟩) EOL))
⟨tbound⟩ → ⟨commentoptional⟩ (⟨tapplication⟩ | (((⟨method⟩ | ⟨just⟩) ⟨tname⟩ EOL))
⟨tsubmaster⟩ → ⟨commentoptional⟩ ⟨tmasterbody⟩
⟨submaster⟩ → ⟨commentoptional⟩ ⟨masterbody⟩
⟨masterbody⟩ → ⟨formation⟩ | ⟨atom⟩ | (⟨hanonym⟩ ⟨onameortname⟩ EOL)
⟨tmasterbody⟩ → ⟨tformation⟩ | ⟨atom⟩ | (⟨hanonym⟩ ⟨tname⟩ EOL)
⟨just⟩ → ⟨beginner⟩ | ⟨finisher⟩
⟨atom⟩ → ⟨voids⟩ ⟨suffix⟩ "␣" "?" ⟨testsoreol⟩
⟨formation⟩ → ⟨voids⟩ ⟨onameortname⟩ ⟨innersoreol⟩
⟨tformation⟩ → ⟨voids⟩ ⟨tname⟩ ⟨innersoreol⟩
⟨testsoreol⟩ → ⟨tests⟩ | EOL
⟨innersoreol⟩ → ⟨inners⟩ | EOL
⟨inners⟩ → EOL TAB (⟨bound⟩ | ⟨submaster⟩) { (⟨bound⟩ | ([EOL] ⟨submaster⟩) ) } UNTAB
⟨tests⟩ → EOL TAB (⟨tbound⟩ | ⟨tsubmaster⟩) { (⟨tbound⟩ | ([EOL] ⟨tsubmaster⟩) ) } UNTAB
⟨voids⟩ → "[" [⟨void⟩ { "␣" ⟨void⟩ } "]" "
⟨void⟩ → ⟨name⟩ | "@
⟨application⟩ → (⟨happlicationextended⟩ ⟨onameortname⟩ EOL)
| ⟨vapplication⟩
⟨tapplication⟩ → (⟨happlicationextended⟩ ⟨tname⟩ EOL)
| ⟨tvapplication⟩
⟨happlication⟩ → (⟨happlicationhead⟩ ⟨happlicationtail⟩)
| ⟨happlicationreversed⟩
⟨happlicationreversedhead⟩ → ⟨reversed⟩ "␣" ⟨happlicationreversedfirst⟩
⟨happlicationextended⟩ → (⟨happlicationheadextended⟩ ⟨happlicationtail⟩)
| ⟨happlicationreversed⟩
⟨onlyaphi⟩ → ⟨happlicationheadextended⟩ ⟨happlicationtail⟩ ⟨aphi⟩
⟨aphi⟩ → "␣" ">" ">" "␣" ⟨voids⟩
⟨happlicationreversed⟩ → ⟨happlicationreversedhead⟩ [⟨happlicationtail⟩]
⟨happlicationhead⟩ → ⟨hmethod⟩ | ⟨applicable⟩
⟨happlicationheadextended⟩ → ⟨vmethod⟩ | ⟨happlicationhead⟩
⟨applicable⟩ → "*" | ⟨name⟩ | "@
⟨happlicationargunbound⟩ → "␣" ⟨happlicationarg⟩
⟨happlicationtailscoped⟩ → { ⟨happlicationargunbound⟩ } "␣" ⟨happlicationargscoped⟩
⟨happlicationtail⟩ → { ⟨happlicationargunbound⟩ ⟨as⟩ }+ | { ⟨happlicationargunbound⟩ }+
⟨happlicationreversedfirst⟩ → ⟨happlicationarg⟩
⟨happlicationarg⟩ → ⟨just⟩ | ⟨hmethod⟩ | ⟨scope⟩
⟨happlicationargscoped⟩ → ⟨voids⟩ ⟨aname⟩ ⟨innersoreol⟩
⟨vapplication⟩ → (⟨vapplicationhead⟩ ⟨onameortname⟩ ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨onameortname⟩ ⟨vapplicationargsreversed⟩)
⟨tvapplication⟩ → (⟨vapplicationhead⟩ ⟨tname⟩ ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨tname⟩ ⟨vapplicationargsreversed⟩)
⟨vapplicationhead⟩ → ⟨applicable⟩ | ⟨hmethod⟩ | ⟨vmethod⟩ | ⟨compactarray⟩
⟨compactarray⟩ → "$" | "QQ" | ⟨name⟩ { "." ⟨name⟩ } "␣" "*" [(int)]
⟨vapplicationargs⟩ → EOL TAB ⟨vapplicationargsspecific⟩ UNTAB
⟨vapplicationargsreversed⟩ → EOL TAB ⟨vapplicationargunbound⟩ [⟨vapplicationargsspecific⟩] UNTAB
⟨vapplicationargsspecific⟩ → { ⟨vapplicationargbound⟩ }+ | { ⟨vapplicationargunbound⟩ }+
⟨vapplicationargbound⟩ → (⟨vapplicationargboundcurrent⟩ EOL)
| ⟨vapplicationargboundnext⟩
⟨vapplicationargboundcurrent⟩ → ( ( "(" ⟨happlicationextended⟩ ")" ) | ⟨just⟩ | ⟨method⟩ ⟨as⟩ [(oname)] ) | (⟨commentoptional⟩ "(" ⟨hanonym⟩ ")" ⟨as⟩ [(fname)] )
⟨vapplicationargboundnext⟩ → (⟨commentoptional⟩ ⟨voids⟩ ⟨as⟩ [(fname)] ⟨innersoreol⟩) | (⟨vapplicationhead⟩ ⟨as⟩ [(oname)] ⟨vapplicationargs⟩) | (⟨reversed⟩ ⟨as⟩ [(oname)] ⟨vapplicationargsreversed⟩)
⟨vapplicationargunbound⟩ → (⟨onlyaphi⟩ | (⟨vapplicationargunboundcurrent⟩ [(aphi)] EOL)
| ⟨vapplicationargunboundnext⟩
⟨vapplicationargunboundcurrent⟩ → (⟨happlicationextended⟩ | ⟨just⟩ | ⟨method⟩ [(oname)] ) | (⟨commentoptional⟩ ⟨hanonym⟩ [(fname)] )
⟨vapplicationargunboundnext⟩ → ⟨formationnamed⟩ | (⟨vapplicationhead⟩ [(oname) | ⟨aphi⟩] ⟨vapplicationargs⟩) | (⟨reversed⟩ [(oname)] ⟨vapplicationargsreversed⟩) | (⟨happlicationhead⟩ | ⟨happlicationreversedhead⟩ ⟨happlicationtailscoped⟩)
⟨formationnamed⟩ → ⟨commentoptional⟩ ⟨voids⟩ [(fname)] ⟨innersoreol⟩
⟨hformation⟩ → ⟨voids⟩ { ⟨hanonyminner⟩ }+
⟨hanonym⟩ → ⟨hformation⟩ | (⟨hmethod⟩ | ⟨happlication⟩ | ⟨hformation⟩ | ⟨just⟩ { ⟨onlyphitail⟩ }+ )
⟨onlyphitail⟩ → ⟨arrow⟩ ⟨voids⟩
⟨hanonyminner⟩ → "␣" "(" (⟨hmethod⟩ | ⟨happlication⟩ | ⟨hanonym⟩ | ⟨just⟩) ⟨oname⟩ ")"
⟨method⟩ → ⟨hmethod⟩ | ⟨vmethod⟩
⟨hmethod⟩ → (⟨just⟩ | ⟨scope⟩) { ⟨methodtail⟩ }+
⟨vmethod⟩ → (⟨vmethodheadvapplication⟩ | ( ( ⟨just⟩ | ⟨hanonym⟩ ) [(oname)] EOL | ⟨formationnamed⟩) ⟨methodtail⟩ { ⟨vmethodheadapplicationtail⟩ ⟨methodtail⟩ }
⟨vmethodheadapplicationtail⟩ → [(oname)] ⟨vapplicationargs⟩ | EOL | (⟨happlicationtail⟩ [(oname)] EOL)
⟨vmethodheadvapplication⟩ → (⟨applicable⟩ | ⟨hmethod⟩ [(oname)] ⟨vapplicationargs⟩) | (⟨reversed⟩ [(oname)] ⟨vapplicationargsreversed⟩)
⟨methodtail⟩ → "." (⟨finisher⟩ | ( " " (int) ) )
⟨beginner⟩ → "*" | "Q" | "QQ" | "$" | ⟨data⟩
⟨finisher⟩ → ⟨name⟩ | "@ | "^
⟨reversed⟩ → (⟨finisher⟩ | ( " " (int) ) ) "."
⟨aname⟩ → ">" ">" [!"]
⟨fname⟩ → ⟨oname⟩ | ("␣" ⟨aname⟩)
⟨onameortname⟩ → ⟨oname⟩ | ⟨tname⟩
⟨oname⟩ → ⟨suffix⟩ [!"]
⟨tname⟩ → ⟨tarrow⟩ ("@" | ⟨name⟩)
⟨tarrow⟩ → "␣" "+" ">" "␣"
⟨suffix⟩ → ⟨arrow⟩ ("@" | ⟨name⟩) [!"]
⟨arrow⟩ → "␣" ">" "␣"
⟨scope⟩ → "(" (⟨happlication⟩ | ⟨hanonym⟩) ")"
⟨as⟩ → ":" (⟨name⟩ | (int))
⟨data⟩ → ⟨bytes⟩ | ⟨text⟩ | ⟨string⟩ | (int) | (float) | (hex)
⟨commentary⟩ → "#" [ [^\\r\\n] ] [^\\r\\n\\t] ]
⟨meta⟩ → "+" ⟨name⟩ { "␣" [^\\t\\r\\n] }+
⟨indent⟩ → "␣" "␣"
⟨linebreak⟩ → ["\\r" "\\n"
⟨byte⟩ → [0-9A-F] [0-9A-F]
⟨empty_bytes⟩ → "_" "_"
⟨line_bytes⟩ → ⟨byte⟩ { "-" ⟨byte⟩ }+
⟨bytes⟩ → ⟨empty_bytes⟩ | (⟨byte⟩ "-" | (⟨line_bytes⟩ { "-" EOL ⟨line_bytes⟩ } )
⟨escape_sequence⟩ → "\\{" [b t n f r "' \\ { } ] ( [ [0-3] [0-7] [0-7] ] | ( { "u" }+ ⟨byte⟩ ⟨byte⟩ ) )
⟨string⟩ → DQ { [^"\\{ } \\r\\n] | ⟨escape_sequence⟩ } DQ
⟨int⟩ → [ ("+" | "-") ] ("0" | ([0] [1-9] { [0-9] } ) )
⟨exponent⟩ → ("e" | "E") [ ("+" | "-") ] { [0-9] }+
⟨float⟩ → [ ("+" | "-") ] { [0-9] }+ "." { [0-9] }+ [⟨exponent⟩]
⟨hex⟩ → "0x" { [0-9a-fA-F] }+
⟨name⟩ → [a-z] [ [^_,.!' : ; ! ?] []-] (\\r\\n\\t\\xF335]
⟨text⟩ → DQ DQ DQ ["\\r" "\\n" { [^\\{ } ] | ⟨escape_sequence⟩ } ] DQ DQ DQ

```