DIGITAL RELICS

ARCHIVE DIVISION

TECHNICAL SPECIFICATIONS // INTERNAL OPERATIONAL DOCUMENT

CLASSIFICATION	OPEN ACCESS
ARCHIVE REF	DR-ARCH-2274
ISSUING BODY	DIGITAL RELICS ARCHIVE DIVISION
OPERATOR	ManicWebmaster Archive Systems
OPERATOR TERMINAL	manicwebmaster.com/digital-relics-archive/
DOC STATUS	ACTIVE
LAST UPDATED	2274.05.07
VERSION	1.0

01 // ARCHIVE OVERVIEW

The DIGITAL RELICS Archive is the primary repository for recovered physical and signal-emitting artifacts sourced from post-operational technological strata. Its mandate covers stabilization, formal cataloging, and continuous passive observation of dormant field hardware, memory-dense objects, and unclassified infrastructure components.

The archive operates under a standing observation directive. All entries are monitored for spontaneous signal re-engagement, structural decay, or anomalous residue fluctuation. No active intervention protocol is authorized without a RESTRICTED-tier clearance event trigger.

Current operating status: ACTIVE. System integrity: NOMINAL. Entry count: 012. Origin data completeness: 0.0%.

02 // ARCHIVE INFRASTRUCTURE

HOSTING & DELIVERY

The archive operates on a hardened static distribution model. Assets are served as immutable memory objects from edge-cached nodes to ensure availability without exposing writable surfaces. No server-side execution layer is present. Injection and post-recovery modification of origin data are structurally prevented.

SIGNAL VERIFICATION

Each cataloged asset passes a 64-step verification protocol confirming hash alignment against the source object before terminal display. Bit-density variance beyond threshold triggers an automatic container lock and flags the entry for manual audit. Verification status is embedded in the display layer of each entry.

ACCESS CLASSIFICATION TIERS

OPEN General telemetry available for public audit. No credential required.

RESTRICTED Requires level-4 cryptographic handshake. Grants access to raw signal data and unredacted origin fields.

SEALED Terminal access only. Physical or signal isolation required. Currently applies to RELIC_03 and RELIC_08.

ASSET FORMAT SPECIFICATIONS

ASSET TYPE	DIMENSIONS	ENCODING
PRIMARY WALLPAPER	1290 x 2796	WebP Q88 M6
SECONDARY PREVIEW	1000 x 1500	WebP Q88 M6
SIGNAL BROADCAST	1200 x 630	WebP Q88 M6 / JPEG Q90

03 // CATALOG ENTRY FORMAT

All relic entries adhere to the following standard data structure. Fields marked INCOMPLETE indicate data not recoverable from the artifact itself or from the recovery environment. No inference or extrapolation is permitted in these fields.

ARCHIVE ID	Unique alphanumeric designation. Format: RELIC_XX
RELIC NAME	Functional designation or recovery moniker
CLASS	Categorization based on primary visible function
STATUS TAG	Current operational or signal state at time of cataloging
CONDITION	Physical integrity: Worn / Stable / Sealed / Active / Intact
LIGHTING PROFILE	Dominant wavelength and intensity of photographic capture
ORIGIN DATA	Recovery context. Status: INCOMPLETE for all current entries
RESIDUE RATING	Psychometric imprint weight. Scale 1.0 – 10.0
ACCESS LEVEL	Required clearance: OPEN / RESTRICTED / SEALED

04 // RELIC CATALOG — CURRENT ENTRIES (012)

The following table represents all currently cataloged entries as of version 1.0. RR denotes Residue Rating on a scale of 1.0–10.0. All origin data fields are INCOMPLETE.

ID	NAME	CLASS	STATUS	COND	RR
RELIC_01	THE SCANNER	Field Unit	SIGNAL VERIFIED	Worn	6.1
RELIC_02	THE COMPASS	Field Unit	VECTOR LOCKED	Worn	5.8
RELIC_03	THE BLACK BOX	Unknown	SYSTEM DORMANT	Sealed	9.2
RELIC_04	THE CASSETTE	Memory Unit	MEMORY INTACT	Stable	7.4
RELIC_05	THE LIGHTER	Field Tool	MANUAL OVERRIDE	Used	4.3
RELIC_06	THE KEYCARD	Access Token	CLEARANCE LEVEL 7A	Active	6.7
RELIC_07	THE NODE	Network Relay	LINK STATUS: ACTIVE	Operational	5.5
RELIC_08	THE DRIVE	Data Cache	FILES SEALED	Sealed	8.1
RELIC_09	THE MEMORY MODULE	Memory Module	DATA INTEGRITY: VERIFIED	Stable	7.9
RELIC_10	THE LIGHT	Field Lamp	POWER STATUS: NOMINAL	Sealed	8.8
RELIC_11	THE TOKEN	Access Token	STATUS: VERIFIED	Intact	7.2
RELIC_12	THE WATCH	Timekeeper	SYNC STATUS: LOCKED	Excellent	6.4

05 // CATALOGING METHODOLOGY

Objects are assessed via a tripartite evaluation framework applied in sequence:

I. VISIBLE FUNCTION Determined through mechanical and optical analysis of the artifact's surface geometry, interface ports, and operational markings. Classification is assigned based on closest functional analog in known infrastructure typologies.

II. RECOVERED SIGNAL Monitored using passive wide-band receivers across the 0.1–40 GHz range. Signal events are logged without acknowledgment or response. Active interrogation of recovered signals is prohibited.

III. EMOTIONAL RESIDUE A quantified psychometric measurement of the localized imprint weight associated with the artifact. This metric does not correspond to any currently understood physical phenomenon. It is nonetheless reproducible and consistent across independent audits.

Note: Despite successful classification across all three axes, origin data for every entry remains statistically non-existent. Objects appear in the recovery record without clear developmental lineage, manufacturing provenance, or deployment context. This is not treated as an anomaly requiring resolution. It is treated as a standing condition of the archive.

06 // ACCESS & SIGNAL DISTRIBUTION

The archive is accessed via its primary terminal node:

manicwebmaster.com/digital-relics-archive/

The terminal presents all OPEN-tier entries in a cataloged visual format. Each entry exposes its designation, class, status tag, condition, and a high-resolution render of the artifact against void. Signal-verified assets are available for direct retrieval without credential exchange.

Secondary signal distribution channels operate independently of the primary terminal. These nodes extend telemetry reach across external networks without requiring archive-level access credentials. Distribution is read-only. No write operations are possible through secondary channels.

Access tier enforcement is applied at the terminal layer. RESTRICTED and SEALED entries are not surfaced through the public interface.

07 // OPERATIONAL WARNINGS

The following warnings are issued for specific entries and general archive conditions. All warnings are standing until formally resolved or reclassified.

WARNING 01 // RELIC_03 THE BLACK BOX emits a non-periodic rhythmic pulse at an observed interval of approximately 47 minutes. The pulse does not correspond to any known transmission protocol. Do not attempt to synchronize external systems to this signal. Do not log the pulse as a clock reference.

WARNING 02 // RELIC_08 THE DRIVE contains an active dead-man failsafe. Any attempt to breach, bypass, or interface with the seal will result in immediate terminal data erasure. No recovery protocol exists post-trigger. Last accessed: never. Intended access: unknown.

WARNING 03 // RELIC_09 THE MEMORY MODULE external interface is locked. Standard hardware and neural bridge protocols are incompatible. 3,847 files have been index-verified through passive scan. Physical extraction of data is not recommended and has not been attempted.

WARNING 04 // RELIC_10 THE LIGHT operates via an unverified internal power source. Measured lumen output consistently exceeds the rated capacity of any known micro-cell configuration. The unit has been sealed. Do not open. Do not expose to atmospheric contamination.

WARNING 05 // GENERAL Emotional Residue Ratings above 8.0 have been associated with technician audit irregularities in two documented cases. Audits of RELIC_03 and RELIC_10 require two-person protocol. Solo observation sessions lasting longer than 40 minutes are not authorized.

08 // ARCHIVE LOG — SELECTED ENTRIES

Objects are cataloged by visible function, recovered signal behavior, and emotional residue. Origin data remains incomplete for all entries. The following log represents selected recovery and observation events drawn from the operational record.

[00.01] SCANNER recovered from inactive fulfillment corridor. Signal persists without power source.

[00.02] BLACK BOX moved to sealed containment following initial pulse detection. Interval: 47 min.

[00.03] CASSETTE magnetic residue confirmed readable. Estimated duration: 60 minutes. Content: classified.

[00.04] DRIVE seal integrity confirmed. Failsafe mechanism active. No retrieval attempt authorized.

[00.05] MEMORY MODULE index completed via passive scan. 3,847 files. Access log: none. Interface: locked.

[00.06] THE LIGHT output measured at 280 LM. Internal cell capacity: insufficient to account for output.

09 // OPERATOR

Archive systems, signal infrastructure, and visual cataloging operations are maintained by ManicWebmaster. All entry rendering, distribution architecture, and terminal interface design originate from this node.

PRIMARY TERMINAL manicwebmaster.com/digital-relics-archive/

OPERATOR DOMAIN manicwebmaster.com

Maintained by ManicWebmaster Archive Systems

Archive Status: **ACTIVE** // Signal: **VERIFIED**

"Origin data for all entries remains incomplete. Do not attempt to resolve."