

ABBREVIATIONS

ACT	ACOUSTICAL CEILING TILE	M	MALE
ACM	ALUMINUM COMPOSITE MATERIAL	MATL	MATERIAL
ADD	ADDENDUM	MAX	MAXIMUM
ADA	AMERICANS WITH DISABILITIES ACT	MECH	MECHANICAL
ADAPT	ADAPTABLE	MED	MEDIUM
ADJ	ADJUSTABLE; ADJACENT	MEZZ	MEZZANINE
AFB	ABOVE FINISH FLOOR	MFC	MINERAL FIBER CEMENT
AFG	ABOVE FINISH GRADE	MFD	MANUFACTURED
AHR	AUTHORITY HAVING JURISDICTION	MFR	MANUFACTURER
AHJ	ANCHOR	MH	MANHOLE
ALUM	ALUMINUM	MIN	MINIMUM; MINUTE
ALT	ALTERNATE	MIRR	MIRROR
ANOD	ANODIZE(D)	MISC	MISCELLANEOUS
APPROX	APPROXIMATE	MO	MASONRY OPENING
ARCH	ARCHITECTURAL	MTD	MOUNTED
ASI	ARCHITECT'S SUPPLEMENTAL INSTRUCTION	MTG	MOUNTING
A/V	AUDIO / VIDEO	MTL	METAL
AWB	AIR AND WATER BARRIER	N	NORTH
AWI	ARCHITECTURAL WOODWORK INSTITUTE	N/A	NOT APPLICABLE
		NIC	NOT IN CONTRACT
		NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
BC	BRICK COLOR	NO	NUMBER
BD	BOARD	NOM	NOMINAL
BLDG	BUILDING	NTS	NOT TO SCALE
BLK	BLOCK		
BLKG	BLOCKING		
BM	BEAM	OC	ON CENTER
BO	BOTTOM OF	OCC	OCCUPANT
BOD	BASIS OF DESIGN	OD	OUTSIDE DIAMETER / DIMENSION
BTWN	BETWEEN	OH	OVERHEAD; OVERHAND
		OPH	OPPOSITE HAND
CCBR	CLOSED CELL BACKER ROD	OPNG	OPENING
CHPL	CUSTOM HIGH PRESSURE LAMINATE	OPP	OPPOSITE
CIP	CAST-IN-PLACE	PBD	PARTICLE BOARD
CL	CEILING	PC	PRECAST
CLKG	CAULKING	PFM	PREFINISHED METAL
CL	CENTER LINE	PL	PROPERTY LINE; PLATE
CLO	CLOSE	PLAM	PLASTIC LAMINATE
CLR	CLEAR	PLAS	PLASTIC; PLASTER
CMU	CONCRETE MASONRY UNIT	PLYVD	PLYWOOD
COL	COLUMN	PAIR	PAIR
CONC	CONCRETE	PREP	PREPARE
COND	CONDITION	PT	PAINT; POINT; PRESSURE
CONN	CONNECTION	TREAT	TREATED
CONST	CONSTRUCTION	PVC	POLYVINYL CHLORIDE
CONT	CONTINUOUS	QTY	QUANTITY
CPT	CARPET	QT	QUARRY TILE
CRCQ	COLD ROLLED		
	COMMERCIAL QUALITY	R	RADIUS
CT	CERAMIC TILE	RB	RESILIENT BASE
CVG	CLEAR VERTICAL GRAIN	RCP	REFLECTED CEILING PLAN
		RD	ROOF DRAIN
D	DEGREE	RE	REFER TO
DEG	DEMOLITION; DEMOLISH	REFR	REFRIGERATOR
DEMO		REINF	REINFORCING (ED)
DET	DETERMINE	REQ	REQUIREMENTS; REQUIRED
DETER		REV	REVISION
DF	DRINKING FOUNTAIN	RF	RESILIENT FLOORING
DIA	DIAMETER	RFG	RECESSED FOOT GRILLE
DIAG	DIAGONAL	RISER(S)	
DIM	DIMENSION	RI	ROOM
DN	DOWN	RO	ROUGH OPENING
DS	DOWN SPOUT		
DW	DISHWASHER	S	SOUTH
DWG	DRAWING	SAF	SELF-ADHERED FLASHING
DWR	DRAWER	SC	SOLID CORE
		SCHED	SCHEDULE
E	EAST	SECT	SECTION
(E)	EXISTING	SF	SQUARE FEET; STOREFRONT
EA	EACH	SHT	SHEET
EIFS	EXTERIOR INSULATING FINISH SYSTEM	SHR	SHOWER
EJ	EXPANSION JOINT	SIM	SIMILAR
EL	ELEVATION	SL	SLOPE
ELEC	ELECTRICAL	SPEC	SPECIFICATION
ELEV	ELEVATOR	SPF	SPRAY POLYURETHANE FOAM
EMER	EMERGENCY	SQ	SQUARE
ENCL	ENCLOSURE	SSTL	STAINLESS STEEL
EPS	EXPANDED POLYSTYRENE BOARD	ST	STAIN; STREET
EQ	EQUAL	STC	SOUND TRANSMISSION CLASS
EQUIP	EQUIPMENT	STD	STANDARD
EWC	ELECTRIC WATER COOLER	STL	STEEL
EXP	EXPOSED; EXPANSION	STO	STORAGE
EXT	EXTERIOR	STRUCT	STRUCTURAL
		SUSP	SUSPENDED
F	FEMALE	T	TEMPERED
FA	FIRE ALARM	T & B	TOP AND BOTTOM
FD	FLOOR DRAIN	T & G	TONGUE AND GROOVE
FDC	FIRE DEPARTMENT CONNECTION	TBD	TO BE DETERMINED
FDTN	FOUNDATION	THK	THICKNESS
FE	FIRE EXTINGUISHER	TO	TOP OF
FEC	FIRE EXTINGUISHER CABINET	TPD	TOILET PAPER DISPENSER
FF EL	FINISH FLOOR ELEVATION	TR	TREAD(S)
FFAE	FURNITURE, FIXTURES AND EQUIPMENT	TRM	TOILET ROOM
FFF	FROM FINISH FACE	TS	TUBE STEEL
FHC	FIRE HOSE CABINET	TYP	TYPICAL
FIN	FINISH		
FLD	FIELD	UL	UNDERWRITERS LABORATORY
FLR	FLOOR	UNFIN	UNFINISHED
FLUOR	FLUORESCENT	UNO	UNLESS NOTED OTHERWISE
FO	FINISHED OPENING	UTIL	UTILITIES
FOS	FACE OF STUD	V	VINYL
FR	FIRE PROTECTION RATING	VB	VAPOR BARRIER
FRP	FIBERGLASS REINFORCED POLYESTER	VCT	VINYL COMPOSITION TILE
FRT	FIRE RETARDANT TREATED	VERT	VERTICAL
FS	FLOOR SINK	VF	VERIFY IN FIELD
FT	FOOT; FEET	VOC	VOLATILE ORGANIC COMPOUND
FTG	FOOTING	VR	VAPOR RETARDER
FUNC	FUNCTION	VTR	VENT-THRU ROOF
		W	WEST; WIDE
GA	GALVE; GYPSUM ASSOCIATION	WC	WATER CLOSET; WALLCOVERING
GALV		WDW	WINDOW
GB	GENERAL CONTRACTOR	WH	WATER HEATER
GC	GLAZING	WIR	WALK-IN REFRIGERATOR
GLAZ		WIF	WALK-IN FREEZER
GSM	GALVANIZED SHEET METAL	W/	WITH
GYP	GYPSUM	W/I	WITHIN
H	HIGH	W/O	WITHOUT
HB	HOSE BIB	WRB	WATER RESISTIVE BARRIER
HC	HOLLOW CORE	WD	WOOD
HIC	HANDICAP	WT	WEIGHT
HDW	HARDWARE		
HDWD	HARDWOOD	XPS	EXTRUDED POLYSTYRENE BOARD
HFR	HOUR FIRE PROTECTION	YD	YARD
HFR	HOUR FIRE RESISTANCE	YR	YEAR
HM	HOLLOW METAL		
HORIZ	HORIZONTAL	&	AND
HP	HIGH POINT	∠	ANGLE
HR	HOUR	@	AT
HT	HEIGHT	x	BY; MULTIPLY
HVAC	HEATING, VENTILATING AND AIR CONDITIONING	CL	CENTERLINE
		°	DEGREE
IBC	INTERNATIONAL BUILDING CODE	Ø	DIAMETER
ID	INSIDE DIAMETER; IDENTIFIER	/	DIVIDE, PER
IN	INCH	'	FEET
INCL	INCLUDED(D)	>	GREATER THAN
INFO	INFORMATION	≥	GREATER THAN OR EQUAL TO
INSUL	INSULATION	"	INCHES
INT	INTERIOR	<	LESS THAN
IT	INFORMATION TECHNOLOGY	≤	LESS THAN OR EQUAL TO
JAN	JANITOR	#	NUMBER, POUND
JST	JOIST	%	PERCENT
JT	JOINT	⊥	PERPENDICULAR
KIT	KITCHEN	±	APPROXIMATELY (PLUS OR MINUS)
KO	KNOCKOUT		
LAB	LABORATORY		
LAV	LAVATORY		
LB	POUND		
LF	LINEAR FEET		
LL	LANDLORD		
LP	LOW POINT		
LT	LIGHT		
LVL	LEVEL		

MATERIAL LEGEND

SECTION	
	EARTH
	GRAVEL
	CONCRETE, CAST IN PLACE
	CONCRETE, PRECAST
	BRICK
	CONCRETE MASONRY
	STONE
	CAST STONE
	MANUFACTURED STONE
	WOOD (ROUGH) CONTINUOUS
	WOOD (ROUGH) BLOCKING OR SHIM
	WOOD (FINISH)
	SAND, PLASTER, MORTAR, GROUT
	METAL
	EIFS
	RIGID INSULATION
	BATT, LOOSE-FILL INSULATION
	ACOUSTICAL TILE & PANELS
	CERAMIC TILE, QUARRY TILE
	RESILIENT FLOORING, PLASTIC LAMINATE
	CARPET
	GYPSUM BOARD
	PLYWOOD
	PARTICLE BOARD
	GLASS
	METAL STUDS (LARGE SCALE)
	METAL STUDS (SMALL SCALE)
	WOOD STUDS

PLAN and ELEVATION

	BRICK MASONRY
	CONCRETE MASONRY
	LAP SIDING
	STONE VENEER
	STANDING SEAM METAL ROOFING
	STUCCO, EIFS
	GYPSUM BOARD, PLASTER
	ASPHALT
	CONCRETE
	CARPET
	CERAMIC TILE
	MIRROR

ARCHITECTURAL SYMBOLS

	BUILDING SECTION: DRAWING NUMBER / SHEET NUMBER
	WALL SECTION: DRAWING NUMBER / SHEET NUMBER
	DETAIL SECTION: DRAWING NUMBER / SHEET NUMBER
	EXTERIOR ELEVATION: DRAWING NUMBER / SHEET NUMBER
	INTERIOR ELEVATION: DRAWING NUMBER / SHEET NUMBER
	SECTION/DETAIL: DRAWING NUMBER / SHEET NUMBER
	DETAIL ENLARGEMENT: DRAWING NUMBER / SHEET NUMBER
	REFERENCE GRID
	EXISTING REFERENCE GRID
	VERTICAL ELEVATION DATUM
	PLAN ELEVATION DATUM
	PLAN ELEVATION CHANGE STAIR DIRECTION SYMBOL, SLOPE DIRECTION
	ORIGIN OF CHANGE
	VERTICAL ELEVATION CHANGE ROOF SLOPE
	PLAN NORTH INDICATOR TRUE NORTH
	ROOM IDENTIFIER: ROOM NAME ROOM NUMBER
	DOOR IDENTIFIER
	WINDOW IDENTIFIER
	KEYNOTE
	FFE IDENTIFIER
	FINISH IDENTIFIER
	WALL TYPE
	PARTITION TYPE
	REVISION CLOUD
	REVISION INDICATOR: ISSUE NUMBER REVISION TYPE

LINE SYMBOLS

	LINE OF OBJECT BELOW (BEYOND) PLANE OF VIEW
	LINE OF OBJECT ABOVE (BEHIND) PLANE OF VIEW
	IMAGINARY LINE
	PROPERTY LINE
	GRID LINE, ELEVATION LINE
	CENTER LINE
	BREAK LINE
	NON-RATED WALL TO STRUCTURE
	SMOKE PARTITION
	1 HOUR FIRE-RATED WALL
	2 HOUR FIRE-RATED WALL
	3 HOUR FIRE-RATED WALL

ITEMS IN ORANGE

ITEMS IN ORANGE INDICATE INSTRUCTIONS TO THE OWNER, OR PLACES WHERE THE OWNER IS INTENDED TO MAKE A SELECTION. PLEASE COMPLETE ALL ORANGE ITEMS PRIOR TO SUBMITTING FOR PERMIT OR PROCEEDING WITH ANY KIND OF COST ESTIMATE.

ITEMS IN BLUE

ITEMS IN BLUE INDICATE PLACES WHERE THE OWNER'S ENGINEER IS INTENDED TO MAKE A SELECTION. PLEASE COMPLETE ALL BLUE ITEMS PRIOR TO SUBMITTING FOR PERMIT OR PROCEEDING WITH ANY KIND OF COST ESTIMATE.

GENERAL NOTES

- ALL WORK SHALL BE EXECUTED IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL CODES AND AGENCIES HAVING JURISDICTION. IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR AND RESPECTIVE SUB-CONTRACTORS TO BUILD TO SATISFY THESE CODES AND CALL FOR ALL NECESSARY INSPECTIONS.
- DO NOT SCALE DRAWINGS. ALL NOTES AND NOTED DIMENSIONS TAKE PRECEDENCE OVER VISUAL REPRESENTATIONS OF ASSUMED INFORMATION SHOWN. ALL MANUFACTURERS' OR FABRICATORS' PRINTED WARNINGS, SPECIFICATIONS AND INSTALLATION INSTRUCTIONS TAKE PRECEDENCE OVER CONSTRUCTION DRAWINGS UNLESS AN EXCEPTION IS NOTED. MANUFACTURERS' OPERATING RECOMMENDATIONS SHALL BE STRICTLY OBSERVED.
- ALL DIMENSIONS SHALL BE FIELD VERIFIED AND COORDINATED WITH ALL OF THE WORK OF ALL TRADES.
- THE TERM "CONTRACTOR" OR "GENERAL CONTRACTOR" USED IN THIS DOCUMENT REFERS TO THE PARTY RESPONSIBLE FOR ALL WORK PERFORMED IN ACCORDANCE WITH THE CONSTRUCTION OF THE HOME SHOWN HEREIN.
- IF THE CONTRACTOR ASCERTAINS AT ANY TIME THAT REQUIREMENTS OF THIS CONTRACT CONFLICT WITH, OR ARE IN VIOLATION OF APPLICABLE LAWS, CODES, REGULATIONS AND ORDINANCES, HE/SHE SHALL NOT PROCEED WITH WORK IN QUESTION, EXCEPT AT HIS/HER OWN RISK, UNTIL THE COUNTY HAS BEEN NOTIFIED IN WRITING AND WRITTEN DETERMINATION IS MADE BY THE COUNTY. WHERE COMPLETED OR PARTIALLY COMPLETED WORK IS DISCOVERED TO BE IN VIOLATION WITH APPLICABLE LAWS, CODES, REGULATIONS AND ORDINANCES, CONTRACTOR SHALL BE REQUIRED TO REMOVE THAT WORK FROM THE PROJECT AND REPLACE SUCH WORK WITH ALL NEW COMPLYING WORK AT NO ADDITIONAL COST TO THE OWNER.
- ANY WORK INSTALLED IN CONFLICT WITH THE CONTRACT DOCUMENTS SHALL BE CORRECTED BY THE CONTRACTOR AT HIS/HER EXPENSE AND AT NO ADDITIONAL EXPENSE TO THE OWNER OR THEIR CONSULTANTS.
- THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING UTILITIES BELOW GRADE AND RELATED SERVICES CONNECTIONS WITH THE RESPECTIVE UTILITY COMPANIES.
- INSTALLATION OF ALL SELECTED MATERIALS SHALL BE COMPLETE IN ALL RESPECTS PRIOR TO FINAL ACCEPTANCE. ANY MISCELLANEOUS ITEMS OR MATERIALS NOT SPECIFICALLY NOTED BUT REQUIRED FOR PROPER INSTALLATION SHALL BE FURNISHED BY THE CONTRACTOR.
- ALL ITEMS TO BE INSTALLED PER MANUFACTURERS' SPECIFICATIONS AT MINIMUM. NOTIFY OWNER OF ANY DISCREPANCIES BETWEEN THE DRAWINGS AND MANUFACTURERS' RECOMMENDATIONS PRIOR TO INSTALLATION.
- DIMENSIONS SHOWN ON FLOOR PLANS, SECTIONS, ELEVATIONS, AND DETAILS ARE TO GRID LINES, FINISH FACE OF EXISTING WALLS, AND TO THE FACE OF STUDS, MASONRY, AND CONCRETE OF NEW WALLS UNLESS OTHERWISE NOTED.
- DETAILS AND NOTES DESIGNATED AS TYPICAL SHALL APPLY IN ALL CASES UNLESS NOTED OTHERWISE.
- CONTRACTOR SHALL PROVIDE AND INSTALL ALL STIFFENERS, BRACINGS, BACK-UP PLATES AND SUPPORTING BRACKETS REQUIRED FOR THE INSTALLATION OF ALL CASEWORK, TOILET ACCESSORIES AND OF ALL FLOOR-MOUNTED OR SUSPENDED EQUIPMENT.
- PROVIDE PRESSURE TREATED LUMBER WHERE WOOD IS IN CONTACT WITH CONCRETE AND IN ALL EXTERIOR WALL AND ROOF ASSEMBLIES. ENSURE FASTENERS ARE APPROVED FOR PRESSURE TREATED WOOD. IF PT W/D IS IN DIRECT CONTACT WITH OTHER METALS, PROVIDE MEMBRANE BARRIER TO PREVENT CORROSION OF METAL BY CHEMICALS USED IN THE PRESSURE TREATMENT PROCESS.

CODE SUMMARY

- Applicable Codes:**
- 2021 International Residential Code (IRC)
 - 2021 International Wildland Urban Interface Code (IWUIC) – **IR2-Class 2**
 - 2021 International Energy Conservation Code (IECC)
 - Compliance path: Prescriptive (*R401.2.1*)
 - Required Additional Energy Efficiency Package: More Efficient HVAC Equipment Performance (*R401.2 > 401.2.5 > R408.2, and R408.2.2*)
 - DOE Zero Energy Ready
 - Gunnison County Amendments
- Climatic Design Criteria:**
- Climate Zone 7
 - Ground Snow Load:
(<https://seacolorado.org/docs/2016-Colorado-Design-Snow-Loads.pdf>)
 - Gunnison: 45 psf
 - Crested Butte: 125 psf
 - Other: ___ psf
 - Seismic: C for soil class D
 - Frost Line: 36"
 - Wind Speed: 104 mph, 3 second gusts, Exposure C

Thermal Envelope:	Required	Proposed
Fenestration:	U-0.25 Max*	U-0.25
Skylights:	U-0.55 Max	U-0.25
Roof:	R-60 Min / U-0.024 Max	R-60
Wall:	U-0.045 Max	U-0.040
Crawl Space Wall:	R-19 Min.	R-19
Exterior Doors:	U-0.30 Max	U-0.30

* Per DOE Zero Energy Ready Home

IWUIC Requirements (Wildland Fire Resistance):

This house is designed to comply with IR2 / Class 2 requirements. This assumes that you have compliant Defensible Space, conforming water supply, a site slope of less than 40%.

Roof: Class A roofing.

Exterior Walls: Noncombustible or ignition-resistant materials

Decks: Fire-retardant-treated wood structure and/or Approved non-combustible or ignition-resistant materials

INDEX OF DRAWINGS

SHEET	NAME	100%	-	-	-
1	COVER SHEET				
2	GENERAL INFORMATION				
3	SPECIFICATIONS				
4	SITE PLAN				
5	LANDSCAPE PLAN				
6	CONSTRUCTION PLANS				
7	ROOF PLAN				
8	FINISH PLANS				
9	EXTERIOR ELEVATIONS				
10	BUILDING SECTIONS				
11	WALL SECTIONS				
12	EXTERIOR ENVELOPE DETAILS				
13	EXTERIOR OPENING, ROOF, AND CLADDING DE...				
14	DOORS, WINDOWS, AND FIXTURE SCHEDULES				
15	INTERIOR ELEVATIONS				
16	INTERIOR ELEVATIONS				
17	STRUCTURAL GENERAL NOTES AND SCHEDULES				
18	FRAMING PLANS				
19	FOUNDATION DETAILS				
20	FRAMING DETAILS				
21	MECHANICAL PLANS				
22	MECHANICAL SCHEDULES				
23	ELECTRICAL NOTES, DIAGRAM, AND SCHEDULES				
24	ELECTRICAL PLANS				

GUNNISON
COUNTY

GUNNISON
HOMES

2-Story Modern

PROJECT 24.0630

Issue

CONSTRUCTION DOCUMENTS
02.28.2025

2021 INTERNATIONAL RESIDENTIAL CODE (IRC) REQUIREMENTS:

EXTERIOR WALLS

R302.1	EXTERIOR WALLS CONSTRUCTION, PROJECTIONS, OPENINGS AND PENETRATIONS OF EXTERIOR WALLS OF DWELLINGS SHALL COMPLY WITH TABLE R302.1(1) WHERE AN AUTOMATIC SPRINKLER SYSTEM IS NOT PROVIDED.
	EXTERIOR WALLS: 1 HOUR LESS THAN 5 FEET FIRE SEPARATION DISTANCE
	PROJECTIONS: NOT ALLOWED LESS THAN 2 FEET
	OPENINGS IN WALLS: NOT ALLOWED LESS THAN 3 FEET
	PENETRATIONS: COMPLY WITH R302.4 LESS THAN 3 FEET

THE REQUIRED FIRE-RESISTANCE RATING OF EXTERIOR WALLS WITH A FIRE SEPARATION DISTANCE OF LESS THAN 5 FEET SHALL BE RATED FOR EXPOSURE TO FIRE FROM BOTH SIDES.

2024 IRC WHERE A LOT LINE DOES NOT EXIST BETWEEN ADJACENT TOWNHOUSE UNITS, / IMAGINARY LINE SHALL BE ASSUMED BETWEEN THE ADJACENT TOWNHOUSE UN AND FIRE SEPARATION DISTANCE OF EXTERIOR WALLS SHALL BE MEASURED TO IMAGINARY LINE.

TOWNHOUSES

R302.2.2	COMMON WALLS SEPARATING TOWNHOUSE UN
-----------------	---