



MYLES
NELSON
McKENZIE
DESIGN

Telephone: 949-683-6895
Email: info@mylesmckenzie.com
Web: www.mylesmckenzie.com

These drawings documents and specifications are an instrument of service, copyright and the property of MYLES NELSON MCKENZIE DESIGN and shall not be used or reproduced in any part or whole, except by written agreement with the Architect or Designer of MYLES NELSON MCKENZIE DESIGN. Their use for publication shall be restricted to the original project in which they are designed for.

Written dimensions shall be verified on the job site. Any discrepancy shall be brought to notice of the Architect or Designer of MYLES NELSON MCKENZIE DESIGN prior to the commencement of any construction.

These plans have been reviewed and approved by:

A NEW CUSTOM HOME DESIGN FOR:
MESECHER - CLOUTREAU
RESIDENCE
LOT 221, BLOCK 124, RIVERBEND
BLUFFTON TOWNSHIP, SC

WALL LEGEND:

- EXTERIOR WALLS:**
- 2x6 @ 16" O.C. WOOD STUD FRAMING WITH 1/2" GYPSUM BOARD INTERIOR FINISH, R-19 MINIMUM WALL INSULATION, EXTERIOR FINISH SYSTEM PER EXTERIOR ELEVATIONS.
- INTERIOR WALLS:**
- 2x6 @ 16" O.C. WOOD STUD FRAMING WITH 1/2" GYPSUM BOARD FINISH EACH SIDE.
- INTERIOR WALLS:**
- 2x4 @ 16" O.C. WOOD STUD FRAMING WITH 1/2" GYPSUM BOARD FINISH EACH SIDE.

GENERAL NOTES:

- REFER TO A2.1 - First Floor Plan - Dimensional AND A3.1 - Second Floor Plan - Dimensional FOR PLAN DIMENSIONS.
 - TYPICAL CEILING: 1/2" NON-SAG GYPSUM BOARD, FINISHED.
 - ALL WINDOWS SHALL BE LOW-E DOUBLE PANE GLAZING (SHGC 0.25 U-FACTOR 0.40).
 - TYPICAL BATHROOM NOTES:
 - DASHED LINE AT WATER CLOSET INDICATES MINIMUM CLEAR SPACE NOT LESS THAN 30" WIDE AND NOT LESS THAN 21" IN FRONT. (IRC R307.1)
 - BATHROOMS SHALL BE MECHANICALLY VENTILATED. PROVIDE MINIMUM EXHAUST (R303.3).
 - SHOWER AND TUB ENCLOSURES SHALL BE 1/2" THICK x 84" HIGH (U.N.O.) TEMPERED GLASS (R308.1).
 - WINDOWS AT SHOWERS AND TUBS SHALL BE TEMPERED IF LESS THAN 60" ABOVE A STANDING SURFACE AND DRAIN INLET. (R308.1)
 - CEMENT, FIBER CEMENT, FIBER-MAT REINFORCED CEMENT, GLASS MAT GYPSUM OR FIBER-REINFORCED GYPSUM BACKERS SHALL BE USED AS A BASE FOR WALL TILE IN TUB AND SHOWER AREAS AND WALL AND CEILING PANELS IN SHOWER AREAS. (R702.4.2)
 - TILE SHOWER WALLS AND FLOOR, 80" HIGH MINIMUM NON-ABSORBENT FINISH AT SHOWER WALL. (R307.2). REFER WITH OWNER FOR BENCH OPTIONS.
 - SHOWER AREA FLOORS SHALL NOT BE LESS THAN 30" IN MINIMUM DIMENSION AND SHALL HAVE AT LEAST 800 SQUARE INCHES OF INTERIOR CROSS-SECTIONAL AREA. (IRC P2708.1).
 - ALL HABITABLE ROOMS SHALL HAVE AN AGGREGATE GLAZING AREA OF NOT LESS THAN 8 PERCENT OF THE FLOOR AREA OF SUCH ROOMS. NATURAL VENTILATION SHALL BE THROUGH WINDOWS, DOORS, LOUVERS OR OTHER APPROVED OPENINGS TO THE OUTDOOR AIR. SUCH OPENINGS SHALL BE PROVIDED WITH READY ACCESS OR SHALL OTHERWISE BE READILY CONTROLLABLE BY THE BUILDING OCCUPANTS. THE MINIMUM OPENABLE AREA TO THE OUTDOORS SHALL BE 4 PERCENT OF THE FLOOR AREA BEING VENTILATED. R303.1
- AIR CHANGE EXCEPTION:**
AN APPROVED MECHANICAL VENTILATION SYSTEM CAPABLE OF PRODUCING 35% AIR CHANGE PER HOUR IN THE ROOM IS INSTALLED OR A WHOLE HOUSE MECHANICAL VENTILATION SYSTEM IS INSTALLED CAPABLE OF SUPPLYING OUTDOOR VENTILATION AIR OF 15 CUBIC FEET PER MINUTE (CFM) (78 L/S) PER OCCUPANT COMPUTED ON THE BASIS OF TWO OCCUPANTS FOR THE FIRST BEDROOM AND ONE OCCUPANT FOR EACH ADDITIONAL BEDROOM.
- WHERE EMERGENCY ESCAPE AND RESCUE OPENINGS ARE PROVIDED, THEY SHALL HAVE A SILL HEIGHT OF NOT MORE THAN 44 INCHES ABOVE THE FINISHED FLOOR.
 - OPENINGS BETWEEN THE GARAGE AND RESIDENCE SHALL BE EQUIPPED WITH SOLID WOOD DOORS NOT LESS THAN 1 3/8 INCH IN THICKNESS, SOLID OR HONEYCOMB CORE STEEL DOORS NOT LESS THAN 1 3/8 INCHES THICK, OR 20-MINUTE FIRE-RATED DOORS. DOORS PROVIDING OPENING PROTECTION SHALL BE MAINTAINED SELF-CLOSING AND SELF-LATCHING.
 - PLEASE REFER TO DETAILS 1-5 OF PAGE A1.2 FOR EXTERIOR, INTERIOR WINDOW AND DOOR TRIM.
 - CABINET DIMENSIONS AND DESIGN BY OTHERS.

KEYNOTES:

- REFER TO GENERAL NOTES FOR TYPICAL BATHROOM PATIOS.
- RAW WOOD CLOSET ROD AND PAINTED SHELF. CLOSET SHELVEING AND CONFIGURATION BY OTHERS.
- CLOTHES WASHER AND DRYER BY OWNER.
- 48" FREESTANDING GAS RANGE.
- DISHWASHER.
- REFRIGERATOR WITH ICE MAKER. PROVIDE WATER SUPPLY. SEE CABINET PLANS.
- RANGE VENT HOOD TO HAVE THE CAPACITY TO EXHAUST 100 CFM MINIMUM INTERMITTENT AIRFLOW PER TABLE M1505.4.4.
- HOSE BIBB.
- ELECTRICAL SERVICE ENTRANCE.
- GAS TANKLESS WATER HEATER.
- 5/8" GYPSUM BOARD FIRE SEPARATION ON GARAGE SIDE OF WALLS (TABLE R302.6). MINIMUM R-15 BATT INSULATION BETWEEN GARAGE AND RESIDENCE.
- REFER TO GENERAL NOTES FOR PROTECTION REQUIREMENTS OF OPENING BETWEEN GARAGE AND RESIDENCE.
- 5/8" GYPSUM BOARD ON GARAGE CEILING. PROVIDE R-19 MINIMUM FLOOR INSULATION.
- 4" DIAMETER CLOTHES DRYER EXHAUST DUCT PIPE TOTAL LENGTH IS LIMITED TO 14'-0" MAX. COMBINED HORIZONTAL AND VERTICAL LENGTHS (6" DIAMETER PIPE LIMITED TO 28'-0") PER IRC M1502.4.5.
- PROVIDE HARD SURFACE LANDING AT EXTERIOR DOORS. THE WIDTH OF THE LANDING SHALL NOT BE LESS THAN THE DOOR SERVED AND SHALL HAVE A MINIMUM DIMENSION OF 36 INCHES MEASURED IN THE DIRECTION OF TRAVEL. EXTERIOR LANDINGS SHALL BE PERMITTED TO HAVE A SLOPE NOT TO EXCEED 1/4" VERTICAL IN 12" HORIZONTAL (2-PERCENT). (R311.3)
- PASSENGER ELEVATOR. REFER TO MANUFACTURER'S REQUIREMENTS FOR SIZES, INSTALLATION REQUIREMENTS AND ELECTRICAL NEEDS. CONTRACTOR TO COORDINATE DOOR LOCATIONS WITH MANUFACTURER. ELEVATOR SHAFT SHALL BE A MINIMUM OF 5/8" TYPE "X" GYPSUM BOARD, 1 HOUR RATING.
- AIR CONDITIONING COMPRESSOR ON CONCRETE SLAB.
- ATTIC MOUNTED AIR HANDLER UNITS. REFER TO ELECTRICAL PLANS FOR ELECTRICAL REQUIREMENTS.
- SERVICE YARD SCREENING FENCE. REFER TO EXTERIOR ELEVATIONS.
- CONCRETE SLAB ON GRADE AT SERVICE YARD. SLOPE TO DRAIN THROUGH GATE OPENING.
- LINE OF STONE VENEER. REFER TO EXTERIOR ELEVATIONS.
- UNDER STAIR SURFACES TO BE PROTECTED BY 1/2" GYPSUM BOARD MINIMUM (R302.7).
- LINEAR SHOWER DRAIN.
- HANDHELD SHOWER HEAD.
- 18" HIGH SHOWER BENCH. 12" DEEP AT SHOWER HEAD WALL. 15" DEEP AT LINEAR DRAIN WALL. FINISH TO MATCH SHOWER SURROUND.
- RAINFALL SHOWER HEAD.
- SPA BY OWNER. COORDINATE INSTALLATION PRIOR TO INSTALLATION OF SCREENING SYSTEM.
- SQUARE-TOP OR FLUSH-CEILING GYPSUM BOARD SOFFIT. TOP AT 9'-0" A.F.F. SPRING POINT AT 8'-0" A.F.F. REFER W/OWNER FOR DESIGN AND FINISHED HEIGHTS.
- LINE OF STUCCO SOFFIT @ 8'-0". TYPICAL AT EXTERIOR PATIOS.
- 4" WIDE x 3" DEEP VERTICAL STUCCO BAND. REFER TO EXTERIOR ELEVATIONS.
- LINE OF DRIVEWAY PAVING. REFER TO SITE PLAN.
- CONCRETE STEPS WITH EQUAL RISERS NOT TO EXCEED 7-3/4" IN HEIGHT. PROVIDE INTEGRAL NOSING WITH 1" OVERHANG. INCLUDE PAVERS WHERE OCCURS.
- GARBAGE AND RECYCLING CONTAINERS BY OTHERS.
- PANTRY CABINETS AS PER CABINET PLANS.
- WALL OVENS.
- WINE COOLERS. REFER TO OWNER FOR TYPE AND SIZE.
- UNDER COUNTER WINE COOLER.
- LINEN CABINET.
- 9'-0" HIGH GYPSUM BOARD SOFFIT.
- SHOWER PAN CURB.
- 36" HIGH FLOOR MOUNTED GUARDRAIL / HANDRAIL. REFER TO OWNER FOR STYLE AND COLOR.
- DASHED LINE INDICATES STUCCO SOFFIT ABOVE. REFER TO EXTERIOR ELEVATIONS.
- 16" DEEP NON-FLAMMABLE HEARTH. REFER TO OWNER FOR MATERIAL AND COLOR.
- NOT USED.
- 48" TWO-SIDED WOOD BURNING FIREPLACE.
- 18" HIGH x 12" DEEP SHOWER BENCH. FINISH TO MATCH SHOWER SURROUND.
- NOT USED.
- LINE OF 6" GYPSUM BOARD CEILING STEPS DOWN FROM TYPICAL CEILING HEIGHT.
- MOISTURE RESISTANT GYPSUM BOARD VAULTED CEILING ON UNDERSIDE OF ROOF RAFTERS.
- JAMES HARDIE PANEL BOARD ON CEILING JOISTS WITH 3" FLAT TRIM OVER ALL JOINTS. CAULK.
- REFER TO CABINET PLANS FOR DESIGN AND LAYOUTS.
- LOWER DRESSING CABINETS. REFER TO OWNER FOR HEIGHT AND CONFIGURATION.
- GUARDRAIL / HANDRAIL. PROVIDE HARDWOOD CAP. REFER TO OWNER FOR FINISH. REFER WITH OWNER FOR WOOD CAP AND METAL BALUSTERS.
- COUNTERTOP MICROWAVE OVEN BY OWNER.
- UNDERCOUNTER REFRIGERATOR.
- GYPSUM BOARD CEILING ON UNDERSIDE OF ROOF RAFTERS OR CEILING JOISTS.
- MICROWAVE OVEN. REFER TO CABINET PLANS FOR LOCATION.
- ELECTRICAL SUB-PANEL.
- ALUMINUM FRAME OR EQUAL. SCREENED IN PORCH WITH MESH GUARD FOUR EQUAL, FIBERGLASS SCREEN.
- UPPER LINEN CABINET.
- LINE OF RAISED CEILING. REFER ALSO TO BUILDING SECTIONS.

NOTE: PLEASE REFER TO WINDOW/DOOR SCHEDULES ON PAGE A1.2 FOR SIZES AND TYPES.

FIRST FLOOR PLAN - NOTATIONAL

SCALE: 1/4" = 1'-0"

0 4 8

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248