




- | FLOOR FRAMING PLAN SYMBOL LEGEND | |
|---|---|
|  | INDICATES DIRECTION OF SPAN OF COMPOSITE CONCRETE FLOOR SLAB. STRUCTURAL SLAB TO BE 3 1/4" LIGHT WEIGHT CONCRETE OVER 2" GAGGE COMPOSITE METAL DECK (TOTAL THICKNESS = 5 1/4") REINFORCED WITH 6#-16S@22" W/C |
|  | INDICATES DIRECTION OF SPAN OF "X" DEEP, X GAGE, WIDE RIB, GALVANIZED METAL ROOF DECK, SEE SPECIFICATIONS. |
|  | INDICATES DIRECTION OF SPAN OF "X" DEEP, X GAGE, RIB, GALVANIZED, ACOUSTICAL METAL ROOF DECK, SEE SPECIFICATIONS. |
|  | INDICATES DIRECTION OF SPAN OF WIDE RIB, GALVANIZED, METAL ROOF DECK, SEE SPECIFICATIONS. |
|  | INDICATES COORDINATE FINAL DIMENSIONS WITH ARCHITECTURAL DRAWINGS, EQUIPMENT SUPPLIER, AND EQUIPMENT CONTRACTOR. |
|  | INDICATES MOMENT CONNECTION TO DEVELOP FULL BENDING AND SHEAR CAPACITY OF BEAM OR GIRDER, UNLESS OTHERWISE NOTED. |
|  | INDICATES FULL DEPTH FITTED STIFFENER CONNECTION, SEE "X/SX". |
|  | INDICATES CONCRETE HOUSEKEEPING SLAB, COORDINATE QUANTITY, SIZE, AND LOCATION WITH MEP DRAWINGS, SEE "X/SX". |