

Maximum Likelihood

Assume that we are given a coin, and we need to find out whether the coin is biased or not (i.e. whether it's more likely to land heads than tails). Furthermore, we also want to find out how biased the coin is (i.e. how likely it will land heads the next time we flip it). In this exercise, we will use the maximum likelihood principle to determine the bias of a coin from the observed data.


Let $c \in \{0, 1\}$ be a random variable associated with a flip of a coin (0-tails, 1-heads). The probability that a coin lands heads is denoted by a parameter μ , which is what we want to find. The distribution of a random variable c can then be written as: $P(c; \mu) = \mu^c(1 - \mu)^{1-c}$. Now imagine that we flip a coin N times and denote the outcome of the i^{th} flip by a variable $c^{(i)}$. We assume that all flips are independent of each other. Also, assume that we observe heads H times.

Your task is to write a function `MaxLikelihood` that computes the maximum likelihood value and the maximum likelihood parameter of the observed data $D = \{c^{(1)}, c^{(2)}, \dots, c^{(N-1)}, c^{(N)}\}$. Maximum likelihood parameter denotes a parameter μ_{max} that explains the observed data the best. In the context of our problem, finding the parameter that corresponds to the maximum likelihood would allow us to determine how biased the coin is.

As its inputs, your function should take a vector of possible parameters μ , a number of heads H that we observed in data D , and a total number of coin flips N . It should then do three things:

- 1) First, you will need to compute a likelihood value for every parameter μ in the provided input vector variable `mu_list`. Store all of these values into a vector variable `L_list`.
- 2) Second, select the maximum likelihood value `max_L` from the previously computed values in `L_list`.
- 3) Finally, select the maximum likelihood parameter `max_mu` by finding the parameter that is associated with the maximum likelihood value `max_L`.

Your Function

 Save  Reset  MATLAB Documentation (<https://www.mathworks.com/help/>)

```
1 function [max_L,max_mu]=MaxLikelihood(mu_list,H,N)
2     % compute the maximum likelihood value and its parameters
3     %
4     % Input:
5     % - mu_list: a vector of possible parameter values, e.g. mu_list=[0:0.01:1]
6     % - H: number of Heads
7     % - N: number of total coin flips
8     % Output:
9     % - max_L: maximum likelihood value over all the parameters mu_list
10    % - max_mu: a parameter value corresponding to the maximum likelihood value max_L
11
12    % Compute a vector of likelihoods L_list
13    % Every element in L_list should store a likelihood value
14    % associated with its respective parameter from mu_list.
15    s = H; % sum
16    L_list= mu_list.^s .* (1-mu_list).^(N-s);
17
18    % Compute the maximum likelihood value by selecting a maximum
19    % value from L_list
20
21    [m, idx] = max(L_list);
22
23    max_L= m;
24
25    % Find the parameter mu that corresponds to the maximum
26    % likelihood value
27    max_mu= mu_list(idx);
28 end
29
```

Code to call your function

 Reset

```
1 H=10; N=25;  
2 mu_list=[0:0.01:1];  
3 [max_L,max_mu]=MaxLikelihood(mu_list,H,N);  
4
```

▶ Run Function



Previous Assessment: All Tests Passed

Submit



✔ Is Maximum Likelihood Value Correct?

✔ Is Maximum Likelihood Parameter Correct?