This file configures the analyzer, which statically analyzes Dart code to

check for errors, warnings, and lints.

The issues identified by the analyzer are surfaced in the UI of Dart-enabled

IDEs (https://dart.dev/tools#ides-and-editors). The analyzer can also be

invoked from the command line by running flutter analyze.

The following line activates a set of recommended lints for Flutter apps,

packages, and plugins designed to encourage good coding practices.

include: package:flutter_lints/flutter.yaml

linter:

The lint rules applied to this project can be customized in the

section below to disable rules from the package:flutter_lints/flutter.yaml

included above or to enable additional rules. A list of all available lints

and their documentation is published at https://dart.dev/lints.

Instead of disabling a lint rule for the entire project in the

section below, it can also be suppressed for a single line of

code

or a specific dart file by using the // ignore: name_of_lint and

// ignore_for_file: name_of_lint syntax on the line or in the file

producing the lint.

rules:
avoid_print: false # Uncomment to disable the avoid_print rule
prefer_single_quotes: true # Uncomment to enable the prefer_single_quotes rule

Additional information about this file can be found at

https://dart.dev/guides/language/analysis-options

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN" "http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>
<key>IDEDidComputeMac32BitWarning</key>
<true/>
</dict>
</plist>

#include "../../Flutter/Flutter-Release.xcconfig"
#include "Warnings.xcconfig"

WARNING_CFLAGS = -Wall -Wconditional-uninitialized -Wnullable-to-nonnull-conversion -Wmissing-method-return-type -Woverlength-strings

GCC_WARN_UNDECLARED_SELECTOR = YES

CLANG_UNDEFINED_BEHAVIOR_SANITIZER_NULLABILITY = YES

CLANG_WARN_UNGUARDED_AVAILABILITY = YES_AGGRESSIVE

CLANG_WARN__DUPLICATE_METHOD_MATCH = YES

CLANG_WARN_PRAGMA_PACK = YES

CLANG_WARN_STRICT_PROTOTYPES = YES

CLANG_WARN_COMMA = YES

GCC_WARN_STRICT_SELECTOR_MATCH = YES

CLANG_WARN_OBJC_REPEATED_USE_OF_WEAK = YES

CLANG_WARN_OBJC_IMPLICIT_RETAIN_SELF = YES

GCC_WARN_SHADOW = YES

CLANG_WARN_UNREACHABLE_CODE = YES

distributionBase=GRADLE_USER_HOME
distributionPath=wrapper/dists
zipStoreBase=GRADLE_USER_HOME
zipStorePath=wrapper/dists
distributionUrl=https://services.gradle.org/distributions/gradle-9.1.0-all.zip

// This is a generated file; do not edit or check into version control.
FLUTTER_ROOT=/opt/flutter
FLUTTER_APPLICATION_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven
FLUTTER_FRAMEWORK_SWIFT_PACKAGE_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven/macos/Flutter/ephemeral/Packages/.packages/FlutterFramework
COCOAPODS_PARALLEL_CODE_SIGN=true

FLUTTER_BUILD_DIR=build
FLUTTER_BUILD_NAME=1.0.0
FLUTTER_BUILD_NUMBER=1
DART_OBFUSCATION=false
TRACK_WIDGET_CREATION=true
TREE_SHAKE_ICONS=false
PACKAGE_CONFIG=.dart_tool/
package_config.json

cmake_minimum_required(VERSION 3.13)
project(runner LANGUAGES CXX)

Define the application target. To change its name, change BINARY_NAME in the

top-level CMakeLists.txt, not the

value here, or flutter run will no longer

work.

Any new source files that you add to the application should be added here.

add_executable({FLUTTER_MANAGED_DIR}/generated_plugin_registrant.cc"
)

Apply the standard set of build settings. This can be removed for applications

that need different build settings.

apply_standard_settings($`{BINARY_NAME})

Add preprocessor definitions for the application ID.

add_definitions(-DAPPLICATION_ID="`$
{APPLICATION_ID}")

Add dependency libraries. Add any application-specific dependencies here.

target_link_libraries({BINARY_NAME} PRIVATE
PkgConfig::GTK)

target_include_directories({CMAKE_SOURCE_DIR

}")

```
// This is a basic Flutter widget test.
//
// To perform an interaction with a widget in your test, use the WidgetTester
// utility in the flutter_test package. For example, you can send tap and scroll
// gestures. You can also use WidgetTester to find child widgets in the widget
// tree, read text, and verify that the values of widget properties are correct.

import 'package:flutter/material.dart';
import 'package:flutter_test/flutter_test.dart';

import 'package:eleven/main.dart';

void main() {
testWidgets('Counter increments smoke test',
```

```
(WidgetTester tester) async {
// Build our app and trigger a frame.
await tester.pumpWidget(const MyApp());

// Verify that our counter starts at 0.
expect(find.text('0'), findsOneWidget);
expect(find.text('1'), findsNothing);

// Tap the '+' icon and trigger a frame.
await tester.tap(find.byIcon(Icons.add));
await tester.pump();

// Verify that our counter has incremented.
expect(find.text('0'), findsNothing);
expect(find.text('1'), findsOneWidget);
});
}
```

```
#include "../../Flutter/Flutter-Debug.xcconfig"
#include "Warnings.xcconfig"
```

```
// swift-tools-version: 5.9
// The swift-tools-version declares the minimum
version of Swift required to build this package.
//
// Generated file. Do not edit.
//

import PackageDescription

let package = Package(
name: "FlutterGeneratedPluginSwiftPackage",
platforms: [
.macOS("10.15")
 ],
products: [
.library(name:
"FlutterGeneratedPluginSwiftPackage", type:
.static, targets:
["FlutterGeneratedPluginSwiftPackage"])
```

```
],
dependencies: [

],
targets: [
.target(
name: "FlutterGeneratedPluginSwiftPackage"
)
 ]
)

// Application-level settings for the Runner target.
//
// This may be replaced with something auto-generated from metadata (e.g., pubspec.yaml) in the
// future. If not, the values below would default to using the project name when this becomes a
// 'flutter create' template.
```

// The application's name. By default this is also the title of the Flutter window.
PRODUCT_NAME = eleven

// The application's bundle identifier
PRODUCT_BUNDLE_IDENTIFIER = com.example.eleven

// The copyright displayed in application information
PRODUCT_COPYRIGHT = Copyright © 2026 com.example. All rights reserved.

pluginManagement {
val flutterSdkPath =
run {
val properties = java.util.Properties()
file("local.properties").inputStream().use { properties.load(it) }
val flutterSdkPath =

```
properties.getProperty("flutter.sdk")
require(flutterSdkPath != null) { "flutter.sdk not
set in local.properties" }
flutterSdkPath
}

includeBuild("$flutterSdkPath/packages/
flutter_tools/gradle")

repositories {
google()
mavenCentral()
gradlePluginPortal()
}
}

plugins {
id("dev.flutter.flutter-plugin-loader") version
"1.0.0"
id("com.android.application") version "8.11.1"
```

```
apply false
id("org.jetbrains.kotlin.android") version "2.2.20"
apply false

}

include(":app")
```

Marketplace App

Una aplicación de compra y venta moderna y ágil que reimagina la experiencia de Facebook Marketplace con una presentación fresca, directa y elegante. Permite a los usuarios descubrir productos locales organizados por categorías, contactar directamente a vendedores mediante chat y ofertas rápidas, y

publicar artículos con fotos, descripción y precio en pocos pasos.

Decisiones de diseño acordadas

- Enfoque: Marketplace multirubro general (ropa, tecnología, hogar, vehículos y servicios).
- Registro de perfil: Flujo guiado con pantalla dedicada para foto de perfil, nombre, edad y ubicación tras el inicio de sesión.
- Contacto y compra: Modal emergente rápido desde el producto con mensaje predeterminado ('¿Sigue disponible?') y oferta personalizada, que conecta directamente al chat.
- Publicación de productos: Botón 'Vender' para subir fotos, nombre, precio, categoría y ubicación.

- Sistema de mensajería: Bandeja de entrada con historial de conversaciones vinculadas al artículo de interés.
- Estilo visual: Moderno y fresco con fondo claro (#F8FAFC), acentos verde esmeralda (#059669), esquinas suaves (14-16px) y tipografía Plus Jakarta Sans.

org.gradle.jvmargs=-Xmx8G
-XX:MaxMetaspaceSize=4G
-XX:ReservedCodeCacheSize=512m -XX:
+HeapDumpOnOutOfMemoryError
android.useAndroidX=true

This newDsl flag was added by the Flutter template

android.newDsl=false

This builtInKotlin flag was added by the Flutter template

android.builtInKotlin=false

allprojects {
repositories {
google()
mavenCentral()
}
}

val newBuildDir: Directory =
rootProject.layout.buildDirectory
.dir("../../build")
.get()
rootProject.layout.buildDirectory.value(newBuild
Dir)

```
subprojects {
val newSubprojectBuildDir: Directory =
newBuildDir.dir(project.name)
project.layout.buildDirectory.value(newSubprojec
tBuildDir)
}
subprojects {
project.evaluationDependsOn(":app")
}

tasks.register<Delete>("clean") {
delete(rootProject.layout.buildDirectory)
}


name: "eleven"
description: "A new Nowa project."
publish_to: "none"
version: "1.0.0+1"
environment:
sdk: ">=3.2.0 <4.0.0"
```

```
dependencies:
flutter:
sdk: "flutter"
nowa_runtime: "^0.2.0"
provider: "^6.1.5"
shared_preferences: "^2.5.4"
dio: "^5.9.1"
go_router: "^17.1.0"
supabase_flutter: "^2.12.2"
flutter_web_plugins:
sdk: "flutter"
dev_dependencies:
flutter_test:
sdk: "flutter"
flutter_lints: "^5.0.0"
flutter:
uses-material-design: true
assets:
- "assets/"
- "assets/fonts/"
```

```
fonts:
- family: "Plus Jakarta Sans"
fonts:
- asset: "assets/fonts/Plus Jakarta Sans.ttf"


{
"images" : [
{
"size" : "16x16",
"idiom" : "mac",
"filename" : "app_icon_16.png",
"scale" : "1x"
},
{
"size" : "16x16",
"idiom" : "mac",
"filename" : "app_icon_32.png",
"scale" : "2x"
},
{
```

"size" : "32x32",
"idiom" : "mac",
"filename" : "app_icon_32.png",
"scale" : "1x"
},
{
"size" : "32x32",
"idiom" : "mac",
"filename" : "app_icon_64.png",
"scale" : "2x"
},
{
"size" : "128x128",
"idiom" : "mac",
"filename" : "app_icon_128.png",
"scale" : "1x"
},
{
"size" : "128x128",
"idiom" : "mac",

"filename" : "app_icon_256.png",
"scale" : "2x"
},
{
"size" : "256x256",
"idiom" : "mac",
"filename" : "app_icon_256.png",
"scale" : "1x"
},
{
"size" : "256x256",
"idiom" : "mac",
"filename" : "app_icon_512.png",
"scale" : "2x"
},
{
"size" : "512x512",
"idiom" : "mac",
"filename" : "app_icon_512.png",
"scale" : "1x"

},
{
"size" : "512x512",
"idiom" : "mac",
"filename" : "app_icon_1024.png",
"scale" : "2x"
}
 ],
"info" : {
"version" : 1,
"author" : "xcode"
}
}

import java.util.Properties
import java.io.FileInputStream

plugins {
id("com.android.application")
id("kotlin-android")

```
id("dev.flutter.flutter-gradle-plugin")

}

val keystoreProperties = Properties()
val keystorePropertiesFile =
rootProject.file("key.properties")
if (keystorePropertiesFile.exists()) {
keystoreProperties.load(FileInputStream(keystor
ePropertiesFile))
}

android {
namespace = "com.example.eleven1bee02"
compileSdk = flutter.compileSdkVersion
ndkVersion = flutter.ndkVersion

compileOptions {
sourceCompatibility = JavaVersion.VERSION_11
targetCompatibility = JavaVersion.VERSION_11
```

```
}

kotlinOptions {
jvmTarget = JavaVersion.VERSION_11.toString()
}

defaultConfig {
applicationId = "com.example.eleven1bee02"
// You can update the following values to match your application needs.
// For more information, see: https://docs.flutter.dev/deployment/android#reviewing-the-gradle-build-configuration.
minSdk = flutter.minSdkVersion
targetSdk = flutter.targetSdkVersion
versionCode = flutter.versionCode
versionName = flutter.versionName
}
```

```
signingConfigs {
create("release") {
if (System.getenv("CI") != null) { // CI=true is
exported by Codemagic
storeFile = file(System.getenv("CM_BUILD_DIR")
+ "/codemagic.keystore")
storePassword =
System.getenv("CM_KEYSTORE_PASSWORD")
keyAlias = System.getenv("CM_KEY_ALIAS")
keyPassword =
System.getenv("CM_KEY_PASSWORD")
} else {
keyAlias = keystoreProperties["keyAlias"] as
String?
keyPassword =
keystoreProperties["keyPassword"] as String?
storeFile = keystoreProperties["storeFile"]?.let {
file(it as String) }
storePassword =
keystoreProperties["storePassword"] as String?
```

```
}
}
}

buildTypes {
release {
signingConfig =
signingConfigs.getByName("release")
}
}
}

flutter {
source = "../.."
}

dependencies {

}
```

This file controls Flutter-level build steps. It should not be edited.

cmake_minimum_required(VERSION 3.10)

set(EPHEMERAL_DIR "$`{CMAKE_CURRENT_SOURCE_DIR}/ephemeral")

Configuration provided via flutter tool.

include(`${EPHEMERAL_DIR}/generated_config.cmake)

TODO: Move the rest of this into files in ephemeral. See

https://github.com/flutter/flutter/issues/57146.

Serves the same purpose as list(TRANSFORM ... PREPEND ...),

which isn't available in 3.10.

```
function(list_prepend LIST_NAME PREFIX)
set(NEW_LIST "")
foreach(element {LIST_NAME}})
list(APPEND NEW_LIST "{element}")
endforeach(element)
set({NEW_LIST}" PARENT_SCOPE)
endfunction()
```

=== Flutter Library ===

System-level dependencies.

find_package(PkgConfig REQUIRED)
pkg_check_modules(GTK REQUIRED
IMPORTED_TARGET gtk+-3.0)
pkg_check_modules(GLIB REQUIRED
IMPORTED_TARGET glib-2.0)
pkg_check_modules(GIO REQUIRED
IMPORTED_TARGET gio-2.0)

set(FLUTTER_LIBRARY "$`{EPHEMERAL_DIR}/
libflutter_linux_gtk.so")

Published to parent scope for install step.

```
set(FLUTTER_LIBRARY ${FLUTTER_LIBRARY} PARENT_SCOPE) set(FLUTTER_ICU_DATA_FILE "${EPHEMERAL_DIR}/icudtl.dat" PARENT_SCOPE)
set(PROJECT_BUILD_DIR "${PROJECT_DIR}/build/" PARENT_SCOPE) set(AOT_LIBRARY "${PROJECT_DIR}/build/lib/libapp.so" PARENT_SCOPE)

list(APPEND FLUTTER_LIBRARY_HEADERS
"fl_basic_message_channel.h"
"fl_binary_codec.h"
"fl_binary_messenger.h"
"fl_dart_project.h"
"fl_engine.h"
"fl_json_message_codec.h"
"fl_json_method_codec.h"
"fl_message_codec.h"
"fl_method_call.h"
"fl_method_channel.h"
```

```
"fl_method_codec.h"
"fl_method_response.h"
"fl_plugin_registrar.h"
"fl_plugin_registry.h"
"fl_standard_message_codec.h"
"fl_standard_method_codec.h"
"fl_string_codec.h"
"fl_value.h"
"fl_view.h"
"flutter_linux.h"
)
list_prepend(FLUTTER_LIBRARY_HEADERS "${EPHEMERAL_DIR}/flutter_linux/")
add_library(flutter INTERFACE)
target_include_directories(flutter INTERFACE "${EPHEMERAL_DIR}"
)
target_link_libraries(flutter INTERFACE "`${FLUTTER_LIBRARY}")
target_link_libraries(flutter INTERFACE
```

PkgConfig::GTK
PkgConfig::GLIB
PkgConfig::GIO
)
add_dependencies(flutter flutter_assemble)

=== Flutter tool backend ===

phony is a non-existent file to force this command to run every time,

since currently there's no way to get a full input/output list from the

flutter tool.

add_custom_command(

```
OUTPUT {FLUTTER_LIBRARY_HEADERS}
{CMAKE_COMMAND} -E env
{FLUTTER_ROOT}/packages/flutter_tools/bin/
tool_backend.sh"
{CMAKE_BUILD_TYPE}
VERBATIM
)
add_custom_target(flutter_assemble DEPENDS
"{FLUTTER_LIBRARY_HEADERS}
)
```

```
import Cocoa
import FlutterMacOS
import XCTest

class RunnerTests: XCTestCase {

func testExample() {
// If you add code to the Runner application,
consider adding tests here.
```

// See https://developer.apple.com/documentation/xctest for more information about using XCTest.
}

}

@if "%DEBUG%" == "" @echo off
@rem ##
@rem
@rem Gradle startup script for Windows
@rem
@rem ##

```
@rem Set local scope for the variables with
windows NT shell
if "%OS%"=="Windows_NT" setlocal

@rem Add default JVM options here. You can
also use JAVA_OPTS and GRADLE_OPTS to
pass JVM options to this script.
set DEFAULT_JVM_OPTS=

set DIRNAME=%~dp0
if "%DIRNAME%" == "" set DIRNAME=.
set APP_BASE_NAME=%~n0
set APP_HOME=%DIRNAME%

@rem Find java.exe
if defined JAVA_HOME goto
findJavaFromJavaHome

set JAVA_EXE=java.exe
%JAVA_EXE% -version >NUL 2>&1
```

```
if "%ERRORLEVEL%" == "0" goto init

echo.
echo ERROR: JAVA_HOME is not set and no
'java' command could be found in your PATH.
echo.
echo Please set the JAVA_HOME variable in your
environment to match the
echo location of your Java installation.

goto fail

:findJavaFromJavaHome
set JAVA_HOME=%JAVA_HOME:"=%
set JAVA_EXE=%JAVA_HOME%/bin/java.exe

if exist "%JAVA_EXE%" goto init

echo.
echo ERROR: JAVA_HOME is set to an invalid
```

```
directory: %JAVA_HOME%
echo.
echo Please set the JAVA_HOME variable in your
environment to match the
echo location of your Java installation.

goto fail

:init
@rem Get command-line arguments, handling
Windowz variants

if not "%OS%" == "Windows_NT" goto
win9xME_args
if "%@eval[2+2]" == "4" goto 4NT_args

:win9xME_args
@rem Slurp the command line arguments.
set CMD_LINE_ARGS=
set _SKIP=2
```

```
:win9xME_args_slurp
if "x%~1" == "x" goto execute

set CMD_LINE_ARGS=%*
goto execute

:4NT_args
@rem Get arguments from the 4NT Shell from
JP Software
set CMD_LINE_ARGS=%$

:execute
@rem Setup the command line

set CLASSPATH=%APP_HOME%
\gradle\wrapper\gradle-wrapper.jar

@rem Execute Gradle
"%JAVA_EXE%" %DEFAULT_JVM_OPTS%
```

```
%JAVA_OPTS% %GRADLE_OPTS% "-
Dorg.gradle.appname=%APP_BASE_NAME%"
-classpath "%CLASSPATH%"
org.gradle.wrapper.GradleWrapperMain
%CMD_LINE_ARGS%

:end
@rem End local scope for the variables with
windows NT shell
if "%ERRORLEVEL%"=="0" goto mainEnd

:fail
rem Set variable GRADLE_EXIT_CONSOLE if you
need the script return code instead of
rem the cmd.exe /c return code!
if not "" == "%GRADLE_EXIT_CONSOLE%" exit 1
exit /b 1

:mainEnd
if "%OS%"=="Windows_NT" endlocal
```

:omega

flutter/ephemeral

Project-level configuration.

cmake_minimum_required(VERSION 3.13)
project(runner LANGUAGES CXX)

The name of the executable created for the application. Change this to change

the on-disk name of your application.

set(BINARY_NAME "eleven")

The unique GTK application identifier for this application. See:

https://wiki.gnome.org/HowDoI/ChooseApplicationID

set(APPLICATION_ID "com.example.eleven")

Explicitly opt in to modern CMake behaviors to avoid warnings with recent

versions of CMake.

cmake_policy(SET CMP0063 NEW)

lib/ directory relative to the binary.

set(CMAKE_INSTALL_RPATH "$`ORIGIN/lib")

Root filesystem for cross-building.

if(FLUTTER_TARGET_PLATFORM_SYSROOT)
set(CMAKE_SYSROOT $
{FLUTTER_TARGET_PLATFORM_SYSROOT})
set(CMAKE_FIND_ROOT_PATH $
{CMAKE_SYSROOT})
set(CMAKE_FIND_ROOT_PATH_MODE_PROGRA
M NEVER)
set(CMAKE_FIND_ROOT_PATH_MODE_PACKAGE
 ONLY)
set(CMAKE_FIND_ROOT_PATH_MODE_LIBRARY
ONLY)
set(CMAKE_FIND_ROOT_PATH_MODE_INCLUDE
ONLY)
endif()

Define build configuration options.

```
if(NOT CMAKE_BUILD_TYPE AND NOT
CMAKE_CONFIGURATION_TYPES)
set(CMAKE_BUILD_TYPE "Debug" CACHE
STRING "Flutter build mode" FORCE)
set_property(CACHE CMAKE_BUILD_TYPE
PROPERTY STRINGS
"Debug" "Profile" "Release")
endif()
```

Compilation settings that should be applied to most targets.

Be cautious about adding new options here, as plugins use this

function by

default. In most cases, you should add new options to specific targets instead

of modifying this function.

```
function(APPLY_STANDARD_SETTINGS TARGET)
target_compile_features(${TARGET} PUBLIC cxx_std_14) target_compile_options(${TARGET} PRIVATE -Wall -Werror)
target_compile_options(${TARGET} PRIVATE "$<$&lt;NOT:$<CONFIG:Debug>>:-O3>")
target_compile_definitions(${TARGET} PRIVATE "$<$&lt;NOT:$<CONFIG:Debug>>:NDEBUG>")
endfunction()
```

Flutter library and tool build rules.

set(FLUTTER_MANAGED_DIR "${CMAKE_CURRENT_SOURCE_DIR}/flutter")
add_subdirectory(${FLUTTER_MANAGED_DIR})

System-level dependencies.

find_package(PkgConfig REQUIRED)
pkg_check_modules(GTK REQUIRED IMPORTED_TARGET gtk+-3.0)

Application build; see runner/CMakeLists.txt.

add_subdirectory("runner")

Run the Flutter tool portions of the build. This must not be removed.

add_dependencies(`${BINARY_NAME}
flutter_assemble)

Only the install-generated bundle's copy of the executable will launch

correctly, since the resources must in the right relative locations. To avoid

people trying to run the unbundled copy, put it in a subdirectory instead of

the default top-level location.

set_target_properties({CMAKE_BINARY_DIR}/
intermediates_do_not_run"
)

Generated plugin build rules,
which manage building the
plugins and adding

them to the application.

include(flutter/generated_plugins.cmake)

=== Installation ===

By default, "installing" just makes a relocatable bundle in the build

directory.

```
set(BUILD_BUNDLE_DIR "{BUILD_BUNDLE_DIR}"
CACHE PATH "..." FORCE)
endif()
```

Start with a clean build bundle directory every time.

```
install(CODE "
file(REMOVE_RECURSE
"$`{BUILD_BUNDLE_DIR}/")
" COMPONENT Runtime)

set(INSTALL_BUNDLE_DATA_DIR "$
```

{CMAKE_INSTALL_PREFIX}/data")
set(INSTALL_BUNDLE_LIB_DIR "$
{CMAKE_INSTALL_PREFIX}/lib")

install(TARGETS ${BINARY_NAME} RUNTIME
DESTINATION "${CMAKE_INSTALL_PREFIX}"
COMPONENT Runtime)

install(FILES "${FLUTTER_ICU_DATA_FILE}"
DESTINATION "${INSTALL_BUNDLE_DATA_DIR}"
COMPONENT Runtime)

install(FILES "${FLUTTER_LIBRARY}"
DESTINATION "${INSTALL_BUNDLE_LIB_DIR}"
COMPONENT Runtime)

foreach(bundled_library $
{PLUGIN_BUNDLED_LIBRARIES}) install(FILES "$
{bundled_library}"
DESTINATION "`${INSTALL_BUNDLE_LIB_DIR}"

COMPONENT Runtime)
endforeach(bundled_library)

Copy the native assets provided by the build.dart from all packages.

set(NATIVE_ASSETS_DIR
"{NATIVE_ASSETS_DIR}"
DESTINATION "$`{INSTALL_BUNDLE_LIB_DIR}"
COMPONENT Runtime)

Fully re-copy the assets directory on each build to avoid having stale files

from a previous install.

set(FLUTTER_ASSET_DIR_NAME "flutter_assets")

```
install(CODE "
file(REMOVE_RECURSE "$
{INSTALL_BUNDLE_DATA_DIR}/$
{FLUTTER_ASSET_DIR_NAME}")
" COMPONENT Runtime)
install(DIRECTORY "${PROJECT_BUILD_DIR}/$
{FLUTTER_ASSET_DIR_NAME}"
DESTINATION "`$
{INSTALL_BUNDLE_DATA_DIR}" COMPONENT
Runtime)
```

Install the AOT library on non-Debug builds only.

```
if(NOT CMAKE_BUILD_TYPE MATCHES "Debug")
install(FILES "{INSTALL_BUNDLE_LIB_DIR}"
COMPONENT Runtime)
endif()
```

FLUTTER_ROOT=/opt/flutter

FLUTTER_APPLICATION_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven

FLUTTER_FRAMEWORK_SWIFT_PACKAGE_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven/macos/Flutter/ephemeral/Packages/.packages/FlutterFramework

COCOAPODS_PARALLEL_CODE_SIGN=true

FLUTTER_BUILD_DIR=build

FLUTTER_BUILD_NAME=1.0.0

FLUTTER_BUILD_NUMBER=1

DART_OBFUSCATION=false

TRACK_WIDGET_CREATION=true

TREE_SHAKE_ICONS=false

PACKAGE_CONFIG=.dart_tool/package_config.json

#include "my_application.h"

```
#include <flutter_linux/flutter_linux.h>
#ifdef GDK_WINDOWING_X11
#include <gdk/gdkx.h>
#endif

#include "flutter/generated_plugin_registrant.h"

struct _MyApplication {
GtkApplication parent_instance;
char** dart_entrypoint_arguments;
};

G_DEFINE_TYPE(MyApplication, my_application,
GTK_TYPE_APPLICATION)

// Called when first Flutter frame received.
static void first_frame_cb(MyApplication* self,
FlView* view) {
gtk_widget_show(gtk_widget_get_toplevel(GTK_
WIDGET(view)));
```

```
}

// Implements GApplication::activate.
static void
my_application_activate(GApplication*
application) {
MyApplication* self =
MY_APPLICATION(application);
GtkWindow* window =
GTK_WINDOW(gtk_application_window_new(GT
K_APPLICATION(application)));

// Use a header bar when running in GNOME as
this is the common style used
// by applications and is the setup most users
will be using (e.g. Ubuntu
// desktop).
// If running on X and not using GNOME then just
use a traditional title bar
// in case the window manager does more exotic
```

```
layout, e.g. tiling.
// If running on Wayland assume the header bar
will work (may need changing
// if future cases occur).
gboolean use_header_bar = TRUE;
#ifdef GDK_WINDOWING_X11
GdkScreen* screen =
gtk_window_get_screen(window);
if (GDK_IS_X11_SCREEN(screen)) {
const gchar* wm_name =
gdk_x11_screen_get_window_manager_name(sc
reen);
if (g_strcmp0(wm_name, "GNOME Shell") != 0) {
use_header_bar = FALSE;
}
}
#endif
if (use_header_bar) {
GtkHeaderBar* header_bar =
GTK_HEADER_BAR(gtk_header_bar_new());
```

```
gtk_widget_show(GTK_WIDGET(header_bar));
gtk_header_bar_set_title(header_bar, "eleven");
gtk_header_bar_set_show_close_button(header_
bar, TRUE);
gtk_window_set_titlebar(window,
GTK_WIDGET(header_bar));
} else {
gtk_window_set_title(window, "eleven");
}

gtk_window_set_default_size(window, 1280,
720);

g_autoptr(FlDartProject) project =
fl_dart_project_new();
fl_dart_project_set_dart_entrypoint_arguments(
project, self->dart_entrypoint_arguments);

FlView* view = fl_view_new(project);
GdkRGBA background_color;
```

```
// Background defaults to black, override it here
if necessary, e.g. #00000000
// for transparent.
gdk_rgba_parse(&background_color, "#000000");
fl_view_set_background_color(view,
&background_color);
gtk_widget_show(GTK_WIDGET(view));
gtk_container_add(GTK_CONTAINER(window),
GTK_WIDGET(view));

// Show the window when Flutter renders.
// Requires the view to be realized so we can
start rendering.
g_signal_connect_swapped(view, "first-frame",
G_CALLBACK(first_frame_cb),
self);
gtk_widget_realize(GTK_WIDGET(view));

fl_register_plugins(FL_PLUGIN_REGISTRY(view));
```

```
gtk_widget_grab_focus(GTK_WIDGET(view));
}

// Implements
GApplication::local_command_line.
static gboolean
my_application_local_command_line(GApplicatio
n* application,
gchar*** arguments,
int* exit_status) {
MyApplication* self =
MY_APPLICATION(application);
// Strip out the first argument as it is the binary
name.
self->dart_entrypoint_arguments =
g_strdupv(*arguments + 1);

g_autoptr(GError) error = nullptr;
if (!g_application_register(application, nullptr,
&error)) {
```

```
g_warning("Failed to register: %s", error-
>message);
*exit_status = 1;
return TRUE;
}

g_application_activate(application);
*exit_status = 0;

return TRUE;
}

// Implements GApplication::startup.
static void
my_application_startup(GApplication*
application) {
// MyApplication* self =
MY_APPLICATION(object);

// Perform any actions required at application
```

```
startup.

G_APPLICATION_CLASS(my_application_parent_
class)->startup(application);
}

// Implements GApplication::shutdown.
static void
my_application_shutdown(GApplication*
application) {
// MyApplication* self =
MY_APPLICATION(object);

// Perform any actions required at application
shutdown.

G_APPLICATION_CLASS(my_application_parent_
class)->shutdown(application);
}
```

```
// Implements GObject::dispose.
static void my_application_dispose(GObject*
object) {
MyApplication* self = MY_APPLICATION(object);
g_clear_pointer(&self-
>dart_entrypoint_arguments, g_strfreev);
G_OBJECT_CLASS(my_application_parent_class)
->dispose(object);
}

static void
my_application_class_init(MyApplicationClass*
klass) {
G_APPLICATION_CLASS(klass)->activate =
my_application_activate;
G_APPLICATION_CLASS(klass)-
>local_command_line =
my_application_local_command_line;
G_APPLICATION_CLASS(klass)->startup =
my_application_startup;
```

```
G_APPLICATION_CLASS(klass)->shutdown =
my_application_shutdown;
G_OBJECT_CLASS(klass)->dispose =
my_application_dispose;
}

static void my_application_init(MyApplication*
self) {}

MyApplication* my_application_new() {
// Set the program name to the application ID,
which helps various systems
// like GTK and desktop environments map this
running application to its
// corresponding .desktop file. This ensures
better integration by allowing
// the application to be recognized beyond its
binary name.
g_set_prgname(APPLICATION_ID);
```

return
MY_APPLICATION(g_object_new(my_application
_get_type(),
"application-id", APPLICATION_ID, "flags",
G_APPLICATION_NON_UNIQUE, nullptr));
}

flutter.sdk=/opt/flutter

#!/usr/bin/env bash

##
##
########

Gradle start up script for UN*X

##
##
########

Add default JVM options here. You can also use JAVA_OPTS and GRADLE_OPTS to pass JVM options to this script.

```
DEFAULT_JVM_OPTS=""

APP_NAME="Gradle"
APP_BASE_NAME=basename "$0"`
```

Use the maximum available, or set MAX_FD != -1 to use that value.

```
MAX_FD="maximum"

warn ( ) {
echo "`$*"
```

```
}

die ( ) {
echo
echo "$*"
echo
exit 1
}
```

OS specific support (must be 'true' or 'false').

```
cygwin=false
msys=false
darwin=false
case "uname" in
CYGWIN* )
cygwin=true
;;
```

```
Darwin* )
darwin=true
;;
MINGW* )
msys=true
;;
esac
```

Attempt to set APP_HOME

Resolve links: $0 may be a link

```
PRG="$`0"
```

Need this for relative symlinks.

```
while [ -h "$PRG" ] ; do ls=ls -ld "ls" : '.-> (.)link" :
'/.*' > /dev/null; then
PRG="PRG""/$link"
fi
```

done
SAVED="pwd"
cd "dirname \"$PRG"/" >/dev/null
APP_HOME="pwd -P" cd "$SAVED" >/dev/null

CLASSPATH=`$APP_HOME/gradle/wrapper/
gradle-wrapper.jar

Determine the Java command to use to start the JVM.

if [-n "JAVA_HOME/jre/sh/java"] ; then
IBM's JDK on AIX uses strange locations for the executables
JAVACMD="JAVA_HOME/bin/java"
fi
if [! -x "JAVA_HOME

Please set the JAVA_HOME variable in your

environment to match the
location of your Java installation."
fi
else
JAVACMD="java"
which java >/dev/null 2>&1 || die "ERROR:
JAVA_HOME is not set and no 'java' command
could be found in your PATH.

Please set the JAVA_HOME variable in your
environment to match the
location of your Java installation."
fi

Increase the maximum file descriptors if we can.

if ["darwin" = "false"] ; then
MAX_FD_LIMIT=ulimit -H -n

```
if [ MAX_FD" = "maximum" -o "MAX_FD_LIMIT"
fi
ulimit -n ? -ne 0 ] ; then
warn "Could not set maximum file descriptor
limit: MAX_FD_LIMIT"
fi
fi
```

For Darwin, add options to specify how the application appears in the dock

```
if GRADLE_OPTS "-Xdock:name=APP_HOME/
media/gradle.icns""
fi
```

For Cygwin, switch paths to

Windows format before running java

if APP_HOME"CLASSPATH=cygpath --path --mixed "JAVACMD"`

We build the pattern for arguments to be converted via cygpath
ROOTDIRSRAW=find -L / -maxdepth 1 -mindepth 1 -type d 2>/dev/null
SEP=""
for dir in ROOTDIRSdir"
SEP="|"
done
OURCYGPATTERN="(^(GRADLE_CYGPATTERN" != ""] ; then
OURCYGPATTERN="GRADLE_CYGPATTERN)"
fi
Now convert the arguments - kludge to limit ourselves to /bin/sh

```
i=0
for arg in "arg"|egrep -c "arg"|egrep -c "^-"` ###
Determine if an option

if [ CHECK2 -eq 0 ] ; then ### Added a condition
eval echo args$i=cygpath --path --ignore --mixed
"$arg"
else
eval echo args$i="\"$arg""
fi
i=i in
(0) set -- ;;
(1) set -- "args0" "args0" "args2" ;;
(4) set -- "args1" "args3" ;;
(5) set -- "args1" "args3" "args0" "args2" "args4"
"args0" "args2" "args4" "args6" ;;
(8) set -- "args1" "args3" "args5" "args7" ;;
(9) set -- "args1" "args3" "args5" "args7" "$`args8"
;;
esac
```

fi

Split up the JVM_OPTS And GRADLE_OPTS values into an array, following the shell quoting and substitution rules

function splitJvmOpts() {
JVM_OPTS=("$@") } eval splitJvmOpts
$DEFAULT_JVM_OPTS $JAVA_OPTS
$GRADLE_OPTS
JVM_OPTS[${#JVM_OPTS[*]}]="-
Dorg.gradle.appname=$APP_BASE_NAME"

exec "$JAVACMD" "${JVM_OPTS[@]}" -classpath
"`$CLASSPATH"
org.gradle.wrapper.GradleWrapperMain "$@"

gradle-wrapper.jar

/.gradle

/captures/

/gradlew

/gradlew.bat

/local.properties

GeneratedPluginRegistrant.java

.cxx/

Remember to never publicly share your keystore.

See https://flutter.dev/to/reference-keystore

key.properties

**/*.keystore*

**/.jk

#include "ephemeral/Flutter-Generated.xcconfig"

#!/bin/sh

This is a generated file; do not edit or check into version control.

export "FLUTTER_ROOT=/opt/flutter"
export "FLUTTER_APPLICATION_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven"
export "FLUTTER_FRAMEWORK_SWIFT_PACKAGE_PATH=/usr/projects/1bee0229-139a-4eaa-8322-c19a66f5252f/eleven/macos/Flutter/ephemeral/Packages/.packages/FlutterFramework"
export "COCOAPODS_PARALLEL_CODE_SIGN=true"

```
export "FLUTTER_BUILD_DIR=build"
export "FLUTTER_BUILD_NAME=1.0.0"
export "FLUTTER_BUILD_NUMBER=1"
export "DART_OBFUSCATION=false"
export "TRACK_WIDGET_CREATION=true"
export "TREE_SHAKE_ICONS=false"
export "PACKAGE_CONFIG=.dart_tool/
package_config.json"

#ifndef FLUTTER_MY_APPLICATION_H_
#define FLUTTER_MY_APPLICATION_H_

#include <gtk/gtk.h>

G_DECLARE_FINAL_TYPE(MyApplication,
my_application,
MY,
APPLICATION,
GtkApplication)
```

/**

- my_application_new:
- Creates a new Flutter-based application.
- Returns: a new #MyApplication.

/

MyApplication my_application_new();

#endif // FLUTTER_MY_APPLICATION_H_

Generated by pub

See https://dart.dev/tools/pub/glossary#lockfile

packages:

app_links:

dependency: transitive

description:

name: app_links
sha256:
"08ba88bf19d9edea33130cb71c8ced2cb982b4e
00b82efef4a434d1357bc69c3"
url: "https://pub.dev"
source: hosted
version: "7.2.2"
app_links_linux:
dependency: transitive
description:
name: app_links_linux
sha256:
"9ccb5802085a1e57bb07b6256fd1d61a78c7ec1
04944d4965e62938b4fefd9cb"
url: "https://pub.dev"
source: hosted
version: "1.0.4"
app_links_platform_interface:
dependency: transitive
description:

name: app_links_platform_interface
sha256:
"7546f09a6e93f4a2df2fe2bd40a5c6c64310ac46
1b036d82b43033be7a59f809"
url: "https://pub.dev"
source: hosted
version: "2.0.4"
app_links_web:
dependency: transitive
description:
name: app_links_web
sha256:
"382d32c6f486f15b1d7f5d6a37a70a481a4fc083
82eef419d373169921a3e765"
url: "https://pub.dev"
source: hosted
version: "1.0.5"
args:
dependency: transitive
description:

name: args
sha256:
d0481093c50b1da8910eb0bb301626d4d8eb728
4aa739614d2b394ee09e3ea04
url: "https://pub.dev"
source: hosted
version: "2.7.0"
async:
dependency: transitive
description:
name: async
sha256:
e2eb0491ba5ddb6177742d2da23904574082139
b07c1e33b8503b9f46f3e1a37
url: "https://pub.dev"
source: hosted
version: "2.13.1"
audioplayers:
dependency: transitive
description:

name: audioplayers
sha256:
"2ba4bb2944baacbdd5372ff8254a8e7feb8c10d
7739545e392f5605a8f618745"
url: "https://pub.dev"
source: hosted
version: "6.8.1"
audioplayers_android:
dependency: transitive
description:
name: audioplayers_android
sha256:
f5ff5b15620fbab8cb0849e9636c48e2b96c3f0f7
1723bbbe2ad3c761b205f05
url: "https://pub.dev"
source: hosted
version: "5.3.0"
audioplayers_darwin:
dependency: transitive
description:

name: audioplayers_darwin
sha256:
"1ca553add991384ecf421b9569da850f3ab2472
ffb83f6970b0416365abc51be"
url: "https://pub.dev"
source: hosted
version: "6.5.0"
audioplayers_linux:
dependency: transitive
description:
name: audioplayers_linux
sha256:
"15178b726b7cdee5364d0463c8d445630c4e0fb
7d26612b73c767e7d25de9417"
url: "https://pub.dev"
source: hosted
version: "4.3.0"
audioplayers_platform_interface:
dependency: transitive
description:

name: audioplayers_platform_interface
sha256:
"765f6f0e6dca55cb471c9483fc77700564b3484
d19198aca4ebb5147c6c85acb"
url: "https://pub.dev"
source: hosted
version: "7.2.0"
audioplayers_web:
dependency: transitive
description:
name: audioplayers_web
sha256:
ae1e0103c865a03e273f6d13d97b93f5595eac09
915729cd5e37ef96e2857319
url: "https://pub.dev"
source: hosted
version: "5.3.0"
audioplayers_windows:
dependency: transitive
description:

name: audioplayers_windows
sha256:
a70ae82bba2dfcb6eb03dd4815d737a2d46d33e
a5a96a03f535cfcaac490e413
url: "https://pub.dev"
source: hosted
version: "4.4.1"
boolean_selector:
dependency: transitive
description:
name: boolean_selector
sha256:
"8aab1771e1243a5063b8b0ff68042d67334e3fe
ab9e95b9490f9a6ebf73b42ea"
url: "https://pub.dev"
source: hosted
version: "2.1.2"
characters:
dependency: transitive
description:

name: characters
sha256:
faf38497bda5ead2a8c7615f4f7939df04333478b
f32e4173fcb06d428b5716b
url: "https://pub.dev"
source: hosted
version: "1.4.1"
chewie:
dependency: transitive
description:
name: chewie
sha256:
"56b6641693ddd72f0cd54ddfedf4f3e9390e6d7b
7b22dc2503b7e6ad91476f7f"
url: "https://pub.dev"
source: hosted
version: "1.17.2"
clock:
dependency: transitive
description:

name: clock
sha256:
fddb70d9b5277016c77a80201021d40a2247104
d9f4aa7bab7157b7e3f05b84b
url: "https://pub.dev"
source: hosted
version: "1.1.2"
code_assets:
dependency: transitive
description:
name: code_assets
sha256:
bf394f466ba9205f1812a0433b392d6af280f155f
56651eda7c18cc32ed493b8
url: "https://pub.dev"
source: hosted
version: "1.2.1"
collection:
dependency: transitive
description:

name: collection
sha256:
"2f5709ae4d3d59dd8f7cd309b4e023046b57d8a
6c82130785d2b0e5868084e76"
url: "https://pub.dev"
source: hosted
version: "1.19.1"
convert:
dependency: transitive
description:
name: convert
sha256:
b30acd5944035672bc15c6b7a8b47d773e41e2f
17de064350988c5d02adb1c68
url: "https://pub.dev"
source: hosted
version: "3.1.2"
cross_file:
dependency: transitive
description:

name: cross_file
sha256:
f141ea4f277af142a0356955707f6556f37b0394
7d39d55585981a06ca437bd6
url: "https://pub.dev"
source: hosted
version: "0.3.5+5"
crypto:
dependency: transitive
description:
name: crypto
sha256:
c8ea0233063ba03258fbcf2ca4d6dadfefe14f02f
ab57702265467a19f27fadf
url: "https://pub.dev"
source: hosted
version: "3.0.7"
csslib:
dependency: transitive
description:

name: csslib
sha256:
"09bad715f418841f976c77db72d5398dc1253c2
1fb9c0c7f0b0b985860b2d58e"
url: "https://pub.dev"
source: hosted
version: "1.0.2"
cupertino_icons:
dependency: transitive
description:
name: cupertino_icons
sha256:
"41e005c33bd814be4d3096aff55b1908d419fde
52ca656c8c47719ec745873cd"
url: "https://pub.dev"
source: hosted
version: "1.0.9"
dart_jsonwebtoken:
dependency: transitive
description:

name: dart_jsonwebtoken
sha256:
ad84e60181696513d04d5f2078e0bbc20365b91
1f46f647797317414bdc88fbe
url: "https://pub.dev"
source: hosted
version: "3.4.1"
dbus:
dependency: transitive
description:
name: dbus
sha256:
f7db8504e715b835f5ebe5fe74604ccd961d504c
73389a5d8e81bafc2e2f3612
url: "https://pub.dev"
source: hosted
version: "0.8.0"
dio:
dependency: "direct main"
description:

name: dio
sha256:
"852ec3b48cc431ac04fff978413c541502b67ffc
3e26921e74e3d994694192c1"
url: "https://pub.dev"
source: hosted
version: "5.11.1"
dio_web_adapter:
dependency: transitive
description:
name: dio_web_adapter
sha256:
"3a1b2cd7be71086f38504956e3ebcd2837288d2
31ff454bafa78021244102bfc"
url: "https://pub.dev"
source: hosted
version: "2.2.2"
fake_async:
dependency: transitive
description:

name: fake_async
sha256:
"5368f224a74523e8d2e7399ea1638b37aecfca8
24a3cc4dfdf77bf1fa905ac44"
url: "https://pub.dev"
source: hosted
version: "1.3.3"
ffi:
dependency: transitive
description:
name: ffi
sha256:
"6d7fd89431262d8f3125e81b50d3847a091d846
eafcd4fdb88dd06f36d705a45"
url: "https://pub.dev"
source: hosted
version: "2.2.0"
ffi_leak_tracker:
dependency: transitive
description:

name: ffi_leak_tracker
sha256:
"4093d4ef9ca06ffe2786e73bfb25e22aa92112b9
bb4ec941f11e3e6b61489a97"
url: "https://pub.dev"
source: hosted
version: "0.1.2"
file:
dependency: transitive
description:
name: file
sha256:
a3b4f84adafef897088c160faf7dfffb7696046cb1
3ae90b508c2cbc95d3b8d4
url: "https://pub.dev"
source: hosted
version: "7.0.1"
file_selector_linux:
dependency: transitive
description:

name: file_selector_linux
sha256:
da76400e7872ce7637ffdce12749ec24169c25f6
195c28372208e65a24bcd2ab
url: "https://pub.dev"
source: hosted
version: "0.9.4+1"
file_selector_macos:
dependency: transitive
description:
name: file_selector_macos
sha256:
d57c62362766b5e7ae739448650b66c6aab7a68
ba7ecc65e04018652645ae0f4
url: "https://pub.dev"
source: hosted
version: "0.9.5+1"
file_selector_platform_interface:
dependency: transitive
description:

name: file_selector_platform_interface
sha256:
"35e0bd61ebcdb91a3505813b055b09b79dfdc7d
0aee9c09a7ba59ae4bb13dc85"
url: "https://pub.dev"
source: hosted
version: "2.7.0"
file_selector_windows:
dependency: transitive
description:
name: file_selector_windows
sha256:
fbefc5fb92c6d3cbe8d284a2cd971b593bb07d2c
d6da8557b81a862250b4acec
url: "https://pub.dev"
source: hosted
version: "0.9.3+6"
fixnum:
dependency: transitive
description:

name: fixnum
sha256:
b6dc7065e46c974bc7c5f143080a6764ec7a4be
6da1285ececdc37be96de53be
url: "https://pub.dev"
source: hosted
version: "1.1.1"
flutter:
dependency: "direct main"
description: flutter
source: sdk
version: "0.0.0"
flutter_highlight:
dependency: transitive
description:
name: flutter_highlight
sha256:
"7b96333867aa07e122e245c033b8ad622e4e3a
42a1a2372cbb098a2541d8782c"
url: "https://pub.dev"

source: hosted
version: "0.7.0"
flutter_inappwebview:
dependency: transitive
description:
name: flutter_inappwebview
sha256:
"80092d13d3e29b6227e25b67973c67c7210bd5
e35c4b747ca908e31eb71a46d5"
url: "https://pub.dev"
source: hosted
version: "6.1.5"
flutter_inappwebview_android:
dependency: transitive
description:
name: flutter_inappwebview_android
sha256:
"62557c15a5c2db5d195cb3892aab74fcaec266d
7b86d59a6f0027abd672cddba"
url: "https://pub.dev"

source: hosted
version: "1.1.3"
flutter_inappwebview_internal_annotations:
dependency: transitive
description:
name:
flutter_inappwebview_internal_annotations
sha256:
e30fba942e3debea7b7e6cdd4f0f59ce89dd403a
9865193e3221293b6d1544c6
url: "https://pub.dev"
source: hosted
version: "1.3.0"
flutter_inappwebview_ios:
dependency: transitive
description:
name: flutter_inappwebview_ios
sha256:
"5818cf9b26cf0cbb0f62ff50772217d41ea8d3d9
cc00279c45f8aabaa1b4025d"

url: "https://pub.dev"
source: hosted
version: "1.1.2"
flutter_inappwebview_macos:
dependency: transitive
description:
name: flutter_inappwebview_macos
sha256:
c1fbb86af1a3738e3541364d7d1866315ffb0468
a1a77e34198c9be571287da1
url: "https://pub.dev"
source: hosted
version: "1.1.2"
flutter_inappwebview_platform_interface:
dependency: transitive
description:
name: flutter_inappwebview_platform_interface
sha256:
cf5323e194096b6ede7a1ca808c3e0a078e4b33
cc3f6338977d75b4024ba2500

url: "https://pub.dev"
source: hosted
version: "1.3.0+1"
flutter_inappwebview_web:
dependency: transitive
description:
name: flutter_inappwebview_web
sha256:
"55f89c83b0a0d3b7893306b3bb545ba4770a4df
018204917148ebb42dc14a598"
url: "https://pub.dev"
source: hosted
version: "1.1.2"
flutter_inappwebview_windows:
dependency: transitive
description:
name: flutter_inappwebview_windows
sha256:
"8b4d3a46078a2cdc636c4a3d10d10f2a16882f6
be607962dbfff8874d1642055"

url: "https://pub.dev"
source: hosted
version: "0.6.0"
flutter_lints:
dependency: "direct dev"
description:
name: flutter_lints
sha256:
"5398f14efa795ffb7a33e9b6a08798b26a180eda
c4ad7db3f231e40f82ce11e1"
url: "https://pub.dev"
source: hosted
version: "5.0.0"
flutter_plugin_android_lifecycle:
dependency: transitive
description:
name: flutter_plugin_android_lifecycle
sha256:
"3854fe5e3bff0b113c658f260b90c95dea17c92d
b0f2addeac2e343dd9969785"

url: "https://pub.dev"
source: hosted
version: "2.0.35"
flutter_test:
dependency: "direct dev"
description: flutter
source: sdk
version: "0.0.0"
flutter_web_plugins:
dependency: "direct main"
description: flutter
source: sdk
version: "0.0.0"
functions_client:
dependency: transitive
description:
name: functions_client
sha256:
"931e822688d2e97867b2300e2fdbb08c9db73f8
653fc83efc7a259d2e0cca769"

url: "https://pub.dev"
source: hosted
version: "2.7.1"
go_router:
dependency: "direct main"
description:
name: go_router
sha256:
d7a3576cb312649eaa51f2356450aed686085fb
58fcdebda5b359aa951eef7ea
url: "https://pub.dev"
source: hosted
version: "17.5.0"
gotrue:
dependency: transitive
description:
name: gotrue
sha256:
cd73a6de4198baca71341177bed233673d7965a
ca2a0257ab5561feb2abdaf59

url: "https://pub.dev"
source: hosted
version: "2.27.2"
highlight:
dependency: transitive
description:
name: highlight
sha256:
"5353a83ffe3e3eca7df0abfb72dcf3fa66cc56b95
3728e7113ad4ad88497cf21"
url: "https://pub.dev"
source: hosted
version: "0.7.0"
hooks:
dependency: transitive
description:
name: hooks
sha256:
"9a62a50b50b769a737bc0a8ff381f333529df3ab
746b2f6b02e83760231455ba"

url: "https://pub.dev"
source: hosted
version: "2.0.2"
html:
dependency: transitive
description:
name: html
sha256:
"43b67b8f43321ab066817dfac5619596c98bb1b
61624e77203bb4351785f9699"
url: "https://pub.dev"
source: hosted
version: "0.15.7"
http:
dependency: transitive
description:
name: http
sha256:
"87721a4a50b19c7f1d49001e51409bddc46303
966ce89a65af4f4e6004896412"

url: "https://pub.dev"
source: hosted
version: "1.6.0"
http_parser:
dependency: transitive
description:
name: http_parser
sha256:
"178d74305e7866013777bab2c3d8726205dc5a
4dd935297175b19a23a2e66571"
url: "https://pub.dev"
source: hosted
version: "4.1.2"
image_picker:
dependency: transitive
description:
name: image_picker
sha256:
e71b1bd9e40124041128d60fc3034c7b1598e1b
ba4e570bba0c70301c817013a

url: "https://pub.dev"
source: hosted
version: "1.2.4"
image_picker_android:
dependency: transitive
description:
name: image_picker_android
sha256:
"8a7823d5d3e884f7780829d85d92110d072bdc
d9ed48e2be158d2abe91a912d4"
url: "https://pub.dev"
source: hosted
version: "0.8.13+25"
image_picker_for_web:
dependency: transitive
description:
name: image_picker_for_web
sha256:
"66257a3191ab360d23a55c8241c91a6e329d31
e94efa7be9cf7a212e65850214"

url: "https://pub.dev"
source: hosted
version: "3.1.1"
image_picker_ios:
dependency: transitive
description:
name: image_picker_ios
sha256:
"4fb88d4350ffc208c2a09fc321db1f80282688716b8cfe10c8c80acc5ae8934a"
url: "https://pub.dev"
source: hosted
version: "0.8.13+10"
image_picker_linux:
dependency: transitive
description:
name: image_picker_linux
sha256:
"1f81c5f2046b9ab724f85523e4af65be1d47b038160a8c8deed909762c308ed4"

url: "https://pub.dev"
source: hosted
version: "0.2.2"
image_picker_macos:
dependency: transitive
description:
name: image_picker_macos
sha256:
"86f0f15a309de7e1a552c12df9ce5b59fe927e71385329355aec4776c6a8ec91"
url: "https://pub.dev"
source: hosted
version: "0.2.2+1"
image_picker_platform_interface:
dependency: transitive
description:
name: image_picker_platform_interface
sha256:
"2dee4b4e3be429db71472c9c559c981498070a61af1ba82e0e4986fc5dadc042"

url: "https://pub.dev"
source: hosted
version: "2.11.2"
image_picker_windows:
dependency: transitive
description:
name: image_picker_windows
sha256:
d248c86554a72b5495a31c56f060cf73a41c7ff541689327b1a7dbccc33adfae
url: "https://pub.dev"
source: hosted
version: "0.2.2"
intl:
dependency: transitive
description:
name: intl
sha256:
"1ca20c894b1717686a2319b8548763d812bc0aabdac580420a44c5178c57a867"

url: "https://pub.dev"
source: hosted
version: "0.20.3"
jni:
dependency: transitive
description:
name: jni
sha256:
"6b9ca0602fef0230e83149afbe3f9f8227e94f2bb
e84a1da4f14d699742f402d"
url: "https://pub.dev"
source: hosted
version: "1.1.0"
jni_flutter:
dependency: transitive
description:
name: jni_flutter
sha256:
"0dd33d67797560f66e961a6053882d4df54bd34
5bf063b8fe7ea133f7ad8b191"

url: "https://pub.dev"
source: hosted
version: "1.0.4+1"
jni_util:
dependency: transitive
description:
name: jni_util
sha256:
"1ba86da04a5f2bf18fde2edb235587e70c5b0fc5
bd4ba955f46b00942c3fc35f"
url: "https://pub.dev"
source: hosted
version: "1.0.0"
json_annotation:
dependency: transitive
description:
name: json_annotation
sha256:
"2a743920d81b7910627f68ee2c9ac1fc0bfee32b
9fc3403587d7c6791ca12f80"

url: "https://pub.dev"
source: hosted
version: "4.12.0"
leak_tracker:
dependency: transitive
description:
name: leak_tracker
sha256:
"33e2e26bdd85a0112ec15400c8cbffea70d0f9c3
407491f672a2fad47915e2de"
url: "https://pub.dev"
source: hosted
version: "11.0.2"
leak_tracker_flutter_testing:
dependency: transitive
description:
name: leak_tracker_flutter_testing
sha256:
"1dbc140bb5a23c75ea9c4811222756104fbcd1a
27173f0c34ca01e16bea473c1"

url: "https://pub.dev"
source: hosted
version: "3.0.10"
leak_tracker_testing:
dependency: transitive
description:
name: leak_tracker_testing
sha256:
"8d5a2d49f4a66b49744b23b018848400d23e54
caf9463f4eb20df3eb8acb2eb1"
url: "https://pub.dev"
source: hosted
version: "3.0.2"
lints:
dependency: transitive
description:
name: lints
sha256:
c35bb79562d980e9a453fc715854e1ed39e24e7
d0297a880ef54e17f9874a9d7

url: "https://pub.dev"
source: hosted
version: "5.1.1"
logging:
dependency: transitive
description:
name: logging
sha256:
c8245ada5f1717ed44271ed1c26b8ce85ca3228f
d2ffdb75468ab01979309d61
url: "https://pub.dev"
source: hosted
version: "1.3.0"
markdown:
dependency: transitive
description:
name: markdown
sha256:
ee85086ad7698b42522c6ad42fe195f1b9898e4d
974a1af4576c1a3a176cada9

url: "https://pub.dev"
source: hosted
version: "7.3.1"
markdown_widget:
dependency: transitive
description:
name: markdown_widget
sha256:
b52c13d3ee4d0e60c812e15b0593f142a3b8a20
03cde1babb271d001a1dbdc1c
url: "https://pub.dev"
source: hosted
version: "2.3.2+8"
matcher:
dependency: transitive
description:
name: matcher
sha256:
dc0b7dc7651697ea4ff3e69ef44b0407ea32c487
a39fff6a4004fa585e901861

url: "https://pub.dev"
source: hosted
version: "0.12.19"
material_color_utilities:
dependency: transitive
description:
name: material_color_utilities
sha256:
"9c337007e82b1889149c82ed242ed1cb24a660
44e30979c44912381e9be4c48b"
url: "https://pub.dev"
source: hosted
version: "0.13.0"
meta:
dependency: transitive
description:
name: meta
sha256:
"1741988757a65eb6b36abe716829688cf01910
bbf91c34354ff7ec1c3de2b349"

url: "https://pub.dev"
source: hosted
version: "1.18.0"
mime:
dependency: transitive
description:
name: mime
sha256:
bd47de35f07e27267e69c8c8b22edf9473bfee17
0a60d60fcc93730c5144b7f6
url: "https://pub.dev"
source: hosted
version: "2.1.0"
nested:
dependency: transitive
description:
name: nested
sha256:
"03bac4c528c64c95c722ec99280375a6f2fc708
eec17c7b3f07253b626cd2a20"

url: "https://pub.dev"
source: hosted
version: "1.0.0"
nowa_runtime:
dependency: "direct main"
description:
name: nowa_runtime
sha256:
"6d9fd852c42b37c58b6752715a3977f09802 88f
c9f726f16491fd4a0e2d7d956"
url: "https://pub.dev"
source: hosted
version: "0.2.0"
objective_c:
dependency: transitive
description:
name: objective_c
sha256:
b7fb95a6d9a4f009edd63dc5ac69f07420b23a16
161c6dd8660290b59c602e8e

url: "https://pub.dev"
source: hosted
version: "9.5.0"
package_config:
dependency: transitive
description:
name: package_config
sha256:
ffcf4cf3d6c0b74ac43708d9f56625506e8a68aa9
35abe9d267a7330f320eb5d
url: "https://pub.dev"
source: hosted
version: "3.0.0"
package_info_plus:
dependency: transitive
description:
name: package_info_plus
sha256:
"73ef2cd5c11a7548f9b7f6fc2a4f6113de2e64aa
2a70de63feede95548822908"

url: "https://pub.dev"
source: hosted
version: "10.2.2"
package_info_plus_platform_interface:
dependency: transitive
description:
name: package_info_plus_platform_interface
sha256:
db762cb2f4f25ee60fb6359773861b0f199e00b9
0d237bd85a76a1e806b46ef4
url: "https://pub.dev"
source: hosted
version: "4.1.0"
passkeys_platform_interface:
dependency: transitive
description:
name: passkeys_platform_interface
sha256:
"5fca044a6f1a3c5abff645ca5a5417b613c130d1
c4e08513ba9182c7f4834619"

url: "https://pub.dev"
source: hosted
version: "2.10.0"
path:
dependency: transitive
description:
name: path
sha256:
"75cca69d1490965be98c73ceaea117e8a04dd2
1217b37b292c9ddbec0d955bc5"
url: "https://pub.dev"
source: hosted
version: "1.9.1"
path_provider:
dependency: transitive
description:
name: path_provider
sha256:
a7f4874f987173da295a61c181b8ee71dab59b3
32a486b391babf26a1b884825

url: "https://pub.dev"
source: hosted
version: "2.1.6"
path_provider_android:
dependency: transitive
description:
name: path_provider_android
sha256:
"69cbd515a62b94d32a7944f086b2f82b4ac40a1
d45bebfc00813a430ab2dabcd"
url: "https://pub.dev"
source: hosted
version: "2.3.1"
path_provider_foundation:
dependency: transitive
description:
name: path_provider_foundation
sha256:
"2a376b7d6392d80cd3705782d2caa734ca4727
776db0b6ec36ef3f1855197699"

url: "https://pub.dev"
source: hosted
version: "2.6.0"
path_provider_linux:
dependency: transitive
description:
name: path_provider_linux
sha256:
"58c2005f147315b11e9b4a7bc889cd5203e250c
ba8e3f012dae259b4972b5c16"
url: "https://pub.dev"
source: hosted
version: "2.2.2"
path_provider_platform_interface:
dependency: transitive
description:
name: path_provider_platform_interface
sha256:
"484838772624c3a4b94f1e44a3e19897fee738f
2d5c4ce448443b0417f7c9dda"

url: "https://pub.dev"
source: hosted
version: "2.1.3"
path_provider_windows:
dependency: transitive
description:
name: path_provider_windows
sha256:
bd6f00dbd873bfb70d0761682da2b3a2c2fccc2b
9e84c495821639601d81afe7
url: "https://pub.dev"
source: hosted
version: "2.3.0"
petitparser:
dependency: transitive
description:
name: petitparser
sha256:
"91bd59303e9f769f108f8df05e371341b15d59e9
95e6806aefab827b58336675"

url: "https://pub.dev"
source: hosted
version: "7.0.2"
platform:
dependency: transitive
description:
name: platform
sha256:
a36d119c13416516a7b5913fbe8af8531e11633
d784c550b2125f76c758524ec
url: "https://pub.dev"
source: hosted
version: "3.2.0"
plugin_platform_interface:
dependency: transitive
description:
name: plugin_platform_interface
sha256:
"4820fbfdb9478b1ebae27888254d445073732da
e3d6ea81f0b7e06d5dedc3f02"

url: "https://pub.dev"
source: hosted
version: "2.1.8"
pointycastle:
dependency: transitive
description:
name: pointycastle
sha256:
"92aa3841d083cc4b0f4709b5c74fd6409a3e6ba
833ffc7dc6a8fee096366acf5"
url: "https://pub.dev"
source: hosted
version: "4.0.0"
postgrest:
dependency: transitive
description:
name: postgrest
sha256:
b7f957273ba6a1c26cefa987ac524f4138e9ab75
42fbb9e6abdfddacb9895a21

url: "https://pub.dev"
source: hosted
version: "2.9.1"
provider:
dependency: "direct main"
description:
name: provider
sha256:
"4e82183fa20e5ca25703ead7e05de9e4cceed1f
bd1eadc1ac3cb6f565a09f272"
url: "https://pub.dev"
source: hosted
version: "6.1.5+1"
pub_semver:
dependency: transitive
description:
name: pub_semver
sha256:
"261236774e8b1d69cfc6b9eabbc96c40f25e7a2
d6b171f3385d4f65d5734fb24"

url: "https://pub.dev"
source: hosted
version: "2.2.1"
realtime_client:
dependency: transitive
description:
name: realtime_client
sha256:
ff731ce21fd775e0d7accfb1eaccdcf47b6876107
20822ba8b9fd8f5bccb2bd9
url: "https://pub.dev"
source: hosted
version: "2.13.0"
record_use:
dependency: transitive
description:
name: record_use
sha256:
"2551bd8eecfe95d14ae75f6021ad0248be5c27f
138c2ec12fcb52b500b3ba1ed"

url: "https://pub.dev"
source: hosted
version: "0.6.0"
scroll_to_index:
dependency: transitive
description:
name: scroll_to_index
sha256:
b707546e7500d9f070d63e5acf74fd437ec7eeeb
68d3412ef7b0afada0b4f176
url: "https://pub.dev"
source: hosted
version: "3.0.1"
shared_preferences:
dependency: "direct main"
description:
name: shared_preferences
sha256:
"1e85e0dccf5b4a016077fea7dfbb4a7cb39c759a
c1596fcf60c06deadb7da91f"

url: "https://pub.dev"
source: hosted
version: "2.5.6"
shared_preferences_android:
dependency: transitive
description:
name: shared_preferences_android
sha256:
"1e12aafe408aa50da80edfd679a2a6bf63ba7ab
37c7fa98286da459a757b3399"
url: "https://pub.dev"
source: hosted
version: "2.4.28"
shared_preferences_foundation:
dependency: transitive
description:
name: shared_preferences_foundation
sha256:
"2ec3934efa51e46117f23031cc141b8fc878e852
5b94ec1ea4f7f586cf1b47ea"

url: "https://pub.dev"
source: hosted
version: "2.5.7"
shared_preferences_linux:
dependency: transitive
description:
name: shared_preferences_linux
sha256:
"580abfd40f4156115 03cae30adf626e6656dfb2f
0cee8f465ece7b6defb40f2f"
url: "https://pub.dev"
source: hosted
version: "2.4.1"
shared_preferences_platform_interface:
dependency: transitive
description:
name: shared_preferences_platform_interface
sha256:
"649dc798a33931919ea356c4305c2d1f81619ea
6e92244070b520187b5140ef9"

url: "https://pub.dev"
source: hosted
version: "2.4.2"
shared_preferences_web:
dependency: transitive
description:
name: shared_preferences_web
sha256:
c49bd060261c9a3f0ff445892695d6212ff603ef3
115edbb448509d407600019
url: "https://pub.dev"
source: hosted
version: "2.4.3"
shared_preferences_windows:
dependency: transitive
description:
name: shared_preferences_windows
sha256:
"94ef0f72b2d71bc3e700e025db3710911bd51a7
1cefb65cc609dd0d9a982e3c1"

url: "https://pub.dev"
source: hosted
version: "2.4.1"
sky_engine:
dependency: transitive
description: flutter
source: sdk
version: "0.0.0"
source_span:
dependency: transitive
description:
name: source_span
sha256:
"56a02f1f4cd1a2d96303c0144c93bd6d909eea6
bee6bf5a0e0b685edbd4c47ab"
url: "https://pub.dev"
source: hosted
version: "1.10.2"
stack_trace:
dependency: transitive

description:
name: stack_trace
sha256:
"8b27215b45d22309b5cddda1aa2b19bdfec9df0
e765f2de506401c071d38d1b1"
url: "https://pub.dev"
source: hosted
version: "1.12.1"
storage_client:
dependency: transitive
description:
name: storage_client
sha256:
b951281b8e2b293460f0e6cc4e866f2546681390f0e37d24fbbd7b4a0deb27a3
url: "https://pub.dev"
source: hosted
version: "2.8.1"
stream_channel:
dependency: transitive

description:
name: stream_channel
sha256:
"969e04c80b8bcdf826f8f16579c7b14d780458b
d97f56d107d3950fdbeef059d"
url: "https://pub.dev"
source: hosted
version: "2.1.4"
string_scanner:
dependency: transitive
description:
name: string_scanner
sha256:
"921cd31725b72fe181906c6a94d987c78e3b98c
2e205b397ea399d4054872b43"
url: "https://pub.dev"
source: hosted
version: "1.4.1"
supabase:
dependency: transitive

description:
name: supabase
sha256:
"366244964097233 5e50d075a1fceb000b9217e403564305d129a4d287ff4b4c9"
url: "https://pub.dev"
source: hosted
version: "2.16.2"
supabase_common:
dependency: transitive
description:
name: supabase_common
sha256:
a7961a44953cf8d9da049381fc3377516348255042fbb12b9d4f8540816f2fe9
url: "https://pub.dev"
source: hosted
version: "0.1.2"
supabase_flutter:
dependency: "direct main"

description:
name: supabase_flutter
sha256:
"9698f61e83907b939fd6ee6bbf833d8456541e2
9cb38e9c08e52ebf88fa9faf4"
url: "https://pub.dev"
source: hosted
version: "2.18.0"
synchronized:
dependency: transitive
description:
name: synchronized
sha256:
"397b146f97613b83d84bdccb439bc8d0f3aebb6
c1d14a9641e6f24201c490b2d"
url: "https://pub.dev"
source: hosted
version: "3.4.2"
term_glyph:
dependency: transitive

description:
name: term_glyph
sha256:
"7f554798625ea768a7518313e58f83891c7f502
4f88e46e7182a4558850a4b8e"
url: "https://pub.dev"
source: hosted
version: "1.2.2"
test_api:
dependency: transitive
description:
name: test_api
sha256:
"949a932224383300f01be9221c39180316445ec
b8e7547f70a41a35bf421fb9e"
url: "https://pub.dev"
source: hosted
version: "0.7.11"
typed_data:
dependency: transitive

description:
name: typed_data
sha256:
f9049c039ebfeb4cf7a7104a675823cd72dba829
7f264b6637062516699fa006
url: "https://pub.dev"
source: hosted
version: "1.4.0"
url_launcher:
dependency: transitive
description:
name: url_launcher
sha256:
e8cc955c97e06df9879140a1fe301f3d493f01b7
c62dec7f46834be31d7e9fda
url: "https://pub.dev"
source: hosted
version: "6.3.3"
url_launcher_android:
dependency: transitive

description:
name: url_launcher_android
sha256:
"611e87fb320b70d1dd721dc46af89c98aceccea
9b31fde49e084591414e0c610"
url: "https://pub.dev"
source: hosted
version: "6.3.33"
url_launcher_ios:
dependency: transitive
description:
name: url_launcher_ios
sha256:
"8faa1aab294f1ab4040b43660c887b0418d5fa4f
0cffef76a484e6aa1092eb4a"
url: "https://pub.dev"
source: hosted
version: "6.4.2"
url_launcher_linux:
dependency: transitive

description:
name: url_launcher_linux
sha256:
"10f86fef4c2c43563fa6c211ff9cf757adf4d3ab7
62c56bd430664a947d70cd0"
url: "https://pub.dev"
source: hosted
version: "3.2.3"
url_launcher_macos:
dependency: transitive
description:
name: url_launcher_macos
sha256:
"5e835a3b869c2d70325349c81c5a45c28e2079
1265b67b2669da6b08c5cd5201"
url: "https://pub.dev"
source: hosted
version: "3.2.6"
url_launcher_platform_interface:
dependency: transitive

description:
name: url_launcher_platform_interface
sha256:
"552f8a1e663569be95a8190206a38187b531910283c3e982193e4f2733f01029"
url: "https://pub.dev"
source: hosted
version: "2.3.2"
url_launcher_web:
dependency: transitive
description:
name: url_launcher_web
sha256:
"85c81589622fbc87c1c683aaea164d3604a7777495a79d91e39ffcdec39ddb34"
url: "https://pub.dev"
source: hosted
version: "2.4.3"
url_launcher_windows:
dependency: transitive

description:
name: url_launcher_windows
sha256:
"6c5ad3f22cd4c38e089b81963b3cd7bb83b111b
2df5dce008bb066162f42e429"
url: "https://pub.dev"
source: hosted
version: "3.1.6"
uuid:
dependency: transitive
description:
name: uuid
sha256:
"9b129329f58692f6e6578329498a8fe9fbe98f09
0beb764ffbb8ee2eadd01dcd"
url: "https://pub.dev"
source: hosted
version: "4.6.0"
vector_math:
dependency: transitive

description:
name: vector_math
sha256:
d530bd74fea330e6e364cda7a85019c43407018
8383e1cd8d9777ee586914c5b
url: "https://pub.dev"
source: hosted
version: "2.2.0"
video_player:
dependency: transitive
description:
name: video_player
sha256:
"07ae1e03f2d4c8e2e9a75ee678f90acbc4506d4
458a9c628512d119a1eee5754"
url: "https://pub.dev"
source: hosted
version: "2.14.1"
video_player_android:
dependency: transitive

description:
name: video_player_android
sha256:
d27054dea34d748a44f06d433a57005d2aac69944485b0abbaed3303dbcfa3f1
url: "https://pub.dev"
source: hosted
version: "2.12.2"
video_player_avfoundation:
dependency: transitive
description:
name: video_player_avfoundation
sha256:
"4f8a845173377ab250a50f9b9dfe4a43500cc76a7c49dd8410d02d8fc29dfd8b"
url: "https://pub.dev"
source: hosted
version: "2.12.1"
video_player_platform_interface:
dependency: transitive

description:
name: video_player_platform_interface
sha256:
"92c0fbabe20c788e71fd10d26cea998d0d25328
2e65d145aed0818731cf593ce"
url: "https://pub.dev"
source: hosted
version: "6.9.0"
video_player_web:
dependency: transitive
description:
name: video_player_web
sha256:
"9f3c00be2ef9b76a95d94ac5119fb843dca6f2c6
9e6c9968f6f2b6c9e7afbdeb"
url: "https://pub.dev"
source: hosted
version: "2.4.0"
visibility_detector:
dependency: transitive

description:
name: visibility_detector
sha256:
dd5cc11e13494f432d15939c3aa8ae76844c42b
723398643ce9addb88a5ed420
url: "https://pub.dev"
source: hosted
version: "0.4.0+2"
vm_service:
dependency: transitive
description:
name: vm_service
sha256:
"5f37239c4851efcef929cea7824e76df7f2f0970a
ef85d66bbc430afa40e72f0"
url: "https://pub.dev"
source: hosted
version: "15.3.0"
wakelock_plus:
dependency: transitive

description:
name: wakelock_plus
sha256:
"9a91139ee876c24a9ebe1484e4b9b7923b07d3
68566a5e0b2301870b0f5029c8"
url: "https://pub.dev"
source: hosted
version: "1.8.1"
wakelock_plus_platform_interface:
dependency: transitive
description:
name: wakelock_plus_platform_interface
sha256:
"764c25504562abc8ac3406f5d175f126b276e6b
a916c7c2675690b73368ca384"
url: "https://pub.dev"
source: hosted
version: "1.7.0"
web:
dependency: transitive

description:
name: web
sha256:
"868d88a33d8a87b18ffc05f9f030ba328ffefba92
d6c127917a2ba740f9cfe4a"
url: "https://pub.dev"
source: hosted
version: "1.1.1"
web_socket:
dependency: transitive
description:
name: web_socket
sha256:
"34d64019aa8e36bf9842ac014bb5d2f5586ca73
df5e4d9bf5c936975cae6982c"
url: "https://pub.dev"
source: hosted
version: "1.0.1"
web_socket_channel:
dependency: transitive

description:
name: web_socket_channel
sha256:
d645757fb0f4773d602444000a8131ff5d48c9e4
7adfe9772652dd1a4f2d45c8
url: "https://pub.dev"
source: hosted
version: "3.0.3"
win32:
dependency: transitive
description:
name: win32
sha256:
a0b93865d5644f11cf6a8c3f6db909f1ec168958
b5805f6cc684adea957cd63d
url: "https://pub.dev"
source: hosted
version: "6.4.0"
xdg_directories:
dependency: transitive

description:
name: xdg_directories
sha256:
"7a3f37b05d989967cdddcbb571f1ea834867ae2
faa29725fd085180e0883aa15"
url: "https://pub.dev"
source: hosted
version: "1.1.0"
xml:
dependency: transitive
description:
name: xml
sha256:
"67f0aff7be013d107995e9b75bf4e7f2c3ef2dfdb
2c8e68024bba0a7fd5756a4"
url: "https://pub.dev"
source: hosted
version: "7.0.1"
yaml:
dependency: transitive

description:
name: yaml
sha256:
f67cdd8e07d3c6329146aaef1ba043542b3134c1
2489f553ca9a7435d1068aea
url: "https://pub.dev"
source: hosted
version: "3.1.4"
yet_another_json_isolate:
dependency: transitive
description:
name: yet_another_json_isolate
sha256:
eaa26beb5990b25a49d942374fd5a0c5aa67a83
7e03b14b4c26134aaa1ed01a9
url: "https://pub.dev"
source: hosted
version: "2.1.1"
sdks:
dart: ">=3.12.0 <4.0.0"

flutter: ">=3.44.0"

Generated file, do not edit.

list(APPEND FLUTTER_PLUGIN_LIST
app_links_linux
audioplayers_linux
file_selector_linux
url_launcher_linux
)

list(APPEND FLUTTER_FFI_PLUGIN_LIST
jni
)

set(PLUGIN_BUNDLED_LIBRARIES)

foreach(plugin {plugin}/linux plugins/

{BINARY_NAME} PRIVATE <TARGET_FILE:
{$`{plugin}_bundled_libraries})
endforeach(plugin)

foreach(ffi_plugin $
{FLUTTER_FFI_PLUGIN_LIST})
add_subdirectory(flutter/
ephemeral/.plugin_symlinks/${ffi_plugin}/linux
plugins/${ffi_plugin}) list(APPEND
PLUGIN_BUNDLED_LIBRARIES ${`${ffi_plugin}
_bundled_libraries})
endforeach(ffi_plugin)

Flutter-related

**/Flutter/ephemeral/
**/Pods/

Xcode-related

**/dgph
**/xcuserdata/

// !!
{
archiveVersion = 1;
classes = {
};
objectVersion = 54;
objects = {

/* Begin PBXAggregateTarget section */
33CC111A2044C6BA0003C045 / Flutter Assemble */ = {*
isa = PBXAggregateTarget;
buildConfigurationList = 33CC111B2044C6BA0003C045 / Build*

configuration list for PBXAggregateTarget
"Flutter Assemble" */;
buildPhases = (
33CC111E2044C6BF0003C045 /* ShellScript */,
);
dependencies = (
);
name = "Flutter Assemble";
productName = FLX;
};
/* End PBXAggregateTarget section */

/* Begin PBXBuildFile section */
331C80D8294CF71000263BE5 /*
RunnerTests.swift in Sources */ = {isa =
PBXBuildFile; fileRef =
331C80D7294CF71000263BE5 /*
RunnerTests.swift */; };
335BBD1B22A9A15E00E9071D /*
GeneratedPluginRegistrant.swift in Sources */ =

{isa = PBXBuildFile; fileRef =
335BBD1A22A9A15E00E9071D /
GeneratedPluginRegistrant.swift */; };*
33CC10F12044A3C60003C045 /
AppDelegate.swift in Sources */ = {isa =*
PBXBuildFile; fileRef =
33CC10F02044A3C60003C045 /
AppDelegate.swift */; };*
33CC10F32044A3C60003C045 /
Assets.xcassets in Resources */ = {isa =*
PBXBuildFile; fileRef =
33CC10F22044A3C60003C045 /
Assets.xcassets */; };*
33CC10F62044A3C60003C045 / MainMenu.xib*
in Resources */ = {isa = PBXBuildFile; fileRef =*
33CC10F42044A3C60003C045 / MainMenu.xib*
/; };
33CC11132044BFA00003C045 /
MainFlutterWindow.swift in Sources */ = {isa =*
PBXBuildFile; fileRef =

33CC11122044BFA00003C045 /
MainFlutterWindow.swift */; };
78A318202AECB46A00862997 /
FlutterGeneratedPluginSwiftPackage in
Frameworks */ = {isa = PBXBuildFile; productRef
= 78A3181F2AECB46A00862997 /*
FlutterGeneratedPluginSwiftPackage */; };
/* End PBXBuildFile section */

/* Begin PBXContainerItemProxy section */
331C80D9294CF71000263BE5 /
PBXContainerItemProxy */ = {
isa = PBXContainerItemProxy;
containerPortal =
33CC10E52044A3C60003C045 / Project object*
/;
proxyType = 1;
remoteGlobalIDString =
33CC10EC2044A3C60003C045;
remoteInfo = Runner;

};

33CC111F2044C79F0003C045 /

PBXContainerItemProxy */ = {*

isa = PBXContainerItemProxy;

containerPortal =

33CC10E52044A3C60003C045 / Project object*

/;

proxyType = 1;

remoteGlobalIDString =

33CC111A2044C6BA0003C045;

remoteInfo = FLX;

};

/ End PBXContainerItemProxy section */

/* Begin PBXCopyFilesBuildPhase section */

33CC110E2044A8840003C045 / Bundle*

Framework */ = {*

isa = PBXCopyFilesBuildPhase;

buildActionMask = 2147483647;

dstPath = "";

dstSubfolderSpec = 10;
files = (
);
name = "Bundle Framework";
runOnlyForDeploymentPostprocessing = 0;
};
/ End PBXCopyFilesBuildPhase section */

/* Begin PBXFileReference section */
331C80D5294CF71000263BE5 /
RunnerTests.xctest */ = {isa = PBXFileReference;*
explicitFileType = wrapper.cfbundle;
includeInIndex = 0; path = RunnerTests.xctest;
sourceTree = BUILT_PRODUCTS_DIR; };
331C80D7294CF71000263BE5 /
RunnerTests.swift */ = {isa = PBXFileReference;*
lastKnownFileType = sourcecode.swift; path =
RunnerTests.swift; sourceTree = "<group>"; };
333000ED22D3DE5D00554162 /
Warnings.xcconfig */ = {isa = PBXFileReference;*

lastKnownFileType = text.xcconfig; path =
Warnings.xcconfig; sourceTree = "<group>"; };
335BBD1A22A9A15E00E9071D /
GeneratedPluginRegistrant.swift */ = {isa =*
PBXFileReference; fileEncoding = 4;
lastKnownFileType = sourcecode.swift; path =
GeneratedPluginRegistrant.swift; sourceTree =
"<group>"; };
33CC10ED2044A3C60003C045 / eleven.app */ =*
{isa = PBXFileReference; explicitFileType =
wrapper.application; includeInIndex = 0; path =
"eleven.app"; sourceTree =
BUILT_PRODUCTS_DIR; };
33CC10F02044A3C60003C045 /
AppDelegate.swift */ = {isa = PBXFileReference;*
lastKnownFileType = sourcecode.swift; path =
AppDelegate.swift; sourceTree = "<group>"; };
33CC10F22044A3C60003C045 /
Assets.xcassets */ = {isa = PBXFileReference;*
lastKnownFileType = folder.assetcatalog; name

= Assets.xcassets; path = Runner/ Assets.xcassets; sourceTree = "<group>"; }; 33CC10F52044A3C60003C045 / Base */ = {isa = PBXFileReference; lastKnownFileType = file.xib; name = Base; path = Base.lproj/MainMenu.xib; sourceTree = "<group>"; }; 33CC10F72044A3C60003C045 /* Info.plist */ = {isa = PBXFileReference; lastKnownFileType = text.plist.xml; name = Info.plist; path = Runner/ Info.plist; sourceTree = "<group>"; }; 33CC11122044BFA00003C045 /* MainFlutterWindow.swift */ = {isa = PBXFileReference; lastKnownFileType = sourcecode.swift; path = MainFlutterWindow.swift; sourceTree = "<group>"; }; 33CEB47222A05771004F2AC0 /* Flutter-Debug.xcconfig */ = {isa = PBXFileReference; lastKnownFileType = text.xcconfig; path = "Flutter-Debug.xcconfig"; sourceTree =*

"<group>"; };
33CEB47422A05771004F2AC0 / Flutter-*
Release.xcconfig *= {isa = PBXFileReference;*
lastKnownFileType = text.xcconfig; path =
"Flutter-Release.xcconfig"; sourceTree =
"<group>"; };
33CEB47722A0578A004F2AC0 / Flutter-*
Generated.xcconfig *= {isa = PBXFileReference;*
lastKnownFileType = text.xcconfig; name =
"Flutter-Generated.xcconfig"; path = "ephemeral/
Flutter-Generated.xcconfig"; sourceTree =
"<group>"; };
33E51913231747F40026EE4D /
DebugProfile.entitlements *= {isa =*
PBXFileReference; lastKnownFileType =
text.plist.entitlements; path =
DebugProfile.entitlements; sourceTree =
"<group>"; };
33E51914231749380026EE4D /
Release.entitlements *= {isa =*

PBXFileReference; fileEncoding = 4; lastKnownFileType = text.plist.entitlements; path = Release.entitlements; sourceTree = "<group>"; }; 33E5194F232828860026EE4D / AppInfo.xcconfig */ = {isa = PBXFileReference; lastKnownFileType = text.xcconfig; path = AppInfo.xcconfig; sourceTree = "<group>"; }; 78E0A7A72DC9AD7400C4905E /* FlutterGeneratedPluginSwiftPackage */ = {isa = PBXFileReference; lastKnownFileType = wrapper; name = FlutterGeneratedPluginSwiftPackage; path = ephemeral/Packages/FlutterGeneratedPluginSwiftPackage; sourceTree = "<group>"; }; 7AFA3C8E1D35360C0083082E /* Release.xcconfig */ = {isa = PBXFileReference; lastKnownFileType = text.xcconfig; path = Release.xcconfig; sourceTree = "<group>"; }; 9740EEB21CF90195004384FC /* Debug.xcconfig*

/ = {isa = PBXFileReference; fileEncoding = 4;
lastKnownFileType = text.xcconfig; path =
Debug.xcconfig; sourceTree = "<group>"; };
/ End PBXFileReference section */

/* Begin PBXFrameworksBuildPhase section */
331C80D2294CF70F00263BE5 / Frameworks */*
= {
isa = PBXFrameworksBuildPhase;
buildActionMask = 2147483647;
files = (
);
runOnlyForDeploymentPostprocessing = 0;
};
33CC10EA2044A3C60003C045 / Frameworks */*
= {
isa = PBXFrameworksBuildPhase;
buildActionMask = 2147483647;
files = (
78A318202AECB46A00862997 /

FlutterGeneratedPluginSwiftPackage in Frameworks */,
);
runOnlyForDeploymentPostprocessing = 0;
};
/* End PBXFrameworksBuildPhase section */

/* Begin PBXGroup section */
331C80D6294CF71000263BE5 /* RunnerTests */ = {
isa = PBXGroup;
children = (
331C80D7294CF71000263BE5 /* RunnerTests.swift */,
);
path = RunnerTests;
sourceTree = "<group>";
};
33BA886A226E78AF003329D5 /* Configs */ = {
isa = PBXGroup;

children = (

33E5194F232828860026EE4D /

AppInfo.xcconfig */,*

9740EEB21CF90195004384FC / Debug.xcconfig

/,

7AFA3C8E1D35360C0083082E /

Release.xcconfig */,*

333000ED22D3DE5D00554162 /

Warnings.xcconfig */,*

);

path = Configs;

sourceTree = "<group>";

};

33CC10E42044A3C60003C045 = {

isa = PBXGroup;

children = (

33FAB671232836740065AC1E / Runner */,*

33CEB47122A05771004F2AC0 / Flutter */,*

331C80D6294CF71000263BE5 / RunnerTests */,*

33CC10EE2044A3C60003C045 / Products */,*

D73912EC22F37F3D000D13A0 / Frameworks */,
);
sourceTree = "<group>";
};
33CC10EE2044A3C60003C045 / Products */ = {
isa = PBXGroup;
children = (
33CC10ED2044A3C60003C045 / eleven.app */,
331C80D5294CF71000263BE5 /
RunnerTests.xctest */,
);
name = Products;
sourceTree = "<group>";
};
33CC11242044D66E0003C045 / Resources */ = {
isa = PBXGroup;
children = (
33CC10F22044A3C60003C045 /
Assets.xcassets */,
33CC10F42044A3C60003C045 / MainMenu.xib

/,

33CC10F72044A3C60003C045 / Info.plist */,*

);

name = Resources;

path = ..;

sourceTree = "<group>";

};

33CEB47122A05771004F2AC0 / Flutter */ = {*

isa = PBXGroup;

children = (

78E0A7A72DC9AD7400C4905E /

FlutterGeneratedPluginSwiftPackage */,*

335BBD1A22A9A15E00E9071D /

GeneratedPluginRegistrant.swift */,*

33CEB47222A05771004F2AC0 / Flutter-*

Debug.xcconfig */,

33CEB47422A05771004F2AC0 / Flutter-*

Release.xcconfig */,

33CEB47722A0578A004F2AC0 / Flutter-*

Generated.xcconfig */,

```
);
path = Flutter;
sourceTree = "<group>";
};
33FAB671232836740065AC1E /* Runner */ = {
isa = PBXGroup;
children = (
33CC10F02044A3C60003C045 /*
AppDelegate.swift */,
33CC11122044BFA00003C045 /*
MainFlutterWindow.swift */,
33E51913231747F40026EE4D /*
DebugProfile.entitlements */,
33E51914231749380026EE4D /*
Release.entitlements */,
33CC11242044D66E0003C045 /* Resources */,
33BA886A226E78AF003329D5 /* Configs */,
);
path = Runner;
sourceTree = "<group>";
```

```
};
D73912EC22F37F3D000D13A0 / Frameworks /
= {
isa = PBXGroup;
children = (
);
name = Frameworks;
sourceTree = "<group>";
};
/ End PBXGroup section */

/* Begin PBXNativeTarget section /
331C80D4294CF70F00263BE5 / RunnerTests /
= {
isa = PBXNativeTarget;
buildConfigurationList =
331C80DE294CF71000263BE5 / Build
configuration list for PBXNativeTarget
"RunnerTests" /;
buildPhases = (
```

331C80D1294CF70F00263BE5 / Sources /,
331C80D2294CF70F00263BE5 / Frameworks /,
331C80D3294CF70F00263BE5 / Resources /,
);
buildRules = (
);
dependencies = (
331C80DA294CF71000263BE5 /
PBXTargetDependency /,
);
name = RunnerTests;
productName = RunnerTests;
productReference =
331C80D5294CF71000263BE5 /
RunnerTests.xctest /;
productType = "com.apple.product-
type.bundle.unit-test";
};
33CC10EC2044A3C60003C045 / Runner / = {
isa = PBXNativeTarget;

buildConfigurationList =
33CC10FB2044A3C60003C045 / Build configuration list for PBXNativeTarget "Runner" */;*
buildPhases = (
33CC10E92044A3C60003C045 / Sources */,*
33CC10EA2044A3C60003C045 / Frameworks */,*
33CC10EB2044A3C60003C045 / Resources */,*
33CC110E2044A8840003C045 / Bundle Framework */,*
3399D490228B24CF009A79C7 / ShellScript */,*
);
buildRules = (
);
dependencies = (
33CC1120204C79F0003C045 / PBXTargetDependency */,*
);
name = Runner;
packageProductDependencies = (
78A3181F2AECB46A00862997 /

FlutterGeneratedPluginSwiftPackage */,
);
productName = Runner;
productReference =
33CC10ED2044A3C60003C045 / eleven.app /;
productType = "com.apple.product-
type.application";
};
/ End PBXNativeTarget section */

/* Begin PBXProject section /
33CC10E52044A3C60003C045 / Project object
/ = {
isa = PBXProject;
attributes = {
BuildIndependentTargetsInParallel = YES;
LastSwiftUpdateCheck = 0920;
LastUpgradeCheck = 1510;
ORGANIZATIONNAME = "";
TargetAttributes = {

```
331C80D4294CF70F00263BE5 = {
CreatedOnToolsVersion = 14.0;
TestTargetID = 33CC10EC2044A3C60003C045;
};
33CC10EC2044A3C60003C045 = {
CreatedOnToolsVersion = 9.2;
LastSwiftMigration = 1100;
ProvisioningStyle = Automatic;
SystemCapabilities = {
com.apple.Sandbox = {
enabled = 1;
};
};
};
33CC111A2044C6BA0003C045 = {
CreatedOnToolsVersion = 9.2;
ProvisioningStyle = Manual;
};
};
};
```

buildConfigurationList =
33CC10E82044A3C60003C045 / Build*
configuration list for PBXProject "Runner" */;
compatibilityVersion = "Xcode 9.3";
developmentRegion = en;
hasScannedForEncodings = 0;
knownRegions = (
en,
Base,
);
mainGroup = 33CC10E42044A3C60003C045;
packageReferences = (
781AD8BC2B33823900A9FFBB /
XCLocalSwiftPackageReference "Flutter/
ephemeral/Packages/
FlutterGeneratedPluginSwiftPackage" */,
);
productRefGroup =
33CC10EE2044A3C60003C045 / Products */;*
projectDirPath = "";

projectRoot = "";
targets = (
33CC10EC2044A3C60003C045 / Runner */,*
331C80D4294CF70F00263BE5 / RunnerTests */,*
33CC111A2044C6BA0003C045 / Flutter Assemble */,*
);
};
/ End PBXProject section */

/* Begin PBXResourcesBuildPhase section */
331C80D3294CF70F00263BE5 / Resources */ = {*
isa = PBXResourcesBuildPhase;
buildActionMask = 2147483647;
files = (
);
runOnlyForDeploymentPostprocessing = 0;
};
33CC10EB2044A3C60003C045 / Resources */ = {*
isa = PBXResourcesBuildPhase;

buildActionMask = 2147483647;
files = (
33CC10F32044A3C60003C045 /
Assets.xcassets in Resources */,
33CC10F62044A3C60003C045 / MainMenu.xib*
in Resources */,
);
runOnlyForDeploymentPostprocessing = 0;
};
/ End PBXResourcesBuildPhase section */

/* Begin PBXShellScriptBuildPhase section */
3399D490228B24CF009A79C7 / ShellScript */ = {*
isa = PBXShellScriptBuildPhase;
alwaysOutOfDate = 1;
buildActionMask = 2147483647;
files = (
);
inputFileListPaths = (
);

```
inputPaths = (
);
outputFileListPaths = (
);
outputPaths = (
);
runOnlyForDeploymentPostprocessing = 0;
shellPath = /bin/sh;
shellScript = "echo "PRODUCT_NAME.app\" &gt;
\"PROJECT_DIR"/Flutter/
ephemeral/.app_filename && "FLUTTER_ROOT\"/
packages/flutter_tools/bin/macos_assemble.sh
embed\n"; }; 33CC111E2044C6BF0003C045 /*
ShellScript */ = { isa =
PBXShellScriptBuildPhase; buildActionMask =
2147483647; files = ( ); inputFileListPaths = (
Flutter/ephemeral/FlutterInputs.xcfilelist, );
inputPaths = ( Flutter/ephemeral/tripwire, );
outputFileListPaths = ( Flutter/ephemeral/
FlutterOutputs.xcfilelist, ); outputPaths = ( );
```

runOnlyForDeploymentPostprocessing = 0;
shellPath = /bin/sh; shellScript =
"\"FLUTTER_ROOT"/packages/flutter_tools/bin/
macos_assemble.sh && touch Flutter/
ephemeral/tripwire";
};
/ End PBXShellScriptBuildPhase section */

/* Begin PBXSourcesBuildPhase section */
331C80D1294CF70F00263BE5 / Sources */ = {*
isa = PBXSourcesBuildPhase;
buildActionMask = 2147483647;
files = (
331C80D8294CF71000263BE5 /
RunnerTests.swift in Sources */,
);
runOnlyForDeploymentPostprocessing = 0;
};
33CC10E92044A3C60003C045 / Sources */ = {*
isa = PBXSourcesBuildPhase;

buildActionMask = 2147483647;

files = (

33CC11132044BFA00003C045 /

MainFlutterWindow.swift in Sources */,

33CC10F12044A3C60003C045 /

AppDelegate.swift in Sources */,

335BBD1B22A9A15E00E9071D /

GeneratedPluginRegistrant.swift in Sources */,

);

runOnlyForDeploymentPostprocessing = 0;

};

/ End PBXSourcesBuildPhase section */

/* Begin PBXTargetDependency section */

331C80DA294CF71000263BE5 /

PBXTargetDependency */ = {

isa = PBXTargetDependency;

target = 33CC10EC2044A3C60003C045 /

Runner */;

targetProxy = 331C80D9294CF71000263BE5 /

PBXContainerItemProxy /;
};
33CC11202044C79F0003C045 /
PBXTargetDependency / = {
isa = PBXTargetDependency;
target = 33CC111A2044C6BA0003C045 / Flutter
Assemble /;
targetProxy = 33CC111F2044C79F0003C045 /
PBXContainerItemProxy /;
};
/ End PBXTargetDependency section */

/* Begin PBXVariantGroup section /
33CC10F42044A3C60003C045 / MainMenu.xib
/ = {
isa = PBXVariantGroup;
children = (
33CC10F52044A3C60003C045 / Base /,
);
name = MainMenu.xib;

path = Runner;

sourceTree = "<group>";

};

/ End PBXVariantGroup section */

/* Begin XCBuildConfiguration section */

331C80DB294CF71000263BE5 / Debug */ = {*

isa = XCBuildConfiguration;

buildSettings = {

BUNDLE_LOADER = "(TEST_HOST)";

CURRENT_PROJECT_VERSION = 1;

GENERATE_INFOPLIST_FILE = YES;

MARKETING_VERSION = 1.0;

PRODUCT_BUNDLE_IDENTIFIER =

com.example.eleven.RunnerTests;

PRODUCT_NAME = "(TARGET_NAME)";

SWIFT_VERSION = 5.0;

TEST_HOST = "(BUILT_PRODUCTS_DIR)/

eleven.app/

(BUNDLE_EXECUTABLE_FOLDER_PATH)/eleven";

```
};
name = Debug;
};
331C80DC294CF71000263BE5 / Release / = {
isa = XCBuildConfiguration;
buildSettings = {
BUNDLE_LOADER = "(TEST_HOST)";
CURRENT_PROJECT_VERSION = 1;
GENERATE_INFOPLIST_FILE = YES;
MARKETING_VERSION = 1.0;
PRODUCT_BUNDLE_IDENTIFIER =
com.example.eleven.RunnerTests;
PRODUCT_NAME = "(TARGET_NAME)";
SWIFT_VERSION = 5.0;
TEST_HOST = "(BUILT_PRODUCTS_DIR)/
eleven.app/
(BUNDLE_EXECUTABLE_FOLDER_PATH)/eleven";
};
name = Release;
};
```

```
331C80DD294CF71000263BE5 /* Profile */ = {
isa = XCBuildConfiguration;
buildSettings = {
BUNDLE_LOADER = "$(TEST_HOST)";
CURRENT_PROJECT_VERSION = 1;
GENERATE_INFOPLIST_FILE = YES;
MARKETING_VERSION = 1.0;
PRODUCT_BUNDLE_IDENTIFIER =
com.example.eleven.RunnerTests;
PRODUCT_NAME = "$(TARGET_NAME)";
SWIFT_VERSION = 5.0;
TEST_HOST = "$(BUILT_PRODUCTS_DIR)/
eleven.app/
$(BUNDLE_EXECUTABLE_FOLDER_PATH)/eleven";
};
name = Profile;
};
338D0CE9231458BD00FA5F75 /* Profile */ = {
isa = XCBuildConfiguration;
baseConfigurationReference =
```

7AFA3C8E1D35360C0083082E /
Release.xcconfig */;*
buildSettings = {
ALWAYS_SEARCH_USER_PATHS = NO;
*ASSETCATALOG_COMPILER_GENERATE_SWIFT_*
ASSET_SYMBOL_EXTENSIONS = YES;
CLANG_ANALYZER_NONNULL = YES;
CLANG_ANALYZER_NUMBER_OBJECT_CONVER
SION = YES_AGGRESSIVE;
CLANG_CXX_LANGUAGE_STANDARD = "gnu14";
CLANG_CXX_LIBRARY = "libc";
CLANG_ENABLE_MODULES = YES;
CLANG_ENABLE_OBJC_ARC = YES;
CLANG_WARN_BLOCK_CAPTURE_AUTORELEASI
NG = YES;
CLANG_WARN_BOOL_CONVERSION = YES;
CLANG_WARN_CONSTANT_CONVERSION = YES;
CLANG_WARN_DEPRECATED_OBJC_IMPLEMEN
TATIONS = YES;
CLANG_WARN_DIRECT_OBJC_ISA_USAGE =

YES_ERROR;
CLANG_WARN_DOCUMENTATION_COMMENTS = YES;
CLANG_WARN_EMPTY_BODY = YES;
CLANG_WARN_ENUM_CONVERSION = YES;
CLANG_WARN_INFINITE_RECURSION = YES;
CLANG_WARN_INT_CONVERSION = YES;
CLANG_WARN_NON_LITERAL_NULL_CONVERSION = YES;
CLANG_WARN_OBJC_LITERAL_CONVERSION = YES;
CLANG_WARN_OBJC_ROOT_CLASS = YES_ERROR;
CLANG_WARN_RANGE_LOOP_ANALYSIS = YES;
CLANG_WARN_SUSPICIOUS_MOVE = YES;
CODE_SIGN_IDENTITY = "-";
COPY_PHASE_STRIP = NO;
DEAD_CODE_STRIPPING = YES;
DEBUG_INFORMATION_FORMAT = "dwarf-with-dsym";

ENABLE_NS_ASSERTIONS = NO;

ENABLE_STRICT_OBJC_MSGSEND = YES;

ENABLE_USER_SCRIPT_SANDBOXING = NO;

GCC_C_LANGUAGE_STANDARD = gnu11;

GCC_NO_COMMON_BLOCKS = YES;

GCC_WARN_64_TO_32_BIT_CONVERSION = YES;

GCC_WARN_ABOUT_RETURN_TYPE =

YES_ERROR;

GCC_WARN_UNINITIALIZED_AUTOS =

YES_AGGRESSIVE;

GCC_WARN_UNUSED_FUNCTION = YES;

GCC_WARN_UNUSED_VARIABLE = YES;

MACOSX_DEPLOYMENT_TARGET = 10.15;

MTL_ENABLE_DEBUG_INFO = NO;

SDKROOT = macosx;

SWIFT_COMPILATION_MODE = wholemodule;

SWIFT_OPTIMIZATION_LEVEL = "-O";

};

name = Profile;

};

*338D0CEA231458BD00FA5F75 /*Profile */ = {
isa = XCBuildConfiguration;
baseConfigurationReference =
33E5194F232828860026EE4D /*
AppInfo.xcconfig */;
buildSettings = {
ASSETCATALOG_COMPILER_APPICON_NAME =
AppIcon;
CLANG_ENABLE_MODULES = YES;
CODE_SIGN_ENTITLEMENTS = Runner/
DebugProfile.entitlements;
CODE_SIGN_STYLE = Automatic;
COMBINE_HIDPI_IMAGES = YES;
INFOPLIST_FILE = Runner/Info.plist;
LD_RUNPATH_SEARCH_PATHS = (
"(inherited)", "@executable_path/../Frameworks",
); PROVISIONING_PROFILE_SPECIFIER = "";
SWIFT_VERSION = 5.0; }; name = Profile; };
338D0CEB231458BD00FA5F75 /* Profile */ = {
isa = XCBuildConfiguration; buildSettings = {

CODE_SIGN_STYLE = Manual; PRODUCT_NAME = "(TARGET_NAME)";

};

name = Profile;

};

33CC10F92044A3C60003C045 / Debug */ = {*

isa = XCBuildConfiguration;

baseConfigurationReference = 9740EEB21CF90195004384FC / Debug.xcconfig */;*

buildSettings = {

ALWAYS_SEARCH_USER_PATHS = NO;

ASSETCATALOG_COMPILER_GENERATE_SWIFT_ASSET_SYMBOL_EXTENSIONS = YES;

CLANG_ANALYZER_NONNULL = YES;

CLANG_ANALYZER_NUMBER_OBJECT_CONVERSION = YES_AGGRESSIVE;

CLANG_CXX_LANGUAGE_STANDARD = "gnu14";

CLANG_CXX_LIBRARY = "libc";

CLANG_ENABLE_MODULES = YES;

CLANG_ENABLE_OBJC_ARC = YES;
CLANG_WARN_BLOCK_CAPTURE_AUTORELEASI
NG = YES;
CLANG_WARN_BOOL_CONVERSION = YES;
CLANG_WARN_CONSTANT_CONVERSION = YES;
CLANG_WARN_DEPRECATED_OBJC_IMPLEMEN
TATIONS = YES;
CLANG_WARN_DIRECT_OBJC_ISA_USAGE =
YES_ERROR;
CLANG_WARN_DOCUMENTATION_COMMENTS
= YES;
CLANG_WARN_EMPTY_BODY = YES;
CLANG_WARN_ENUM_CONVERSION = YES;
CLANG_WARN_INFINITE_RECURSION = YES;
CLANG_WARN_INT_CONVERSION = YES;
CLANG_WARN_NON_LITERAL_NULL_CONVERSI
ON = YES;
CLANG_WARN_OBJC_LITERAL_CONVERSION =
YES;
CLANG_WARN_OBJC_ROOT_CLASS =

YES_ERROR;
CLANG_WARN_RANGE_LOOP_ANALYSIS = YES;
CLANG_WARN_SUSPICIOUS_MOVE = YES;
CODE_SIGN_IDENTITY = "-";
COPY_PHASE_STRIP = NO;
DEAD_CODE_STRIPPING = YES;
DEBUG_INFORMATION_FORMAT = dwarf;
ENABLE_STRICT_OBJC_MSGSEND = YES;
ENABLE_TESTABILITY = YES;
ENABLE_USER_SCRIPT_SANDBOXING = NO;
GCC_C_LANGUAGE_STANDARD = gnu11;
GCC_DYNAMIC_NO_PIC = NO;
GCC_NO_COMMON_BLOCKS = YES;
GCC_OPTIMIZATION_LEVEL = 0;
GCC_PREPROCESSOR_DEFINITIONS = (
"DEBUG=1",
"(inherited)",);
GCC_WARN_64_TO_32_BIT_CONVERSION =
YES; GCC_WARN_ABOUT_RETURN_TYPE =
YES_ERROR;

GCC_WARN_UNINITIALIZED_AUTOS =
YES_AGGRESSIVE;
GCC_WARN_UNUSED_FUNCTION = YES;
GCC_WARN_UNUSED_VARIABLE = YES;
MACOSX_DEPLOYMENT_TARGET = 10.15;
MTL_ENABLE_DEBUG_INFO = YES;
ONLY_ACTIVE_ARCH = YES; SDKROOT =
macosx;
SWIFT_ACTIVE_COMPILATION_CONDITIONS =
DEBUG; SWIFT_OPTIMIZATION_LEVEL = "-
Onone"; }; name = Debug; };
33CC10FA2044A3C60003C045 /* Release */ = {
isa = XCBuildConfiguration;
baseConfigurationReference =
7AFA3C8E1D35360C0083082E /*
Release.xcconfig */; buildSettings = {
ALWAYS_SEARCH_USER_PATHS = NO;
ASSETCATALOG_COMPILER_GENERATE_SWIFT_
ASSET_SYMBOL_EXTENSIONS = YES;
CLANG_ANALYZER_NONNULL = YES;

CLANG_ANALYZER_NUMBER_OBJECT_CONVERSION = YES_AGGRESSIVE;
CLANG_CXX_LANGUAGE_STANDARD = "gnu++14"; CLANG_CXX_LIBRARY = "libc++";
CLANG_ENABLE_MODULES = YES;
CLANG_ENABLE_OBJC_ARC = YES;
CLANG_WARN_BLOCK_CAPTURE_AUTORELEASING = YES; CLANG_WARN_BOOL_CONVERSION = YES; CLANG_WARN_CONSTANT_CONVERSION = YES;
CLANG_WARN_DEPRECATED_OBJC_IMPLEMENTATIONS = YES;
CLANG_WARN_DIRECT_OBJC_ISA_USAGE = YES_ERROR;
CLANG_WARN_DOCUMENTATION_COMMENTS = YES; CLANG_WARN_EMPTY_BODY = YES;
CLANG_WARN_ENUM_CONVERSION = YES;
CLANG_WARN_INFINITE_RECURSION = YES;
CLANG_WARN_INT_CONVERSION = YES;
CLANG_WARN_NON_LITERAL_NULL_CONVERSI

ON = YES;
CLANG_WARN_OBJC_LITERAL_CONVERSION = YES; CLANG_WARN_OBJC_ROOT_CLASS = YES_ERROR;
CLANG_WARN_RANGE_LOOP_ANALYSIS = YES;
CLANG_WARN_SUSPICIOUS_MOVE = YES;
CODE_SIGN_IDENTITY = "-";
COPY_PHASE_STRIP = NO;
DEAD_CODE_STRIPPING = YES;
DEBUG_INFORMATION_FORMAT = "dwarf-with-dsym"; ENABLE_NS_ASSERTIONS = NO;
ENABLE_STRICT_OBJC_MSGSEND = YES;
ENABLE_USER_SCRIPT_SANDBOXING = NO;
GCC_C_LANGUAGE_STANDARD = gnu11;
GCC_NO_COMMON_BLOCKS = YES;
GCC_WARN_64_TO_32_BIT_CONVERSION = YES; GCC_WARN_ABOUT_RETURN_TYPE = YES_ERROR;
GCC_WARN_UNINITIALIZED_AUTOS = YES_AGGRESSIVE;

GCC_WARN_UNUSED_FUNCTION = YES; GCC_WARN_UNUSED_VARIABLE = YES; MACOSX_DEPLOYMENT_TARGET = 10.15; MTL_ENABLE_DEBUG_INFO = NO; SDKROOT = macosx; SWIFT_COMPILATION_MODE = wholemodule; SWIFT_OPTIMIZATION_LEVEL = "-O"; }; name = Release; }; 33CC10FC2044A3C60003C045 / Debug */ = { isa = XCBuildConfiguration; baseConfigurationReference = 33E5194F232828860026EE4D /* AppInfo.xcconfig */; buildSettings = { ASSETCATALOG_COMPILER_APPICON_NAME = AppIcon; CLANG_ENABLE_MODULES = YES; CODE_SIGN_ENTITLEMENTS = Runner/DebugProfile.entitlements; CODE_SIGN_STYLE = Automatic; COMBINE_HIDPI_IMAGES = YES; INFOPLIST_FILE = Runner/Info.plist; LD_RUNPATH_SEARCH_PATHS = ("(inherited)", "@executable_path/../Frameworks",*

```
);
PROVISIONING_PROFILE_SPECIFIER = "";
SWIFT_OPTIMIZATION_LEVEL = "-Onone";
SWIFT_VERSION = 5.0;
};
name = Debug;
};
33CC10FD2044A3C60003C045 / Release / = {
isa = XCBuildConfiguration;
baseConfigurationReference =
33E5194F232828860026EE4D /
AppInfo.xcconfig /;
buildSettings = {
ASSETCATALOG_COMPILER_APPICON_NAME =
AppIcon;
CLANG_ENABLE_MODULES = YES;
CODE_SIGN_ENTITLEMENTS = Runner/
Release.entitlements;
CODE_SIGN_STYLE = Automatic;
COMBINE_HIDPI_IMAGES = YES;
```

INFOPLIST_FILE = Runner/Info.plist;
LD_RUNPATH_SEARCH_PATHS = (
"(inherited)", "@executable_path/../Frameworks",
); PROVISIONING_PROFILE_SPECIFIER = "";
SWIFT_VERSION = 5.0; }; name = Release; };
33CC111C2044C6BA0003C045 / Debug */ = {*
isa = XCBuildConfiguration; buildSettings = {
CODE_SIGN_STYLE = Manual; PRODUCT_NAME
= "(TARGET_NAME)";
};
name = Debug;
};
33CC111D2044C6BA0003C045 / Release */ = {*
isa = XCBuildConfiguration;
buildSettings = {
CODE_SIGN_STYLE = Automatic;
PRODUCT_NAME = "$(TARGET_NAME)";
};
name = Release;
};

/ End XCBuildConfiguration section */

/* Begin XCConfigurationList section /
331C80DE294CF71000263BE5 / Build configuration list for PBXNativeTarget "RunnerTests" / = {
isa = XCConfigurationList;
buildConfigurations = (
331C80DB294CF71000263BE5 / Debug /,
331C80DC294CF71000263BE5 / Release /,
331C80DD294CF71000263BE5 / Profile /,
);
defaultConfigurationIsVisible = 0;
defaultConfigurationName = Release;
};
33CC10E82044A3C60003C045 / Build configuration list for PBXProject "Runner" / = {
isa = XCConfigurationList;
buildConfigurations = (
33CC10F92044A3C60003C045 / Debug /,

33CC10FA2044A3C60003C045 / Release */,
338D0CE9231458BD00FA5F75 / Profile */,
);
defaultConfigurationIsVisible = 0;
defaultConfigurationName = Release;
};
33CC10FB2044A3C60003C045 / Build* configuration list for PBXNativeTarget "Runner" */ = {
isa = XCConfigurationList;
buildConfigurations = (
33CC10FC2044A3C60003C045 / Debug */,
33CC10FD2044A3C60003C045 / Release */,
338D0CEA231458BD00FA5F75 / Profile */,
);
defaultConfigurationIsVisible = 0;
defaultConfigurationName = Release;
};
33CC111B2044C6BA0003C045 / Build* configuration list for PBXAggregateTarget

"Flutter Assemble" */ = {
isa = XCConfigurationList;
buildConfigurations = (
33CC111C2044C6BA0003C045 /* Debug */,
33CC111D2044C6BA0003C045 /* Release */,
338D0CEB231458BD00FA5F75 /* Profile */,
);
defaultConfigurationIsVisible = 0;
defaultConfigurationName = Release;
};
/* End XCConfigurationList section */

/* Begin XCLocalSwiftPackageReference section */
781AD8BC2B33823900A9FFBB /* XCLocalSwiftPackageReference "Flutter/ephemeral/Packages/FlutterGeneratedPluginSwiftPackage" */ = {
isa = XCLocalSwiftPackageReference;
relativePath = Flutter/ephemeral/Packages/

FlutterGeneratedPluginSwiftPackage;
};
/ End XCLocalSwiftPackageReference section */

/* Begin XCSwiftPackageProductDependency section */
78A3181F2AECB46A00862997 / FlutterGeneratedPluginSwiftPackage */ = {*
isa = XCSwiftPackageProductDependency;
productName = FlutterGeneratedPluginSwiftPackage;
};
/ End XCSwiftPackageProductDependency section */
};
rootObject = 33CC10E52044A3C60003C045 / Project object */;*
}

Introduction

The United Nations General Assembly (UNGA), through Resolution 64/236 of 24 December 2009, decided to organize the United Nations Conference on Sustainable Development, Rio de Janeiro, 3 to 6 June 2012 (UNCSD, also referred to as Rio+20).
The preparatory process foresees three sessions of the preparatory Committee and three inter-sessional meetings.

The Second Preparatory Committee of UNCSD, held in March 2011, has invited “Member States, the relevant United Nations system organizations, and relevant stakeholders to provide their inputs and contributions in writing by 1 November 2011 for inclusion in a compilation document to serve as basis for the preparation of the zero-draft of the outcome

document”.

Since May 2010, FAO’s active contribution to the preparatory process of UNCSD has resulted in the inclusion of food security among the priority areas under consideration. FAO is particularly contributing to shaping the green economy agenda of UNCSD by providing elements pertaining to its mandate. To this end, an analysis has been carried out on the interactions between the green economy and the food and agriculture sector, including opportunities and constraints.

The Greening the Economy with Agriculture (GEA) Initiative seeks to contribute to the definition and implementation of the green economy, with a particular emphasis on food security. As part of this initiative, FAO organized broad stakeholder consultations through an FAO/

UNCTAD/Biovision side event in New York on 8 March 2011, and a joint FAO/OECD Expert Meeting on Greening the Economy with Agriculture in Paris, France, 5 to 7 September 2011. An informal seminar was held with Permanent Representatives to FAO on 4 November 2011 to brief them on progress made thus far.

GEA aims to promote a dialogue between the agriculture, forestry and fisheries constituencies and other partners, on sustainable development strategies, as well as the overall participation of food and agriculture stakeholders into the Rio+20 process and beyond, with a view to facilitating their access to the resources and institutional arrangements that will be put in place in order to effectively move towards sustainable development. By taking a proactive role in international, regional and national

debates G r e e n i n g t h e E c o n o m y w i t h A g r i c u l t u r e 3 gea for Rio+20 and beyond, the GEA Initiative would create bridges among different types of stakeholders and between constituencies, notably between agriculture and the environment, while strengthening the overall resilience of countries to exogenous shocks, either macroeconomic or ecological.

Concepts and definitions

Although UN Member States have not yet come to an agreement on the definition of the green economy, they recognize that an efficient, functioning economy is a precondition for addressing the environmental and social pillars of sustainability. Therefore, the green economy is seen as a key implementation tool for sustainable development.

GEA refers to ensuring the right to adequate food, as well as food and nutrition security – in terms of food availability, access, stability and utilization – and contributing to the quality of rural livelihoods, while efficiently managing natural resources and improving resilience and equity throughout the food supply chain, taking into account countries' individual circumstances.

GEA can be achieved by applying an ecosystem approach to agriculture, forestry and fisheries management in a manner that addresses the multiplicity of societal needs and desires, without jeopardizing the options for future generations to benefit from the full range of goods and services provided by terrestrial, aquatic and marine ecosystems. Therefore, GEA strives to:

- Achieve food and nutrition security through an appropriate balance between domestic production and trade;

- Contribute to achieving the right to adequate food for all;
- Ensure decent rural livelihoods;
- Use traditional and scientific knowledge to maintain healthy ecosystems that integrate

food
production and respect natural resource constraints.