



# Module 3 Day 7

## JavaScript Functions

# Array Functions

- `concat()`
  - Let `newArray = array1.concat(array2)`
- `join()`
  - Joins all elements into a string
- `slice(startElement, nonInclusiveEndElement)`
  - Returns a portion of an array (akin to substring). Does not modify original
- `splice(start, count, newelements...)`
  - Removes / adds elements to an array. Modifies the original array.
- `indexOf()`, `lastIndexOf()`
- [https://www.w3schools.com/jsref/jsref\\_obj\\_array.asp](https://www.w3schools.com/jsref/jsref_obj_array.asp)
- [https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global\\_Objects/Array#](https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Global_Objects/Array#)

# Named Functions

- Denoted by the function keyword plus name
- Parameters, but no types
- No return type declared
- Functions not overloaded, but overwritten

```
/**
 * Create JSDoc documentation so that VSCode can understand and give you IntelliSense.
 *
 * @param {any} parameter1 The first parameters to append
 * @param {string} parameter2 The second parameter to append
 * @returns {string} The two parameters concatenated.
 */
function someFunction(parameter1, parameter2) {
  let s = '' + parameter1 + parameter2;
  return s;
}
```

# Parameters

- Always optional, but default to **undefined**
- Default values can be assigned
  - Can be expressions, call functions, new objects, create arrays
  - Can refer to parameters to the left in the list

```
function greet(name, greeting, message = greeting + ' ' + name) {
```

- Passing **undefined** results in the default value
- [https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Functions/Default\\_parameters](https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference/Functions/Default_parameters)
- **arguments** can be used to get all the arguments passed in
- Arguments and parameters are *not technically* the same thing ([w3schools](https://www.w3schools.com/js/default.asp))

Function **parameters** are the **names** listed in the function definition.

Function **arguments** are the real **values** passed to (and received by) the function.

Let's  
Code

# Functions are "first-class"

- Functions are data!
- Can be stored in variables
- Can be defined as properties of an object
- Can be passed as parameters into other functions!
- Like other values, can be "named", or can be literal (anonymous)

# Anonymous Functions

- Functions (blocks of code) can be passed around like other values
  - You can pass strings, numbers, arrays, objects and functions as parameters
  - (this is true in C# also)
- Are all values named?
  - We don't always create a variable before passing it into a function
  - We don't have to create a function before passing it in either
- Syntax:
  - `function (s) {return s.toUpperCase();}`
  - OR, the "fat arrow" / lambda syntax:
    - `(s) => {return s.toUpperCase();}`
  - OR, even briefer:
    - `s => s.toUpperCase()`
- NOTE: any amount of code can be inside the { }



# Array functions requiring function parameter

JS Function	Parameters	Returns	C# Linq
<a href="#">forEach</a>	Item	Executes the code iteratively, for each element in the array. No return value.	
<a href="#">filter</a>	Item	Array of the same type ( $\leq$ original size), filtered by the function	Where
<a href="#">map</a>	Item	Array of same size, original elements "mapped" to something new	Select
<a href="#">sort</a>	Item1, Item2	Array of same size and type, with elements sorted. Return 1 if Item1 > Item2, -1 if item1 < item2, 0 otherwise	OrderBy
<a href="#">reduce</a>	Accum, Item	A single value, allows calculating a running value	Sum, Aggregate
<a href="#">every</a>	Item	Boolean, true if every item meets the condition	All
<a href="#">some</a>	Item	Boolean, true if at least one item meets the condition	Any

Let's  
Code

# JSDoc

- VS Code uses this documentation for IntelliSense
- `@param {type} param-name Parameter-description`
- `@param {type} [param-name=default-value] Description...`
- `@returns {type} Return-value-description`
- <https://jsdoc.app/>, <https://jsdoc.app/index.html#block-tags>