


# Explainable Artificial Intelligence

---



## Approaches to Robust Online Explanations

August 2021



- Introduction
  - Motivation
  - Properties
- Experiments
- Results
- (Outlook)



- Data streams
  - Noise, Concept drift
  - Retraining of explained model

- Data streams
  - Noise, Concept drift
  - Retraining of explained model
- Inconsistent explanations

- Data streams
  - Noise, Concept drift
  - Retraining of explained model
- Inconsistent explanations
- Example:
  - At time:  $t$ 
    - Transient model state
    - Loan not approved with explanation  $e$
  - At time:  $t + N$ 
    - Loan not approved with explanation  $e' \neq e$
    - e.g. Applicant increased expenses, but transient model state passed

# Introduction: Properties

---

- Concentration on Approaches:
  - (Explained) Model agnostic
  - Handle Post-hoc explanations
  - Explanations = Feature attributions
- Model attributions from weights as ground truth



- Concentration on Approaches:
  - (Explained) Model agnostic
  - Handle Post-hoc explanations
  - Explanations = Feature attributions
- Model attributions from weights as ground truth
- Desired properties
  - Local faithfulness
  - Global faithfulness
  - Efficiency
  - Stability



- Local Explainers

- LIME
- SHAP

$$a_t = l(x_t, f(x_t), X)$$

- $X$  is baseline



- Global Explainers
  - FIRES
    - Feature scores used as Feature attributions
    - Importance + Uncertainty

$$a_t = FIRES(x_t, f(x_t))$$

- Global Explainers

- FIRES

- Feature scores used as Feature attributions
    - Importance + Uncertainty

$$a_t = \text{FIRES}(x_t, f(x_t))$$

- Weighted Gaussian Explainer

- Outputs linearly dependent on attributions

$$P(y_t | x_t, a_t) = \mathcal{N}(y_t; x_t^T a_t, \Lambda)$$

- Mean of posterior

# Approaches: Combination of Local and Global Explainers

---

# Approaches: Combination of Local and Global Explainers

---

- Ensemble of Explainers
  1. FIRES → Model distribution
  2. Sample N Models
  3. Local explainer → Explain predictions of N models
    1. LIME or SHAP
  4. Aggregate explanations (e.g. Mean of explanations)



# Approaches: Combination of Local and Global Explainers

---

- Ensemble of Explainers

1. FIRES → Model distribution
2. Sample N Models
3. Local explainer → Explain predictions of N models
  1. LIME or SHAP
4. Aggregate explanations (e.g. Mean of explanations)

- Weighted Local and Global Explainers

$$a_t = \frac{w_l \cdot l(x_t, f(x_t)) + w_g \cdot g(x_t, f(x_t))}{w_l + w_g}$$



- xEvaluator
  - Environment for experimentation with explanations and data streams

- xEvaluator
  - Environment for experimentation with explanations and data streams
- Datasets:
  - Synthetic, 5000 samples
  - From practice:
    - Spambase
    - Card default

- xEvaluator
  - Environment for experimentation with explanations and data streams
- Datasets:
  - Synthetic, 5000 samples
  - From practice:
    - Spambase
    - Card default
- Ground truth:
  - Explained model weights

**Desired Properties**

**Evaluation Metrics**

## Desired Properties

Local faithfulness

## Evaluation Metrics

$$LF_{t+1} = LF_t + \left| \frac{a_{t+1}}{\sum_i |a_{t+1_i}|} - \frac{g_{t+1}}{\sum_i |g_{t+1_i}|} \right|$$

## Desired Properties

Local faithfulness

Global faithfulness

## Evaluation Metrics

$$LF_{t+1} = LF_t + \left| \frac{a_{t+1}}{\sum_i |a_{t+1_i}|} - \frac{g_{t+1}}{\sum_i |g_{t+1_i}|} \right|$$

Top-10 Ranking Accuracy



## Desired Properties

Local faithfulness

Global faithfulness

Efficiency

## Evaluation Metrics

$$LF_{t+1} = LF_t + \left| \frac{a_{t+1}}{\sum_i |a_{t+1_i}|} - \frac{g_{t+1}}{\sum_i |g_{t+1_i}|} \right|$$

Top-10 Ranking Accuracy

Timings

## Desired Properties

Local faithfulness

Global faithfulness

Efficiency

Stability

## Evaluation Metrics

$$LF_{t+1} = LF_t + \left| \frac{a_{t+1}}{\sum_i |a_{t+1_i}|} - \frac{g_{t+1}}{\sum_i |g_{t+1_i}|} \right|$$

Top-10 Ranking Accuracy

Timings

$$S_{t+1} = S_t + \left| \frac{a_{t+1}}{\sum_i |a_{t+1_i}|} - \frac{a_t}{\sum_i |a_{t_i}|} \right|$$

# Results: Time and Stability

---

# Results: Time and Stability

---

- Average over all data sets

# Results: Time and Stability

---

- Average over all data sets

---

	<b>Explainer</b>	<b>Time (ms)</b>
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

---

## Results: Time and Stability

- Average over all data sets

---

	<b>Explainer</b>	<b>Time (ms)</b>
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

---

---

	<b>Explainer</b>	<b>Stablity</b>
1.	FIRES	106.36
2.	WeightedGaussian	108.73
3.	LIME+FIRES	1296.45
4.	LIME	1906.25
5.	LIME-Ensemble	2431.43
6.	SHAP+FIRES	4567.24
7.	SHAP-Ensemble	6079.14
8.	SHAP	7192.02

---

## Results: Time and Stability

- Average over all data sets

	Explainer	Time (ms)
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

	Explainer	Stablity
1.	FIRES	106.36
2.	WeightedGaussian	108.73
3.	LIME+FIRES	1296.45
4.	LIME	1906.25
5.	LIME-Ensemble	2431.43
6.	SHAP+FIRES	4567.24
7.	SHAP-Ensemble	6079.14
8.	SHAP	7192.02

- Global better than Local

# Results: Time and Stability

- Average over all data sets

	Explainer	Time (ms)
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

	Explainer	Stablity
1.	FIRES	106.36
2.	WeightedGaussian	108.73
3.	LIME+FIRES	1296.45
4.	LIME	1906.25
5.	LIME-Ensemble	2431.43
6.	SHAP+FIRES	4567.24
7.	SHAP-Ensemble	6079.14
8.	SHAP	7192.02

- Global better than Local

- LIME better than SHAP



# Results: Time and Stability

- Average over all data sets

	Explainer	Time (ms)
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

	Explainer	Stablity
1.	FIRES	106.36
2.	WeightedGaussian	108.73
3.	LIME+FIRES	1296.45
4.	LIME	1906.25
5.	LIME-Ensemble	2431.43
6.	SHAP+FIRES	4567.24
7.	SHAP-Ensemble	6079.14
8.	SHAP	7192.02

- Ensemble efficiency penalty

- Global better than Local

- LIME better than SHAP

# Results: Time and Stability

- Average over all data sets

	Explainer	Time (ms)
1.	FIRES	0.87
2.	WeightedGaussian	2.34
3.	LIME	8.00
4.	LIME+FIRES	8.95
5.	SHAP	9.56
6.	SHAP+FIRES	10.10
7.	LIME-Ensemble	115.92
8.	SHAP-Ensemble	158.85

- Ensemble efficiency penalty

	Explainer	Stablity
1.	FIRES	106.36
2.	WeightedGaussian	108.73
3.	LIME+FIRES	1296.45
4.	LIME	1906.25
5.	LIME-Ensemble	2431.43
6.	SHAP+FIRES	4567.24
7.	SHAP-Ensemble	6079.14
8.	SHAP	7192.02

- Ensemble stabilizes SHAP

- Global better than Local


- LIME better than SHAP

# Results: Local Faithfulness vs Stability


---




# Results: Local Faithfulness vs Stability




# Results: Local Faithfulness vs Stability




# Results: Local Faithfulness vs Stability



# Results: Local Faithfulness vs Stability




# Results: Local Faithfulness vs Stability





# Results: Local Faithfulness vs Stability




# Results: Global Faithfulness vs Stability


---




# Results: Global Faithfulness vs Stability




# Results: Global Faithfulness vs Stability




# Results: Global Faithfulness vs Stability




# Results: Global Faithfulness vs Stability




↓ Better



# Results: Global Faithfulness vs Stability




# Results: Global Faithfulness vs Stability





# Results: Global Faithfulness vs Stability






- Feature selection scores as explanations

- Feature selection scores as explanations
- Global + Local explainers
  - e.g. Include local explainer output into prior of global explainers

- Feature selection scores as explanations
- Global + Local explainers
  - e.g. Include local explainer output into prior of global explainers
- (Time-weighted) sliding window for ranking accuracy

- Feature selection scores as explanations
- Global + Local explainers
  - e.g. Include local explainer output into prior of global explainers
- (Time-weighted) sliding window for ranking accuracy
- Surrogate rule extraction approaches

- (Global) explanations through visualization
- Explainer evaluation through visualization



---

# Thank you!