

(/)



You just released the optional tasks of this project. Have fun!

0x14. C - Bit manipulation

C

By: Julien Barbier

Weight: 1

Project will start Aug 23, 2022 12:00 AM, must end by Aug 24, 2022 12:00 AM

✓ was released at Aug 23, 2022 6:00 AM

✓ An auto review will be launched at the deadline

A	B	$A \mid B$	$A \& B$	$A \wedge B$	$\sim A$
0	0	0	0	0	1
0	1	1	0	1	1
1	0	1	0	1	0
1	1	1	1	0	0

Resources

Read or watch:

- Google (/rltoken/-tOFAtANisYQthxNBmJB8g)
- Youtube (/rltoken/-PNa1vv5T3tqVvY4PRIGrg)

Learning Objectives



At the end of this project, you are expected to be able to explain to anyone (/rltoken/l5Fy78OBq-wgaGEpcgq2oA), **without the help of Google**:

General

- Look for the right source of information without too much help
- How to manipulate bits and use bitwise operators

Copyright - Plagiarism

- You are tasked to come up with solutions for the tasks below yourself to meet with the above learning objectives.
- You will not be able to meet the objectives of this or any following project by copying and pasting someone else's work.
- You are not allowed to publish any content of this project.
- Any form of plagiarism is strictly forbidden and will result in removal from the program.

Requirements

General

- Allowed editors: `vi`, `vim`, `emacs`
- All your files will be compiled on Ubuntu 20.04 LTS using `gcc`, using the options `-Wall -Werror -Wextra -pedantic -std=gnu89`
- All your files should end with a new line
- A `README.md` file, at the root of the folder of the project is mandatory
- Your code should use the `Betty` style. It will be checked using `betty-style.pl` (<https://github.com/holbertonschool/Betty/blob/master/betty-style.pl>) and `betty-doc.pl` (<https://github.com/holbertonschool/Betty/blob/master/betty-doc.pl>)
- You are not allowed to use global variables
- No more than 5 functions per file
- The only C standard library functions allowed are `malloc`, `free` and `exit`. Any use of functions like `printf`, `puts`, `calloc`, `realloc` etc... is forbidden
- You are allowed to use `_putchar` (https://github.com/holbertonschool/_putchar.c/blob/master/_putchar.c)
- You don't have to push `_putchar.c`, we will use our file. If you do it won't be taken into account
- In the following examples, the `main.c` files are shown as examples. You can use them to test your functions, but you don't have to push them to your repo (if you do we won't take them into account). We will use our own `main.c` files at compilation. Our `main.c` files might be different from the one shown in the examples
- The prototypes of all your functions and the prototype of the function `_putchar` should be included in your header file called `main.h`
- Don't forget to push your header file
- All your header files should be include guarded



Quiz questions

Great! You've completed the quiz successfully! Keep going! ([Hide quiz](#))

Question #0

What is 0x89 in base10?

- ☐ 89
- ☐ 135
- ☒ 137
- ☐ 139

Question #1

What is 0x89 in base2?

- ☐ 0b10101001
- ☒ 0b10001001
- ☐ 0b01101001
- ☐ 0b10001000

Question #2

What is 0b001010010 in base10?

- ☐ 81
- ☒ 82
- ☐ 83
- ☐ 84

Question #3

What is 0b01101101 in base16?

- ☐ 0x36
- ☒ 0x6D
- ☐ 0x6E



- ☐ 0x7D
(/)
☐ 0xD6



Question #4

What is 98 in base2?

- ☐ 0b01010010
☒ 0b01100010
☐ 0b10011000

Question #5

What is 98 in base16?

- ☒ 0x62
☐ 0x98
☐ 0x96

Question #6

$0x01 \& 0x01 = ?$

- ☐ 0x00
☒ 0x01
☐ 0x02

Question #7

$0x01 | 0x01 = ?$

- ☐ 0x00
☒ 0x01
☐ 0x02

Question #8

$0x01 \& 0x00 = ?$

- ☒ 0x00



☐ 0x01

(/)

☐ 0x02

Question #9

0x01 | 0x00 = ?

☐ 0x00☒ 0x01☐ 0x02

Question #10

0x66 & 0x22 = ?

☒ 0x22☐ 0x44☐ 0x66

Question #11

0x44 | 0x22 = ?

☐ 0x22☐ 0x44☒ 0x66

Question #12

0x89 & 0x01 = ?

☐ 0x00☒ 0x01☐ 0x88☐ 0x89

Question #13

0x88 & 0x01 = ?



☒ 0x00

(/)

☐ 0x01☐ 0x88☐ 0x89

Question #14

0x02 >> 1 = ?

☐ 0x02☒ 0x01☐ 0x00

Question #15

0x89 >> 3 = ?

☐ 0x89☐ 0x44☐ 0x22☒ 0x11☐ 0x08

Question #16

0x01 << 1 = ?

☐ 0x00☐ 0x01☒ 0x02☐ 0x03☐ 0x10

Question #17

0x13 << 1 = ?

☐ 0x13☒ 0x26

- ☐ 0x4C
(/)
☐ 0x98



Question #18

~ 0x12 = ?

- ☒ 0xED
☐ 0xFD
☐ 0xEE
☐ 0x21

Question #19

~ 0x98 = ?

- ☐ 0x66
☒ 0x67
☐ 0x68

Tasks

0.0

mandatory

Write a function that converts a binary number to an `unsigned int`.

- Prototype: `unsigned int binary_to_uint(const char *b);`
- where `b` is pointing to a string of `0` and `1` chars
- Return: the converted number, or `0` if
 - there is one or more chars in the string `b` that is not `0` or `1`
 - `b` is `NULL`



```
julien@ubuntu:~/0x14. Binary$ cat 0-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    unsigned int n;

    n = binary_to_uint("1");
    printf("%u\n", n);
    n = binary_to_uint("101");
    printf("%u\n", n);
    n = binary_to_uint("1e01");
    printf("%u\n", n);
    n = binary_to_uint("1100010");
    printf("%u\n", n);
    n = binary_to_uint("00000000000000000000110010010");
    printf("%u\n", n);
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 0-main.
c 0-binary_to_uint.c -o a
julien@ubuntu:~/0x14. Binary$ ./a
1
5
0
98
402
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: alx-low_level_programming
- Directory: 0x14-bit_manipulation
- File: 0-binary_to_uint.c

☒ Done!

Help

Check your code



Write a function that prints the binary representation of a number.

(/)

- Prototype: void print_binary(unsigned long int n);
- Format: see example
- You are not allowed to use arrays
- You are not allowed to use malloc
- You are not allowed to use the % or / operators

```
julien@ubuntu:~/0x14. Binary$ cat 1-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    print_binary(0);
    printf("\n");
    print_binary(1);
    printf("\n");
    print_binary(98);
    printf("\n");
    print_binary(1024);
    printf("\n");
    print_binary((1 << 10) + 1);
    printf("\n");
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 1-main.
c 1-print_binary.c _putchar.c -o b
julien@ubuntu:~/0x14. Binary$ ./b
0
1
1100010
10000000000
100000000001
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: alx-low_level_programming
- Directory: 0x14-bit_manipulation
- File: 1-print_binary.c

✓ Done!

Help

Check your code



2/10

mandatory

Write a function that returns the value of a bit at a given index.

- Prototype: `int get_bit(unsigned long int n, unsigned int index);`
- where `index` is the index, starting from 0 of the bit you want to get
- Returns: the value of the bit at index `index` or -1 if an error occurred

```
julien@ubuntu:~/0x14. Binary$ cat 2-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    int n;

    n = get_bit(1024, 10);
    printf("%d\n", n);
    n = get_bit(98, 1);
    printf("%d\n", n);
    n = get_bit(1024, 0);
    printf("%d\n", n);
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 2-main.c 2-get_bit.c -o c
julien@ubuntu:~/0x14. Binary$ ./c
1
1
0
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: `alx-low_level_programming`
- Directory: `0x14-bit_manipulation`
- File: `2-get_bit.c`

☒ Done!

Help

Check your code



3.11

(/)

Write a function that sets the value of a bit to 1 at a given index.

- Prototype: `int set_bit(unsigned long int *n, unsigned int index);`
- where `index` is the index, starting from 0 of the bit you want to set
- Returns: 1 if it worked, or -1 if an error occurred

```
julien@ubuntu:~/0x14. Binary$ cat 3-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    unsigned long int n;

    n = 1024;
    set_bit(&n, 5);
    printf("%lu\n", n);
    n = 0;
    set_bit(&n, 10);
    printf("%lu\n", n);
    n = 98;
    set_bit(&n, 0);
    printf("%lu\n", n);
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 3-main.
c 3-set_bit.c -o d
julien@ubuntu:~/0x14. Binary$ ./d
1056
1024
99
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: `alx-low_level_programming`
- Directory: `0x14-bit_manipulation`
- File: `3-set_bit.c`

✓ Done!

Help

Check your code



4/100

mandatory

Write a function that sets the value of a bit to 0 at a given index.

- Prototype: `int clear_bit(unsigned long int *n, unsigned int index);`
- where `index` is the index, starting from 0 of the bit you want to set
- Returns: 1 if it worked, or -1 if an error occurred

```
julien@ubuntu:~/0x14. Binary$ cat 4-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    unsigned long int n;

    n = 1024;
    clear_bit(&n, 10);
    printf("%lu\n", n);
    n = 0;
    clear_bit(&n, 10);
    printf("%lu\n", n);
    n = 98;
    clear_bit(&n, 1);
    printf("%lu\n", n);
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 4-main.c 4-clear_bit.c -o e
julien@ubuntu:~/0x14. Binary$ ./e
0
0
96
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: `alx-low_level_programming`
- Directory: `0x14-bit_manipulation`
- File: `4-clear_bit.c`

☒ Done!

Help

Check your code



5/101

mandatory

Write a function that returns the number of bits you would need to flip to get from one number to another.

- Prototype: `unsigned int flip_bits(unsigned long int n, unsigned long int m);`
- You are not allowed to use the `%` or `/` operators

```
julien@ubuntu:~/0x14. Binary$ cat 5-main.c
#include <stdio.h>
#include "main.h"

/**
 * main - check the code
 *
 * Return: Always 0.
 */
int main(void)
{
    unsigned int n;

    n = flip_bits(1024, 1);
    printf("%u\n", n);
    n = flip_bits(402, 98);
    printf("%u\n", n);
    n = flip_bits(1024, 3);
    printf("%u\n", n);
    n = flip_bits(1024, 1025);
    printf("%u\n", n);
    return (0);
}
julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 5-main.c 5-flip_bits.c -o f
julien@ubuntu:~/0x14. Binary$ ./f
2
5
3
1
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: `alx-low_level_programming`
- Directory: `0x14-bit_manipulation`
- File: `5-flip_bits.c`

☒ Done!



6. Endianness

#advanced

Write a function that checks the endianness.

- Prototype: `int get_endianness(void);`
- Returns: 0 if big endian, 1 if little endian

```
julien@ubuntu:~/0x14. Binary$ cat 100-main.c
#include <stdio.h>
#include "main.h"

int main(void)
{
    int n;

    n = get_endianness();
    if (n != 0)
    {
        printf("Little Endian\n");
    }
    else
    {
        printf("Big Endian\n");
    }
    return (0);
}

julien@ubuntu:~/0x14. Binary$ gcc -Wall -pedantic -Werror -Wextra -std=gnu89 100-main.c 100-get_endianness.c -o h
julien@ubuntu:~/0x14. Binary$ ./h
Little Endian

julien@ubuntu:~/0x14. Binary$ lscpu | head
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:             Little Endian
CPU(s):                 1
On-line CPU(s) list:   0
Thread(s) per core:    1
Core(s) per socket:    1
Socket(s):              1
NUMA node(s):          1
Vendor ID:              GenuineIntel
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: `alx-low_level_programming`
- Directory: `0x14-bit_manipulation`
- File: `100-get_endianness.c`





Done!

Help

Check your code



7. Crackme3

#advanced

Find the password for this program (<https://github.com/holbertonschool/0x13.c>).

- Save the password in the file 101-password
- Your file should contain the exact password, no new line, no extra space

```
julien@ubuntu:~/0x14. Binary$ ./crackme3 `cat 101-password`  
Congratulations!  
julien@ubuntu:~/0x14. Binary$
```

Repo:

- GitHub repository: alx-low_level_programming
- Directory: 0x14-bit_manipulation
- File: 101-password



Done!

Help

Check your code

>_ Get a sandbox

Copyright © 2022 ALX, All rights reserved.

