

Karl Fischer Titrator

TITR-41V TITR-41C



TITR-41V

Selling point

-  7.0-inch high-contrast color LCD touch screen
-  Coulometric KF Titration
-  Support oven sampling method, to meet the gas, solid, liquid in the constant moisture, trace moisture measurement.

Features

- Color High contrast LCD touchscreen, 7.0 inches.
- Coulometric KF Titration.
- Support oven sampling method, to meet the gas, solid, liquid in the constant moisture, trace moisture measurement.

Data Management



Auto/manual drift adjust ensures accurate results.



Selectable units including μg , mg, %, ppm, mg/L and $\mu\text{g/mL}$.



User password management.



Support for USB communication for PC software.



Store up to 200 titration data sets (GLP-compliant).



Support for RS-232 communication for print and the print format can be alternate.



It needs GMP software to implement GMP management functions.



Support for U disk for data export with CSV format.

TITR-41C



TITR-41V



Includes

- Solvent manager
- 10mL burette
- Volumetric vessel
- Measuring electrode

Volumetric Karl Fischer Titration

Support Auto Titration Method, KF Titer Determination Method, Oven Titration Method and Oven Blank Titration Method.

The solvent manager adopts anti-leakage liquid and anti-pour design of waste liquid bottle, supports to fill titrant, drain solution, feed solvent, mix titrant and clean burette, ensure safe handling of Karl Fischer chemicals.

TITR-41C



Includes

- Solvent manager
- Coulometric vessel
- Measuring electrode
- Generator electrode

Coulometric Karl Fischer Titration

Support Auto Titration Method, Oven Titration Method, Oven Blank, and Coefficient correction Method.

The solvent manager adopts anti-leakage liquid and anti-pour design of waste liquid bottle, supports to drain solution and feed solvent, ensure safe handling of Karl Fischer chemicals.



Specifications

Model	TITR-41V	TITR-41C
Karl Fischer Volumetric Titration		
Water Range	(0.1~250.0)mg	/
Water Resolution	1μg	/
Water Unit	μg, mg, %, ppm, μg/mL, mg/L	/
Water Repeatability	≤0.5%	/
mV Range	(0~2000)mV	/
mV Resolution	1mV	/
Polarization Current Range	/	/
Polarization Current Accuracy	±3%	/
Polarization Current Fluctuation	±2.5%/30min	/
Karl Fischer Coulometric Titration		
Water Range	/	10.0μg~200mg
Water Resolution	/	0.1μg
Water Unit	/	μg, mg, %, ppm, μg/mL, mg/L
Water Repeatability	/	≤1%
mV Range	/	(0~2000)mV
mV Resolution	/	0.1mV
Polarization Current Range	/	/
Polarization Current Accuracy	/	±3%
Polarization Current Fluctuation	/	±2.5%/30min
Working Current Accuracy	/	±0.5%
Working Current Fluctuation	/	±0.2%/10min
General		
Power Supply	AC 100~240V, 47~63Hz	AC 100~240V, 47~63Hz
Dimensions	240×370×270mm	240×370×270mm
Net Weight	About 4kg	About 4kg