

Water Bath

WB-1R1H-3 WB-1R2H-7 WB-2R4H-15 WB-2R6H-25



Features

- Intelligent temperature controller with PID program, digital tube display and function of timing and over-temperature protection.
- Add the electric drain switch, one-button operation ,convenient to drain, Note: single hole water baths have no drain function.
- Power off when water shortage to ensure the safe operation of the product.



Stainless steel stretching inner container and roof cover.



Specifications

Model		WB-1R1H-3	WB-1R2H-7	WB-2R4H-15	WB-2R6H-25
Classification Specifications		1 hole	1 row & 2 holes	2 rows & 4 holes	2 rows & 6 holes
Heating Mode		Nature water convection heat transfer			
Function	Temp. Range	RT+5~100℃			
	Temp. Resolution Ratio	0.1℃			
	Temp. Motion	±0.5℃			
	Temp. Uniformity	±1.0℃			
Structure	Inner Chamber	Stainless steel			
	Outer Shell	Cold-rolled steel plate, Surface electrostatic spraying			
	Heater	Stainless steel heating tube			
	Power Rating	0.4kW	0.5kW	1.0kW	1.5kW
Controller	Temp. Control Mode	PID			
	Temp. Setting Mode	Touch button setting			
	Temp. Display Mode	Measuring temperature: displayed on the upper row of the three-digit LED; Setting temperature: displayed on the lower row of the three-digit LED			
	Timer	0~9999min (with timing wait function)			
	Operation Function	Fixed temperature operation, timing function, auto stop.			
	Additional Function	Deviation Correction, menu key locked, power failure back-up, power-off memory			
	Sensor	NTC			
Safety Device		Over temperature alarm			
Specification	Inner Chamber size(W*L*H)(mm)	150*135*150	300*135*150	325*300*150	500*300*150
	Exterior size (W*L*H)(mm)	170*154*210	318*168*210	350*318*210	524*322*210
	Package Dimension(W*L*H)(mm)	240*230*280	410*260*300	440*420*310	610*420*300
	Volume	3.4L	6.1L	14.6L	22.5L
	Load per rack	5kg			
	Shelf Number	1			
	Power Supply (50/60Hz)	AC220V/1.8A	AC220V/2.3A	AC220V/4.5A	AC220V/6.8A
	Current rating N.W./G.W. (kg)	3.3/4	4.5/5	6/7.5	7.5/9.5