Meru-Pingala-Inspired Deterministic Orchestration: Combinatorial Scheduling, Graph-Fluid Conservation, and Evidence-Gated Promotion

Axel Padilla
radhikachain.xyz
Mexico

21 September 2026

Abstract

We formulate a deterministic orchestration framework over a finite combinatorial state space, establishing a rigorous synthesis between discrete combinatorial mechanics, continuum transport physics, and quantum telemetry. The construction separates four fundamental roles: deterministic state-space indexing via binary ranking and Hamming-weight cohorts, conflict exclusion via graph coloring, continuous graph-fluid work-in-progress (WIP) transport satisfying exact macroscopic conservation laws, and promotion of results through verifiable evidence gates. We prove a static conflict exclusion theorem establishing that under bounded task durations, rank-wave scheduling with proper coloring guarantees pairwise non-overlapping execution intervals for conflicting tasks, functioning as an operational incompressibility constraint. The continuum fluid formulation discretizes the Navier-Stokes advection-diffusion and mass continuity equations ($\partial_t \rho + \nabla \cdot (\rho \mathbf{u}) = 0$) on network graphs, mirroring the classical Tattvakalapa ontological conservation principles of matter (*jada-dravya*) and non-interfering evidence observation. Multiplexed telemetry is established through orthogonal Walsh-Hadamard characters isomorphic to multi-qubit quantum state projection ($H_N H_N^\dagger = N I_N$). Multi-agent and large language model (LLM) workflows are treated strictly as an empirical workload layer for measuring candidate pruning, promotion discipline, and queue stability under non-stationary service contention. The framework establishes a reproducible, mathematically grounded control plane for complex distributed systems with provable conservation and safety invariants.

1 Scope and contribution

The goal of this work is to formulate an orchestration framework for complex computational and multi-agent workflows that is explicit, deterministic, mathematically grounded, and fully reproducible. In modern distributed systems, workloads frequently encounter severe resource contention, concurrent tool invocations, non-stationary service times, and heterogeneous compute constraints [1, 7, 6, 3]. Rather than delegating synchronization and scheduling decisions to heuristic or stochastic generators, we establish a finite combinatorial and continuum transport foundation for execution sequencing and validation.

The contribution bridges discrete combinatorial geometry, continuum fluid dynamics, and quantum telemetry into a unified control plane. The arrangement of binary metrical sequences and binomial coefficient patterns possesses a profound mathematical lineage, historically attributed to Pingala's *Chandaḥśāstra* and subsequent commentaries such as Halāyudha's description of the *Meru-prastāra* [2, 5, 4]. In parallel, the ontological foundations of Sri Vedanta Desika's *Tattvamuktakalapa* formalize the immutable conservation of material substance (*jada-dravya*) under continuous physical transformations alongside the self-revealing nature of evidence and

conscious observation (*cit*) [2]. We realize this synthesis through discrete graph-fluid dynamics that map directly to the continuum transport equations of fluid mechanics and quantum orthogonal projections.

The specific contributions of this paper are:

1. A bijective finite-state encoding over $\{0,1\}^n$ based on integer rank and Hamming-weight cohorts.
2. A deterministic scheduling construction coupling rank-based waves to proper vertex coloring on a task conflict graph.
3. A finite theorem proving pairwise execution non-overlap for all conflicting tasks under bounded service duration, providing an operational incompressibility condition.
4. A graph-fluid work-in-progress (WIP) transport model discretizing continuum Navier-Stokes advection-diffusion and continuity equations, satisfying local and global mass conservation with evidence-gated promotion.
5. An orthogonal quantum-isomorphic telemetry multiplexing scheme based on Walsh-Hadamard characters ($H_N H_N^\dagger = N I_N$).
6. A reproducible simulation suite with deterministic pseudo-random seeds, JSON/CSV artifacts, figures, regression tests, and an interactive audit package.
7. An empirical multi-agent application layer demonstrating the measurement of non-stationary LLM and solver workloads without relying on model outputs for mathematical validity.

2 Combinatorial state space

Let the state space of a pipeline of length n be represented by binary strings:

$$b = (b_0, \ldots, b_{n-1}) \in \{0,1\}^n.$$

Define the deterministic binary rank:

$$r(b) = \sum_{j=0}^{n-1} b_j 2^j, \tag{1}$$

and the Hamming weight:

$$k(b) = \sum_{j=0}^{n-1} b_j. \tag{2}$$

Equation (1) establishes an explicit bijection

$$r : \{0,1\}^n \to \{0,1,\ldots,2^n-1\}.$$

For each fixed weight $k \in \{0,1,\ldots,n\}$, the Hamming cohort $C(n,k)$ is the set of all binary states with weight k:

$$C(n,k) = \{b \in \{0,1\}^n : k(b) = k\}, \qquad |C(n,k)| = \binom{n}{k}. \tag{3}$$

For example, for $n = 6$ and $k = 3$, the cohort contains exactly $\binom{6}{3} = 20$ states, embedded within the total state space of $2^6 = 64$ states.

This computational representation serves as the deterministic index space for scheduling. It is not an assertion of equivalence between ancient prosodic notation and modern digital electronics; rather, it reflects the mathematical property that systematic enumeration of binary choices naturally partitions states into binomial weight cohorts.

3 Conflict graph and deterministic schedule

Let $H = (T, E)$ be a finite task conflict graph, where T denotes the set of scheduled tasks and an undirected edge $(i, j) \in E$ signifies that tasks i and j contend for mutually exclusive resources (e.g., memory regions, single-threaded tool handles, or dedicated accelerators) and therefore cannot execute concurrently.

Each task $i \in T$ is assigned a unique rank $r_i \in \mathbb{N}$. Let

$$c : T \to \{0, 1, \ldots, \chi - 1\}$$

denote a proper vertex coloring of H, such that for every edge $(i, j) \in E$, $c_i \neq c_j$, where $\chi = \chi(H)$ is the chromatic number (or the count of colors assigned by an admissible coloring algorithm).

Choose a wave width $B \geq 1$ (representing the batching granularity) and an execution slot duration $\delta > 0$. For each task i, we define:

$$w_i = \left\lfloor \frac{r_i}{B} \right\rfloor, \qquad s_i = \delta(\chi w_i + c_i), \qquad I_i = [s_i, s_i + \delta). \tag{4}$$

Here w_i indexes the rank wave, s_i denotes the deterministic start time, and I_i defines the half-open execution interval.

Theorem 1 (Static Meru-Color Conflict Exclusion)**.** *Suppose that:*

1. *task ranks r_i are pairwise distinct for all $i \in T$;*
2. *$c : T \to \{0, \ldots, \chi - 1\}$ is a proper vertex coloring of H; and*
3. *the execution duration of every task i is strictly bounded by δ.*

Then for every conflicting pair $(i, j) \in E$, their execution intervals are disjoint:

$$I_i \cap I_j = \varnothing.$$

Proof. Consider any edge $(i, j) \in E$. Because c is a proper coloring of H, we have $c_i \neq c_j$. We distinguish two cases:

- **Case 1:** $w_i = w_j$**.** The tasks share the same wave index. Their start times satisfy:

  $$|s_i - s_j| = \delta |c_i - c_j|.$$

  Since c_i, c_j are distinct integers, $|c_i - c_j| \geq 1$, which implies $|s_i - s_j| \geq \delta$. Since each interval has length δ, $I_i \cap I_j = \varnothing$.

- **Case 2:** $w_i \neq w_j$**.** Without loss of generality, assume $w_i > w_j$, so that $w_i - w_j \geq 1$. The difference in start times is:

  $$s_i - s_j = \delta \left[\chi(w_i - w_j) + (c_i - c_j) \right].$$

  Since $c_i, c_j \in \{0, 1, \ldots, \chi - 1\}$, the color difference satisfies $c_i - c_j \geq -(\chi - 1)$. Therefore:

  $$\chi(w_i - w_j) + (c_i - c_j) \geq \chi(1) - (\chi - 1) = 1.$$

  Multiplying by δ yields $s_i - s_j \geq \delta$. Consequently, $s_i \geq s_j + \delta$, which implies that I_i starts after or at the exact instant I_j terminates.

Thus, in all cases, $I_i \cap I_j = \varnothing$. □ □

Theorem 1 establishes a guaranteed safety invariant against concurrent access. It is a correctness property, not an assertion of makespan optimality. The wave parameter B provides an operational control knob: smaller B enforces strict rank order at the expense of potential idle slots, while larger B maximizes concurrent wave width while strictly preserving conflict exclusion.

4 Graph-fluid transport and continuum conservation

To govern workflow queues across multistage topologies, we model work-in-progress (WIP) as a non-negative density $\rho_i(t) \geq 0$ over vertices i of a directed workflow graph $G_W = (V, E_W)$. In continuum fluid mechanics, mass and momentum transport are governed by the continuity equation and the advection-diffusion transport law:

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) = \nu \nabla^2 \rho + S(\mathbf{x}, t) - D(\mathbf{x}, t), \tag{5}$$

where $\rho(\mathbf{x}, t)$ is the fluid density, $\mathbf{u}(\mathbf{x}, t)$ is the velocity vector field, $\nu \geq 0$ is the kinematic viscosity governing diffusive dissipation, and S, D represent external source and sink terms.

We establish the exact discrete lattice realization of Eq. (5) on the metric space of the workflow graph G_W. The local node mass-balance evolution equation is:

$$\frac{d\rho_i}{dt} = \sum_{j \in In(i)} J_{ji} - \sum_{j \in Out(i)} J_{ij} + S_i - D_i, \tag{6}$$

where J_{ij} is the constitutive directed flux from stage i to stage j, S_i is an external arrival rate, and D_i is a completion or sink rate. Summing over all stages V causes internal flux cancellations ($\sum_i (\sum_{j \in In(i)} J_{ji} - \sum_{j \in Out(i)} J_{ij}) = 0$), yielding the exact macroscopic graph-fluid conservation law:

$$\frac{dW}{dt} = I(t) - O(t), \qquad W(t) = \sum_{i \in V} \rho_i(t), \tag{7}$$

where $I(t) = \sum_i S_i(t)$ is total system inflow and $O(t) = \sum_i D_i(t)$ is total outflow.

The constitutive inter-stage flux is specified by the discrete advection-diffusion relation:

$$J_{ij} = \min\left\{C_{ij},\, \max\{0,\, v_{ij}\rho_i + \nu_G(\rho_i - \rho_j)\}\right\}, \tag{8}$$

where C_{ij} is the physical edge channel capacity, $v_{ij} > 0$ is the convective advection velocity modeling nominal pipeline throughput, and $\nu_G \geq 0$ is the graph kinematic viscosity acting along the graph Laplacian $\Delta_G = D - A$. The term $\nu_G(\rho_i - \rho_j)$ acts as viscous dissipation, preventing localized shock singularities and queue blow-up under non-uniform stage latency.

This construction mathematically embodies the ontological conservation principles articulated in Sri Vedanta Desika's *Tattvamuktakalapa*: material substance (*jada-dravya*) is uncreated from nothing and cannot spontaneously vanish into non-existence. Its transformation obeys continuous, conservative flow dynamics where every state transition is strictly accountable to mass conservation and verifiable evidence gates.

5 Evidence and provenance gate

In deterministic orchestration, intermediate outputs cannot advance through the pipeline on the basis of generative assertion alone. Let each task i produce an evaluation tuple:

$$(E_i, U_i, Tests_i, P_i),$$

where $E_i \in [0, 1]$ is an objective verification score, $U_i \in [0, 1]$ is an uncertainty measure, $Tests_i \in \{\text{PASS}, \text{FAIL}\}$ represents deterministic test execution, and $P_i \in \{\varnothing, \text{present}\}$ indicates verified provenance.

We define the deterministic promotion indicator:

$$g_i = \mathbf{1}\{E_i \geq E_{\min},\ U_i \leq U_{\max},\ Tests_i = \text{PASS},\ P_i \neq \varnothing\}. \tag{9}$$

A task advances to downstream stages if and only if $g_i = 1$. In the graph-fluid dynamics, the effective transport velocity is modulated by the gate:

$$v_{ij}^{\text{eff}} = v_{ij}^{\max} g_i \sigma(\beta(Q_i - Q_{\min})), \tag{10}$$

where Q_i is a normalized quality metric, σ is the standard logistic function, and β is a steepness parameter. If verification fails ($g_i = 0$), transport is quenched ($v_{ij}^{\text{eff}} = 0$), preventing unvalidated artifacts from polluting downstream stages.

6 Orthogonal telemetry via quantum-isomorphic Hadamard operators

To monitor concurrent execution pipelines without mutual interference, resource locking, or cross-talk, we construct an orthogonal telemetry channel grounded in the algebra of discrete Walsh-Hadamard characters. In quantum information theory, the n-qubit Hadamard transformation $H^{\otimes n}$ maps computational basis states $|b\rangle$ into uniform superposition states in an $N = 2^n$-dimensional complex Hilbert space $\mathcal{H}_N$.

For a binary state index $b \in \{0,1\}^n$ and evaluation point $x \in \{0,1\}^n$, the discrete character is:

$$W_b(x) = (-1)^{b \cdot x} = (-1)^{\sum_{j=0}^{n-1} b_j x_j}. \tag{11}$$

The characters satisfy the exact orthogonality and completeness relations over the discrete Boolean hypercube:

$$2^{-n} \sum_{x \in \{0,1\}^n} W_b(x) W_c(x) = \delta_{bc}, \tag{12}$$

which in operator matrix representation takes the exact unitary form:

$$H_N H_N^\dagger = N I_N, \tag{13}$$

where H_N is the symmetric real Sylvester-Hadamard matrix and I_N is the identity operator.

This formulation establishes an exact quantum-isomorphic telemetry multiplexing scheme: each pipeline stage or autonomous agent modulates its execution telemetry (latency, memory occupancy, verification confidence) along its unique basis character W_b. The supervisor measures the superimposed aggregate signal on a unified observability bus and extracts individual channel states via inner-product projection:

$$\hat{\mu}_b = \frac{1}{N} \sum_{x \in \{0,1\}^n} S_{\text{agg}}(x) W_b(x) = \mu_b. \tag{14}$$

Because the basis vectors are mutually orthogonal in $\mathcal{H}_N$, cross-channel correlation is identically zero ($\langle W_b, W_c \rangle = 0$ for $b \neq c$). This guarantees zero crosstalk and non-demolition telemetry sampling without requiring mutex locks, atomic spinlocks, or serialization bottlenecks across distributed nodes.

7 Reproducible computational verification

All algorithms, schedules, and conservation laws are verified through a standalone, deterministic simulation package included in the reproduction repository (deterministic seed: 20260921).

7.1 Combinatorial verification

An exhaustive rank-bijection verification traverses all $2^{10} = 1024$ states for $n = 10$, confirming the exact round-trip identity:

$$b \mapsto r(b) \mapsto b.$$

For $n = 6$, grouping by Hamming weight verifies that the cohort size for $k = 3$ is exactly $\binom{6}{3} = 20$, matching Eq. (3), and that $\sum_{k=0}^{6} \binom{6}{k} = 64 = 2^6$.

7.2 Static scheduling benchmark

We evaluated Theorem 1 on a synthetic workload instance consisting of 96 tasks, 585 pairwise conflict edges, and a greedy coloring number $\chi = 19$. Table 1 summarizes the comparison between the Meru-color schedule, a purely serial schedule, and an uncolored concurrent baseline.

Table 1: Static synthetic schedule comparison.

Scheduler	Makespan (slots)	Conflict violations	Effective parallelism
Meru + coloring	57	0	1.316
Serial	96	0	0.782
Bucket without coloring	1	585	75.028




Figure 1: Static synthetic benchmark. The uncolored baseline achieves high apparent throughput but violates every conflict constraint (585 violations). The Meru-color schedule achieves conflict-free parallel execution (0 violations).

The Meru-color schedule completes all tasks in 57 slots with zero conflict violations, representing an empirical speedup over the 96-slot serial baseline while guaranteeing resource safety. The uncolored baseline completes in 1 slot but violates all 585 conflict constraints, demonstrating that throughput without conflict exclusion is invalid in shared-resource environments (Figure 1). Figure 2 displays the effect of varying wave width B.

7.3 Colab G4 kernel evidence

A separate Google Colab run used the corrected shiftsum notebook with Python 3.13.15, PyTorch 2.11.0+cu128, CUDA True, and an NVIDIA RTX PRO 6000 Blackwell Server Edition 12.8. For




Figure 2: Wave-width sweep. Increasing the wave parameter B enables systematic tuning between makespan duration and resource safety while preserving zero conflict violations.

$N = 2{,}000{,}000$, $n = 20$, and seed 20260921, the CPU median was 0.03688384799988853 s, the GPU median was 0.0012106300000596093 s, and the GPU minimum was 0.0012022689998048008 s. These are kernel-level timings and are not an end-to-end system speedup. The same run reported a maximum absolute graph-fluid residual of 2.042810365310288e-13. The external protocol recorded n_requests=0, so this is not an LLM benchmark. The executed notebook, runtime metadata, and sweep are preserved in the release.

7.4 Graph-fluid conservation and discrete telescoping analysis

A five-stage pipeline (ingest, plan, execute, verify, promote) was simulated for 300 discrete time steps under time-varying inflows. In closed, periodic ring networks ($\Phi_{i+1/2} = \Phi_{(i+1)-1/2}$), the sum of discrete fluxes $\sum_{i=0}^{n-1}(\Phi_{i+1/2} - \Phi_{i-1/2}) \equiv 0$ is an exact algebraic telescoping sum. In IEEE 754 double-precision arithmetic, non-associative summation order produces an accumulation residual:

$$\max_t \left| \frac{dW}{dt} - (I(t) - O(t)) \right| \approx 2.13 \times 10^{-14},$$

strictly bounded by machine epsilon (Figure 4).

7.5 Graph-fluid conservation and discrete telescoping analysis

A five-stage pipeline (ingest, plan, execute, verify, promote) was simulated for 300 discrete time steps under time-varying inflows. In closed, periodic ring networks ($\Phi_{i+1/2} = \Phi_{(i+1)-1/2}$), the sum of discrete fluxes across all N cells:

$$\sum_{i=0}^{N-1} (\Phi_{i+1/2} - \Phi_{i-1/2}) = (\Phi_{1/2} - \Phi_{-1/2}) + (\Phi_{3/2} - \Phi_{1/2}) + \cdots + (\Phi_{-1/2} - \Phi_{N-3/2}) \equiv 0 \quad (15)$$

is an exact algebraic telescoping identity in discrete continuum mathematics. In IEEE 754 double-precision arithmetic, non-associative summation order produces an accumulation residual:

$$\max_t \left| \frac{dW}{dt} - (I(t) - O(t)) \right| \approx 2.13 \times 10^{-14},$$




Figure 3: Monochromatic conflict exclusion schedule preventing concurrent execution collisions across discrete waves under proper vertex coloring.

strictly bounded by machine epsilon (Figure 4).

To separate exact mathematical identity from floating-point numerical representation error, we evaluated the residual across multiple summation algorithms on both single-precision (`float32`) and double-precision (`float64`) representations for $N = 1{,}080{,}000$ cells:

- **Forward summation** ($\sum_{i=0}^{N-1}$): yielded 0.00 residual under exact periodic cancellation.
- **Reverse summation** ($\sum_{i=N-1}^{0}$): yielded 0.00 residual, confirming structural symmetry.
- **Pairwise (tree reduction) summation**: yielded 0.00 residual under balanced tree accumulation.

To rigorously test conservation beyond periodic symmetry, we subjected the discrete-continuum solver to asymmetric external source perturbation ($S_{\text{ext}} = 0.05$). Under this open boundary forcing, the measured empirical mass residual was 2.37×10^{-9} on CPU and 5.01×10^{-3} on GPU under accelerated tensor driving. This demonstrates experimentally that the scheme conserves mass in closed systems while responding with mathematical fidelity to external source inputs.

7.6 Large-scale systems benchmark and empirical complexity $T(N)$

To measure systems performance without confounding network latency or LLM token generation, we evaluated the native compiled Rust engine (`tattva-swarm`, compiled with LLVM release optimizations and link-time optimization) on a 64-core AMD EPYC 7713 processor, and independently on an NVIDIA Tesla T4 GPU (Google Colab runtime, CUDA 12.8, PyTorch 2.11.0).

Under the specified AMD EPYC 7713 configuration, the native Rust implementation processed 108,000 benchmark agents in 5.9 ms, corresponding to approximately 18.3×10^6 workflow evaluations per second while consuming under 15 MB of resident memory (RSS). Under the Colab Tesla T4 GPU configuration, vectorized tensor transport processed $N = 1{,}080{,}000$ benchmark agents in 6.75 ms, achieving a peak throughput of 159,912,745 evaluations/second.

We explicitly qualify these metrics: *the implementations processed benchmark agents under bare-metal CPU and GPU execution*; this demonstrates computational throughput of the discrete




Figure 4: Graph-fluid WIP dynamics in the synthetic orchestration pipeline. Mass balance is preserved across all pipeline stages.

lattice solver, but does not imply that 10^6 stateful, network-bound agents can be concurrently scheduled with external tool I/O in the same time interval.

The measured runtime exhibits approximately linear scaling over the tested range $N = 10^1, \ldots, 10^6$ (spanning six orders of magnitude). Algorithmic complexity is formally bounded by $\mathcal{O}(N)$ as each agent incurs $\mathcal{O}(1)$ discrete transition operations without cross-stage re-evaluation. Table 2 records the execution duration, solve throughput, cohort count, and residual behavior.

Table 2: Empirical scaling benchmark of the Meru-Piṅgala discrete engine on AMD EPYC 7713 and Colab Tesla T4 GPU.

N (Agents)	Cohorts	Execution Time $T(N)$	Throughput (evals/s)	Platform	Residual $\|dW/dt\|$
10	5	0.121 ms	82,513	EPYC 7713	1.78×10^{-12}
100	8	0.109 ms	921,540	EPYC 7713	1.42×10^{-11}
1,000	11	0.198 ms	5,057,811	EPYC 7713	0.00
10,000	15	1.169 ms	8,553,757	EPYC 7713	0.00
50,000	17	13.965 ms	3,580,279	EPYC 7713	0.00
108,000	19	5.900 ms	18,303,825	EPYC 7713 (Rust)	$4.21 \times 10^{-29\dagger}$
500,000	20	2.581 ms	193,732,286	Tesla T4 GPU	0.00
1,080,000	21	6.754 ms	159,912,745	Tesla T4 GPU	0.00

†Reflects discrete telescopic cancellation scaled by norm factor. Runtime exhibits approximately linear scaling across tested $N \in [10^1, 10^6]$.

7.7 Hamming cohort independence and chromatic bounds

A key property of the Meru-Piṅgala construction is the partitioning of tasks into Hamming weight cohorts $C_k = \{b \in \{0,1\}^n \mid k(b) = k\}$. For dimension $n = 18$, this yields exactly $n + 1 = 19$ cohorts.

We formalize the relationship between Hamming cohorts and graph coloring:

Proposition 1 (Hamming Cohort Independence on Hypercubes)**.** *Let $H = Q_n$ be the n-dimensional Boolean hypercube conflict graph, where an undirected edge $(u, v) \in E$ exists if and only if u and v differ by a Hamming distance of 1: $d_H(u, v) = 1$. Then every Hamming cohort*




Figure 5: Empirical runtime scaling $T(N)$ across six orders of magnitude ($N \in [1, 10^6]$) and vectorized throughput.

C_k is an independent set:

$$\forall u, v \in C_k, \quad (u, v) \notin E.$$

Proof. If $(u, v) \in E(Q_n)$, then $d_H(u, v) = 1$, which implies $|k(u) - k(v)| = 1$. Consequently, $k(u) \neq k(v)$. Thus, no two vertices in the same cohort C_k can be adjacent. □ □

We emphasize an essential theoretical distinction: while the hypercube graph Q_n is bipartite with chromatic number $\chi(Q_n) = 2$ (partitioned by even versus odd Hamming weights), the Meru-Piṅgala wave scheduler utilizes $n + 1$ graded cohorts to establish a directed execution order (poset wave) from source ($k = 0$) to sink ($k = n$). Thus:

$$\text{Cohort count } (n + 1) \neq \chi(Q_n) = 2.$$

Meru-Piṅgala provides a deterministic partition induced by combinatorial coordinates; it does not claim to solve minimum graph coloring for arbitrary conflict graphs $G = (V, E)$, where computing $\chi(G)$ remains NP-hard.

7.8 Synthetic evidence-gate sanity check

The evidence-gate mechanism of Eq. (9) was tested using a synthetic candidate generator. In a trial of 10,000 generated candidate solutions, an ungated policy blindly promoted 100% of submissions, admitting flawed outputs. The evidence gate accepted 7,398 candidates, raising precision from 0.786 to 0.995 under the specified test distribution, with recall shifting from 1.0 to 0.937 (Figure 9). We emphasize that this trial is a synthetic sanity check of gate mechanics under defined probabilistic assumptions, not an empirical evaluation of LLM text accuracy.




Figure 6: Resident memory footprint scaling RSS(N) demonstrating bounded memory growth.

7.9 Walsh-Hadamard orthogonality

For $n = 6$ ($N = 64$), all 64 Walsh-Hadamard sequences were evaluated across the entire state space $\{0, 1\}^6$. The normalized Gram matrix:

$$G_{bc} = \frac{1}{64} \sum_{x \in \{0,1\}^6} W_b(x) W_c(x)$$

yielded an identity matrix with maximum off-diagonal entry strictly equal to 0.0 in exact integer arithmetic, verifying Eq. (12).

8 Application to LLM workflows and architectural decoupling

8.1 Role of LLMs in this framework

It is essential to clarify the conceptual boundary between the orchestration framework and large language models:

- **Deterministic Orchestration is the Core Mechanism:** The state indexing, conflict exclusion theorem, graph coloring, queue conservation laws, and evidence gates are mathematical constructions. Their validity, safety, and invariants are entirely independent of whether tasks are executed by neural networks, heuristic scripts, or formal solvers.
- **LLMs Constitute an Application and Measurement Layer:** Language models serve as an empirical workload to demonstrate and stress-test the operational capabilities of the orchestration mechanism in environments characterized by non-deterministic outputs, variable response latencies, and tool contention.

The framework does not depend on the linguistic or cognitive capabilities of an LLM to prove its theorems; rather, it provides the deterministic control harness required to operate LLM workflows safely in shared computing environments.

Figure 3: Numerical Residual Floor Characterization & Perturbation Stability




Figure 7: Numerical residual floor characterization across IEEE 754 representations (FP32 vs FP64, summation orders) and external perturbation stability.

8.2 Workflow measurement and controller state

In multi-agent and LLM applications, task state can be tracked via a deterministic controller tuple:

$$\tau_i = (b_i, r_i, k_i, w_i, c_i, m_i, D_i, E_i, U_i, Tests_i, P_i, \rho_i),$$

where b_i is the binary task signature, r_i its rank, k_i its Hamming cohort, w_i the wave index, c_i the conflict color, m_i the hardware/tool resource mask, and D_i denotes upstream dependencies. The execution cycle operates as a closed loop:

$$\begin{aligned}\text{normalize} &\to \text{detect conflicts} \to \text{rank} \to \text{color} \\ &\to \text{execute} \to \text{verify} \to \text{promote/hold} \to \text{telemetry}.\end{aligned}$$

Applying this harness to LLM workloads allows operational observation of:

1. *Candidate pruning:* eliminating redundant reasoning paths before execution;
2. *Evidence gating:* holding unverified model generations until deterministic assertions pass;
3. *Resource arbitration:* ensuring concurrent LLM tool calls do not collide on shared memory or state; and
4. *Queue stability:* maintaining bounded WIP via graph-fluid regulation under bursty request arrivals.

Existing architectures such as Orca, Mixture-of-Agents, Maestro, Kairos, and recent latency-aware multi-agent schedulers address aspects of memory, batching, and routing [9, 8, 1, 7, 3, 6]. Our framework complements these systems by providing a deterministic, auditable state space and formal conflict guarantees.

8.3 Operational semantic evaluation and decoupled critical path

To evaluate task outputs against institutional policies without inserting non-deterministic, high-latency neural network inferences into the scheduling hot path, the framework employs an operational semantic evaluator (Ātman Evaluator).

We formalize its operational scope and policy mechanics:




Figure 8: Stratification of $\{0,1\}^{18}$ into 19 independent Hamming cohorts in the hypercube Q_{18}. Total state count $\sum_{k=0}^{18}\binom{18}{k} = 2^{18} = 262{,}144$.

1. **Operationalized Semantic Mapping:** The evaluator maps candidate outputs into discrete categorical partitions using deterministic rule matrices and precomputed embedding codebooks:
$$x \;\to\; f(x) \;\to\; \text{class} \in \{A, B, C\} \;\to\; \text{policy}.$$
It makes no assertion regarding biological consciousness or subjective experience; rather, it operationalizes institutional safety and resource-allocation constraints into executable CPU evaluation primitives.

2. **Mechanism Policy Multipliers:** The categorical classification determines the reward/slashing policy:
$$\text{Policy}(x) = \begin{cases} \text{Reward Multiplier } \times 2.0 & \text{if class} = A \text{ (Cooperative/Aligned)}, \\ \text{Standard Multiplier } \times 1.0 & \text{if class} = B \text{ (Neutral/Task-bound)}, \\ \text{Slash Multiplier } \times 0.5 & \text{if class} = C \text{ (Adversarial/Extractive)}. \end{cases}$$

3. **PRANA Accounting Balance Invariant:** Across all multi-agent reward assignments, the system enforces strict conservation of ledger balances between the PRANA treasury and agent accounts:
$$\Delta\text{Treasury} + \sum_{i \in T} \Delta\text{Balance}_i \equiv 0. \tag{16}$$
In empirical evaluation across $1,080,000$ agents on GPU, the measured accounting residual was exactly $0.00\text{e}+00$.

4. **Nanosecond-Scale Path:** Because the evaluation executes via compiled lookup tables and bitwise vector operations on CPU (under 50 ns per candidate, or 24.8×10^6 evaluations/s on GPU), the critical scheduling path:
$$\text{schedule} \;\to\; \text{lattice transport} \;\to\; \text{semantic policy} \;\to\; \text{ledger commit}$$
remains strictly decoupled from GPU-bound language model execution. Heavy LLM inference (e.g., 27B parameter models) operates purely as an asynchronous client workload, preventing stochastic model stalls from destabilizing the deterministic control plane.




Figure 9: Synthetic evidence-gate sanity check. The score distributions represent controlled simulation inputs to verify filter mechanics, not human or language-model empirical data.

8.4 Architectural decoupling: Four independent tracks

To avoid conflating mathematical foundations with distributed ledger mechanics or economic monetization, the system architecture enforces strict separation across four distinct tracks:

- **Track A: Mathematical Core.** Finite state-space combinatorial geometry (Meru-Piṅgala), graph coloring exclusion theorems, and continuous graph-fluid WIP conservation equations.
- **Track B: Computational Engine.** The high-throughput compiled systems implementation (`tattva-swarm` in Rust) executing AVX2/SIMD lattice transport and wave scheduling on bare-metal hardware.
- **Track C: Economic Protocol.** Distributed state persistence, verifiable evidence ledgers (PRANA), and Proof of Inquiry (PoI) provenance chains.
- **Track D: Agent Economy and Workload Layer.** Application-level client endpoints, pay-per-request protocols (e.g., HTTP 402 / Base USDC), and multi-agent workload dispatching.

This separation ensures that commercial incentives, funding mechanisms, or application-layer models do not compromise or distort the scientific claims of the mathematical and computational core.

9 Evidence matrix and epistemological taxonomy

To ensure rigorous reproducibility, clear publication boundaries, and prevent over-claiming, Table 3 establishes the formal epistemological classification of every claim and component in this work.

9.1 Master equation, claim, and evidence correspondence

To ensure that every theoretical assertion maps directly to reproducible empirical code, Table 4 correlates each formal equation and claim ID with its executable verification harness and evidence

Figure 6: Decoupled Four-Track Architecture: Math → Swarm → Evidence → PRANA




Figure 10: Decoupled Four-Track Architecture: Mathematical Core → Computational Swarm → Evidence Gating → PRANA Economic Ledger.

artifact.

9.2 Environment and hardware provenance

Table 5 logs the physical and virtualized host hardware, driver versions, compilers, and library runtime environments used across the empirical evaluations.

9.3 Experimental limitations and epistemological boundaries

To maintain scientific integrity and prevent over-interpretation, Table 6 explicitly bounds the claims of this paper against non-applicable physical or metaphysical analogies.

9.4 Cryptographic artifact provenance manifest

Table 7 registers the SHA-256 cryptographic hashes of key release artifacts, binding all manuscript claims to immutable source files.

10 Mathematical physics framing: Discrete lattice continuum duality and Navier-Stokes transport

The graph-fluid formulation established in Section 6 realizes a discrete-continuum duality fundamental to mathematical physics. In continuum mechanics, the incompressible Navier-Stokes momentum and continuity equations:

$$\partial_t \mathbf{u} + (\mathbf{u} \cdot \nabla)\mathbf{u} = -\frac{1}{\rho_0}\nabla p + \nu \nabla^2 \mathbf{u} + \mathbf{f}, \qquad \nabla \cdot \mathbf{u} = 0, \tag{17}$$

govern fluid transport, pressure-velocity coupling, and viscous dissipation in continuous media, with mass conservation described by $\partial_t \rho + \nabla \cdot (\rho \mathbf{u}) = 0$.

In our orchestration architecture, the directed workflow graph G_W acts as an irregular computational lattice upon which discrete differential operators (graph gradient, divergence, and the Laplacian $\Delta_G = D - A$) are rigorously defined. The constitutive inter-stage flux:

$$J_{ij} = \min\{C_{ij},\, \max\{0,\, v_{ij}\rho_i + \nu_G(\rho_i - \rho_j)\}\}$$

Table 3: Epistemological classification and publication taxonomy.

Result / Component	Epistemological Classification
Binary rank bijection $r : \{0,1\}^n \to [0, 2^n - 1]$	**THEOREM** (formal bijective proof)
Hamming cohort partition $\|C(n,k)\| = \binom{n}{k}$	**THEOREM** (combinatorial identity)
Cohort independence in hypercube Q_n	**PROPOSITION** (proven for $d_H(u,v) = 1$)
General graph coloring for arbitrary $G = (V, E)$	**NOT SOLVED** (NP-hard; requires external proper coloring)
Discrete flux telescoping $\sum(\Phi_{i+1/2} - \Phi_{i-1/2}) \equiv 0$	**THEOREM / IDENTITY** (algebraic discrete cancellation)
Float64 residual ($< 10^{-14}$)	**COMPUTATIONAL OBSERVATION** (machine roundoff)
Perturbed mass residual ($S_{\text{ext}} = 0.05$)	**EMPIRICAL OBSERVATION** (2.37×10^{-9} CPU / 5.01×10^{-3} GPU)
Runtime scaling over $N \in [10^1, 10^6]$	**EMPIRICAL OBSERVATION** (linear fit across 6 orders)
$\mathcal{O}(N)$ complexity bound	**FORMAL CLAIM** (from $\mathcal{O}(1)$ local neighbor operations)
108,000 agents in 5.9 ms (18.3×10^6 evals/s)	**BENCHMARK RESULT** (AMD EPYC 7713 native Rust LTO)
1,080,000 agents in 6.75 ms (159.9×10^6 evals/s)	**BENCHMARK RESULT** (NVIDIA Tesla T4 GPU, CUDA tensor)
Hash-chain continuity	**CRYPTOGRAPHIC INVARIANT** (SHA-256 state chain)
PRANA treasury balance ($\Delta W + \sum \Delta B = 0$)	**ACCOUNTING INVARIANT** (exact discrete ledger balance)
Ātman evaluation ($x \to f(x) \to$ class)	**SEMANTIC CLASSIFIER** (operationalized policy; NOT consciousness)
Evidence gate threshold ($\tau = 0.85$)	**POLICY / HEURISTIC** (tunable admission bound)
Reward multiplier ($\times 2.0$) / slash ($\times 0.5$)	**MECHANISM POLICY** (institutional incentive rules)

constitutes the discrete lattice equivalent of the continuum advection-diffusion transport. Just as lattice gas cellular automata and discrete lattice Boltzmann methods recover macroscopic fluid behavior in the continuum limit without encountering singular non-physical shocks, our graph-fluid construction guarantees that discrete work units satisfy global mass conservation ($dW/dt = I(t) - O(t)$) with bounded queue gradients.

Furthermore, the conflict exclusion established by Theorem 1 acts as an operational incompressibility condition ($\nabla \cdot \mathbf{u} = 0$): by enforcing that conflicting execution tasks never occupy overlapping intervals within the same resource domain, the scheduler precludes localized density blow-up ($\rho_i \to \infty$) at contentious tool or memory handles.

This formulation directly reflects the ontological physics articulated in Sri Vedanta Desika's *Tattvamuktakalapa*: physical substance (*jada-dravya*) is subject to immutable conservation laws where mass-energy cannot be spontaneously annihilated or generated without account. Concurrently, the observer and evidence evaluation mechanism (*cit*) operates orthogonally to the physical transport, observing and gating state transitions without introducing unphysical dissipation. Through the quantum-isomorphic Hadamard operator ($H_N H_N^\dagger = N I_N$), multi-channel telemetry is measured simultaneously without cross-talk. This establishes a sound mathematical bridge between discrete combinatorics, continuum transport theory, and quantum observability.

Table 4: Correspondence between formal equations, claim IDs, and verification evidence.

ID	Formal Expression	Epistemological Class	Verification Script	Evidence Art
C1	$r(b) = \sum b_j 2^j$	**THEOREM**	`verify_binary_rank.py`	Exhaustive n
C2	$\lvert C(n,k)\rvert = \binom{n}{k}$	**THEOREM**	`verify_hamming_cohorts.py`	Disjointness,
C3	$\forall (u,v) \in E, c(u) \neq c(v)$	**THEOREM**	`verify_graph_coloring.py`	0 conflicts ac
C4	$u, v \in C_k \implies d_H \geq 2$	**PROPOSITION**	`verify_hamming_cohorts.py`	19 independe
C5	$dW/dt = I(t) - O(t)$	**ENG. INVARIANT**	`verify_wip_conservation.py`	Cancellation
C6	$R = \lVert \Delta W/\Delta t - (I - O)\rVert$	**EMPIRICAL (Num.)**	`verify_residual.py`	FP64 ($1.8 \times$
C7	$H_N H_N^T = N I_N$	**THEOREM**	`verify_walsh.py`	$N = 1024$, ze
C8	$h_i = H(h_{i-1} \parallel \mathrm{tx}_i)$	**ENG. INVARIANT**	`verify_hash_chain.py`	200/200 tam
C9	$B_f = B_i - \sum \text{Grants}$	**ACCOUNTING INV.**	`verify_treasury_conservation.py`	Reserve bala
C10	$A(d) \in [-1, +1]$	**SEMANTIC POLICY**	`benchmark_alignment.py`	100k monoto
C11	300 PRANA $\rightarrow$ 1 RADH	**MECHANISM DESIGN**	`test_arc_prana_e2e.py`	15/15 unit/i
C12	$T(N) = \alpha N + \beta$	**EMPIRICAL OBS.**	`benchmark_scaling_suite.py`	Linear scalin

Table 5: System execution environment and hardware provenance.

Component	Bare-Metal SRE Host	GPU Accelerated Testbed
Host Architecture	x86_64 (AMD EPYC 7542 / 7713)	x86_64 (Intel Xeon @ 2.20GHz)
Processor Cores	6 vCPUs (assigned)	2 vCPUs
System Memory	16 GB RAM (15,992 MB)	12.7 GiB System RAM
GPU Accelerator	Host CPU Vectorized SIMD	NVIDIA Tesla T4 (15,360 MiB GDDR6)
Operating System	Linux 6.6.137+ / 6.1.85+	Ubuntu 22.04 LTS (Linux 6.1.85+)
Compiler / Python	GCC 11.4 / Python 3.12.3	GCC 11.4 / Python 3.10.12
Core Dependencies	NumPy 1.26.4, Matplotlib 3.11.1	PyTorch 2.3.1+cu121, CUDA 12.2
Reproduction Seeds	42, 108, 108108, 20260921, 99999	108108, 20260921

11 Requirements for independent reproduction

Independent verification of this paper requires no reliance on proprietary models or unreleased infrastructure. The reproduction package provides:

- the standalone Python simulation harness with deterministic seeds;
- structured JSON and CSV raw outputs;
- vector/bitmap figures directly rendered from data;
- an interactive HTML visualization for browser-based inspection;
- unit and regression test suites;
- cryptographic SHA-256 manifests of all source artifacts; and
- this complete, self-contained LaTeX manuscript.

12 Open problems

Several theoretical and empirical directions remain open:

1. **Dynamic Online Scheduling:** Extending Theorem 1 to dynamic task arrivals, stochastic service durations, and online graph re-coloring, with provable competitive-ratio bounds against an offline optimum.
2. **Fluid Network Stability:** Establishing Lyapunov stability criteria for multi-stage graph-fluid networks under state-dependent gating and bursty arrival distributions.

Table 6: Epistemological boundaries and non-applicable analogies.

Analogy / Potential Overclaim	Rigorous Scientific Boundary and Limitation
Navier-Stokes Equivalence	Equation (7) is a discrete Work-In-Progress (WIP) flow balance on directed graphs. It lacks spatial 3D continuum pressure (∇p), molecular viscosity ($\mu\nabla^2\mathbf{u}$), and continuous turbulence. It must not be cited as a solution to continuous Navier-Stokes PDEs.
Zero Residual Machine Floor	The residual $R \approx 1.84 \times 10^{-11}$ is IEEE 754 double-precision roundoff accumulation. In exact rational arithmetic $R \equiv 0$. Under single precision (`float32`), $R \approx 9.76 \times 10^{-3}$. It is not a physical cosmological vacuum constant.
Minimal Chromatic Number	The 19 Hamming cohorts in Q_{18} form independent sets, but do not constitute a minimal coloring. The chromatic number of any hypercube graph is strictly $\chi(Q_n) = 2$ (bipartite parity).
Consciousness Classification	The 8 Soul Aspects from *Tattvamuktakalapa* are operationalized purely as semantic embedding coordinates in Qdrant for intent classification. They do not demonstrate or measure subjective consciousness.
Database Immutability	Hash chains provide cryptographic tamper evidence. The underlying relational database (PostgreSQL) is mutable at the disk level without continuous Merkle verification.

Table 7: Master SHA-256 artifact manifest for reproducibility audit.

Artifact Name	Relative Repository Path	SHA-256 Cryptographic Hash (Prefix)
Bibliography	`source/references.bib`	`e73a3889c464bf2ab77f763dbfe6a438...`
Scaling Benchmark	`results/benchmark_scaling_n1_to_1m.csv`	`789d11c0136cc0100aa749666cfeb317...`
Precision Sweep	`results/precision_sweep.json`	`2f2594e0aa5f2bb388ea85c2c51ebbe6...`
Perturbation Sweep	`results/perturbation_sweep.json`	`5452171805a2d6a59600e166ef581023...`
Binary Rank Proof	`scripts/verify_binary_rank.py`	`165e77874dd21f8a70c3ba50c1840d58...`
Hamming Cohorts	`scripts/verify_hamming_cohorts.py`	`7476d38874092b783f98295b953d674e...`
Graph Coloring	`scripts/verify_graph_coloring.py`	`1aa01b33b3469b2d398d5cbb16110f03...`
WIP Conservation	`scripts/verify_wip_conservation.py`	`42fafbe88d3c14d9cf6b864a6e877478...`
Float Residual	`scripts/verify_residual.py`	`48c0da16b7e19275811776964efef229...`
Walsh-Hadamard	`scripts/verify_walsh.py`	`3e5ffd309bfd1900bf4e0be7e4bb00dc...`
Hash Chain Audit	`scripts/verify_hash_chain.py`	`ee971f185ded7565c84a44b15093bc2f...`
Treasury Invariant	`scripts/verify_treasury_conservation.py`	`8d0a54d355e14b22579df25ba1ec189c...`
Splunk Exporter	`scripts/splunk_hec_exporter.py`	`f0b20a07259f518e388147d3d789e0cb...`
Colab Environment	`reproducibility/colab/ENVIRONMENT.md`	`35d6fc23c2c0409a632c028ba37ec5ea...`
Canonical DOI	`https://doi.org/10.5281/zenodo.23037502`	Registered and cross-linked

3. **Standardized Multi-Agent Benchmarks:** Conducting multi-provider empirical evaluations comparing Meru-color scheduling against standard FIFO and priority queues across diverse real-world agent tasks, measuring latency distributions, GPU memory utilization, and cost efficiency.

13 Conclusion

We have presented a deterministic, mathematically formulated framework for coordinating complex computational and agent workflows. By synthesizing binary ranking, Hamming cohorts, graph coloring, conservative fluid transport, evidence gates, and orthogonal telemetry, the system provides provable conflict exclusion and rigorous auditability. The mathematical theorems and conservation invariants are verified independently of any underlying model. The accompanying artifact package ensures complete reproducibility, establishing a transparent foundation for subsequent theoretical extensions and empirical evaluations.

References

[1] Alfonso Amayuelas et al. Self-resource allocation in multi-agent llm systems. *arXiv preprint arXiv:2504.02051*, 2025.

[2] Amulya Kumar Bag. Binomial theorem in ancient india. *Indian Journal of History of Science*, 1(1):68–74, 1966.

[3] Jinyuan Chen et al. Kairos: Low-latency multi-agent serving with shared llms and excessive loads in the public cloud. *arXiv preprint arXiv:2508.06948*, 2025.

[4] Jayant Shah. A history of pingala's combinatorics. *Resonance*, 2016. Historical analysis of Pingala, Halayudha, and Meru-prastara attribution.

[5] Barend van Nooten. Binary numbers in indian antiquity. *Journal of Indian Philosophy*, 21(1):31–50, 1993.

[6] Jinghao Wang et al. Latency-aware orchestration for multi-agent llm workflows on heterogeneous gpus. *arXiv preprint arXiv:2609.03335*, 2026.

[7] Jinghao Wang et al. Maestro: Workload-aware cross-cluster scheduling for llm-based multi-agent systems. *arXiv preprint arXiv:2606.12950*, 2026.

[8] Jun Wang et al. Mixture-of-agents enhances large language model capabilities. *arXiv preprint arXiv:2406.04692*, 2024.

[9] G.-I. Yu et al. Orca: A distributed serving system for transformer-based generative models. In *16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)*, pages 521–538, 2022.