

Next steps in simplifying DELPH-IN MRS representations

Dan Flickinger

CSLI Stanford

`danf@csli.stanford.edu`

Reminder of recent change to our MRSs

- Elimination of messages

Introduction of sentence force via feature on events

Remaining work to do for 'information structure'

passivization; 'focus' in topicalized sentences



Proposed changes

- Elimination of quantifiers for pronouns and proper names

pronoun_q_rel and *proper_q_rel*

Instead, identify these indices as exempt from binding

Identify LBL of selector's relation with LBL of complement *named_rel* and *pron_rel* – more consistent with semantic algebra for composition.



MRS with unwanted quantifier

with quantifier (current)

```
qqq<h1,e2:PROP:PRES:INDICATIVE:+:-,  
{h3:_the_q_rel<0:3>(x5:3:SG:+, h6, h4),  
h7:_dog_n_1_rel<4:7>(x5),  
h8:_chase_v_1_rel<11:18>(e2, x5, x9:1:PL:STD_PRON),  
h10:pron_rel<19:22>(x9),  
h11:pronoun_q_rel<19:22>(x9, h12, h13)},  
{h6 qeq h7, h12 qeq h10}>
```

without quantifier (proposed)

```
<h1,e2:PROP:PRES:INDICATIVE:+:-,  
{h3:_the_q_rel<0:3>(x5:3:SG:+, h6, h4),  
h7:_dog_n_1_rel<4:7>(x5),  
h8:_chase_v_1_rel<11:18>(e2, x5, x9:1:PL:STD_PRON),  
h8:pron_rel<19:22>(x9),  
{h6 qeq h7}>
```



Related change: Revision of appositives treatment

- *This candidate, the famous actor, arrived.*
- Identify LBL of *appos_rel* with that of selector of the whole NP, rather than with a relation within NP

```
<h1,e2:PROP:PAST:INDICATIVE:-:-,  
{h3:appos_rel<0:33>(e6, x5:3:SG:+, x4:3:SG:+),  
h7:_this_q_dem_rel<0:4>(x5, h9, h8),  
h10:_candidate_n_1_rel<5:15>(x5),  
h11:_the_q_rel<16:19>(x4, h13, h12),  
h14:_famous_a_1_rel<20:26>(e15, x4, i16),  
h14:_actor_n_1_rel<27:33>(x4),  
h3:_arrive_v_1_rel<34:42>(e2, x5)},  
{h9 qeq h10, h13 qeq h14}>
```



Related change: Add non-restrictive relative clauses

- Treat semantically as paraphrase of appositive construction
- *This candidate, who came from Austria, is better*
- *This candidate, one who came from Austria, is better*

