

altairsim — Changelog

2026-08-03 · 348b425

Changelog

Every release of **altairsim**, newest first. Each entry is the short version — what you can do here that you could not do in the release before it. The User Manual describes the program as it is now; this document is the record of how it got there.

Unreleased

BREAK IO and **BREAK MEM** now stop *before* the instruction runs

A cycle breakpoint used to let the triggering instruction finish and stop at the next boundary, so **BREAK IO R 19** on an **IN A, (19)** came back with the PC on the *following* instruction and **A** already loaded from the port. Now every **MEM / IO** cycle breakpoint stops with the PC sitting **on** the instruction that tripped it, having executed nothing: no port read, no byte written, registers pristine — the same place a **BREAK <addr>** stops. A bare **RUN** or **STEP** then executes that instruction fresh. (A **BREAK MEM W** on a *DMA* transfer still stops at the boundary after the write — a board's own transfer has no CPU instruction to unwind.) **SHOW BUS / WHO** will not reflect the stopped-on cycle, because it never ran.

A machine file can leave the operator a note — **#>**

A comment line in a machine file that begins **#>** is a *note*: instead of being discarded like an ordinary **#** comment, its text is printed to you when the machine loads — right after the **loaded ...** line and before the **startup** commands run. It is where a config's author writes the one or two sentences you need to actually use it: **#> Type DIR at the A> prompt , #> Disk B is blank**. Each **#>** line prints as one line, a bare **#>** prints a blank one, and one can trail a setting. It sets nothing and **CONFIG SAVE** does not write it back — a saved machine is the backplane, not the prose around it.

EDIT assembles an instruction in place

EDIT has taken hex bytes one at a time since it existed. Now, on a machine with a CPU, you can type an **instruction** where a byte would go and it is assembled on the spot: **EDIT 100**, then **IN**

10 , writes DB 10 and drops the prompt to 0102 — the next address falls out of the encoding's length, not a fixed one byte. It is the disassembler read the other way, so DISASM reads back exactly what you typed. Operands are numbers in the console base (a trailing H or Q overrides), and a bare value is still a plain byte, so nothing about the old byte-at-a-time entry changed. This is the 8080; a machine whose CPU we do not yet assemble for keeps taking bytes.

BREAK TAPE STOP — stop right after a cassette load lands

The debugger gained a breakpoint that watches a device rather than the program: BREAK TAPE STOP halts the machine the moment a cassette deck reaches auto-stop — the instant the tape parks itself after a load has finished feeding. It is how you catch what a load left behind without having to know the loader's end address: arm it, run, and the machine stops inside the loader as the tape stops. It is a third kind of breakpoint, next to the PC-address stops and the MEM / IO bus-cycle watches — and it re-arms on its own, so a rewind and a fresh load fire it again.

Altair BASIC 1.0 — the first one — as an example

examples/basic/basic1.toml boots "8080 BASIC VER 1.0", the original Altair BASIC Bill Gates and Paul Allen wrote in 1975, off a period cassette image with the bootstrap MITS shipped, both unmodified. It boots the raw two-move way its primitive bootstrap forced and the later 4K/8K loaders did away with: RUN 1800 reads the tape, then — because that loader neither stops nor jumps — you press ^E (the operator's STOP/RESET) and RUN 0 to start BASIC. It reaches MEMSIZ? (spelled exactly that way: Microsoft set the end-of-message bit on the Z instead of spending a byte on a trailing E). A pty acceptance test drives the two-step boot end to end.

The live tape counter holds its finished frame

The tape: mm:ss / total (nn%) readout the 88-ACR paints while a cassette loads no longer vanishes the instant the head reaches the end — it now rests on its final (100%) frame. This matters at the flat-out default, where a load is over before a single paint window can catch the counter climbing: tape: 02:30 / 02:30 (100%) is then the only frame there is, and leaving it on screen is how you know the tape is done and it is time to stop and run what loaded. It still cannot repaint over a prompt: the run loop retires the line the moment the guest prints over it.

MOUNT reads ImageDisk (.IMD) files

MOUNT <id>:<unit> disk.imd now Just Works: an ImageDisk container is converted to a raw disk.dsk written next to it, and that is mounted — so the disk boards, which read only raw sector-linear images, need no changes. The conversion de-interleaves each track into sector-ID order, expands the format's compressed runs, and fills any unavailable sector with the CP/M blank byte; it narrates what it built (the IMD's own description line and the emitted geometry)

so you can check it against the disk you expected. For a double-sided disk the head order is taken from the controller you are mounting on, not guessed. An existing `disk.dsk` is never overwritten — remove it, or mount it directly. (A single-sided CP/M disk round-trips byte-for-byte.)

VersaFloppy double-sided disks lay out cylinder-major

The SD Systems VersaFloppy now stores a double-sided image **cylinder-major** — both sides of a cylinder adjacent (`T0H0`, `T0H1`, `T1H0`, ...) — which is how the `vf.z80` dump tool writes these disks and how the DDBIOS `FMAT` records them (it formats both sides of a cylinder before stepping to the next). Single-sided disks, and the double-sided SDOS master already in the tree, are unaffected. This also flows into the `.IMD` conversion above: a double-sided ImageDisk mounted on a VersaFloppy is now emitted in the same cylinder-major order the controller reads back.

Tab completion, and a fuller line editor at the prompt

`Tab` now completes what you are typing at the monitor prompt — a command, then a board id, then that board's property names, then a property's legal values (`SET mem0 fill=` then `Tab` offers `zero` and `random`). It reads the candidates off the machine itself, so a board you plug in is completable straight away with no list to maintain; a second `Tab` lists the choices when more than one fits. Completion now reaches a board's **units** and the **other target-taking commands** too: `SET sio0:` then `Tab` offers that board's ports, and `SET sio0:a` completes the unit's own property names and values. Every command that takes a target now completes it: `SHOW`, `MOUNT`, `UNMOUNT`, `CONNECT`, `DISCONNECT` and the board verbs (`REWIND`, ...) all complete a board id or `id:unit` argument, filtered to what fits — `MOUNT` offers only mountable units, `CONNECT` only serial ones — while `SHOW` adds its keyword arguments (`BUS`, `MOUNTS`, ...) and `BOARDS ADD` completes the board *type* names. The line editor also grew the keys it was missing: **Home** and **End** (and their `Ctrl-A`/`Ctrl-E` equivalents), **word motion** with `Alt-B`/`Alt-F` or `Ctrl-Left`/`Ctrl-Right`, and **Ctrl-K** to kill to the end of the line. And the **history now survives a restart**: it is saved to a hidden `.altairsim_history` in the directory you launched from — per project, not per user, so there is no home directory to depend on (Windows has none). Depth is the `history` console property (default `50`; `0` turns the file off), settable in TOML as `[console] history=N` or at the prompt with `SET CONSOLE history=N`. Only an interactive session writes it — a script, a pipe, or `--mcp` never touches the file.

Cromemco CDOS boots — the 16FDC and 64FDC floppy controllers

`BOARDS ADD 16fdc` (or `64fdc`) puts a **Cromemco disk controller** in the backplane — the S-100 card that ran Cromemco's own machines. It is three things on one board: a **WD FD1793** floppy controller, a **TMS 5501** UART wired as the console, and the **RDOS boot PROM** (2.52 on the

16FDC, 3.12 on the 64FDC) at `C000`. With `bootstrap` on, RESET runs the PROM, which reads the boot track and loads **CDOS** — Cromemco's CP/M-1.4 work-alike. `altairsim` `examples/cdos` comes up at the CDOS `A.` prompt off an 8" double-sided, mixed-density diskette with **nothing typed**: the card is strapped for its fixed 300-baud "modem" console, so it skips the terminal auto-baud that would otherwise want a Return. The Z80 runs at the real Cromemco **4 MHz** — not a knob but a requirement, since RDOS's double-density read loop must keep up with a 500 kbit/s byte or the FD1793 reports Lost Data. It is proven end to end by an acceptance test that boots the tracked master to `A.` and lists the directory.

Driving altairsim with an AI — now with the missing step

The briefing that ships for an AI assistant is renamed **DRIVING-WITH-AI.md** (from `USING-ALTAIRSIM.md`) and works with any MCP-capable assistant, not just one. It gains the step that was actually missing: **how to register the server** so the assistant drives it hands-free — the one-line `claude mcp add altairsim -- altairsim <machine> --mcp` for Claude Code, and the `mcpServers` JSON block for Claude Desktop and other clients — plus sections on investigating a program you did not write (disassemble, break, single-step over MCP) and on moving from the simulator to a real machine by pointing the same serial channel at `serial:/dev/cu.*`. A new example, `examples/ai-mcp/`, is a ready-made working directory: a tiny CP/M program with a planted bug, and a walkthrough where the assistant assembles it, sees the wrong output, single-steps the loop to find the fault, fixes the source, and reassembles — entirely over MCP.

Blank soft-sector floppies can be formatted from inside the guest

The Tarbell and SD Systems VersaFloppy controllers now honour the WD177x **Write Track** command, so a fresh disk can be `FORMAT` ted by the operating system running on it — no pre-built image required. On the single-density **Tarbell #1011** (`tarbell`), CP/M's `FORMAT` lays down a bootable SSSD disk; the double-density **#2022** (`tarbelldd`) `DFORMAT` s a mixed-density CP/M disk (single density on track 0, double on the rest) and still reads plain single-density media. The **VersaFloppy** (`versafloppy`) formats all **ten** SD Systems disk geometries under SDOS. Together with the blank hard-sector disks added earlier, a blank diskette is now something the guest can bring to life on its own.

SAVE can write a disassembly or octal listing

`SAVE <file> <range>` grew a `FORMAT=` that is no longer just `BIN` or `HEX`: `FORMAT=PRN` writes the range as a **disassembly listing** — the same text `DISASM` prints to the screen, labels and symbolic operands included when symbols are loaded — and `FORMAT=OCTAL` writes an octal one. The flavour also follows the file's own extension, so `SAVE out.prn 100-1FF` writes a listing and `SAVE out.oct 100-1FF` writes octal without a `FORMAT=` at all. It captures a listing to read, diff, or feed a toolchain, straight from the monitor.

CONNECT ... |FILE — tap a serial line to a hex log

Append **|FILE** to any endpoint and the line is also written to a text file — both directions, in hex and ASCII, with timestamps — a poor man's serial protocol analyzer. `CONNECT sio0:b socket:2323|bbs.hex` telnets a guest in and captures the whole conversation; the guest cannot tell the tap is there, and it never alters a byte (8-bit clean, unlike the console's filters). Three layouts pick how it reads: `?fmt=dump` (the default — one chronological hex row per line, greppable), `?fmt=cols` (guest-sent on the left, received on the right, so a request/response reads down the page), and `?fmt=jsonl` (one JSON record per transfer, for diffing and scripting). `?ts=elapsed|wall|none` chooses the timestamp style, `?width=N` the bytes per row, `?gap=MS` when an idle burst flushes, and `?pins=off` drops the modem control-line edges (DTR/RTS/DCD/CTS/RI/break) that are logged inline by default. The whole tap round-trips through `SHOW` and `CONFIG SAVE`.

usio — a serial board you describe instead of one we picked

`BOARDS ADD usio` puts a **universal serial card** in the backplane — instead of emulating one specific UART, you describe the interface by **strap**: where the status/control and data ports sit, which status bit means **receive-data-ready** and which means **transmit-empty**, and the polarity of each. It talks only to `ByteStream` and the shared `CONNECT` endpoint grammar, so `file:`, `socket:`, `serial:`, `null`, `loopback` and `in:/out:` all work with no board-specific code. Built-in **profiles** bundle the straps for common cards — the **Cromemco TU-ART**, the **IMSAI SIO-2**, and the CompuPro **Interfacer II** and **System Support 1** serial channels, transcribed from the manuals (added under `reference/`) — and a profile's name becomes a value of the `profile` property, so `SET usio0 profile=...` picks one. A `baud` strap programs a connected **real serial port** (always 8N1); it is inert on other endpoints and does not pace the emulated line. Polled only — interrupts are a documented later phase. The new Developer Guide **serial-I/O** chapter walks the board/chip → `ByteStream` → `resolveEndpoint` layering behind it.

`SHOW BOARD <type>` now also lists a property's **legal values** under its help — enum choices, `on/off`, bounded ranges — so the built-in profiles are discoverable straight off the type card. This applies to every board, not just `usio`.

pmmi — the PMMI MM-103 telephone modem

The first S-100 modem board joins the catalogue: a **Bell 103 modem on one card**, unit `line`, four ports from a four-port boundary (default `C0`). It carries the card's real quirk — **read and write at the same port are different registers**, and the three control registers are write-only — and moves characters over its serial line to whatever you `CONNECT` it to. For now that is a byte source and sink: `CONNECT pmmi0:line in:incoming.tap,out:outgoing.tap` transmits and receives through a pair of files. It does **not** dial (placing a call is `CONNECT`'s job, not a decoded phone number), its modem status is a fixed "connected and ready" value rather than a real

handshake, and it raises no interrupts — the dialer, the answer/originate handshake and interrupts are still to come. `SHOW pmmi0` shows the live frame, baud, UART flags and modem lines. The `pmmi` machine is `default` with one fitted.

`altairsim rombasic` — MITS Extended ROM BASIC 16K

A new built-in machine boots **ALTAIR ROM BASIC 4.1** straight out of ROM: the interpreter lives in eight 2K PROMs at `C000 – FFFF` and runs in place, so it uses no RAM to hold itself and leaves the full **48K** below it (`0000 – BFFF`) free for your program. Just run `altairsim rombasic` , answer `MEMORY SIZE?` and `LINEPRINTER? ( C )` , and you are at the `OK` prompt on the 88-2SIO console — no tape to load. The ROM ships as the new `builtin:rombasic` ; its last 2K is the disk bootloader, still reachable with `RUN FF00` .

Blank hard-sector disks can be created and formatted from inside the simulator

A hard-sector controller — the 88-DCDD (including the 8 MB FDC+ image) and the 88-MDS minidisk — now **mounts a file of any size** and lets the guest's own `FORMAT` program define the disk by writing it: the image carries no geometry, so it grows one sector at a time as `FORMAT` runs, up to the controller's maximum reach. A brand-new disk starts with `MOUNT ... CREATE` (or `create = true` in a machine file), which writes an empty file and mounts it; run your period `FORMAT` utility and you have a fresh, formatted disk without ever leaving the program. The same `CREATE` flag makes a blank byte tape for the ACR/Sol cassette deck. An unformatted or partially-written disk reads back exactly as real hardware does — the guest's own sync-byte and checksum checks reject the sectors that were never written. (Soft-sector `FORMAT` is not yet supported.)

The video window resizes proportionally and shows when the machine has stopped

A video window now opens locked to its picture's aspect ratio, so dragging any corner — the first drag included — resizes it proportionally and the picture fills the new size without snapping back on the next redraw. A thin, even bezel frames the picture on **all four sides** and stays even at any size. While the machine is halted the title bar reads "**simulator stopped**", and clears again the moment it runs.

The video window's size is now a per-board `width` , in pixels

How big a video window opens is set with a `width` property on the video board itself (`SET vdm0 width=1024` , or `width = 1024` in the board's table) rather than the old `[display] scaling` . It is a width in **pixels** — `auto` , the default, opens the window about **half the screen wide** — and the **height follows the board's own aspect**, so you size one axis and the other

comes with it. The picture is still drawn at a whole-number multiple of the board's pixels, so a 1970s frame stays a crisp grid. `width` lives on the board because on real hardware each board has its own video-out; the old `[display] scaling` key is gone.

CUTS tapes the simulator writes now load on a real Sol-20

A `.WAV` the Sol records is now built the way a real Sol's cassette modem builds it — a flip-flop dividing a master clock into a square on a fixed grid, rounded by an RC filter, at a genuine dub's recording level — instead of a free-running oscillator at full volume. The old output round-tripped perfectly *here* but a real Sol read the header and then failed: its decoder times the tone's transitions, and the old modulation smeared those crossings off the clock grid and recorded them twice as hot as a real cassette. Two new deck properties expose the fix — `level` (recording level, percent of full scale, default 36) and `rc` (the Sol's edge-rounding corner in Hz, default 4000); the 88-ACR gains `level` too. Both defaults are measured off the one genuine dub in the package, and the simulator's output now matches that dub's level, crossing timing, and waveform curvature. Reading real dubs, and the shipped example tapes, were never affected.

DISASM lines up in octal, and undocumented opcodes read the way DDT prints them

`SET CONSOLE base=octal` no longer produces a ragged listing: the disassembly's byte column now widens for octal's three-digit bytes, so the mnemonics line up the way they always have in hex. And the twelve undocumented 8080 opcodes now disassemble the way real **DDT** and **SID** show them — each as a **single byte** marked `??= <byte>`, followed by a bare `*JMP / *CALL / *NOP / *RET` naming what the byte would do if it ran. Previously `CB` was decoded as a three-byte `JMP`, which invents an address out of whatever two bytes happened to follow; a disassembler cannot know a stray byte is code rather than data, so it now advances one byte and re-syncs, exactly as DDT does. (The `CPU` still *executes* `CB` as a real three-byte `JMP`; only the disassembler treats each as one opaque byte.)

The Tarbell floppy controllers boot CP/M — by themselves

`altairsim examples/tarbell/tarbell.toml` comes up at a CP/M `A>` prompt with **nothing typed** — no monitor, no boot command. The `Tarbell #1011` (`tarbell`) carries its own **32-byte boot PROM**, so RESET arms it at address 0000, it reads the first sector off the disk through its WD FD1771, and the instant the loaded code runs the PROM's shadow of low memory falls away (released by a single address line) and CP/M loads itself. The double-density `#2022` (`tarbelldd`) is its twin with a WD FD1791, booting the same way off a **mixed-density** disk — single density on track 0 so the shared PROM can read it, double density on the rest. Both are

proven end to end by acceptance tests that boot the tracked masters to `A>` and read the directory. The single-density disk ships with the `HDIR / R / W` host-bridge utilities installed.

CP/M 2.2 boots on the SBC-200 — with interrupts and the PROM switch-out

`altairsim examples/sdsys/cpm.toml`, press Enter, type `C`, and **SD Systems CP/M 2.2** comes up to its `A>` prompt off the VersaFloppy — and this time everything you type at that prompt arrives through a **hardware interrupt**. Where SDOS polled the keyboard, CP/M's CBIOS takes console input *only* through a **Z80 mode-2 vectored interrupt**: the SBC-200's 8251 raises its `RxDY` line, the onboard **Z80-CTC** turns that into an interrupt on channel 1, and the card puts vector `0x82` on the bus so the CPU jumps to the CBIOS keyboard handler. It is the first machine here whose console depends on interrupts to work at all. The board also grew the **SBC-200 memory switch-out**: `cpm.toml` is a full **64K** machine whose monitor and DDBIOS live in the SBC's own **onboard boot-PROM sockets** (`[[board.socket]]`), shadowing RAM until CP/M's cold boot does `OUT 7F,3` to drop the PROM out of the map and run from the 64K underneath. Both the interrupt path and the switch-out are proven end to end — the acceptance test types `DIR` and reads the directory back, which only works if every link in that chain does.

SDOS boots on the video console — with its interrupt keyboard

`altairsim examples/sdsys/sdosv.toml` cold-boots **SDOS on the VDB-8024 video console** instead of the serial port. It looks like the serial `sdos.toml`, but it exposes the same lesson CP/M did, one board over: the `SDMONV21` monitor *polls* the video keyboard, so it boots and takes the `C` command with no interrupt at all — but SDOS's **video CBIOS runs console input under a Z80 mode-2 interrupt**, and until now a booted OS never saw a key on the video console. The `VDB-8024` now carries the authentic keyboard-strobe **interrupt strap** (`interrupt = vi2`): each keystroke raises S-100 **VI2**, the SBC-200's **Z80-CTC** turns that into the mode-2 vector `0x02`, and the CBIOS keyboard ISR reads the byte — the video twin of the serial console's `0x82` path. It is proven end to end: a test boots the real SDOS master off the VersaFloppy and types a command that can only echo back if that whole `VI2 → CTC → ISR` chain works.

A video console: the SD Systems VDB-8024

`BOARDS ADD vdb8024` puts an **SD Systems VDB-8024** in the backplane — an **80×24 video terminal on one board**, the video-console alternative to the `SBC-100/200`'s 8251 serial port. Despite the name it is **not** memory-mapped: to the computer it is two I/O ports (a status port and a data port, fixed at `00 / 01`) that behave like a terminal on a wire — read the status for a waiting key or a ready display, write a character or a control word, read a typed key back. It runs the **SD monitor's video build**, `sdmonv21` (the same monitor as `sbc200`, built to talk to this board instead of the 8251), so `altairsim sbc200v` comes up at the monitor's `.` prompt **on**

the video display with no "press Enter first" — the VDB is not a serial line with a speed to measure. Like a Sol-20 the **window is the console** (window and terminal keys reach the monitor as one stream), and the glyphs are drawn from the board's own character-generator font — transcribed from the manual's Appendix E — with true lower-case descenders. It understands its firmware's control codes (CR, LF, backspace, tab, cursor moves, clear/home, and the ESC cursor-position and erase sequences), wraps a full line, and scrolls at the bottom. `examples/sdsys/sbc200v.toml` is the ready-made machine.

SDOS boots: the SD Systems VersaFloppy floppy controller

`BOARDS ADD versafloppy` puts an **SD Systems VersaFloppy** in the backplane — the S-100 soft-sector floppy controller built around a Western Digital FD177x. It is **one board for both generations**: `variant=vfii` (the default) is the double-density **FD1791** VersaFloppy II, and `variant=vfi` the single-density **FD1771** VersaFloppy I. With the SBC-200's DDBIOS at `F000`, the monitor's `C` command **cold-boots SDOS** — `altairsim examples/sdsys/sdos.toml`, press Enter, type `C`, and *32K SD-OS Version 1.8B* comes up to its `[A]` prompt off an 8" double-density 256-byte disk. `R` / `W` / `Z` read, write and format. The controller stalls the CPU on the S-100 PRDY line the way the real card did (no DRQ polling — the sector transfer is a bare `IN` / `OUT` loop), and its 63H control latch is negative-true, both as the DDBIOS driver requires. The WD chip is now a proper family (`Wd1771` / `Wd1791` parts sharing one register model), ready for the Tarbell controllers to reuse.

A single-board Z80 console: the SD Systems SBC-100/200

`BOARDS ADD sbc` puts an **SD Systems SBC-100/200** in the backplane — the serial console of a Z80 single-board computer, built around an **Intel 8251 USART** (unit `tty`, data at `7C`, status/command at `7D`) rather than the 6850 the MITS boards use. `variant=sbc200` (the default) or `sbc100`. Its trick is **auto-baud**: `altairsim sbc200` comes up in the **SD monitor (MSMONR21)** waiting for you to press Return, times that one character, and sets its own speed to match — so any common terminal rate just works, and nothing happens until that first Return. It is the console the VersaFloppy boots SDOS through. The parallel ports, timer and interrupts of the real card are a later phase; the console is here now.

A second printer card: the 88-LPC line-printer controller

`BOARDS ADD lpc` puts a **MITS 88-LPC** in the backplane — the controller for the 88-LP line printer, the sibling of the 88-C700. It shares the C700's two-port shape (control at an even base, data at the odd address above it; MITS default `02`) but drives the printer the way it really worked: the guest loads a **6-bit character code** at a time into an 80-character line buffer (`OUT` the data port), and the line commits on a **PRINT** command or when the buffer fills — with **LINE FEED** and **CLEAR** commands beside it (`OUT` the control port). The capture is the printed page

— the codes decoded to their glyphs, one text line per printed line — because unlike the C700's transparent byte pipe, the LPC's line breaks are *commands*, not data. `CONNECT` it anywhere a line can go (a `file:`, the `console`, a `socket:`, a `printer:` queue). The `machines/lineprinter-lpc.toml` machine has one wired at 02. Polled, like the C700 (the hardware interrupt is not modeled).

Serial and cassette on one card: the 88-UIO

`BOARDS ADD uio` puts a **MIT 88-UIO** in the backplane — the Universal I/O board, a 6850 serial port and an 88-ACR cassette on a single card. It comes up as the two boards it replaces: a serial console (unit `serial`, default `10`) and a cassette deck (unit `tape`, default `06`), at the standard addresses, so software that expects a 2SIO console and an ACR tape finds both. Over two separate boards it adds **motor control** and the **SW-1 modulation switch** — MIT 300-baud or Kansas City — since the UIO was sold to talk to either. The tape half brings the same `WIND / REWIND / EXTRACT` verbs and position counter the 88-ACR does.

`HISTORY` remembers the processor — and the bus view names

`HISTORY` is a flight recorder that runs while the machine does, so the run-up to a breakpoint is already caught before you ask for it. It now **defaults to the CPU**: the last sixteen instructions, each line exactly what `STEP` prints — the registers, flags and the decoded mnemonic — read from the bytes that *actually ran*, so self-modifying code reads truthfully. The bus-cycle recorder it used to be is still there as `HISTORY BUS` (and `HISTORY CPU` names the default out loud).

`HISTORY BUS` now also shows **who drove each cycle and who answered it**: `cpu` for an ordinary cycle, or the **DMA board** that stole the bus, on one side; the board that decoded the address on the other, or `--` when nobody did and the read floated to `FF`. `TRACE` lines carry the same two columns. It costs the always-on recorder nothing per cycle — the board is noted by an interned handle, not a name copied onto every record.

The board and machine catalogues moved to `SHOW`, and read like tables

Asking *what can I build?* is now one family of commands. `SHOW BOARDS` lists every board type with its description in an aligned, wrapped table, and `SHOW BOARD <type>` drills into one — its description and every property, with the help text. This is what `BOARDS TYPES` used to do; that spelling is gone, and the catalogue sits beside the new `SHOW MACHINES` (the built-in machines you can boot, the same list `--list` prints) and `SHOW MACHINE <name>` (one built-in's backplane and startup, without disturbing the machine you are running). A bare `SHOW MACHINE` is still the live machine.

`HELP` gained worked examples and fuller text for `HISTORY`, `BREAK ... IF`, `EDIT`, `MOVE`, `COMPARE`, `DISASM`, `CONSOLE`, `REGS` and `QUIT`, and the `CONNECT` endpoint grammar now

reaches the printed reference instead of a literal token. The reserved `RECORD`, `REPLAY` and `STOP` commands were **dropped** — not deferred — so their abbreviations are free again and the command list no longer carries a `*` legend for entries that do not exist.

Printing to a real printer: the `printer:` endpoint

A line can now go to a **real print queue on the host**, not just to a file. `CONNECT lpt0:prn printer:linewriter` hands what the 88-C700 — or any board with a line — prints to your operating system's print system as a job. Like `file:` it is a write-only, 8-bit-clean sink and not tied to any one board, so a serial printer on a 2SIO would use it too.

A printer has no end-of-job signal, so the endpoint decides where one job ends: after a few seconds idle (`?idle=N`, the default), on a form feed (`?onff`), or at a byte ceiling (`?max=N`), whichever comes first — and an empty buffer never prints, so no blank pages. The queue must pass data through untouched (a *raw* queue), created once in your OS printer setup; `printer:` with no name lists the queues it can see, and a failed job says so rather than vanishing. Built where the host print system is present (CUPS on macOS and Linux); see the User Manual's serial chapter and issue #70.

A tape boot loader in the PROM socket: `builtin:mb1`

The Altair **Multi Boot Loader** is now a built-in ROM. Where `dbl`, `mdbl` and `cdbl` boot a disk, `mb1` boots a **tape**: it reads any of the punched-/cassette-tape formats MITS designed, building a reader routine in RAM for whichever board — 2SIO, SIO, ACR, 4PIO, PIO or HSR — you pick on the front-panel switches, then loading and checksumming the payload and jumping to it. Put it in a socket with `mount = "builtin:mb1"` (it lives at `FE00`). It is not `mdbl`, the **minidisk** loader whose name is one letter away — the confusion that prompted this (issue #124). Provenance is in `docs/roms.md`.

`SHOW ROMS` now carries a **description** column too — one hand-written line per ROM (`roms/<NAME>/DESC`) — so `mb1` and `mdbl` read as what they are instead of two near-identical names.

A tape counter, and `WIND` to a time

Both cassette boards — the **88-ACR** and the **Sol** decks — now show **where the head is** as `mm:ss / total (percent)`, on `SHOW MOUNTS`, on `SHOW <id>`, and as a read-only `position` unit property. For a `.WAV` the time is the *recording's own*: the demodulator now keeps each byte's place in the audio, so the counter reads real minutes and seconds with the leader and the silent gaps between programs included — the way a real cassette counter (and a manual that indexes files by seconds) reads. For a byte `.TAP`, which has no audio, the time is estimated from the baud.

A new **WIND <id>:tape <mm:ss | START | END>** verb moves the head to a time, so a cassette holding several programs one after another is finally reachable: read the counter for where the next one starts and wind there. **REWIND** stays as its **WIND ... START** shorthand, so every old script still spells **REW**. And when a tape plays in real time (**rate = real**), a **live counter** ticks up on the console while it loads; it is on by default and turns off with **counter=off** at **MOUNT** or **SET** for a machine whose guest writes to the same terminal.

A **stop mark** completes the pair: **MOUNT ... stop=2:05** (or **SET ... stop=2:05**) makes the tape go quiet at a time — your finger on the recorder's STOP button — so a multi-program load halts at a boundary instead of running into the next program; move the mark forward, or **stop=off**, to carry on. It halts playback only (a recording writes through it) and travels in a snapshot with the head position.

And **extract** turns a multi-program cassette WAV into per-program **.TAP** files: **MOUNT games.wav extract** (or the **EXTRACT <id>:tape** verb on an already-mounted tape) demodulates the recording and writes each program — split at the seconds of silence between them — to its own **games-1.tap**, **games-2.tap**, ... beside the WAV, printing each file's name and size. A single-program tape becomes just **games.tap**; **extract=<base>** names them yourself.

Octal, the MITS way

The monitor can now read and print the **wire class** — addresses, ports, data bytes — in **octal**, the base MITS documentation and the Altair front panel used. **SET CONSOLE base=octal** (or **[console] base = octal** in a machine file) switches it, and it is authentic **split octal**: each byte reads as its own **000 – 377** group and a 16-bit address as two of them, so **0x1234** prints **022 064** — the way the front-panel address lamps group. It moves **EXAMINE**, **DEPOSIT**, **DUMP**, **REGISTERS**, **DISASM** and the rest of the wire class, on both display **and** the default parse base; the decimal class (counts, widths, **baud**) does not move, because octal-vs-hex was never its question. **base=hex** remains the default.

Octal notation is always typeable regardless of the default: **0o377** (matching the **0x / 0b** family) or a trailing **377q** (the historic 8080-assembler marker). And the escapes still work in both directions — in octal mode **0x1234 / \$1234 / 1234h** force hex and **#4660** forces decimal, just as **0o / q** force octal in hex mode. (**0o10K** is refused, the same contradiction as **0x10K**: a **K / M** suffix is always decimal.)

Joysticks — the Cromemco D+7A and the JS-1

The **Cromemco D+7A** joins the backplane (**d7a**): an analog **and** parallel I/O card — one parallel port and **seven analog channels** in a block of eight ports (default base **18**), each channel an A/D converter on read and a D/A on write, in 8-bit two's-complement (**00** = 0 V, **7F** = +2.54 V, **80** = −2.56 V). Its reason for being here is the input end of a Dazzler game

console: it reads one or two **JS-1 joystick consoles** — the X/Y pots on analog inputs `19 / 1A` and `1B / 1C`, and the four buttons (active-low) in the parallel byte at `18`, low nibble for one stick and high nibble for the other.

The stick comes from the host through a new **Joystick service**, injected like the `Display`: a USB **gamepad** where SDL3 is present (its left stick and four face buttons map to a JS-1), or the **keyboard** as a fallback (arrow keys + Space/Z/X/C), and a no-op headless so the board runs and is tested with no controller. `joystick1 / joystick2` pick which host stick drives each console (`auto`, `keyboard`, `none`, or a device index); the board itself never touches SDL. `machines/d7a.toml` is the machine; `examples/dazzler/cpm.toml` boots CP/M with a disk of period Dazzler demos (GDEMO, DAZCHESS, ...), and `examples/dazzler/adctest.toml` auto-runs the **ADCTEST** joystick diagnostic. `reference/D+7A.md`, `reference/JS-1.md` and `docs/boards/cromemco-d7a.md` have the port map, the two's-complement scale, and the sourcing for the active-low buttons. (Sound — a JS-1 speaker is a D/A the CPU writes a waveform to — is designed in the board doc, not yet built.)

The video window learned to be a **display, not a keyboard**. `[display] keyboard` (a new setting, default `console`) says where a focused video window's keystrokes go: `console` (the window is a keyboard, like a Sol-20) or `none` (display-only, like a Dazzler — the keys drive the joystick instead of landing at the CP/M or `altairsim>` prompt, and Ctrl-E in the window stops the guest). The Dazzler examples set `keyboard = "none"`, so you can play in the window without your keystrokes reaching CP/M.

Color graphics — the Cromemco Dazzler

The **Cromemco Dazzler** joins the backplane (`dazzler`), and with it the S-100's first color graphics card. It paints a picture out of a **framebuffer in main RAM** — 512 bytes or 2 KB, placed anywhere on a 512-byte boundary — through two ports at `0E / 0F` (control: on/off and base; format: resolution, size, color) with a two-bit status read (odd/even line, end-of-frame). Four modes fall out of the format byte: 32×32 or 64×64 color/grey elements, and 64×64 or 128×128 high-resolution on/off elements, in 16 colors or 16 greys. `machines/dazzler.toml` is the machine, and `examples/dazzler/kscope.toml` comes up running **Li-Chen Wang's Kaleidoscope** (`KSCOPE`), drawing a four-way-mirrored pattern in a window (ATTN breaks back to the monitor). Like the VDM-1 it renders into the injected `Display`, so a headless build still runs and is tested with no window; `docs/boards/cromemco-dazzler.md` and `reference/Cromemco Dazzler.md` have the port map, the quadrant scan order, and the byte→pixel encoding for every mode.

The video window learned to **size itself** for it. `[display] scaling` (a new setting, default `auto`) opens a window at the largest whole-number multiple that fills about 70% of the screen, so the Dazzler's tiny 64×64 frame no longer comes up a sixth the size of a VDM-1's — both land near the same size, and a fixed multiple (`scaling = 4`) is still there if you want one.

`kscope.toml` also sets `[display] focus = true`, so the window comes to the front and takes the keyboard when it opens (ATTN hands it back), the way a Sol-20's does.

The 8800bt — an Altair with a Turnkey Module

The **MTS 8800b Turnkey Module** joins the backplane (`turnkey`), and with it the front-panel-less "turnkey" Altair. It is one card doing four jobs: a boot PROM at `FC00 – FFFF`, an integrated 6850 serial console at `10h` (compatible with an 88-2SIO's Port A), the sense switches at port `FF`, and an **Auto-Start** circuit. There is no front panel to toggle a bootstrap in from, so `RUN 0000` starts the CPU at 0 and the Auto-Start circuit **jams a JMP onto the bus** — running the boot PROM exactly as the panel's START switch would. The boot PROM is a **phantom**: it shadows the top of memory for reads until the guest's first `IN` from port `FE / FF`, then switches itself out so the machine has the full 64 KB of RAM — which is why an unmodified Altair BASIC drops into 64K after reading the sense switches once. `machines/turnkey.toml` is the machine, and `examples/turnkey/` boots CP/M on it two ways: `floppy.toml` off an 88-DCDD (56K CP/M, DBL) and `hdsk.toml` off an 88-HDSK hard disk (48K CP/M, HDBL). `docs/boards/mts-turnkey.md` and `reference/MTS Turn Key Board.md` have the phantom one-shot, the Auto-Start byte sequence, and the sockets. The card's serial half is a new reusable `Sio2Port` section, which the 88-2SIO will adopt in a later change.

Boot CP/M off a hard disk — the 88-HDSK Datakeeper

The **MTS 88-HDSK** hard disk controller joins the backplane (`hdsk`), and with it CP/M boots off a Pertec platter instead of a floppy. It is an outboard "Datakeeper" controller — eight ports at `A0h – A7h`, a command/handshake protocol, and four internal 256-byte page buffers — so unlike the floppy cards it moves whole sectors for you rather than shifting bits in real time. The **HDBL** PROM at `FC00` (already in the tree, and until now a boot loader with nothing to boot) reads the disk's descriptor page and brings the system up. `examples/hdsk/` is the ready-made machine: `altairsim hdsk.toml` lands you at `A>` on a 4.8 MB CP/M 2.2 platter. It is read/write — CP/M saves to it — and `docs/boards/mts-88hdsk.md` and `reference/88-HDSK.md` have the full protocol, the geometry, and the one place the manual's prose and the boot ROM disagree.

Edit memory a byte at a time — EDIT

`EDIT <addr>` is an interactive `DEPOSIT`. The prompt shows an address and the byte that is there — `0100 C3` — and you type its replacement; Enter writes it and drops to the next byte, a bare Enter leaves the byte as it was and drops to the next, and `.` returns you to the monitor. It runs the same real bus write `DEPOSIT` does, so it tells you when no board decodes the address rather than letting the byte vanish, and `EDIT <addr> ROM` burns a PROM the same way. It reads its bytes from the monitor's own input, so it works at the keyboard and from a piped script alike;

where there is no input at all — an MCP `command`, a `startup` list — it says so and points you at `DEPOSIT`.

Two parallel-I/O boards — `pio` and `4pio`

The MITS parallel ports join the backplane, with the same connect-anything interface as the line printer. The **88-PIO** (`pio`) is an 8-bit parallel port with two lines you `CONNECT` independently — `out` (an output device) and `in` (an input device) — so it drives a printer to a `file:`, reads a keyboard off the `console`, or moves bytes over a `socket:`, all at once. The **88-4PIO** (`4pio`) is its programmable cousin, up to four Motorola 6820 PIAs whose data direction the guest sets in software; each section (`ja`, `jb`, ... per populated port) is its own connectable line. Both come up at the monitor and in a machine file exactly like every other board — `SET pio0 port=...`, `CONNECT pio0:out file:print.txt`, `SHOW`, `CONFIG SAVE` — and `machines/parallel.toml` is a ready-made example. Both are **polled** (like the C700): a byte moves when a driver polls the status port for it. `docs/boards/mits-88pio.md` and `docs/boards/mits-884pio.md` have the full register maps and the deliberate departures.

Reach the host shell without leaving the machine — `!`

A monitor line that begins with `!` runs the rest of it in **your host shell** and returns you to the prompt when it finishes — `!ls`, `!cp game.dsk save.dsk`, `!vi HELLO.PRN` to edit a file in place. Everything after the `!` is passed through verbatim, spaces and all, and an interactive program like `vi` gets a normal terminal because the monitor is not holding the keyboard when it hands off. It runs with *your* privileges, not the guest's, and the machine keeps its state underneath — `!` borrows you, not the processor. A bare `!` just shows the form.

Save the machine and pick it back up — `SNAPSHOT` and `RESTORE`

`SNAPSHOT <file>` writes the whole machine's **state** to a small, portable, CRC-checked file: the CPU — down to the hidden micro-state a register dump never shows, the EI and interrupt-acknowledge latches, the Z80's `WZ`, `IFF2` and interrupt mode — the clock, and every board's registers, latches and RAM. `RESTORE <file>` reads it back into a machine of the same shape. A snapshot is *state*, not configuration, so `RESTORE` validates the file's checksum, version and board topology **before** it applies a single byte: a corrupt or mismatched file is refused with the reason, and your running machine is left untouched. This is the largest piece of the design's replay groundwork; the deterministic `RECORD` / `REPLAY` half stays reserved and is unblocked by it.

The disassembler reads symbols

Load an assembler listing and `DISASM` stops speaking in hex. A program label heads its own line the way a listing prints it, and a 16-bit operand shows the name it points at — `CALL 0005`

becomes `CALL BDOS`, `JMP 0100` becomes `JMP LOOP`. Single-stepping shows it too, on the `STEP` and `REGS` line. A leading `LABEL:` line comes from real program labels only — an `EQU` never heads a line, because a constant that merely equals a code address must not masquerade as one — but an operand *reference* uses any symbol, so `CALL BDOS` works even though `BDOS` is an `EQU`, and a real label wins when the two share a value. Only a 16-bit operand is an address: a byte like `IN 10` stays a number. Nothing changes until you `SYMBOLS LOAD`.

`examples/debugger/` is new alongside it — a 46-byte program with its listing and Intel HEX, a machine that comes up at the monitor prompt, and a walkthrough (shipped as `README.pdf` as well as Markdown) from `SYMBOLS LOAD` through symbolic `DISASM`, single-stepping, breaking on a label *by name*, and running it until it prints `HELLO, WORLD`. It is the fifth example in the package.

The examples boot themselves — a new `TYPE` command

`TYPE` injects keystrokes into the console the way a key from the terminal or the VDM window does — type-ahead the guest reads when it next looks, with `\r`, `\n`, `\t`, `\\` and `\"` decoded. A machine file's `startup` runs *monitor* commands and so could never reach a program running inside the guest; a `TYPE` before the `RUN` that boots it leaves the command waiting at the first prompt. That is what now lets the four Sol-20 cassette games — `trek80`, `atc`, `pacman`, `raiders` — mount their tape, type their own `XE <name>` and come up on their own at the Sol's real 2.045 MHz, instead of dropping you at the SOLOS prompt to launch them by hand.

The bus says when a board isn't there — `SET BUS UNCLAIMED`

A guest that reached for a board that isn't in the backplane used to read `0xFF` forever and hang with nothing on the screen. `SET BUS UNCLAIMED WARN` now logs the reach — `warning: OUT 0FE <- 01 at PC=0113: no board decodes port 0xFE` — and runs on; `HALT` logs it and stops the guest at that instruction, so `SHOW REG` and `DUMP` see the machine exactly as it wedged. It is I/O only (a guest scans memory constantly), reported once per port and direction per `RUN`, and `Silent` by default so nothing that was quiet becomes noisy.

One command from clone to binary

`build.sh`, and its plain-PowerShell twin `build.bat`, takes a fresh clone to a built binary in one command — no flags to choose, no generator to pick — and if CMake is missing it prints how to get it for your platform rather than failing deep in a configure. SDL3 stays optional: a plain build needs nothing installed, and `--with-sdl` links a private static SDL3 so the binary carries its own. For a release, `tools/build-checksums.sh` writes `dist/SHA256SUMS`, refusing unless all four platform archives of a version are present — a partial checksum file is worse than none.

0.3.0

0.3.0 adds no machines and no boards. It changes one thing, and it is the thing the manual has described all along: the copy you download now opens the video window.

The window the manual documents is finally in the package

Every release through 0.2.0 shipped a **headless** binary. SDL3 was not compiled into it, so the VDM-1 and Sol-20 windows the boards and configuring chapters describe at length could not open from anything you were handed — the machines ran, and drew nothing. `SHOW VERSION` said so in a row nobody had reason to read:

```
altairsim> SHOW VERSION
altairsim  0.3.0
video      SDL3 -- windowed      <- 0.2.0 and before, the download read: none -- headless
commit     v0.3.0
tree       clean
```

0.3.0 is the first release whose downloaded package reads `SDL3 -- windowed`. Run `altairsim sol20`, and a window opens. That is the headline, and most of the rest of this entry is how it was made true on every platform at once.

Nothing to install, on any of the four

The packages are built on the hardware they target now, rather than assembled by CI, and SDL3 is **linked statically into the binary**. So there is no `SDL3.dll` to sit beside the `.exe`, no `.framework`, no `libSDL3.so.0`, and nothing to install before the program runs — the claim altairsim has always made for itself is now true of its video too. On Windows the C runtime is static as well, so a clean machine that has never had a compiler on it runs the `.exe` with no Microsoft redistributable to chase.

The one visible cost is a single extra file in the archive — `LICENSE-SDL3`, SDL3's zlib licence, because SDL3's code now travels inside the binary and its licence travels with it.

macOS ships as two builds, each tested on its own hardware

0.2.0 shipped one *universal* macOS archive. 0.3.0 ships two — `altairsim-0.3.0-macos-arm64` and `altairsim-0.3.0-macos-x86_64` — and the reason is honesty, not size. The universal binary's Intel half had been built and tested by nobody, because the machine that produced it was Apple Silicon; the previous two releases said so in their own notes. Each of the two archives is now built **and** run on the architecture it targets, so the Intel download is exercised on an Intel

Mac before it ships. Take the one that matches your Mac; `altairsim --version` and the download filename both name the architecture.

Windows, proven end to end

The Windows package is built with MSVC, links SDL3 and the C runtime statically, passes the full test suite on the machine that builds it, and opens a real VDM-1 window that a person has sat in front of. `dumpbin /dependents` on the shipped `.exe` shows system DLLs only — no `SDL3.dll`, no `VCRUNTIME140`. It is held to the same bar as the other three, and it is no longer an asterisk on the release.

The four downloads

Platform	File
macOS Apple Silicon	<code>altairsim-0.3.0-macos-arm64.tar.gz</code>
macOS Intel	<code>altairsim-0.3.0-macos-x86_64.tar.gz</code>
Linux x86_64	<code>altairsim-0.3.0-linux-x86_64.tar.gz</code>
Windows x86_64	<code>altairsim-0.3.0-windows-x86_64.zip</code>

Each holds the program, this changelog, the **User Manual**, `DRIVING-WITH-AI.md`, both licences, and `examples/` — four machines that boot, media included. Unzip it and run it; nothing needs fetching first.

What did not change

The simulator itself is byte-for-byte the machine 0.2.0 was — the same sixteen machines, the same boards, the same two CPU cores. The holes named in the manual's introduction are still holes: no snapshot, no replay, the six reserved monitor verbs still reserved, still no audio. Everything that moved is in the box the program arrives in.

0.2.0

The second release. It added machines and made the video window behave like a window — but note that the packages were still **headless** (see 0.3.0): everything below was true of a build made *with* SDL3, which is not what the archives carried until 0.3.0.

Three more monitors that boot from a bare command line

`amon`, `acuter` and `cdbl` became machines, so Martin Eberhard's Altair ROMs boot by name — nothing to fetch, nothing to mount:

```
altairsim amon      AMON 3.1 in a 4K EPROM at F000 -- a full-featured Altair monitor
altairsim acuter    ACUTER at F000 -- CUTER on a plain Altair, driving a terminal
altairsim cdbl      the default machine, with the Combo Disk Boot Loader in the socket
```

The ROM images shipped in 0.1.0 already; what was new is that each got a machine built around it — the whole distance between shipping an image and being able to run it. `hdbl` was deliberately left out: it boots an 88-HDSK hard disk, and there is no 88-HDSK board here. **Sixteen machines** became built in.

The video window behaves like a window

- **It does not steal the keyboard when it opens.** The terminal keeps the keys while you type at the monitor prompt; `SET DISPLAY focus=on` hands them to the guest, stopping it hands them back.
- **It is named after the machine**, so `sol20` and `vdm1` are two windows you can tell apart.
- **It is sized to fit the screen it opened on**, and **arrows and HOME reach the guest**.
- **Closing it stops the guest**, instead of leaving a machine running with nothing to draw on.

Two of those were bugs worth naming: typed input could lag a whole frame, and the VDM-1 could repaint hundreds of times per emulated millisecond. Both gone. The VDM-1's cursor now blinks on the board's own oscillator — wall-clock time, as the hardware did.

Disk BASIC, and smaller things

- `examples/diskbasic` boots **Altair Disk BASIC 4.1** off a floppy, media included — a fourth worked example alongside CP/M, cassette BASIC and the Sol-20.
- A binary now names the commit it was built from: `SHOW VERSION` and `--version` carry it, so a report against a nightly or a CI artifact can be traced to the code that produced it.
- `writeprotect` is accepted wherever `readonly` is, in machine files and at `SET`.
- The manual and the program say **board**, not card.

0.1.0

The first release — a simulator for the MITS Altair 8800 and the S-100 bus, in C++20, with **nothing to fetch**: the TOML parser, the JSON encoder and the line editor are all in-tree, so a

fresh clone builds with a C++20 compiler and CMake and no network.

Two validated CPU cores

Both cleared their gate before a single board was built on them, and for the release the exercisers were re-run on all three platforms — roughly 15 billion instructions each:

- **8080** — TST8080, 8080PRE, CPUTEST, 8080EXM
- **Z80** — ZEXDOC, ZEXALL

Fourteen boards, thirteen machines

88-2SIO · 88-SIO · 88-ACR · 88-DCDD · 88-MDS · 88-VI/RTC · 88-C700 · front panel · memory · 8080 CPU · Z80 CPU · VDM-1 · Processor Technology Sol-PC · Host Bridge (our own design).

CP/M 2.2 cold-boots from both 8-inch and 5.25-inch disks. MITS 4K and 8K BASIC and Programming System II load from cassette — including **real .WAV audio, played and recorded**, at measured CUTS/ACR parameters.

Debugging, and an assistant that can drive it

Breakpoints, watchpoints, tracepoints, conditional breaks (`BREAK ... IF`), execution history, and symbolic reference loaded from `.PRN` and `.SYM` files — DDT and SID run under it, self-modifying RST 7 breakpoints and all. An **MCP server** lets an AI assistant drive a running guest.