


## Chapter 4.4

# Customer Retrial Model with Finite Number of Sources

## Performance Evaluation of the Internet of Things (IoT)

Module Course: Performance Evaluation of Distributed Systems

Prof. Tobias Hoßfeld, Summer Semester 2022



# Disclaimer and Copyright Notice

Lecture slides, figures, and scripts are based on the open access text book "Performance Modeling and Analysis of Communication Networks". The book and scripts are licensed under the Creative Commons License Attribution-ShareAlike 4.0 International ([CC BY-SA 4.0](https://creativecommons.org/licenses/by-sa/4.0/)). If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

**The book must be cited and the disclaimer attached when using lectures slides or scripts.**

*Tran-Gia, P. & Hossfeld, T. (2021).  
Performance Modeling and Analysis of Communication  
Networks - A Lecture Note. Würzburg University Press.  
<https://doi.org/10.25972/WUP-978-3-95826-153-2>*

Website to download book, exercises, slides and scripts:  
<https://modeling.systems/>

# Chapter 4

## 4 Analysis of Markovian Systems

### 4.1 Loss System M/M/n

- 4.1.1 Model Structure and Parameters
- 4.1.2 State Process and State Probabilities
- 4.1.3 Other System Characteristics
- 4.1.4 Generalization to Loss System M/GI/n
- 4.1.5 Modeling Examples and Applications

### 4.2 Delay System M/M/n

- 4.2.1 Model Structure and Parameters
- 4.2.2 State Process and State Probabilities
- 4.2.3 Other System Characteristics
- 4.2.4 Delay Distribution
- 4.2.5 Example: Single Server Delay System

### 4.3 Loss System with Finite Number of Sources

- 4.3.1 Model Structure and Parameters
- 4.3.2 State Process and State Probabilities
- 4.3.3 Example: Mobile Cell with Finite Number of Sources

### 4.4 Customer Retrial Model with Finite Number of Sources

- 4.4.1 Model Structure and Parameters
- 4.4.2 Recursive Analysis Algorithm
- 4.4.3 Calculation of Traffic Flows
- 4.4.4 Example: Mobile Cell with Customer Retrials

### 4.5 Processor Sharing Model M/M/1-PS

# Model of Customer Behavior with Retrial


## ► Blocked customer

- will retry with probability  $\Theta$  : enter wait-for-retrial state
- will abandon with probability  $1 - \Theta$  : remain in idle state

idle time  $I$

$$I(t) = P(I \leq t) = 1 - e^{-\alpha t},$$

$$E[I] = \frac{1}{\alpha}.$$



call duration  $B$   
(service time)

$$B(t) = P(B \leq t) = 1 - e^{-\mu t},$$


$$E[B] = \frac{1}{\mu}.$$

time in wait-for-retrial state  $R$

$$R(t) = P(R \leq t) = 1 - e^{-\alpha_0 t},$$

$$E[R] = \frac{1}{\alpha_0}.$$

# Retrial Model



# Model Parameters

$\alpha$	call rate of a customer in the idle state
$m$	number of sources,
$\mu$	service rate of a server in the server stage
$n$	number of servers
$\alpha_0$	retrial rate of a customer in the wait-for-retrial state
$\Theta$	retrial probability of customers
$X$	r.v. for the number of occupied servers
$Z$	r.v. for the number of customers waiting for retrial
$x(i, j)$	$P(X = i, Z = j) = x(i, j), \quad i = 0, 1, \dots, n, \quad j = 0, 1, \dots, m - n$ probability that $i$ customers are in server stage and $j$ customers are in the wait-for-retrial stage.




# State Transition Diagram

# State Transition Diagram (f.)




# State Transition Diagram

- Can be solved numerically
- See notebook script at <https://modeling.systems/>




# Traffic Flows



- $F$  fresh call, first attempt
- $R$  retrial, repeated call
- $S$  successful call, completed call
- $U$  unsuccessful call or blocked call which will be repeated
- $B$  unsuccessful call or blocked call which is abandoned

# Traffic Flows of Fresh Calls



$$\lambda_{FS} = \alpha \sum_{i=0}^{n-1} \sum_{j=0}^{m-n} (m-i-j) \cdot x(i, j),$$

$$\lambda_{FU} = \theta \cdot \alpha \sum_{j=0}^{(m-n)-1} (m-n-j) \cdot x(n, j),$$


$$\lambda_{FB} = (1-\theta) \cdot \alpha \sum_{j=0}^{(m-n)-1} (m-n-j) \cdot x(n, j).$$

$$\lambda_F = \lambda_{FS} + \lambda_{FU} + \lambda_{FB},$$

blocking probability for fresh calls

$$p_{B_F} = \frac{\lambda_{FU} + \lambda_{FB}}{\lambda_F}.$$

# Mean Number of Attempts for Successful Calls




$$\left. \begin{aligned} \lambda_{RS} &= \alpha_0 \cdot \sum_{i=0}^{n-1} \sum_{j=0}^{m-n} j \cdot x(i, j), \\ \lambda_{RU} &= \theta \cdot \alpha_0 \sum_{j=0}^{m-n} j \cdot x(n, j), \\ \lambda_{RB} &= (1 - \theta) \cdot \alpha_0 \sum_{j=0}^{m-n} j \cdot x(n, j). \end{aligned} \right\}$$

$$\lambda_R = \lambda_{RS} + \lambda_{RU} + \lambda_{RB}.$$

Mean number of attempts for successful calls

$$\begin{aligned} \eta_F &= \frac{\lambda_{FU} + \lambda_{FS} + \lambda_{RU} + \lambda_{RS}}{\lambda_{FS} + \lambda_{RS}} \\ &= \frac{\lambda_F + \lambda_R - \lambda_B}{\lambda_F - \lambda_B} = 1 + \frac{\lambda_R}{\lambda_F - \lambda_B} \end{aligned}$$

# Results: Retrial Model



# Results: Retrial Model

