

Exam

Answer Set Solving in Practice

Torsten Schaub, Javier Romero
University of Potsdam — Winter Semester 2021/2022
Date: 18.2.2022

You have 120 minutes to do the exam, plus 15 additional minutes to upload the generated PDF file in Moodle.

To pass the exam you must obtain at least out of 91 possible points.

All **non electronic** support material can be used.

Name:

Matriculation Number:

Points:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	Total:
---------	-----	-----	-----	-----	-----	-----	-----	-----	-----	--------

Exercise 1 (5 Points)

Find the stable models of the following logic program P :

$$P = \left\{ \begin{array}{l} a \leftarrow c, \neg b \\ b \leftarrow \neg a, \neg d \\ b \leftarrow \neg a, \neg c \\ b \leftarrow c, d \\ c \leftarrow \neg b \\ d \leftarrow b, \neg c \end{array} \right\}$$

Exercise 2 (5 Points)

Find the stable models of the following logic program with variables P :

$$P = \left\{ \begin{array}{l} p(a, b, c) \leftarrow \\ q(X) \leftarrow p(X, Y, Z), \neg q(Z) \\ q(Y) \leftarrow p(X, Y, Z), \neg q(X) \\ q(c) \leftarrow q(X), \neg q(a) \end{array} \right\}$$

Exercise 3 (8 Points)

Consider the following logic program P :

$$P = \left\{ \begin{array}{l} \{a\} \leftarrow \\ b \leftarrow \neg a \\ c \leftarrow 1\{a, b\}1 \\ \leftarrow \neg c \end{array} \right\}$$

- 3-a)** Compile P into a normal logic program P' using the translations from the lecture slides. In particular, use the $x(i, j)$ construction to translate the cardinality rule of the program.
- 3-b)** Determine the stable models of P and the corresponding stable models of P' .

Exercise 4 (5 + 10 = 15 Points)

For the following logic program P and set of facts I :

- Find the dependency graph G_P , the positive dependency graph G_P^+ , and one topological order L_P . Moreover, given L_P , determine the set of atoms R_r for every rule $r \in P$.
- Find the ground instantiation of P and I . Start by initializing the sets of true atoms F and possible atoms D to I . Then, ground successively the components of L_P applying on-the-fly simplifications. For this, use the sets F , D and R_r , and update F and D after grounding each component.

$$P = \left\{ \begin{array}{l} \text{choose}(C) \leftarrow \text{course}(C), \neg \text{nchoose}(C) \\ \text{nchoose}(C) \leftarrow \text{course}(C), \neg \text{choose}(C) \\ \text{many}(D) \leftarrow \text{choose}(C1), \text{day}(C1, D), \text{choose}(C2), \text{day}(C2, D), C1 \neq C2 \\ \quad \leftarrow \text{next}(D1, D2), \text{many}(D1), \text{many}(D2) \end{array} \right\}$$

$$I = \left\{ \begin{array}{ll} \text{course}(1..3) \leftarrow & \\ \text{day}(1, \text{mon}) \leftarrow & \text{day}(1, \text{tue}) \leftarrow \\ \text{day}(2, \text{tue}) \leftarrow & \text{day}(2, \text{wed}) \leftarrow \\ \text{day}(3, \text{wed}) \leftarrow & \\ \text{next}(\text{mon}, \text{tue}) \leftarrow & \text{next}(\text{tue}, \text{wed}) \leftarrow \\ \text{choose}(1..2) \leftarrow & \end{array} \right\}$$

Exercise 5 (15 Points)

Determine the stable models of the following normal logic program P using the simplistic solving algorithm of the lecture, and specify the sets L and U that are generated at each iteration inside the $expand_P$ procedure.

$$P = \left\{ \begin{array}{l} a \leftarrow \neg f \\ b \leftarrow \neg g \\ c \leftarrow \neg b, \neg d \\ c \leftarrow \neg c, \neg e \\ d \leftarrow b, \neg e \\ e \leftarrow f \\ f \leftarrow e \\ g \leftarrow a, \neg b \end{array} \right\}$$

Exercise 6 (5 + 3 = 8 Points)

Let P be the following normal logic program:

$$P = \left\{ \begin{array}{lll} a \leftarrow g, \neg b & b \leftarrow a, d & b \leftarrow c, \neg e \\ c \leftarrow d, \neg g & e \leftarrow \neg a, \neg b & e \leftarrow \neg c \\ d \leftarrow \neg f & g \leftarrow e, \neg d & g \leftarrow a, \neg f \end{array} \right\}$$

6-a) Find the Fitting Semantics of P .

6-b) Find the well-founded Semantics of P .

Exercise 7 (5 Points)

Find all the unfounded sets of the following normal program P with respect to the partial interpretation $\langle \{c\}, \{d\} \rangle$.

$$P = \left\{ \begin{array}{l} a \leftarrow d \\ a \leftarrow \neg b, \neg c \\ b \leftarrow c, d \\ b \leftarrow \neg a \\ c \leftarrow b, \neg a \\ d \leftarrow a \end{array} \right\}$$

Exercise 8 (8 + 4 + 3 = 15 Points)

Let P be the following normal logic program:

$$P = \left\{ \begin{array}{lll} a \leftarrow \neg c & a \leftarrow d, \neg e & b \leftarrow a, \neg c \\ c \leftarrow f, \neg b & d \leftarrow a & d \leftarrow e, \neg f \\ e \leftarrow f, \neg c & f \leftarrow b, e & f \leftarrow \neg b \end{array} \right\}$$

- 8-a)** Find all models of $CF(P)$.
- 8-b)** Write the loop formulas in $LF(P)$.
- 8-c)** Find all the stable models of P .

Exercise 9 (10 + 5 = 15 Points)

Let P be the following logic program:

$$P = \left\{ \begin{array}{lll} a \leftarrow c, \neg e & a \leftarrow \neg f, \neg b & b \leftarrow \neg a \\ b \leftarrow d, \neg e & c \leftarrow d, \neg f & c \leftarrow e, \neg b \\ d \leftarrow b, \neg f & e \leftarrow b, \neg d & f \leftarrow e, \neg d \end{array} \right\}$$

The following table represents an assignment A with the decision level dl of every literal. Decision literals are placed under σ_d , and literals under $\bar{\sigma}$ are implied by a nogood $\delta \in \Delta_P \cup \Lambda_P$:

dl	σ_d	$\bar{\sigma}$	δ
1	T c		
2	F $\{e, \neg d\}$	F f	$\{\mathbf{T}f, \mathbf{F}\{e, \neg d\}\}$
3	T d		

9-a) Find a conflict nogood ε with $\text{NogoodPropagation}(P, \emptyset, A)$.

9-b) Derive a conflict nogood δ with the FirstUIP method starting from ε .