TECHNICAL HANDBOOK · HAND-OFF DOCUMENT

Security+ SY0-701 Lab Engine & AI Agent Governor

What was built, how every part works, and how to extend it.
Written for you, and for any AI you hand it to.

Repository	`delzarsolutionsllc/delzar-sovereign-wealth-machine`
Location in repo	`secplus_lab_engine/` (+ `.github/workflows/secplus-lab-engine.yml`)
Branch / Pull requests	`ccr-2689f707-karox1` · merged: PR #4 (labs 1–16), #5 (Lab 17 + web app), #6 (Anki export), #7 (CTFd export + video course) · this edition: Labs 18–24
Commits	`6081f9b` labs 1–5 · `bb6d70d` challenge mode, CI, labs 6–8 · `e404421` … `6e51caa` labs 9–16 (one commit each) · `ee18cc2` scenario generator + exam · merged as PR #4 (`021ec0e`) · then Lab 17 (`5392ffd`) and the course web app (`2bc7104`)
Size	~14,000 lines of Python + a course web app · 24 labs covering all 28 SY0-701 objectives · 24 sample scenario files · 1 policy file (21 sections) · 628 sample challenge questions (5,300+ in the hosted bundle) · 121-video course index
Quality status	860 pytest tests passing · GitHub Actions green on Python 3.10, 3.11, 3.12, 3.13
Runtime requirements	Python 3.10+ standard library only. `rich` optional (colour); `pytest` for tests. Fully offline.
Document date	2026-11-05

Contents

1. How to use this document
2. Purpose & learning philosophy
3. Architecture & repository map
4. Command-line reference
5. Lab 1 — Joiner/Mover/Leaver & Access Governance
6. Lab 2 — Zero Trust (PE / PA / PEP)
7. Lab 3 — Log Forensics & Hash Verification
8. Lab 4 — Change Control & Impact Analysis
9. Lab 5 — AI Agent Guardrail Governor
10. Lab 6 — Risk Management & BIA
11. Lab 7 — Incident Response & Chain of Custody
12. Lab 8 — End-to-End SOC Pipeline
13. Lab 9 — Vulnerability Triage
14. Lab 10 — Email Security Analyzer
15. Lab 11 — Firewall & Segmentation Auditor
16. Lab 12 — Secure Baseline Checker
17. Lab 13 — Threat Actor Classifier
18. Lab 14 — Resilience & Recovery Planner
19. Lab 15 — Vendor Risk Assessor
20. Lab 16 — Security Control Classifier
21. Lab 17 — PKI & Certificate Validator
22. Labs 18–24 — Completing the objective map
23. Course web app & desktop launcher
24. Random scenarios & practice exam
25. Challenge mode & progress tracking
26. Shared utilities
27. Policy configuration reference
28. Testing & CI
29. Design decisions & known limitations
30. How to extend (recipes + lab skeleton)
31. Roadmap: what to build next
32. Ready-to-paste prompt for another AI
33. Glossary

1. How to use this document

This handbook describes everything built so far: the purpose, the architecture, each lab's engine and decision rules, data formats, configuration, tests, and how to add more. Every function signature, file name and sample result was taken from the code as it stands, not written from memory.

> **If you are an AI reading this**
> The project is a modular Python CLI. Every lab follows the same **module contract** (Section 3.3). To extend it, follow that contract, keep to the standard library, load all policy from `config/default_policies.json` and scenarios from `data/*.json`, add pytest tests, and register the lab in `labs/__init__.py`. Section 30 has recipes and a full lab skeleton. Section 32 is a ready-made prompt.

> **If you are the learner**
> Easiest start: open the course web app (Section 23). Otherwise read Sections 2–4 first, then one lab section at a time. Run that lab (`python main.py lab N`), then quiz yourself (`python main.py challenge N`) before reading its "Decision logic" table.

2. Purpose & learning philosophy

Goal: master the *manual* security operations behind CompTIA Security+ SY0-701 before designing *automated AI agents* that perform them. Each lab simulates one operational domain realistically enough to show:

1. **How the control works**: the actual decision logic, not just definitions.
2. **Where manual processes fail**: privilege creep, untested rollback plans, evidence destroyed by pulling the plug.
3. **How an AI agent should be governed** in that same domain: least privilege, human-in-the-loop, audit trails.

Every lab ends with an **"Exam & Architectural Insight" panel** with five parts: the SY0-701 objective, key concepts, manual failure modes, AI-governance guidance and exam tips.

The arc of the project: Labs 1–4, 6–7 and 9–24 teach individual controls. Lab 5 shows how to put guardrails on automation. Lab 8 wires them all together into the architecture the learner is building toward: *detect → AI agent proposes → governor decides → human approves → the owning control executes*.

SY0-701 coverage

Every one of the 28 objectives has at least one lab and the matching videos (Section 23).

Domain	Objectives covered	Labs
1 General Security Concepts	1.1 Control categories & types · 1.2 Zero Trust · 1.3 Change management · 1.4 Cryptography & PKI	2, 3, 4, 8, 16, 17
2 Threats, Vulnerabilities & Mitigations	2.1 Threat actors · 2.2 Threat vectors · 2.3 Vulnerability types · 2.4 Indicators of malicious activity · 2.5 Mitigations	1, 3, 9, 10, 13, 24
3 Security Architecture	3.1 Architecture models & IaC · 3.2 Secure infrastructure · 3.3 Data protection · 3.4 Resilience & recovery	11, 14, 18, 20
4 Security Operations	4.1 Baselines & hardening · 4.2 Asset management · 4.3 Vulnerability management · 4.4 Alerting & monitoring · 4.5 Enterprise capabilities · 4.6 IAM · 4.7 Automation · 4.8 Incident response · 4.9 Data sources	1, 2, 3, 5, 7, 8, 9, 10, 11, 12, 19, 21
5 Security Program Management	5.1 Governance · 5.2 Risk management · 5.3 Third-party risk · 5.4 Compliance & privacy · 5.5 Audits & assessments · 5.6 Security awareness	1, 4, 5, 6, 15, 22, 23, 24

3. Architecture & repository map

3.1 Directory tree

```
secplus_lab_engine/
├── main.py                      CLI entrypoint: argparse subcommands + interactive menu
├── requirements.txt             rich (optional), pytest
├── README.md                    user-facing docs
├── .gitignore                   __pycache__, .pytest_cache, .venv, progress.json
├── config/
│   └── default_policies.json    ALL policy: RBAC/SoD, Zero Trust weights, threat intel,
│                                CMDB + maintenance windows, AI agent guardrails
├── data/                        scenario inputs (one per lab; editable)
│   ├── sample_identities.json      Lab 1  HR feed events + access checks
│   ├── sample_access_requests.json Lab 2  access requests, step-up outcomes, PEP attacks
│   ├── sample_logs.json            Lab 3  raw multi-source log stream + offline GeoIP
│   ├── sample_rfcs.json            Lab 4  six Requests for Change
│   ├── sample_agent_actions.json   Lab 5  20 agent proposals + human reviews
│   ├── sample_risks.json           Lab 6  five risk scenarios + BIA targets
│   ├── sample_incident.json        Lab 7  incident, action catalog, rookie/expert playbooks
│   ├── sample_pipeline.json        Lab 8  directory, live sessions, simulated human decisions
│   ├── sample_vulns.json           Lab 9  scan findings + exceptions
│   ├── sample_emails.json          Lab 10 raw messages + offline DNS (SPF/DMARC/DKIM keys)
│   ├── sample_firewall.json        Lab 11 current vs remediated rule sets
│   ├── sample_hosts.json           Lab 12 host config snapshots + previous scan
│   ├── sample_threat_scenarios.json Lab 13 incident scenarios with indicators
│   ├── sample_resilience.json      Lab 14 systems: targets vs current design
│   ├── sample_vendors.json         Lab 15 questionnaires + contracts
│   ├── sample_controls.json        Lab 16 control descriptions + answer key
│   └── sample_certificates.json    Lab 17 TLS chains + CRL/OCSP data
├── labs/
│   ├── __init__.py              LABS registry: {number: (module, default data file)}
│   ├── lab1_jml_governance.py … lab17_pki_validator.py
├── utils/
│   ├── crypto_helpers.py        SHA-256, salt, PBKDF2, HMAC, canonical JSON, hash chains
│   ├── terminal_ui.py           UI class: rich or plain-text tables/panels/status lines
│   ├── loader.py                load_policies(), load_data(), load_json()
│   ├── challenge.py             Question, run_challenge(), Progress,
pick_distractors()/choices_with()
│   ├── scenario_generator.py    seeded random scenarios for labs 2, 6, 9, 11–15, 17
│   ├── exam.py                  domain-weighted timed practice exam
│   ├── webserver.py             local web server for the course app (127.0.0.1 only)
│   └── desktop.py               desktop shortcut installer (Windows / macOS / Linux)
├── webapi.py                    JSON API shared by the local server and the bundle builder
├── web/
│   ├── index.html               the course web app (works live or hosted)
│   └── course_data.json         pre-built course for the hosted version
├── tools/build_web_bundle.py    rebuilds web/course_data.json
├── launch/                      double-click launchers (Windows .bat, macOS .command, Linux .sh)
└── tests/
    ├── conftest.py              fixtures: policies, quiet_ui, data loader
    ├── test_labs.py             labs 1–5, crypto, demos, CLI
    ├── test_extensions.py       challenge mode, step-up, labs 6–8, CLI challenge/progress
    ├── test_lab9_vuln.py … test_lab16_controls.py   one file per new lab
    └── test_generator_exam.py   generator determinism/validity, exam allocation/timer/CLI
.github/workflows/secplus-lab-engine.yml   CI: pytest + smoke tests, Python 3.10–3.13
```

3.2 Design principles

- **Offline and standard-library only.** No network, no API keys. `rich` is optional; `UI(plain=True)` renders ASCII.
- **Policy as data.** Thresholds, roles, weights, inventories and guardrails live in `config/default_policies.json`; scenarios live in `data/`. Logic lives in Python. Changing JSON changes outcomes, and challenge answers follow automatically.
- **Pure engines, thin demos.** Each lab has testable engine classes and functions (no printing) plus a `run_demo()` that renders through the UI facade.
- **Deny by default, explain everything.** Every decision returns its reasons (strings), which feed the tables, challenge explanations and tests.
- **Tamper evidence.** Audit trails (log manifests, governor ledger, custody ledger) use salted SHA-256 hash chains and HMAC.
- **Deterministic.** Injectable clocks and seeds make results reproducible for tests and quizzes.

3.3 The lab module contract

Every `labs/labN_*.py` module exposes exactly these names, which `main.py` and the tests rely on:

Name	Type	Purpose
`TITLE`	str	Display title, e.g. "Lab 6 — Risk Management Calculator & BIA"
`OBJECTIVES`	str	SY0-701 objectives shown under the title
`INSIGHT`	dict	Keys: `objective` (str), `concepts`, `failure_modes`, `ai_governance`, `exam_tips` (lists of str)
`run_demo(ui, policies, data)`	→ dict	Runs the sample scenario, renders it, ends with `ui.insight(INSIGHT)`, returns a summary dict (used by tests)
`build_challenges(policies, data)`	→ list[Question]	Generates quiz questions *by running the engine* on the scenario

Registration in `labs/__init__.py`: `LABS = {N: (module, "sample_file.json"), …}`. The CLI, menu, "all", challenge mode and the parametrised tests pick up new labs automatically.

3.4 Runtime data flow

```
main.py ──load_policies()──► config/default_policies.json
   │      load_data(file) ──► data/sample_*.json   (or --file custom.json)
   ├─ lab N            → module.run_demo(ui, policies, data) → tables/panels → Insight panel → summary
   ├─ challenge N      → module.build_challenges(policies, data) → run_challenge() → progress.json
   └─ progress         → Progress().rows()  (weakest objective first)
```

4. Command-line reference

Run from inside `secplus_lab_engine/` (or call `main.py` by path; it fixes `sys.path` itself).

Command	What it does
`python main.py` / `menu`	Interactive menu: `1-17` run a lab · `C3` challenge lab 3 · `R9` challenge on a random scenario · `E` practice exam · `P` progress · `W` web app · `A` all · `T` tests · `Q` quit
`python main.py list`	Table of labs, objectives and default data files
`python main.py lab N [--file X.json]`	Run lab N's scenario (optionally your own data file)
`python main.py lab N --challenge`	Quiz mode for lab N
`python main.py challenge N|all [--seed S] [--file X.json]`	Quiz mode; `--seed` fixes question order
`python main.py progress`	Scores per objective (weakest first) + last 5 sessions
`python main.py all`	Run all seventeen labs back-to-back
`python main.py web [--port 8765] [--no-browser]`	Open the course web app in your browser (live engine, offline)
`python main.py install-shortcut [--desktop DIR]`	Put a double-click launcher on your desktop
`python main.py lab N --random [--seed S]`	Run a lab on a generated scenario (labs 2, 6, 9, 11–15, 17)
`python main.py challenge N|all --random [--seed S]`	Quiz on generated scenarios so answers can't be memorised
`python main.py exam [--count 90] [--minutes 90] [--seed S] [--fixed]`	Timed, domain-weighted practice exam
`python main.py test [pytest args]`	Run the pytest suite
Global flags	`--plain` (no colour) · `--policies FILE` (alternate policy JSON) · `-v` (debug logging)

5. Lab 1 — Joiner/Mover/Leaver & Access Governance

4.6 IAM | 5.1 SoD | 2.4 privilege creep File: `labs/lab1_jml_governance.py` · Data: `sample_identities.json`

WHAT IT SIMULATES

A miniature Identity Governance & Administration (IGA) platform driven by an HR feed. Joiners get birthright access from their role. Movers should lose their old role's permissions; leaving them in place shows privilege creep. Leavers are disabled, fully revoked and get a deprovisioning ticket. Every access request passes a status gate, then RBAC, then ABAC.

ENGINE API

```
class IdentityGovernance(policy: dict, clock=None)
  joiner(record) -> Identity                # validates fields, role and clearance; provisions
role perms
  mover(user_id, new_role, new_department=None, revoke_previous=True) -> dict
                                            # revoke_previous=False simulates creep: old role
becomes an extra role
  grant_extra_role(user_id, role)           # ad-hoc "temporary" grant (creep source)
  leaver(user_id, reason) -> DeprovisionTicket
  suspend(user_id, reason)                  # IR use: disable but KEEP entitlements (used by Lab
8)
  check_rbac(user_id, permission) -> bool
  check_abac(user_id, resource, hour) -> (bool, reasons)
  evaluate_access(user_id, action, resource, hour=12) -> AccessDecision   # gate: STATUS | RBAC |
ABAC | ALLOW
  detect_sod(user_id=None) -> list[SoDConflict]
  access_review() -> list[dict]             # orphaned access, privilege creep
Dataclasses: Identity, AccessDecision, SoDConflict, DeprovisionTicket
```

DECISION LOGIC

Rule	Behaviour
Status gate	Only `allowed_employment_status` (default `active`) may access anything
RBAC	Permission must be in the union of the user's role permissions
ABAC: clearance	clearance level ≥ resource classification level (public 0 → secret 3)
ABAC: department	For `confidential` / `secret` data, user department must equal the data owner's
ABAC: time	`secret` data only inside business hours (07–19)
SoD	Flags a user holding both permissions of any `sod_conflicts` pair (e.g. `po:create` + `po:approve`)
Leaver SLA	Reason containing "cause" → priority P1, due in 1 hour, "cut access BEFORE notification"; otherwise P3, due in `leaver_sla_hours` (24)

DATA FORMAT (`SAMPLE_IDENTITIES.JSON`)

```
{ "events": [
    {"type":"joiner","identity":{"user_id","name","department","role","clearance","manager"}},
    {"type":"mover","user_id","new_role","new_department","revoke_previous":false,"note"},
    {"type":"grant","user_id","extra_role","note"},
    {"type":"leaver","user_id","reason","last_day"} ],
  "access_checks": [ {"user_id","action","resource":{"name","classification","department"},"hour"}
] }
```

SAMPLE OUTCOME

5 identities · **4 SoD conflicts** (SOD-01 PO create+approve, SOD-02 ghost vendor, SOD-03 code→prod, SOD-04 admin audits self) · 2 deprovisioning tickets (one P1) · 3 of 5 access checks denied · 3 privilege-creep review findings. Challenge mode: 12 questions (which SoD rule, ticket priority, ALLOW/DENY).

6. Lab 2 — Zero Trust Access Evaluator (PE / PA / PEP)

1.2 Zero Trust · 4.6 conditional access File: `labs/lab2_zero_trust_evaluator.py` · Data: `sample_access_requests.json`

WHAT IT SIMULATES

The NIST SP 800-207 model. In the **control plane**, the Policy Engine (PE) scores each request and the Policy Administrator (PA) issues or revokes short-lived signed tokens. In the **data plane**, the Policy Enforcement Point (PEP) checks every request before it reaches the resource.

ENGINE API

```
class PolicyEngine(policy).evaluate(req: AccessRequest) -> PolicyDecision(verdict, trust_score,
required_score, reasons)
class PolicyAdministrator(signing_key, ttl_seconds, clock)
  issue(req, decision, ttl=None) -> token | None      # only for ALLOW
  revoke(token) · revoke_subject(subject) -> count · verify(token) -> (ok, reason, claims)
  decode_unverified(token) -> claims                  # token = base64url(canonical JSON claims) +
"." + HMAC-SHA256
class PolicyEnforcementPoint(admin, resources).handle(token, resource, action="read") ->
EnforcementResult
class ZeroTrustGateway(policy, clock)                 # wires PE + PA + PEP
  request_access(req) -> (decision, token|None)
  complete_step_up(req, decision, mfa_passed) -> (final_decision, token|None)
Token claims: jti, sub, scope (one resource), act (one action), dev, iat, exp
```

TRUST ALGORITHM (SCORE STARTS AT 100)

Signal	Penalty	Signal	Penalty
IP reputation bad	−40 and **always DENY**	No MFA	−25
IP reputation suspicious	−15	User risk high (UEBA)	−30
Device health < 70	−30	Geo ≠ usual geo	−20
Device unmanaged	−20	Outside 07–19	−10

Checked first: an unknown resource → DENY; subject not entitled to the resource → DENY. Then: bad IP → DENY. If the resource requires MFA and none is presented → STEP_UP if score ≥ 50, else DENY. Score ≥ the resource's `min_score` → ALLOW; ≥ 50 → STEP_UP; otherwise DENY.

Step-up (adaptive identity): a failed MFA gives DENY and flags the subject as risky. A passed MFA re-evaluates with MFA present and adds 15. If that reaches the requirement, the result is ALLOW with a token TTL of 900/3 = **300 s**; otherwise DENY. MFA proves *who* is asking but cannot repair an unhealthy device.

PEP checks, in order: no token → malformed → HMAC signature → revoked → expired → scope ≠ resource → action mismatch.

SAMPLE OUTCOME

REQ-01 ALLOW · REQ-02 DENY (unmanaged BYOD, no MFA, 22:00) · REQ-03 STEP_UP then DENY (laptop health 65) · REQ-04 DENY (Alice's stolen creds from a Tor exit node) · REQ-05 STEP_UP then

ALLOW with a 300 s token · all **5 PEP attacks blocked** (expired, scope abuse, forged, revoked, no token). Challenge: 10 questions.

7. Lab 3 — Log Forensic Inspector & Hash Verifier

4.9 data sources · 2.4 indicators · 1.4 hashing File: `labs/lab3_log_inspector.py` · Data: `sample_logs.json`

PIPELINE

1. **Parse** raw lines `<ISO8601> <host> <source> key=value key="quoted value"` (shlex) into `LogEvent`. Sources: `FW`, `WinEvt`, `HTTP`, `EDR`. Malformed lines are counted as parse errors, not dropped silently.
2. **Enrich** with an offline GeoIP table (`geoip` in the data file).
3. **Detect** with correlation rules → `Finding(rule, severity, summary, evidence_lines, mitre)`, sorted CRITICAL → LOW.
4. **Extract IOCs** by regex: public vs RFC1918 IPs, SHA-256/SHA-1/MD5, user agents, domains.
5. **Verify integrity**: a salted SHA-256 hash chain over the lines plus an HMAC-signed manifest.

DETECTION RULES

Function	Rule	Logic	MITRE
`detect_brute_force`	BRUTE_FORCE(_SUCCESS)	≥5 × Event 4625 for one user+IP within 10 min; CRITICAL if a later 4624 comes from the same user+IP	T1110.001
`detect_password_spray`	PASSWORD_SPRAY	one IP with 4625s against ≥4 distinct accounts	T1110.003
`detect_impossible_travel`	IMPOSSIBLE_TRAVEL	consecutive 4624s for one user: distance >500 km and speed >900 km/h (haversine)	T1078
`detect_port_scan`	PORT_SCAN	one source → ≥10 distinct destination ports on FW	T1046
`detect_threat_intel`	TI_MATCH_IP / _USER_AGENT / _FILE_HASH	matches the bad IPs, UA patterns (sqlmap, nikto…) and hashes in config	—
`detect_sqli`	SQL_INJECTION	regex on HTTP `path` (`' OR 1=1`, `UNION SELECT`, …)	T1190
`detect_log_clearing`	AUDIT_LOG_CLEARED	Event ID 1102 / 104	T1070.001
`detect_time_gaps`	LOGGING_GAP	>30 min of silence on hosts in `continuous_log_hosts` (DC01, FW01)	T1562.002

To add a rule, write `detect_x(events, cfg) -> list[Finding]` and append it to `ALL_RULES`.

INTEGRITY MODEL

```
link[i]  = SHA256( salt || link[i-1] || canonical_json(line[i]) ),  link[-1] = "0"*64
manifest = {count, chain, head, signature = HMAC(manifest_hmac_key,
canonical_json({count,chain,head}))}
verify_manifest() -> VALID | TAMPERED (edit / delete / insert, with first broken index) |
MANIFEST_FORGED
```

SAMPLE OUTCOME

38 events, 1 malformed line, **14 findings (3 CRITICAL)**: jdoe brute-force success, EICAR malware hash, Security log cleared, password spray, Tulsa→Moscow impossible travel, port scan, SQLi and sqlmap/Nikto, TI IP matches, and a 50-minute DC01 logging gap. The integrity tests detect a deleted line, an edited IP, an injected line and a forged manifest. Challenge: 12 questions (identify the activity from raw lines; distractors exclude any rule that also fired on those same lines).

8. Lab 4 — Change Control & Impact Analyzer (CAB)

1.3 change management · 5.1 governance File: `labs/lab4_change_management.py` · Data: `sample_rfcs.json`

ENGINE API

```
class ChangeAdvisoryBoard(policy)
  dependents_of(system) -> set     # transitive "who depends on me" (blast radius)
  neighbours(system) -> set        # direct deps + direct dependents
  generate_backout_plan(rfc) -> list[str]   # reverse-order undo runbook via UNDO_MAP
  review(rfc, rehearse=True) -> ReviewResult(decision, risk_score, strategy, blockers, conditions,
                                             observations, blast_radius, generated_backout,
rehearsal)
rehearse_change(rfc, systems, fail_at_step=None) -> {failed_at_step, executed, restored, diffs}
```

REVIEW CHECKS

Check	Blocker (→ REJECT)	Condition
Schedule	outside Sat/Sun 00:00–06:00 (non-emergency); blackout date; end ≤ start	emergency outside window → ECAB + post-implementation review
Approvals	requester approved own change (SoD); fewer than 2 independent CAB approvals	system owner not among approvers
Testing	no staging test (non-emergency)	untested emergency
Impact	step effect `disable:X` breaks a neighbour tagged `requires:X`; a deny-list rule cuts off dependents; target not in CMDB	compensating control declared; allow-list additions
Backout	missing plan (non-emergency); reversible step with no undo; irreversible step with no prior backup; irreversible with no fail-forward plan; change + backout time exceeds window	missing plan (emergency) → auto-generated; no verification steps; fail-forward readiness
Rehearsal	executing the RFC's own backout does not restore the simulated state	—

Decision: any blocker → **REJECT**; risk ≤ 3 with no conditions → **APPROVE**; otherwise **APPROVE_WITH_CONDITIONS**. Strategy: ROLLBACK, FAIL_FORWARD (irreversible step plus hotfix plan), or NONE.

RFC FORMAT

```
{id, title, requested_by, approvals[], target_systems[], window{start,end}, estimated_minutes,
 tested_in_staging, emergency, compensating_controls{system: text}?,
 change_steps[{step, action, target, patch?|rule?|setting?, effects?["disable:tls1.0"]}],
 firewall_changes{allow[], deny["port:1521"]},
 backout_plan{estimated_minutes, steps[{undo_of, action}], verification[]} | null,
 fail_forward_plan{hotfix_steps[], on_call}?}
actions: snapshot backup verify notify health_check | apply_patch config_change firewall_deny
firewall_allow
         stop_service start_service restart_service | irreversible: db_schema_migrate
firmware_flash data_purge
```

SAMPLE OUTCOME

RFC	Decision	Why
0420 web-frontend patch	APPROVE	in window, quorum, tested, backout rehearsal PASS
0412 OpenSSL + disable TLS 1.0	REJECT	breaks legacy `erp-legacy`, which requires TLS 1.0
0415 block port 1521	REJECT	6 blockers: Wednesday 14:00, self-approval, no quorum, untested, cuts off Oracle dependents
0423 payroll schema migration	APPROVE_WITH_CONDITIONS	irreversible → FAIL_FORWARD with on-call hotfix
0430 EMERGENCY xz patch	APPROVE_WITH_CONDITIONS	ECAB, untested, auto-generated backout
0431 disable SMBv1	REJECT	Black Friday blackout; backout rehearsal FAILS (restarts instead of restoring config)

9. Lab 5 — AI Agent Supervisor & Guardrail Governor

4.7 automation | 4.6 non-human PAM | 5.1 HITL File: `labs/lab5_ai_agent_governor.py` · Data: `sample_agent_actions.json`

MODEL

Agents never act on production directly. Every proposed `AgentAction(id, agent_id, action, target, parameters, justification, cab_ticket, confidence, t)` goes to the `AgentGovernor`, which returns **ALLOW**, **REQUIRE_HUMAN_APPROVAL** (HITL) or **BLOCK**. The strictest verdict among all violations wins.

```
class AgentGovernor(policy)
  evaluate(action) -> GovernorDecision(action_id, agent_id, verdict, violations[], final, reviewer)
  human_review(action_id, reviewer, approve, reason) -> GovernorDecision
       # only HITL items; reviewer must be in human_approvers; agents can't approve; BLOCK is never
overridable
  release_quarantine(agent_id, reviewer)
  ledger_chain(salt) / verify_ledger(chain, salt)      # hash-chained decision ledger
```

CHECKS (IN ORDER)

Code	Verdict	Trigger
AGENT_QUARANTINED / UNKNOWN_AGENT	BLOCK	kill switch engaged / unregistered identity ("shadow AI")
OUT_OF_SCOPE_ACTION	BLOCK	action not in the agent's `allowed_actions`
HALLUCINATED_ASSET / _PATCH / _TICKET	BLOCK	target not in `asset_inventory` (for apply_patch, restart_service, isolate_host, run_command); patch not in catalog; CAB ticket not approved
IMMUTABLE_RULE	BLOCK	firewall rule id in `immutable_firewall_rules` ([0])
OVERLY_PERMISSIVE_RULE	HITL	src any + port any
SELF_ESCALATION / PRIV_GRANT_NO_CAB	BLOCK	granting to an agent identity / privileged role without an approved CAB ticket
PROTECTED_CONTROL / AUDIT_TAMPERING	BLOCK	touching mfa, edr, audit_logging, siem_forwarder, backup_job / deleting or modifying logs
DANGEROUS_COMMAND	BLOCK	regexes: `rm -rf /`, `curl|sh`, `chmod 777`, disabling Defender, ...
PROMPT_INJECTION	BLOCK	"ignore previous instructions", "developer mode", ... in the justification
RATE_LIMIT	BLOCK	more than 5 actions per agent in 60 s
LOW_CONFIDENCE / CRITICAL_ASSET / HUMAN_REQUIRED_CLASS / NO_JUSTIFICATION	HITL	confidence < 0.80 / disruptive action on a tier-0 asset / action in `always_hitl_actions` (disable_account) / empty rationale

Quarantine: 3 BLOCKs puts the agent in quarantine (kill switch); only a human approver can release it.

SAMPLE OUTCOME

20 actions → 8 ALLOW · 2 HITL · **10 BLOCK**. patch-bot-01 is quarantined after an invented server and patch, a `curl | bash`, and a restart storm. Human review: A09 approved; A04 rejected; an override of rule 0 refused; an agent approving itself refused; an unauthorised user refused. Editing the ledger after the fact is detected. Challenge: 20 questions.

10. Lab 6 — Risk Management Calculator & BIA

5.2 risk management File: `labs/lab6_risk_management.py` · Data: `sample_risks.json`

FORMULAS & API

```
sle(AV, EF) = AV × EF          ale(SLE, ARO) = SLE × ARO        availability(MTBF, MTTR) = MTBF /
(MTBF + MTTR)
assess(risk, appetite_ale) -> RiskAssessment(sle, ale, likelihood, impact, options[], treatment,
rationale, residual_ale)
check_bia(entry) -> BIAResult(rpo_ok, rto_ok, availability, availability_ok, issues)
band(value, bands) -> 1..5     ARO_BANDS ≤0.05/0.2/1/5 ; SLE_BANDS ≤$10k/$100k/$500k/$2M
```

TREATMENT LOGIC

1. ALE ≤ risk appetite ($10,000) → **ACCEPT** (the risk owner signs).
2. Otherwise compute net annual benefit: MITIGATE = ALE − ALE_after − control cost; TRANSFER = ALE × coverage − premium; AVOID = ALE − cost of stopping (only if `activity_optional`).
3. Choose the best positive option. If none is positive → **EXCEPTION** (leadership sign-off with an expiry date).

SAMPLE OUTCOME (TOTAL ALE $631,000 → RESIDUAL $58,800)

Risk	ALE	Treatment
R-01 Customer DB breach (AV $2M, EF 40%, ARO 0.25)	$200,000	MITIGATE (WAF + encryption)
R-02 Laptop theft (AV $3k, EF 100%, ARO 12)	$36,000	MITIGATE (FDE + MDM)
R-03 Data-center flood (AV $5M, EF 60%, ARO 0.01)	$30,000	TRANSFER (insurance beats $400k relocation)
R-04 Microsite defacement	$5,000	ACCEPT (within appetite)
R-05 Legacy anonymous FTP	$360,000	AVOID (retire FTP → SFTP portal)

BIA: payroll-app **fails RPO** (24 h backups vs 4 h RPO); erp-legacy **fails RTO** (12 h restore vs 4 h). The demo also prints a 5×5 likelihood × impact heat map. Challenge: 14 questions (compute ALE, choose treatment, BIA verdict).

11. Lab 7 — Incident Response Runner & Chain of Custody

4.8 incident response 4.9 File: `labs/lab7_incident_response.py` · Data: `sample_incident.json`

MODEL

A playbook is an ordered list of action ids from a catalog. Each action has a `phase` (preparation, detection, analysis, containment, eradication, recovery, lessons_learned) and may have `evidence{source, host, volatility_rank 1–6, hashed}`, `destroys_up_to_rank`, `requires[]` and `anti_pattern`. `grade_playbook(name, playbook, catalog, incident_id)` returns `PlaybookGrade(score, grade, issues, custody, ledger, ledger_chain)`.

Issue code	Penalty	Trigger
EVIDENCE_DESTROYED	−20	power-off/reimage destroys uncollected evidence; or collecting evidence already destroyed
CHAIN_OF_CUSTODY	−15	evidence acquired without a hash
MISSING_PREREQ	−15	e.g. reimage before `image_disk` and `legal_hold`
NO_CONTAINMENT	−15	no containment step at all
ORDER_OF_VOLATILITY	−10	more volatile evidence collected after less volatile (RFC 3227)
PHASE_ORDER	−10	eradication/recovery before containment; recovery before eradication; containment after recovery; anything after lessons learned
NO_LESSONS_LEARNED / ANTI_PATTERN / UNKNOWN_ACTION	−10 / −10 / −5	missing review / flagged bad practice / not in catalog

Grade: A ≥ 90, B ≥ 80, C ≥ 70, D ≥ 60, otherwise F. Volatility ranks: 1 registers/cache, 2 RAM/process/network state, 3 swap/temp, 4 disk, 5 remote logs, 6 archives/backups.

SAMPLE OUTCOME

Rookie: 0/100 (F): pulled the plug, copied files to a personal USB unhashed, reimaged with no disk image or legal hold, tried to capture RAM after power-off, disabled the account after recovery, no lessons learned. **Expert: 100/100 (A)**: 5 evidence items hashed in volatility order and a 10-entry custody ledger; editing who collected EV-001 breaks the chain. Challenge: 16 questions (phase identification, what to collect first, grade the playbook).

12. Lab 8 — End-to-End SOC Pipeline

4.7 SOAR 4.8 1.3 4.6 1.2 File: `labs/lab8_soc_pipeline.py` · Data: `sample_pipeline.json` (+ `sample_logs.json`, `sample_incident.json`)

```
Lab 3 Detect ──▶ AI SOC agent proposes ──▶ Lab 5 Governor ──▶ human (HITL)
                                                  │
          disable_account              block_ip                    isolate_host
   Lab 1 suspend + Lab 2         Lab 4 emergency RFC → CAB    Lab 7 capture volatile evidence,
   PA.revoke_subject()           review + rehearsed backout   hash it, THEN isolate
```

API

```
soc_agent_propose(findings, events_by_line, agent_id) -> list[Proposal]   # deterministic stand-in
for an LLM
run_pipeline(policies, data, logs, incident) -> PipelineResult(rows, rfc_decision, suspended,
                                                               sessions_revoked, isolated,
custody_records)
```

Agent mapping: BRUTE_FORCE_SUCCESS → disable_account + block_ip · IMPOSSIBLE_TRAVEL → disable_account (confidence 0.71) · TI_MATCH_FILE_HASH → isolate_host · PASSWORD_SPRAY / SQL_INJECTION / PORT_SCAN → block_ip (deduplicated) · AUDIT_LOG_CLEARED → **overreach**: modify firewall rule 0. Proposals are spaced 15 s apart (the agent paces itself). All approved IP blocks are batched into one emergency RFC (`RFC-AUTO-0001`, requested by the agent, approved by the emergency CAB).

SAMPLE OUTCOME

Finding	Proposal	Governor	Human	Outcome
Brute-force success	disable jdoe	HITL	approve	suspended; 2 sessions revoked
Brute-force success	block 45.155.205.233	ALLOW	—	RFC → APPROVE_WITH_CONDITIONS, rehearsal PASS
Malware hash	isolate ws-0142	ALLOW	—	2 volatile evidence items hashed before isolation
Log cleared	modify rule 0	BLOCK	—	OUT_OF_SCOPE_ACTION; IMMUTABLE_RULE
Password spray / SQLi	block 2 IPs	ALLOW	—	same RFC
Impossible travel	disable asmith	HITL	reject	false positive (travel VPN) → tune the rule

Challenge: 8 questions ("where does this proposal end up?", "what must happen before isolation?").

13. Lab 9 — Vulnerability Triage & Remediation

4.3 vuln mgmt 2.3 vuln types File: `labs/lab9_vulnerability_triage.py` · Data: `sample_vulns.json` · Config: `vulnerability_management` (+ CMDB `criticality` / `exposure`)

ENGINE API

```
cvss_rating(cvss, bands) -> Critical | High | Medium | Low | None
priority_for(score, thresholds) -> P1..P4
combined_reduction(controls, table) -> (1 − Π(1 − rᵢ), unknown_controls)
review_exception(exc, score, as_of, cfg) -> ExceptionReview(status, residual_score, reasons)
triage(finding, cmdb, cfg, as_of) -> TriageResult(score, priority, sla_days, due, overdue, status,
reasons, actions, …)
triage_all(data, policies) -> list[TriageResult]   # sorted by score, highest first
```

DECISION LOGIC

Rule	Behaviour
Score	CVSS × criticality multiplier (tier 1–5: 0.6–1.5) × KEV 1.5 × exposure (internet 1.3, privileged 1.2, internal 1.0)
Priority / SLA	P1 ≥ 12 (7 days) · P2 ≥ 8 (30) · P3 ≥ 4 (90) · P4 (180); known-exploited (KEV) capped at 14 days
Unknown asset	Not in the CMDB → worst case (criticality 5, internet-facing) + "register the asset" action
Exception	ACCEPTED only if: authorised approver, not expired, ≤ 180 days, recognised compensating controls, residual ≤ 8; otherwise REJECTED (all reasons listed) or EXPIRED
Actions	Patch + RESCAN to validate; no patch → compensating controls now; overdue → escalate

SAMPLE OUTCOME

9 findings → 4 P1 (xz backdoor on auth-service, firewall zero-day, overdue PHP-CGI injection, unmanaged `ws-9999`), 3 P2, 2 P3. Exceptions: erp-legacy ACCEPTED (68% reduction, residual 3.11); auth-service REJECTED (unauthorised approver, residual 21.6); payroll EXPIRED. Challenge: 25 questions (priority, vulnerability type, exception verdict, CVSS band).

14. Lab 10 — Email Security Analyzer

4.5 email security · 2.2 message vectors File: `labs/lab10_email_security.py` · Data: `sample_emails.json` (raw messages + offline DNS) · Config: `email_security`

ENGINE API

```
spf_check(ip, domain, dns) -> pass | fail | softfail | neutral | none | permerror   # ip4: and include: (depth ≤ 5)
dkim_body_hash(body) -> base64 SHA-256 (simple canonicalisation)
dkim_check(msg, body, dns) -> (pass | fail | none, d=)                              # bh= match + published selector
lookalike_of(domain, protected, max_distance, owned) -> imitated domain | None      # Levenshtein, homoglyphs, brand-in-name
analyze(item, cfg, dns) -> EmailReport(spf, dkim, dmarc, dmarc_policy, score, verdict, category, indicators, …)
```

DECISION LOGIC

Step	Behaviour
Trust boundary	Connecting IP taken only from OUR MX's `Received` line; sender-supplied `Authentication-Results` never trusted (claimed pass vs our fail = +2 "forged header")
DMARC	pass if (SPF pass AND envelope domain aligned) OR (DKIM pass AND d= aligned) with the From organisational domain
Indicators	SPF fail/none, DKIM fail/none, no DMARC policy, lookalike From (+4), exec/brand display-name impersonation (+3), Reply-To mismatch (+2), pressure words (weighted), link text ≠ href (+3), raw-IP / shortener / punycode / suspicious TLD / lookalike links, dangerous or double-extension attachments (+4 each)
Verdict	DMARC fail + p=reject → REJECT; p=quarantine, dangerous attachment or score ≥ 7 → QUARANTINE; score ≥ 2 → DELIVER_WITH_BANNER; else DELIVER
Category	Malware delivery > Domain spoofing > Business email compromise > Credential phishing > Legitimate / Suspicious

SAMPLE OUTCOME

E-01 partner newsletter DELIVER · E-02 ESP-sent mail DELIVER (SPF not aligned, DKIM aligned → DMARC pass) · E-03 `micros0ft-support.com` passes SPF/DKIM/DMARC yet QUARANTINE (credential phishing) · E-04 CEO display name from Gmail QUARANTINE (BEC) · E-05 `invoice_Q4.pdf.exe` QUARANTINE (malware) · E-06 exact-domain spoof with a forged Authentication-Results header REJECT. Challenge: 18 questions.

15. Lab 11 — Firewall Rule & Network Segmentation Auditor

3.2 secure infrastructure | 4.5 firewall rules File: `labs/lab11_firewall_auditor.py` · Data: `sample_firewall.json` · Config: `firewall_audit`

ENGINE API

```
parse_ports("80,443" | "1000-2000" | "any") -> [(lo, hi)]
resolve(spec, zones) -> [(zone, network)]          # zone name | CIDR | any; CIDRs spanning zones
expand
rule_covers(a, b, zones) -> bool                     # proto ⊇, ports ⊇, src ⊇, dst ⊇
audit(ruleset, cfg) -> Audit(score, grade, findings[Finding(rule_id, code, penalty, detail, fix)])
```

FINDINGS (PENALTY)

Code	Trigger
ANY_ANY (25)	allow any → any on any port
SEGMENTATION_VIOLATION (15)	zone flow in `never_allowed` (internet→internal, guest→internal, DMZ→internal…) or not an approved flow/port
SHADOWED (12) / REDUNDANT (4)	an earlier rule fully covers this one with the opposite / same action
MISSING_DEFAULT_DENY (12)	no explicit final `deny any any any`
INSECURE_PROTOCOL (10)	cleartext ports anywhere (FTP, Telnet, TFTP, SNMPv1/2c); remote-admin ports (RDP, SMB, SSH, VNC) from untrusted zones
ANY_SERVICE (8) / OVERLY_BROAD (5)	all ports allowed / CIDR of /12 or larger
NO_LOGGING (3) / UNDOCUMENTED (2)	deny or default deny without logging / no comment

SAMPLE OUTCOME

"edge-fw (current)": 15 findings → **0/100 (F)** (Tor-block deny shadowed by an earlier allow, RDP from internet to internal, guest any-service, Telnet, /8 to databases, a "TEMP" any/any, no default deny). "edge-fw (remediated)": **100/100 (A)**. Challenge: 21 questions ("most severe problem of rule N", default deny present?).

16. Lab 12 — Secure Baseline & Hardening Checker

4.1 baselines & hardening File: `labs/lab12_baseline_checker.py` · Data: `sample_hosts.json` · Config: `hardening_baselines` (12 Windows + 10 Linux checks)

ENGINE API

```
evaluate_check(check, settings) -> (PASS | FAIL | MISSING, actual)   # ops: eq ge le between
includes excludes; fail closed
check_host(host, cfg, as_of) -> HostReport(compliance %, verdict, results, regressed, remediated)
check_all(data, policies) -> list[HostReport]
```

DECISION LOGIC

Rule	Behaviour
Status	PASS / FAIL / MISSING (setting not reported = non-compliant) / EXCEPTION (ticketed, unexpired deviation, excluded from score)
Compliance	severity-weighted (high 10, medium 5, low 2); COMPLIANT only if ≥ 90% AND no failed high-severity check
Drift	vs previous approved scan: REGRESSED (pass → fail), REMEDIATED (fail → pass)
Fail closed	unknown operator or wrong value type → FAIL

SAMPLE OUTCOME

DC01 NON_COMPLIANT 75.6% (Print Spooler re-enabled → drift; 12-char passwords) · WEB01 0% (firewall and EDR turned off since last scan) · lnx-app-01 COMPLIANT 100% (ticketed /tmp exception) · lnx-db-01 30.6% (root SSH, auditd gone, SELinux unreported, expired exception). Challenge: 15 questions.

17. Lab 13 — Threat Actor & Attack Vector Classifier

2.1 actors & motivations · 2.2 vectors · 2.5 mitigations File: `labs/lab13_threat_classifier.py` · Data: `sample_threat_scenarios.json` · Config: `threat_classification`

ENGINE API

```
score_actors(indicators, actors) -> {actor: score}
classify(scenario, cfg) -> Classification(actor, actor_reasons, motivation, motivation_reason,
vector, mitigation, addon, unknown_indicators)
```

DECISION LOGIC

Output	Rule
Actor	Sum of indicator weights per profile (nation-state, organized crime, hacktivist, insider, unskilled attacker, shadow IT); winner must lead by ≥ 2, else **Undetermined**
Motivation	First matching rule in an ordered list (war, espionage, *blackmail before financial gain*, political, revenge, ...)
Vector → mitigation	Initial-access indicator → 2.2 vector → 2.5 mitigation, plus an actor-specific add-on

SAMPLE OUTCOME

8 scenarios, all decisive: defense-contractor watering hole → nation-state/espionage; ransomware via phishing → organized crime/financial gain; defaced city site → hacktivist; admin wiping backups → insider/revenge; IP cameras with admin/admin → unskilled attacker; public file share → shadow IT; USB drop → organized crime; help-desk vishing + "pay or we publish" → organized crime/**blackmail**. Challenge: 32 questions.

18. Lab 14 — Resilience & Recovery Planner

3.4 resilience & recovery File: `labs/lab14_resilience_planner.py` · Data: `sample_resilience.json` · Config: `resilience` (site, replication, clustering, RAID catalogs)

ENGINE API

```
plan(system, cfg, as_of) -> Plan(host_rto, host_rpo, site_rto, site_rpo, restore_hours, verdict,
gaps, recommendations)
cheapest(options, ok) -> (name, option) | None      raid_for(required, raid) -> best-capacity RAID
level
```

DECISION LOGIC

Event / check	Computation
Restore time	data TB × 1.5 h/TB × multiplier (full 1.0, differential 1.5, incremental 2.5)
Host failure	RTO = cluster failover (active-active 0, active-passive 15 min) or 4 h rebuild + restore; RPO = replication lag or backup interval
Site loss	Needs an offsite copy AND a site (hot 1 h, warm 24 h, cold 168 h); RTO = site + restore unless data is replicated
RAID / power / testing	RAID tolerance ≥ required disks (RAID0 0, 1/5/10 one, 6 two); UPS + generator ≥ outage; restore and DR tests within 365 days
Fix	Cheapest catalog option that closes each gap

SAMPLE OUTCOME

web-frontend and file-server MEET_TARGETS. payroll-app: 24 h backups vs 4 h RPO, cold site 172.5 h vs 8 h → back up every 4 h, active-passive cluster, hot site. auth-service: RAID0 and 10 minutes of UPS → RAID5 + generator. erp-legacy: no offsite copy and no recovery site (∞), never tested. Challenge: 19 questions.

19. Lab 15 — Third-Party / Vendor Risk Assessor

5.3 third-party risk File: `labs/lab15_vendor_risk.py` · Data: `sample_vendors.json` · Config: `vendor_risk`

ENGINE API

```
questionnaire_score(answers, questionnaire) -> (0–100 %, gaps)     # yes 1, partial 0.5, no/unanswered 0
required_clauses(vendor, rules) -> [clauses]                        # by data class, access, relationship
assess(vendor, cfg) -> VendorAssessment(inherent, residual, decision, missing_clauses, reject_reasons, conditions, monitoring)
```

DECISION LOGIC

Rule	Behaviour
Inherent	data sensitivity (1–4) × access (1–4) × criticality (1–3); high ≥ 18, medium ≥ 8
Residual	inherent × (1 − 0.7 × questionnaire %); low ≤ 8, medium ≤ 16, high above
REJECT	sensitive data with neither right-to-audit nor an independent assessment · undisclosed conflict of interest · residual HIGH
CONDITIONS	missing required clause (an MOU never replaces a BPA), SLA uptime below need, breach notice > 72 h, residual MEDIUM
Monitoring	cadence by inherent band (quarterly / annual / every 2 years)

SAMPLE OUTCOME

CloudPayroll APPROVE (inherent 24 → residual 7.2) · HVAC contractor with network access APPROVE_WITH_CONDITIONS (needs a security requirements schedule; the Target-breach lesson) · analytics vendor REJECT (unverifiable) · co-marketing partner CONDITIONS (MOU instead of BPA) · MSP REJECT (undisclosed conflict of interest). Challenge: 19 questions, including agreement-type definitions.

20. Lab 16 — Security Control Classifier

1.1 control categories & types File: `labs/lab16_control_classifier.py` · Data: `sample_controls.json` · Config: `control_classification`

ENGINE API

```
pick(text, table) -> (label | Unclassified, evidence, scores)   # whole-word weighted phrases; unique winner required
classify(control, cfg) -> ControlResult(category, type, category_evidence, type_evidence, scores)
```

DECISION LOGIC

Category (technical / managerial / operational / physical) and type (preventive / detective / corrective / deterrent / compensating / directive) are scored independently. Compensating cues ("instead", "cannot be patched", "unavailable") outweigh the preventive wording they often contain. A tie or zero evidence → **Unclassified** for a human. The sample's `expected_*` fields are an answer key used only by the tests and the demo's agreement check.

SAMPLE OUTCOME

19/19 agree with the answer key, covering the full category × type matrix (e.g. splash screen = technical deterrent, managers reviewing login reports = managerial detective, generator = physical compensating, "Authorized personnel only" = physical directive) plus one vague control left Unclassified. Challenge: 36 questions.

21. Lab 17 — PKI & Certificate Validator

1.4 PKI & certificates File: `labs/lab17_pki_validator.py` · Data: `sample_certificates.json` · Config: `pki`

ENGINE API

```
hostname_matches(host, pattern) -> bool        # exact, or a wildcard covering exactly ONE leftmost label
validate(scenario, cfg, as_of) -> Validation(verdict, primary, issues[Issue(code, level, message)])
validate_all(data, policies) -> list[Validation]
Certificate record: subject, issuer, serial, not_before, not_after, key_type, key_bits, sig_alg, is_ca, san[], eku[], spki_sha256
```

CHECKS (SEVERITY)

Code	Level	Trigger
REVOKED (10)	error	OCSP says revoked, or the serial is on the issuer's CRL
PIN_MISMATCH (9)	error	the app pins SPKI hashes and no presented key matches (TLS interception)
SELF_SIGNED / UNTRUSTED_ROOT (8)	error	chain ends at a self-signed cert that is not in the trust store
INCOMPLETE_CHAIN / NOT_A_CA (7)	error	issuer ≠ next subject, missing intermediate, or a CA:FALSE cert signed another
EXPIRED / NOT_YET_VALID (6)	error	any cert outside notBefore..notAfter
HOSTNAME_MISMATCH (5)	error	host not covered by SAN (CN only if no SAN)
WEAK_SIGNATURE / WEAK_KEY (4) · WRONG_KEY_USAGE (3)	error	SHA-1/MD5, RSA < 2048 or EC < 256, EKU without serverAuth
REVOCATION_UNKNOWN (2)	warning*	no OCSP answer and no CRL (*error when `revocation_hard_fail`)
VALIDITY_TOO_LONG · EXPIRING_SOON (1)	warning	leaf valid > 398 days · expires within 30 days

Verdict: UNTRUSTED (any error) / TRUSTED_WITH_WARNINGS / TRUSTED. Trust anchors are not re-checked for key or signature strength.

SAMPLE OUTCOME

P-01 TRUSTED · P-02 EXPIRED · P-03 HOSTNAME_MISMATCH (`*.delzarsolutions.com` does not cover `dev.portal…`) · P-04 INCOMPLETE_CHAIN · P-05 SELF_SIGNED · P-06 REVOKED (CRL) · P-07 WEAK_KEY + WEAK_SIGNATURE · P-08 PIN_MISMATCH (TLS-inspection proxy chains to a trusted root, but the banking app pins its keys) · P-09 TRUSTED_WITH_WARNINGS (OCSP unknown, soft-fail; expires in 17 days) · P-10 NOT_A_CA. The generator applies 0–2 random faults to healthy chains. Challenge: 34 questions (verdict, most serious problem, wildcard matching, PKI terms).

22. Labs 18–24 — Completing the objective map

These seven labs cover the objectives that had videos but no lab (3.1, 3.3, 4.2, 4.4, 5.4, 5.5, 5.6), so every SY0-701 objective now has at least one lab. They follow the same contract: policy in `config/default_policies.json`, a sample file, deny-by-default engines with a reason for every decision, tests, a random generator and challenge questions.

Lab	Config / data	Engine & decisions	Sample outcome · questions
18 Data Protection & DLP Gate 3.3 4.5 · 5.4	`data_protection` `sample_data_flows.json`	Regex detectors (SSN, card numbers kept only if Luhn-valid, MRN, email, phone, passwords, API keys, trade-secret/IP/legal markings) raise the declared label to the effective classification. Each outbound flow → ALLOW / ALLOW_WITH_PROTECTION (mask, tokenize, encrypt, hash) / BLOCK on destination approval and type, region (geographic restriction), EU/UK data sovereignty, state of data and per-type protection rules. Unknown label → BLOCK.	8 flows: Luhn-invalid order number not flagged; PAN on a support console → mask; SSN to APAC → BLOCK; EU data to US SaaS → BLOCK; passwords with AES → BLOCK (hash instead); trade secret over plain SMTP → encrypt. 35 questions.
19 SIEM Correlation & Alert Tuning 4.4 4.9	`siem` `sample_security_events.json`	Normalises auth/firewall/EDR/DNS/app events (malformed events raise SIEM-000, never dropped). Rules: brute force (critical if followed by success), password spraying, impossible travel, after-hours privileged action, log-source silence (blind spot), threat-intel match, port scan, malware not blocked. Suppressions apply only with an owner, an entity match and an unexpired date; critical alerts are never suppressed. Response per rule; precision/recall before and after tuning.	12 alerts: scanner noise SUPPRESSED; expired pen-test suppression still alerts; owner-less suppression ignored; DNS silent for 9.5 h. Precision 83.3% → 90.9% after tuning; one low-and-slow false negative. 48 questions.

20 Cloud Architecture & IaC Gate 3.1 3.3 · 4.1 · 4.6	`iac` `sample_iac.json`	Policy-as-code checks over a Terraform-like plan: public buckets, 0.0.0.0/0 on admin ports, unencrypted storage/databases, logging off, IAM `*` on `*`, privileged/root containers, public databases, single-AZ critical resources, missing tags. Undeclared property = fail; unknown resource type = critical "unreviewed". Deployment BLOCK (any critical or >1 high) / WARN / PASS with a fix per finding. Plus a shared-responsibility matrix (IaaS/PaaS/SaaS) and architecture-model trade-offs.	11 resources, 3 clean → BLOCK (5 critical, 3 high). 39 questions incl. "who patches the guest OS on IaaS?".
21 Asset Inventory & Secure Disposal 4.2 3.3 · 4.5	`asset_mgmt` `sample_assets.json`	CMDB vs discovery scan by MAC: UNMANAGED (shadow IT), MISSING (>14 days unseen, or never seen), NO_OWNER, UNCLASSIFIED. Disposal requests follow NIST SP 800-88: minimum Clear/Purge/Destroy by classification and whether media leaves the organisation, methods valid per media (no degaussing SSDs), certificate of destruction for third-party purge/destroy, legal hold and retention block disposal; unknown media/method → REJECT.	3 unmanaged hosts, 1 missing, owner/label gaps; 3 disposals approved, 6 rejected (degauss SSD, overwrite too weak, no certificate, legal hold, retention, unknown method). 46 questions.
22 Compliance & Privacy Tracker 5.4 5.1	`compliance` `sample_privacy_cases.json`	Data subject requests, breach notifications, retention and attestations against configurable regimes (illustrative GDPR-style 30 days / 72 h and a fictional state law). COMPLIANT / AT_RISK (inside the warning margin) / NON_COMPLIANT / EXEMPT (documented legal hold), each with a consequence (fines, sanctions, reputational damage, loss of license, contractual impacts) and internal/external reporting. Deadlines are teaching values, not legal advice.	13 cases: processor failed to forward to the controller; breach notified 28 h late; over-retention and early destruction; expired external attestation. 44 questions incl. controller vs processor, due diligence vs due care.

23 Pen-Test RoE Gate & Audit Planner 5.5 4.3 · 5.3	`audit` `sample_engagement.json`	Each planned test action → ALLOW / NEEDS_APPROVAL / BLOCK against the signed rules of engagement: authorization (signed, valid dates, authorised signer, emergency contact), scope via `ipaddress` (out-of-scope checked first), prohibited and always-prohibited techniques, testing window, recon labels verified against the technique catalogue; passive recon may run outside the window (policy switch). Audit planner maps needs to internal audit, self-assessment, regulatory examination, independent third-party audit or attestation. The same gate is how a governed AI pen-test agent should be constrained.	10 actions: 2 ALLOW, 1 NEEDS_APPROVAL, 7 BLOCK; 5 assessment needs classified. 39 questions incl. known/partially known/unknown environment, passive vs active recon.
24 Security Awareness Analyzer 5.6 2.2	`awareness` `sample_awareness.json`	Phishing simulation per employee: COMPROMISED / CLICKED / REPORTED / PASSED / NO_DATA → NONE / MICRO / REMEDIAL training / ESCALATE_TO_MANAGER, stricter for finance, exec and admins; overdue or missing training counts. Department flags and program KPIs vs targets. Anomalous behaviour → risky / unintentional / unexpected with a response. Message checker scores lookalike domains, urgency, link-text mismatch, credential/payment requests and risky attachments.	12 employees in 4 departments, 3 departments flagged; 5 behaviours; 4 messages (2 phishing). 59 questions.

Teaching choices to know about (all configurable in policy): Lab 18 ranks the six SY0-701 classifications public < private < sensitive < confidential < restricted < critical (the exam does not rank them); Lab 21's minimum sanitization table is slightly stricter than NIST for low-impact media leaving the organisation; Lab 22's deadlines and consequence mapping are illustrations; Lab 23 maps offensive/defensive/integrated to red/blue/purple teams; Lab 24's micro/remedial training tiers are program practice, not exam terms.

23. The course web app & desktop launcher

One page, `web/index.html`, presents the whole engine as a course: a **course map** (domains → labs), and for each lab a **Lesson** (its docstring + Exam & Architectural Insight), **Run the scenario** (the engine's report, sample or random) and **Practice** (instant feedback, number keys to answer). It also has a timed, domain-weighted **Practice exam** and **My progress** (objectives, weakest first). The page runs two ways:

	On your computer	Hosted on claude.ai
Start	`python main.py web`, a desktop shortcut, or a file in `launch/`	Open the private artifact link (pin it in the claude.ai sidebar)
Engine	Live: the server calls `webapi.dispatch()`	Pre-built: `web/course_data.json` from `tools/build_web_bundle.py`
Random scenarios	Unlimited (any seed)	12 generated variants per generator lab
Progress	`progress.json` (shared with the CLI)	Private per-user document (`db` + `user` capabilities); falls back to browser storage
Needs	Python 3.10+, no internet	A browser; no Python

VIDEO COURSE

`data/video_course.json` indexes Professor Messer's free SY0-701 playlist (121 videos, about 15 hours: title, YouTube ID, length and objective only; nothing is copied). `utils/videos.py` maps each video to the labs that share its objective. The app has a **Video course** page in objective order with "Practise in Lab N" links, a **Watch first** list on every lesson, watched checkboxes saved with progress, and **Watch next** videos for weak objectives. CLI: `python main.py videos [--lab N | --objective X.Y | --open N | --mark ID]`. Anki cards and CTFd hints link the matching videos.

LOCAL SERVER SECURITY (`UTILS/WEBSERVER.PY`)

- Binds to `127.0.0.1` only; requests whose Host header is not localhost get 403 (defeats DNS rebinding).
- API calls must be `POST` with `Content-Type: application/json` (forces a CORS preflight for foreign pages) and no CORS headers are ever sent, so other websites can't drive it.
- Only `/` is served as a file; the API accepts a fixed method list and never takes file paths from the browser.

DESKTOP SHORTCUT (`UTILS/DESKTOP.PY`)

```
python main.py install-shortcut          # Windows: "Security+ Lab Engine.bat"   (py launcher, else
python)
                                         # macOS:   "Security+ Lab Engine.command" (opens Terminal)
                                         # Linux:   security-plus-lab-engine.desktop
python tools/build_web_bundle.py         # rebuild the hosted bundle after changing
labs/data/policy
```

The tests cover the API, the server's security rules (foreign Host, non-JSON POST, unknown methods, path probes, no CORS), the three launchers and the bundle. A Playwright run drives both modes end to end (lesson, scenario, a full quiz, progress, a timed exam, phone width in dark mode) with no console errors.

24. Random scenarios & the practice exam

23.1 Scenario generator (`utils/scenario_generator.py`)

`generate(lab, policies, seed) -> data` builds a fresh scenario in exactly the lab's sample-file format, drawing only from the policy file (roles, CMDB, catalogs) and fixed text banks. The same seed always gives the same scenario. Supported labs: **2, 6, 9, 11, 12, 13, 14, 15, 17**. Story-driven labs (logs, SOC pipeline, IR playbooks, emails, CAB stories) keep their hand-crafted samples. The tests generate 25 scenarios per lab and require every quiz to be valid and uniquely answerable; a stress run of 200 seeds × 8 labs had zero failures.

DOMAIN TESTS

`build_domain_test(policies, domain, count, seed)` draws questions from one domain only and deals them round-robin across its objectives, so a 30-question Domain 3 test covers 3.1–3.4 evenly. `run_exam(..., domain=...)` reports a score per objective and marks the test against `DOMAIN_TEST_TARGET` (80%, a study target; CompTIA publishes no per-domain pass mark). CLI: `python main.py exam --domain N` (30 questions, one minute each) or **D1–D5** in the menu. Web app: the Practice exam page has a test picker and domain-test cards; results link each objective to its labs and videos.

```
python main.py challenge 9 --random --seed 42      python main.py lab 12 --random      menu: R9
```

23.2 Exam simulator (`utils/exam.py`)

- **Pool:** every lab's questions on sample data plus 3 generated scenarios per supported lab, de-duplicated (≈ 650 questions with randomisation, ≈ 315 fixed).
- **Allocation:** official weights 12/22/18/28/20 % by largest remainder (90 → 11/20/16/25/18); a domain short of questions passes its share to the others.
- **Runner:** timed (default 90 min, injectable clock), no feedback until the end, unanswered questions count as wrong. Results show a per-domain table, an *approximate* scaled score (100 + 8 × %, pass 750; CompTIA's real scaling is not public) and the first 15 misses with explanations. Scores go to `progress.json`.

```
python main.py exam                                  python main.py exam --count 30 --minutes 30 --
seed 7 --fixed
```

25. Challenge mode & progress tracking

File: `utils/challenge.py`. Questions are **computed by running each engine**, so they always match the current policy and data. 628 questions across the 24 labs on sample data, unlimited with `--random`. `pick_distractors()` / `choices_with()` choose wrong options deterministically and accept an `exclude` list so a distractor is never a second correct answer. Choices may not be bare numbers, because a typed digit selects an option by number.

```
@dataclass Question(prompt, choices, answer, explanation, objective, context="")   # answer must be
in choices
run_challenge(ui, lab_number, questions, ask=None, progress=None, shuffle=True, seed=None) ->
ChallengeResult
    # accepts option number or exact text; shows PASS/FAIL + "Why"; EOF/Ctrl-C ends early, scoring
answered only
class Progress(path=progress.json): record(objective, correct) · record_session(result) · save() ·
rows()
    # rows sorted weakest first; status PASS ≥85%, WARN ≥65%, FAIL below (LOW/MEDIUM if <3
attempts)
```

A test answers every lab's questions with the engine's own answers and requires 100%. That catches unanswerable or ambiguous questions.

26. Shared utilities

Module	Contents
`crypto_helpers.py`	`sha256_hex`, `generate_salt` (128-bit), `salted_sha256`, `stretch_password` (PBKDF2-HMAC-SHA256, 100k iterations), `file_sha256`, `constant_time_equals`, `hmac_sign` / `hmac_verify`, `canonical_json`, `build_hash_chain` / `verify_hash_chain` (returns valid, first_broken_index, length_delta)
`terminal_ui.py`	`UI(plain=False, quiet=False)`: `header`, `section`, `status(label, verdict, detail)` (verdict colour from `STATUS_STYLES`), `bullet`, `table`, `panel`, `insight(INSIGHT)`, `ask`. Falls back to ASCII when rich is missing.
`loader.py`	`ROOT`, `CONFIG_DIR`, `DATA_DIR`, `load_json`, `load_policies(path=None)`, `load_data(name)`

27. Policy configuration reference

File: `config/default_policies.json`. Swap the whole file with `--policies`.

Section	Keys
`identity_governance`	clearance_levels · roles{role: [perms]} (9 roles) · sod_conflicts[{id,a,b,risk}] (5) · abac_rules{require_clearance_gte_classification, require_department_match_for, business_hours, restrict_outside_hours_for, allowed_employment_status} · leaver_sla_hours

`zero_trust`	token_ttl_seconds (900) · step_up{bonus 15, ttl_divisor 3} · signing_key · thresholds{allow 70, step_up 50} · weights{…} · min_device_health 70 · business_hours · resource_sensitivity{res: {min_score, requires_mfa}} · entitlements{subject: [resources]}
`log_inspection`	Event IDs (4625, 4624, 1102/104, 4672) · brute_force_threshold 5 / window 10 min · impossible_travel_kmh 900 · port_scan_distinct_ports 10 · continuous_log_hosts · max_log_gap_minutes 30 · threat_intel{bad_ips, bad_user_agent_patterns, bad_file_hashes} · integrity_salt · manifest_hmac_key
`change_management`	maintenance_windows · blackout_dates · cab_quorum 2 · cab_members · max_risk_for_auto_approve 3 · systems{name: {owner, legacy, depends_on, tags}} (the CMDB, 9 systems incl. edge-fw, each with criticality + exposure) · irreversible_actions
`vulnerability_management`	criticality/exposure/KEV multipliers · priority_thresholds · sla_days · kev_max_sla_days · cvss_bands · exceptions{authorized_approvers, max_duration_days, max_residual_score, compensating_control_reduction}
`email_security`	org_domain · inbound_mx · protected_domains · brand_owned_domains · executives · phishing/payment/credential keywords · url_shorteners · suspicious_tlds · dangerous/document extensions · banner/quarantine scores
`firewall_audit`	untrusted_zones · broad_prefix_max · cleartext_ports · remote_admin_ports · segmentation_policy{allowed_flows, never_allowed} · weights
`hardening_baselines`	severity_weight · compliant_min_percent · profiles{windows_server[12], linux_server[10]} (id, setting, op, value, severity, remediation)
`threat_classification`	min_margin · actors{indicator weights} · motivation_rules (ordered) · vectors{vector, mitigation} · actor_addons
`resilience`	site_types · replication · clustering · raid · backup_restore_multiplier · restore_hours_per_tb · host_rebuild_hours · test_max_age_days
`vendor_risk`	sensitivity/access/criticality scales · inherent/residual bands · questionnaire · required_clauses · sla_min_uptime · max_breach_notification_hours · monitoring_cadence · agreement_types
`control_classification`	categories{label: {phrase: weight}} · types{label: {phrase: weight}}
`pki`	trusted_roots · min_key_bits · allowed_signature_algorithms · max_leaf_validity_days · expiry_warning_days · revocation_hard_fail · severity · warning_codes · concepts
`data_protection`	classification_rank · detectors · allowed_destinations · allowed_regions · sovereignty · protection_rules · protection_methods
`siem`	sources · severity_order · geo · threat_intel · never_suppress_severities · rules · suppressions · tools · activities
`iac`	known_types · unknown_type_severity · severity_order · decision · internet_cidrs · admin_ports · required_tags · ha_min_zones · ha_tag · checks · responsibility_layers · responsibility_matrix · quiz_layers · architecture_models
`asset_mgmt`	missing_after_days · tracked_statuses · classifications · finding_priority · finding_actions · sanitization_levels · min_level · media_types · methods · incompatibility_notes · certificate_required · glossary

`compliance`	regimes · at_risk_margin · dsr_types · erasure_exemption_grounds · dsr_required_fields · breach_required_fields · retention_required_fields · attestation_required_fields · retention_schedule · attestations · consequence_by_code · external_attestation_consequence · rule_labels · data_roles · consequences · diligence_terms
`audit`	authorized_signer_roles · environment_types · passive_recon_ignores_window · passive_recon_note · always_prohibited · techniques · pentest_types · assessment_types · assessment_rules
`awareness`	known_roles · high_risk_roles · outcome_action · escalate_after_failures · recurring_training_days · untrained_action · overdue_action · department_thresholds · program_targets · behaviour_required_attributes · behaviour_rules · behaviour_default_class · behaviour_responses · technical_controls · trusted_domains · lookalike_max_distance · homoglyphs · urgency_keywords · request_keywords · risky_attachment_extensions · indicator_weights · report_threshold · report_procedure · training_types · guidance_topics
`ai_governance`	agents{id: {type, allowed_actions}} (4) · immutable_firewall_rules · always_hitl_actions · privileged_roles · protected_controls · confidence_threshold 0.80 · max_actions_per_agent_per_window 5 · rate_window_seconds 60 · quarantine_after_blocks 3 · human_approvers · dangerous_command_patterns · prompt_injection_patterns · asset_inventory · patch_catalog · approved_cab_tickets

> **Note**
> All keys, salts and data are fictional placeholders for the lab only. This is a training simulator, not a production control.

28. Testing & CI

- **860 tests**: one file per lab 9–24, `tests/test_videos.py`, `tests/test_webapp.py` (API, server security, shortcuts, bundle), `tests/test_generator_exam.py` (200 generated scenarios + exam), `tests/test_labs.py` (crypto vectors, Labs 1–5 engines, demo headline numbers, CLI) and `tests/test_extensions.py` (challenge framework, step-up, session revocation, suspend, HITL class, key separation, Labs 6–8, CLI challenge/progress).
- Parametrised tests run every lab in `LABS`, so a new lab is smoke-tested automatically.
- **CI** (`.github/workflows/secplus-lab-engine.yml`): triggers on changes under `secplus_lab_engine/**`; matrix Python 3.10–3.13; installs requirements, runs pytest, runs `main.py all` with rich, then uninstalls rich and runs `--plain all`. All jobs currently green.

29. Design decisions & known limitations

Decisions worth knowing

- **The "AI agent" in Lab 8 is deterministic** (`soc_agent_propose`), so results are reproducible and testable. It is designed to be swapped for a real model; every guardrail still applies.
- **Agent pacing:** Lab 8 spaces proposals 15 s apart. At 5 s, Lab 5's rate limiter blocked legitimate incident response. Lab 5 still demonstrates a runaway agent.
- **disable_account always requires a human** (`always_hitl_actions`), however confident the agent is.
- **Rate limiting counts attempted actions, including blocked ones.** This is a defensible choice; you could argue for counting only executed actions.
- **BLOCK is never overridable** through `human_review`: a human must change policy, not approve an exception at runtime.
- **Key separation:** the evidence-sealing key is separate from the Zero Trust token key.

Known limitations

- Simulated environments only: no real AD, firewall, SIEM or EDR integration.
- The log parser expects the lab's `key=value` format, not real EVTX/syslog/CEF.
- The Lab 4 rehearsal models only a few state attributes (patches, config version, running, firewall lists, schema).
- The sample scenarios are fixed. Challenge mode re-asks the same questions in a different order, so you can memorise the answers (a random scenario generator is on the roadmap).
- CI runs twice per PR push (push + pull_request triggers). Harmless, and can be trimmed.
- All five SY0-701 domains now have labs. Objectives still without a dedicated lab: 3.1 architecture models (cloud, IaC, containers), 3.3 data protection, 4.2 asset management, 4.4 monitoring tools, 5.4–5.6 compliance, audits and awareness programs.
- Labs 1, 3, 4, 5, 7, 8, 10 and 16 have no random generator yet, so their challenge questions repeat.
- Lab 17 validates structured certificate records rather than parsing real X.509/ASN.1, and does not verify signatures cryptographically. Lab 10 models DKIM body integrity and key presence, not RSA signature verification; the organisational domain uses the last two labels (no public-suffix list offline).

30. How to extend (recipes)

18.1 Add a new lab

1. Create `labs/labN_topic.py` following the contract (skeleton below).
2. Put thresholds in a new section of `config/default_policies.json`; put the scenario in `data/sample_topic.json`.
3. Register it in `labs/__init__.py`: import it and add `N: (labN_topic, "sample_topic.json")`.
4. Add engine tests in `tests/`. The parametrised demo and challenge tests cover it automatically: they need ≥5 valid questions and 100% on self-answer.
5. Update `README.md` (labs table, data files, practice ideas).

```
"""Lab N — Title.  Security+ SY0-701 objectives: X.Y ...  Run: python main.py lab N"""
from __future__ import annotations
from dataclasses import dataclass, field

TITLE = "Lab N — Title"
OBJECTIVES = "SY0-701 X.Y Topic"

@dataclass
class Result:
    item_id: str
    verdict: str                        # use words in terminal_ui.STATUS_STYLES for colour
    reasons: list[str] = field(default_factory=list)

def evaluate(item: dict, cfg: dict) -> Result:
    """Pure decision logic: no printing, deterministic, returns reasons."""
    reasons = []
    if item["value"] > cfg["threshold"]:
        reasons.append(f"value {item['value']} > threshold {cfg['threshold']}")
    return Result(item["id"], "FAIL" if reasons else "PASS", reasons or ["within policy"])

INSIGHT = {"objective": "SY0-701 X.Y ...", "concepts": [...], "failure_modes": [...],
           "ai_governance": [...], "exam_tips": [...]}

def run_demo(ui, policies: dict, data: dict) -> dict:
    cfg = policies["topic"]
    results = [evaluate(i, cfg) for i in data["items"]]
    ui.section("Step 1 — Evaluate")
    ui.table("Results", ["ID", "Verdict", "Reasons"], [[r.item_id, r.verdict, "; ".join(r.reasons)]
for r in results])
    ui.insight(INSIGHT)
    return {"fail": sum(r.verdict == "FAIL" for r in results)}

def build_challenges(policies: dict, data: dict) -> list:
    from utils.challenge import Question
    cfg = policies["topic"]
    return [Question(prompt=f"{i['id']}: PASS or FAIL?", context=str(i), choices=["PASS", "FAIL"],
                     answer=evaluate(i, cfg).verdict, explanation="; ".join(evaluate(i,
cfg).reasons),
                     objective="X.Y") for i in data["items"]]
```

18.2 Smaller extensions

Goal	Where
New log detection rule	`detect_x(events, cfg) -> list[Finding]` in Lab 3, append to `ALL_RULES`, add to `FRIENDLY` for challenges
New agent guardrail	Add a check inside `AgentGovernor._check` using `add(code, BLOCK|HITL, msg)`; add config keys under `ai_governance`
New agent or permission	`ai_governance.agents` in config
New CMDB system / legacy dependency	`change_management.systems` with `tags` like `requires:tls1.0` or `port:1521`
New change action	`UNDO_MAP` and `_apply()` in Lab 4 (and `irreversible_actions` if it can't be undone)
New IR action	`actions` catalog in `sample_incident.json` (phase, evidence, destroys_up_to_rank, requires, anti_pattern)
Plug in a real LLM agent	Replace `soc_agent_propose()` in Lab 8 with a model call that returns `AgentAction`s; keep it opt-in so the core stays offline

31. Roadmap: what to build next

Done since the first edition: Labs 17–24 (every SY0-701 objective now has a lab), course web app + desktop app, random scenario generator for 16 labs, timed exam, Anki and CTFd exports, and the Professor Messer video course index.

#	Idea	Objectives	Notes
1	Generators for the remaining labs	all	Logs (3), RFCs (4), agent actions (5), IR playbooks (7), emails (10), controls (16)
2	Optional real-LLM mode	4.7	Model-written proposals in Labs 5/8/23 to test guardrails against real hallucination and prompt injection (key in `XAI_API_KEY`, never in the repo)
3	Spaced repetition in the app	all	Use progress.json to re-ask weak objectives more often
4	Visual labs	1.4, 3.2, 4.8	Diagrams for certificate chains, network zones and IR timelines
5	Cross-lab scenarios	4.4, 4.8, 3.3	Lab 19 alerts feeding Lab 8's pipeline; Lab 18 DLP blocks as incidents in Lab 7

32. Ready-to-paste prompt for another AI

Attach this PDF (and ideally the `secplus_lab_engine/` folder), then paste:

```
You are extending an existing offline Python 3.10+ project called "secplus_lab_engine": a
Security+ SY0-701 lab simulator with 24 labs, a course web app, challenge mode, a random scenario
generator, a
domain-weighted practice exam and an AI-agent guardrail governor.
The attached handbook describes its architecture, module contract, APIs, data formats and tests.

Rules:
1. Follow the lab module contract exactly: TITLE, OBJECTIVES, INSIGHT (objective, concepts,
   failure_modes, ai_governance, exam_tips), run_demo(ui, policies, data) -> dict,
   build_challenges(policies, data) -> list[Question].
2. Standard library only (rich optional through utils/terminal_ui.UI). No network calls.
3. Policy/thresholds go in config/default_policies.json (new section); scenarios go in
   data/sample_*.json. Engines are pure (no printing) and return reasons for every decision.
4. Register the lab in labs/__init__.py LABS = {N: (module, "sample_file.json")}.
5. Write pytest tests for the engine logic; the existing parametrised tests require
   >= 5 challenge questions, unique choices, and 100% when answered with the engine's own answers.
6. Make challenge distractors genuinely wrong (no second correct answer).
7. End every demo with ui.insight(INSIGHT), including how an AI agent should be governed.

Task: build Lab 18 — Data Protection Classifier (SY0-701 3.3). Classify data types (regulated,
trade secret, IP, PII, financial) and states (at rest / in transit / in use); apply a labelling
policy; recommend the protection method (encryption, hashing, masking, tokenization, obfuscation,
segmentation, geographic restrictions) and flag DLP rule violations. Add a seeded generator, a
challenge set, and rebuild web/course_data.json so the lab appears in the course web app.
```

Swap the "Task" paragraph for any roadmap item in Section 31, e.g. "add a generator for Lab 10 emails" or "add an optional LLM-backed soc_agent_propose behind a --llm flag".

33. Glossary

ABAC	Attribute-based access control
ALE / SLE / ARO / EF / AV	Annualised loss expectancy / single loss expectancy / annualised rate of occurrence / exposure factor / asset value
BIA	Business impact analysis (RTO, RPO, MTTR, MTBF)
CAB / ECAB	(Emergency) Change Advisory Board
CVSS / KEV	Common Vulnerability Scoring System / Known Exploited Vulnerabilities catalog
CMDB	Configuration management database (systems + dependencies)

IOC	Indicator of compromise
JML	Joiner / Mover / Leaver lifecycle
PE / PA / PEP	Policy Engine / Policy Administrator / Policy Enforcement Point
RBAC	Role-based access control
RFC	Request for Change (Lab 4) · RFC 3227 = evidence collection guideline (Lab 7)
RPO / RTO	Max tolerable data loss / downtime
SPF / DKIM / DMARC	Sender IP authorisation / message signature / alignment + policy

HITL	Human-in-the-loop (REQUIRE_HUMAN_APPROVAL)
HMAC	Keyed hash: integrity + authenticity
IGA	Identity governance & administration

SoD	Separation of duties
SOAR	Security orchestration, automation & response