

GOOGLE LENS FIT TEST

Blue Glee Blob | optional front-film trial | 18 September 2026

Print this paper at 100% / Actual Size. Turn off Fit to Page.

Check the scale bar with a ruler before cutting any transparency.



This bar must measure 50 mm.

1. Cut a rounded lens blank

Use these actual-size outlines as guides on ordinary paper.

Trace or hold the thin transparency over an outline; cut with small scissors.

Start with A. Cut on the thin line. Keep the corners smooth.

A - start here



12.6 x 8.6 mm

B - if A is loose



12.7 x 8.7 mm

C - if A is tight



12.5 x 8.5 mm

These are starting sizes; the printed groove and your film decide the final fit.

2. Check the print before installing the lens

Let the frames cool. Inspect the front edge and the groove under a bright light.

Remove only loose strings. The groove should be continuous, with no fused sections.

Keep one frame untouched as a comparison; use the other for the insertion trial.

3. Insert and test

Seat one long edge in the groove. Gently bow the film to tuck in the opposite edge.

Work the corners into place using a fingernail. Do not force or crease the film.

If it will not seat, try a slightly smaller blank before altering the printed frame.

The lens should lie flat, sit just below the front rim, and cover the whole opening.

Pass checks

- ☐ Film stays seated when inverted and given a gentle shake.
- ☐ Gentle fingertip contact does not pop it out or leave it buckled.
- ☐ Remove and reinstall three times; no cracked lip or permanent film crease.
- ☐ With white foam behind it, the front and angled views still look right.

Report back: blank size, easy/tight/loose fit, whether it stays flat, and any damage.

A front photo and an angled close-up will help. Keep the baseline r5 design unchanged.