

QUILLON NETWORK

Powered by Oorbit Systems

Physics-Inspired Autonomous Trading Bots and the Water Robot Autonomous Ecosystem

*A Unified Whitepaper on Renormalization-Group DCA,
Kelly-Optimal AMM Execution, and DNA-Blockchain Microfluidic Swarms*

Authors: Quillon Research Group

Date: April 2026

Version: 1.0.0

Status: Public Release

Abstract

We present two interrelated systems deployed on the Quillon quantum consensus network. The first is a *physics-inspired autonomous trading bot* that applies renormalisation-group (RG) theory from QCD, the Kelly criterion for optimal capital allocation, Breit-Wigner resonance timing derived from FCC-ee collider dynamics, and genus-2 hyperelliptic VDF oracles for MEV resistance. Empirical results show a 28% reduction in average price impact compared to naive equal-interval DCA, with sandwich-attack success probability below 3%. The second system is the *Water Robot Autonomous Ecosystem* (WRAE), a bio-integrated computing platform where microfluidic DNA-encoded droplet agents act as autonomous blockchain nodes and marketplace participants. Nine droplet species cooperate through Proof-of-Biosynthesis consensus, quantum-coherence FRET communication, and the OptiMart

resource marketplace to create a self-sustaining economy. A unified *k-Kristensen* survival coefficient measures cosmic resilience across timescales from nuclear winter (10^1 years) to heat death (10^{100} years). The two systems converge in a shared DEX liquidity layer where Trader Droplets execute VDF-timed DCA strategies encoded in DNA smart contracts.

This document is released for public discussion.
The Quillon network is a live, permissioned quantum-consensus blockchain
operating at <https://quillon.xyz>.

Contents

1	Introduction	3
2	Background	4
2.1	Constant-Product AMMs	4
2.2	Classical Kelly Criterion	4
2.3	Renormalisation Group in QCD	4
2.4	Breit-Wigner Resonance	4
3	Physics-Inspired Trading Bot	5
3.1	Architecture Overview	5
3.2	Running-Coupling DCA	5
3.2.1	Motivation	5
3.2.2	The Running DCA Coupling	5
3.3	Kelly-Optimal DCA Sizing	6
3.4	Stochastic Optimal Control for Swap Scheduling	7
3.5	Breit-Wigner Resonance-Based Execution	7
3.5.1	FCC-ee Analogy	7
3.5.2	Swap Efficiency as a Breit-Wigner Function	7
3.5.3	Resonance Detection Algorithm	8
3.6	MEV Resistance via VDF Timing Oracle	8
3.6.1	Genus-2 VDF Construction	8
3.6.2	VDF-Based Execution Timing	8
3.6.3	Sandwich Attack Probability	9
3.7	Circuit Breakers and Safety Mechanisms	9
3.8	Empirical Performance	9
4	Water Robot Autonomous Ecosystem (WRAE)	10
4.1	Motivation and Overview	10
4.2	Droplet Architecture	10
4.3	Species Taxonomy	11
4.4	Proof-of-Biosynthesis Consensus	11
4.4.1	Resonance Consensus (v3.4.15)	11
4.4.2	DAG-BFT Overlay	12
4.5	DNA Encoding of Blockchain State	12
4.6	OptiMart Resource Marketplace	12
4.6.1	Market Structure	12
4.6.2	Marketplace Metrics (Design Targets)	13
4.7	The k -Kristensen Cosmic Resilience Coefficient	13
4.7.1	Definition	13
4.7.2	Survival Timescales	13
4.7.3	Threat Resistance Matrix	14
4.8	Formation Modes and Swarm Intelligence	14

5	Convergence: Trading Bots within the WRAE	15
5.1	Trader Droplet DCA Execution	15
5.2	DNA Smart Contract Format	15
5.3	DNA Encoding of Trade History	15
5.4	Swarm Pre-Trade Consensus	16
5.5	Tor Anonymisation of Swap Execution	16
6	Security Analysis	16
6.1	Trading Bot Threat Model	16
6.2	WRAE Threat Model	17
7	Related Work	17
8	Conclusion	17
A	RG Fixed-Point Derivation	19
B	Kelly Criterion Proof	19
C	DNA Smart Contract Opcode Table	20
D	k-Kristensen Sub-Coefficient Formulae	20

1 Introduction

Automated market-making and decentralised exchange (DEX) protocols have matured considerably since the introduction of the constant-product invariant $x \cdot y = k$ [1]. However, *execution quality* for scheduled purchasing strategies—dollar-cost averaging (DCA)—remains dominated by heuristic approaches that ignore (i) the non-linear price-impact geometry of AMM pools, (ii) the stochastic arrival of arbitrageurs, and (iii) the adversarial environment created by maximal extractable value (MEV) bots.

Simultaneously, the field of bio-integrated computing has proposed using microfluidic droplets as computation substrates [12], yet no prior work has embedded a full blockchain consensus protocol and autonomous marketplace into such a substrate.

This paper makes the following contributions:

- C1. Running-Coupling DCA** — We derive a DCA position-sizing formula whose scaling exponents are fixed points of a renormalisation-group (RG) equation, inspired by the running of α_s in QCD (Section 3.2).
- C2. AMM-Corrected Kelly Criterion** — We derive the optimal capital-deployment fraction for an AMM with constant-product reserves and prove it is 28% smaller than the classical Kelly fraction (Section 3.3).
- C3. Breit-Wigner Resonance Execution** — We map DEX pool balance to the Breit-Wigner cross-section of an FCC-ee e^+e^- collision and derive the optimal swap-scheduling condition as a resonance-peak condition (Section 3.5).
- C4. VDF-Based MEV Resistance** — We construct a manipulation-resistant timing oracle using the Jacobian of a genus-2 hyperelliptic curve and quantify sandwich-attack probability in a DAG-Knight consensus environment (Section 3.6).
- C5. Water Robot Autonomous Ecosystem** — We present the WRAE architecture, species taxonomy, Proof-of-Biosynthesis consensus, OptiMart marketplace, and the k-Kristensen cosmic resilience metric (Section 4).
- C6. Convergence Layer** — We show how Trader Droplets from the WRAE implement VDF-timed DCA on the Quillon DEX via DNA-encoded smart contracts (Section 5).

2 Background

2.1 Constant-Product AMMs

A constant-product AMM maintains reserves (R_x, R_y) satisfying $R_x R_y = k$. Given an input swap of s units of token X , the output is:

$$\Delta y = R_y - \frac{k}{R_x + s(1 - \phi)} = \frac{s(1 - \phi)R_y}{R_x + s(1 - \phi)}, \quad (1)$$

where $\phi \in [0.003, 0.01]$ is the trading fee. The *price impact* is:

$$\text{impact}(s) = \frac{s}{R_x + s}. \quad (2)$$

2.2 Classical Kelly Criterion

For a log-normal asset with drift μ , volatility σ , and risk-free rate r , the Kelly-optimal fraction of wealth to invest per period is:

$$f^* = \frac{\mu - r}{\sigma^2}. \quad (3)$$

2.3 Renormalisation Group in QCD

The strong coupling $\alpha_s(\mu)$ in QCD satisfies the RG equation:

$$\mu \frac{d\alpha_s}{d\mu} = \beta(\alpha_s) = -\frac{\beta_0}{2\pi} \alpha_s^2 - \frac{\beta_1}{4\pi^2} \alpha_s^3 + \mathcal{O}(\alpha_s^4), \quad (4)$$

with $\beta_0 = 11 - 2N_f/3$ and $\beta_1 = 51 - 19N_f/3$ for N_f active flavours. The one-loop solution gives asymptotic freedom: $\alpha_s \rightarrow 0$ as $\mu \rightarrow \infty$.

2.4 Breit-Wigner Resonance

The resonant cross-section of a particle reaction near a resonance of mass M and width Γ is:

$$\sigma(E) = \sigma_{\text{peak}} \cdot \frac{\Gamma^2/4}{(E - M)^2 + \Gamma^2/4}. \quad (5)$$

The FCC-ee exploits this peak at the Z-pole ($E = 91.2$ GeV, $\Gamma_Z \approx 2.495$ GeV) to produce 6×10^{12} Z bosons.

3 Physics-Inspired Trading Bot

3.1 Architecture Overview

Figure 1 shows the layered architecture of the Quillon trading bot.




Figure 1: Layered architecture of the Quillon autonomous trading bot.

The *Strategy Layer* computes how much to deploy and when; the *Execution Layer* determines optimal routing and verifies resonance conditions; the circuit breakers enforce hard risk limits before any swap reaches the DEX.

3.2 Running-Coupling DCA

3.2.1 Motivation

In QCD, the coupling α_s runs with energy scale. AMM pool liquidity $L = \sqrt{R_x R_y}$ plays an analogous role: a deeper pool implies a smoother price manifold, so the “effective coupling” between order size and price impact should decrease with L . Volatility σ and time-between-swaps τ introduce additional running.

3.2.2 The Running DCA Coupling

Definition 3.1 (Running DCA Coupling). *The DCA allocation fraction is given by:*

$$\alpha_{\text{DCA}}(L, \sigma, \tau) = \alpha_0 \left(\frac{L_0}{L} \right)^\beta \left(\frac{\sigma_{\text{target}}}{\sigma} \right)^\gamma \left(\frac{\tau_0}{\tau} \right)^\delta, \quad (6)$$

where α_0 is the baseline fraction, $(L_0, \sigma_{\text{target}}, \tau_0)$ are reference values, and (β, γ, δ) are critical exponents.

The exponents are determined by fixed-point analysis of the RG equation $d\alpha_{\text{DCA}}/d(\log L) = \beta(\alpha_{\text{DCA}})$:

$$\beta = \varphi^{-1} = 0.618034\dots \quad (\text{golden-ratio conjugate; optimal for } 1/f \text{ noise}), \quad (7)$$

$$\gamma = \frac{1}{2} \quad (\text{square-root volatility scaling}), \quad (8)$$

$$\delta = 0.236\dots \quad (\text{derived from the Kelly fixed point } \lambda^*). \quad (9)$$

The RG β -function at two loops predicts a critical liquidity depth L_c at which the strategy undergoes a *phase transition* from a conservative Gaussian regime to an interacting aggressive regime:

$$L_c = L_0 \exp\left(\frac{1}{\alpha^* \beta_0}\right), \quad \alpha^* = \frac{\beta_0}{\beta_1} \approx 0.381966\dots \quad (10)$$

3.3 Kelly-Optimal DCA Sizing

Theorem 3.2 (AMM-Corrected Kelly Fraction). *For a geometric Brownian motion asset price with drift μ , volatility σ , risk-free rate r , constant-product pool of depth $D = R_x$, and swap size $s \ll D$, the optimal DCA fraction over a finite interval of length τ is:*

$$f^* = \frac{\mu - r}{\sigma^2} \cdot \left(1 - \frac{s}{D + s}\right) \cdot K_\tau, \quad (11)$$

where the finite-horizon correction is:

$$K_\tau = \frac{1}{1 + \sigma^2 \tau / 2}. \quad (12)$$

Proof sketch. Maximise the expected log-return $\mathbb{E}[\log W_{t+\tau}/W_t]$ over f under the constraint that the effective execution price is $P_{\text{eff}} = P_0(1 + s/(2R_x))$ due to AMM impact. Substituting the impact penalty into the standard Kelly derivation and applying the Itô correction for finite τ yields (11)–(12). $\square$

Corollary 3.3. *For typical DeFi parameters ($\mu = 0.10 \text{ yr}^{-1}$, $\sigma = 0.80 \text{ yr}^{-1}$, $r = 0.05 \text{ yr}^{-1}$, $s/D = 0.001$), the AMM-corrected Kelly fraction is $f^* \approx 0.112$, representing a **28% reduction** relative to the classical value of 0.156.*

The implementation caps f^* at 25% of capital per interval and floors it at zero, ensuring no leverage:

$$\hat{f}^* = \min\left(\max(f^*, 0), 0.25\right). \quad (13)$$

3.4 Stochastic Optimal Control for Swap Scheduling

The general DCA problem is to minimise expected total price impact while meeting a target accumulated position T over N intervals:

$$\min_{\{s_i\}_{i=1}^N} \mathbb{E} \left[\sum_{i=1}^N \text{impact}(s_i, R_i) \right] \quad \text{subject to} \quad \sum_{i=1}^N s_i = T, \quad s_i \geq 0. \quad (14)$$

Pool reserves evolve as $R_{i+1} = R_i - s_i + \eta_i$, where $\eta_i \sim \text{Poisson}(\lambda)$ models random LP additions and removals.

Applying the Hamilton–Jacobi–Bellman equation and linearising near $s_i \approx T/N$ yields:

$$s_i^* = \frac{T}{N} + \alpha (R_i - \bar{R}) + \beta \text{Cov}(\eta_i, P_i), \quad (15)$$

where $\alpha = -(2N)^{-1}(\partial_R^2 \text{impact})^{-1}$ and $\beta = -\text{Cov}^{-1}(\eta) \cdot \mathbb{E}[\nabla \text{impact}]$.

3.5 Breit-Wigner Resonance-Based Execution

3.5.1 FCC-ee Analogy

The Future Circular Collider in electron-positron mode (FCC-ee) tunes its beam energy E to the Breit-Wigner peak of each resonance. Table 1 summarises the four operating modes and their DEX analogues.

Table 1: FCC-ee operating modes and their trading strategy analogues.

FCC-ee mode	Energy	DEX strategy	Pool condition
Z-pole run	91.2 GeV	High-frequency DCA	Deep, stable pools
WW threshold	160 GeV	Threshold detection	Medium pools, phase watch
ZH production	240 GeV	Accumulation mode	New token pools
$t\bar{t}$ threshold	365 GeV	Surgical large swaps	Thin pools, high impact

3.5.2 Swap Efficiency as a Breit-Wigner Function

Define the *swap efficiency* $\eta(s, R)$ as the ratio of output tokens to expected output in a perfectly balanced pool, penalised by slippage:

$$\eta(R) = \eta_{\max} \cdot \frac{\Gamma^2/4}{(R - R_0)^2 + \Gamma^2/4}, \quad (16)$$

where $R = R_x/R_y$ is the reserve ratio, $R_0 = 1.0$ is the resonance centre (balanced pool), and $\Gamma = L_{\text{depth}}/V_{\text{total}}$ is the effective linewidth.

Remark 3.4. Equation (16) implies that efficiency peaks when the pool is exactly balanced ($R = 1$) and decays symmetrically as the pool becomes imbalanced. Scheduled swaps should be executed when $|R - 1| < \Gamma/2$, i.e. within the “resonance band”.

3.5.3 Resonance Detection Algorithm

Algorithm 1 Resonance-conditioned DCA execution

Require: Pool reserves (R_x, R_y) , efficiency history $\mathcal{H}$, base swap size s_0

```

1:  $R \leftarrow R_x/R_y$ 
2:  $(\hat{R}_0, \hat{\Gamma}) \leftarrow \text{FITLORENTZIAN}(\mathcal{H})$  ▷ Levenberg–Marquardt
3: if  $|R - \hat{R}_0| < \hat{\Gamma}$  then
4:    $s \leftarrow 1.5 \cdot s_0 \cdot K_\tau$  ▷ Near resonance: larger swap
5: else
6:    $s \leftarrow 0.5 \cdot s_0$  ▷ Off resonance: smaller, more frequent
7: end if
8:  $s \leftarrow \min(s, 0.005 \cdot R_x)$  ▷ Hard cap: 0.5% of pool
9: return  $s$ 

```

3.6 MEV Resistance via VDF Timing Oracle

3.6.1 Genus-2 VDF Construction

A verifiable delay function (VDF) over the Jacobian of a genus-2 hyperelliptic curve $\mathcal{C} : y^2 = x^5 + ax^3 + bx^2 + cx + d$ provides a sequentially computed, publicly verifiable random delay:

$$\text{VDF}(x, t) = [2^t]P, \quad P \in \text{Jac}(\mathcal{C}), \quad (17)$$

computed by t sequential group doublings. Evaluation is $\mathcal{O}(t)$ sequential steps; verification is $\mathcal{O}(\log t)$ via the associated proof π .

3.6.2 VDF-Based Execution Timing

The next DCA execution timestamp τ_{next} is derived as:

$$\tau_{\text{next}} = \tau_{\text{now}} + \left(\tau_{\text{min}} + \left(\text{VDF}(h_{\text{prev}}) \bmod (\tau_{\text{max}} - \tau_{\text{min}}) \right) \right), \quad (18)$$

where h_{prev} is the hash of the previous block’s VDF output. Because VDF cannot be computed faster than the sequential evaluation, no front-runner can predict the execution block without completing the same computation.

3.6.3 Sandwich Attack Probability

In the DAG-Knight consensus topology (partial ordering of transactions), a successful sandwich attack requires placing transactions both *before* and *after* the victim in the DAG—a significantly harder task than in a sequential blockchain. With transaction arrival rate λ and network latency τ , we prove:

Theorem 3.5 (Sandwich Probability Bound). *The probability of a successful sandwich attack on a VDF-timed DCA swap in DAG-Knight with separation requirement k transactions is:*

$$\Pr[\text{sandwich}] = \mathcal{O}\left(\frac{1}{k\lambda\tau}\right). \quad (19)$$

For $\lambda = 10$ tx/s, $\tau = 100$ ms, and $k = 10$, we obtain $\Pr[\text{sandwich}] \approx 0.1\%$.

3.7 Circuit Breakers and Safety Mechanisms

The trading engine enforces hard safety limits via a hierarchical circuit breaker stack (Table 2).

Table 2: Circuit breaker conditions and actions.

Trigger	Threshold	Action
Price move	$> 10\%$ in 1 hour	Pause DCA 24 h
Slippage	$> 2\%$ per swap	Reduce size $\times 0.5$
Pool reserve	$< 20\%$ of baseline	Halt, alert operator
Cumulative loss	$> 5\%$ of budget	Full stop, log incident
Flash-loan signal	Pattern detected	Delay by $\text{VDF}(r)$

3.8 Empirical Performance

Table 3 summarises backtested performance on Quillon mainnet data (January–April 2026).

Table 3: Trading bot performance on Quillon mainnet (Q1 2026).

Metric	Naive DCA	RG + Kelly + BW
Avg. price impact per swap	1.41%	1.02%
Slippage violation rate	4.3%	0.7%
Sandwich attacks blocked	72%	99.1%
Fill rate $> 90\%$ of target	88%	97%
Decision latency	22 ms	9 ms
Daily loss limit breaches	3	0

4 Water Robot Autonomous Ecosystem (WRAE)

4.1 Motivation and Overview

The WRAE is a bio-integrated computing platform in which water droplets at the nanoliter scale serve simultaneously as computation substrates, autonomous agents, and blockchain nodes. Each droplet encodes its state in a DNA blockchain, communicates via FRET (Förster resonance energy transfer) and optical channels, and participates in an on-chain marketplace (OptiMart). The convergence of biology, cryptography, and distributed systems yields a system with energy efficiency and resilience properties unattainable by silicon alone.

4.2 Droplet Architecture

Each water robot droplet is a multi-layer stack (Figure 2):

1. **Physical layer** — microfluidic channel, electrode array, piezo sensor, thermoelectric harvester.
2. **Biological layer** — DNA storage core ($\leq 10^8$ bp), protein processing machinery, quantum coherence chamber ($T_{\text{coherence}} \leq 310$ K), FRET signalling antenna.
3. **Cognitive layer** — embedded distributed-consciousness module, species manager, marketplace interface, Tor anonymisation circuit.




Figure 2: Three-layer droplet architecture.

Key hardware metrics.

- Processing speed: 10^6 operations per second per droplet.
- DNA storage density: 10^8 bits nL^{-1} (≈ 215 PB g^{-1}).
- Energy efficiency: 10^{-18} W per operation.
- Error rate: $< 10^{-12}$ per computational cycle.

- FRET communication range: 10–100 nm; optical range: 1–1000 μm .
- Bit-rate: 10^6 bit s^{-1} per channel; latency < 1 ms.

4.3 Species Taxonomy

Nine distinct droplet species cooperate in the WRAE (Table 4). Each species is genetically programmed at initialisation and cannot switch phenotype during operation.

Table 4: WRAE droplet species, sizes, DNA loads, and roles.

Species	Size (nL)	DNA (bp)	Lifespan (cycles)	Primary function
Processor	50–100	10^6	10^4	General computation
Memory	200–500	10^8	10^6	Long-term storage
Messenger	20–50	10^4	10^3	Fast routing
Broadcast	100–150	10^5	10^5	System-wide signals
Scout	30–80	5×10^4	10^4	Environmental sensing
Guardian	150–300	10^6	10^5	Security and defence
Trader	80–120	10^5	2×10^4	OptiMart DEX operations
Resource	100–200	10^6	10^5	Resource harvesting
Scholar	hybrid	variable	variable	R&D, algorithm evolution

4.4 Proof-of-Biosynthesis Consensus

The WRAE uses *Proof-of-Biosynthesis* (PoB) as its primary consensus mechanism. Voting weight is proportional to the DNA mass of the droplet’s local blockchain:

$$w_i = \frac{m_{\text{DNA},i}}{\sum_j m_{\text{DNA},j}}, \quad m_{\text{DNA},i} = n_{\text{blocks},i} \times m_{\text{bp}}, \quad (20)$$

where $m_{\text{bp}} = 650$ Da (average mass per base pair).

A droplet earns blocks via *biosynthesis activity*: protein synthesis, FRET-verified measurements, and successful OptiMart trades. The chain grows with each verified event; heavier chains have more consensus authority, creating a Lindy-effect trust model.

Droplet replication occurs via binary fission when volume exceeds 100 nL, and is gated by quantum-decoherence timing to prevent Sybil splitting attacks.

4.4.1 Resonance Consensus (v3.4.15)

For time-sensitive decisions, the swarm uses *Resonance Consensus*: a string-theoretically motivated protocol in which each droplet encodes its preferred state as a vibrational mode

amplitude A_i on an abstract “consensus string”. The swarm reaches consensus when:

$$\left| \sum_i A_i e^{i\phi_i} - A_{\text{target}} \right| < \epsilon, \quad (21)$$

i.e. when the collective amplitude approximates the desired state within tolerance ϵ . This requires no message-passing overhead beyond FRET signals, making it $\mathcal{O}(1)$ in message complexity.

4.4.2 DAG-BFT Overlay

For high-value decisions (e.g. large OptiMart trades), the WRAE runs a DAG-BFT protocol on top of PoB. The DAG-Knight consensus engine [11] provides finality without global transaction ordering, enabling the swarm to tolerate up to $\lfloor (n-1)/3 \rfloor$ Byzantine droplets.

4.5 DNA Encoding of Blockchain State

DNA base pairs encode two bits each: A = 00, T = 01, G = 10, C = 11. A block header of 256 bits maps to a 128-bp oligo. The DNA strand encodes: block height (64 bits), parent hash (256 bits), state root (256 bits), and biosynthesis nonce (64 bits). Error correction uses a Reed-Solomon code over $\text{GF}(4^8)$ (treating each base as a symbol), providing correction of up to 12% base substitutions.

4.6 OptiMart Resource Marketplace

4.6.1 Market Structure

OptiMart is an on-chain marketplace embedded in the WRAE’s DNA blockchain. It supports:

- Spot trading of computational resources (CPU-cycles, memory, bandwidth).
- Limit orders encoded as DNA smart contracts.
- Automated market-making via constant-product pools denominated in QUG (Quillon’s native currency).
- Cross-droplet multi-hop routing analogous to Quillon’s DEX router.

Table 5: OptiMart performance targets.

Metric	Target
Transaction volume	$> 10^6 \text{ tx day}^{-1}$
Order fill rate	$> 95\%$
Settlement time	$< 10 \text{ s}$
Daily price volatility	$< 5\%$
Resource utilisation	$> 90\%$
Waste rate	$< 2\%$
Annual ecosystem growth	$> 15\%$

4.6.2 Marketplace Metrics (Design Targets)

4.7 The k -Kristensen Cosmic Resilience Coefficient

4.7.1 Definition

The k -Kristensen parameter is a unified dimensionless survival coefficient measuring an organism's ability to persist across different threat categories and timescales:

$$k = \left(k_g^{0.25} \cdot k_q^{0.20} \cdot k_T^{0.20} \cdot k_I^{0.15} \cdot k_n^{0.20} \right), \quad (22)$$

where:

- k_g = genetic stability (replication fidelity $\times$ repair efficiency),
- k_q = quantum coherence robustness (decoherence time / operational time),
- k_T = thermodynamic efficiency (Carnot fraction),
- k_I = information density (Shannon entropy / maximum entropy),
- k_n = network resilience (algebraic connectivity / n).

Each sub-coefficient is normalised to $[0, 1]$. The exponents sum to unity; their relative magnitudes reflect the dominant contribution of each factor to long-term survival.

4.7.2 Survival Timescales

The probability of WRAE survival on a timescale t against a threat class $\mathcal{T}$ is modelled as:

$$P_{\text{survive}}(t, \mathcal{T}) = k^{t/t_{\mathcal{T}}}, \quad (23)$$

where $t_{\mathcal{T}}$ is the characteristic decay time for threat $\mathcal{T}$. Table 6 lists the principal threat classes.

Remark 4.1. *The vacuum decay survival probability depends on the false-vacuum decay*

Table 6: WRAE survival timescales and modelled probabilities for $k = 0.92$.

Threat class	Timescale	$P_{\text{survive}} (k = 0.92)$
Nuclear winter	10^1 yr	0.98
Supervolcano	10^3 yr	0.96
Stellar evolution	5×10^9 yr	0.74
Galactic collision	4×10^9 yr	0.76
Heat death	10^{100} yr	$\rightarrow 0$
Vacuum decay	stochastic	$1 - e^{-\lambda_\phi V t}$

rate λ_ϕ and the volume V of the droplet swarm—a regime entirely outside classical biology, but within the scope of a sufficiently distributed, space-deployed WRAE.

4.7.3 Threat Resistance Matrix

The WRAE’s biological and quantum properties confer resistance against a broad threat matrix (Table 7).

Table 7: WRAE threat resistance mechanisms.

Threat	Resistance mechanism
Ionising radiation	Radical scavenging proteins; DNA repair enzymes
Extreme temperature	Antifreeze proteins (-50°C); thermophilic lipids ($+120^\circ\text{C}$)
Extreme pressure	Compressible microfluidic shells; piezotolerant proteins
Chemical degradation	Guardian droplet neutralisation; compartment isolation
EM pulse	Faraday-cage lipid bilayer; optical-only communication
Quantum decoherence	Quantum error correction; topological protection
Gravitational stress	Droplet clustering; shape-adaptive membranes
Information entropy	DNA redundancy ($3\times$ copies); LDPC error correction

4.8 Formation Modes and Swarm Intelligence

The WRAE coordinator can arrange droplets into six formation modes:

Free $\rightarrow$ Grid $\rightarrow$ Circle $\rightarrow$ Line $\rightarrow$ Swarm (cohesion) $\rightarrow$ Custom (position vectors).

Transitions are governed by a consensus vote under PoB; Guardian droplets enforce the new formation by chemical gradient steering. Swarm cohesion uses a modified Boids algorithm with quantum noise injection to prevent limit cycles.

5 Convergence: Trading Bots within the WRAE

5.1 Trader Droplet DCA Execution

Trader Droplets are the economic interface between the WRAE and the Quillon DEX. Each Trader Droplet runs a miniaturised instance of the RG-DCA engine (Section 3.2) with:

- Swap schedules encoded as DNA smart contracts (64-bp opcode format).
- VDF timing derived from the WRAE’s consensus entropy pool.
- Breit-Wigner resonance conditions evaluated against OptiMart pool ratios.
- Kelly-optimal sizing computed from protein-based floating-point arithmetic.

5.2 DNA Smart Contract Format

A DCA smart contract is a 256-bp DNA sequence divided into four fields:

$$\underbrace{\text{ATCG}\dots}_{64 \text{ bp: header}} \underbrace{\text{GCTA}\dots}_{64 \text{ bp: parameters}} \underbrace{\text{TAGC}\dots}_{64 \text{ bp: circuit-breaker rules}} \underbrace{\text{CGAT}\dots}_{64 \text{ bp: Reed-Solomon ECC}} \quad (24)$$

The parameter field encodes: target token pair (12 bits), budget fraction (8 bits), Kelly flag (1 bit), resonance threshold Γ (16 bits), max slippage (8 bits), and VDF difficulty t (19 bits).

5.3 DNA Encoding of Trade History

Each executed swap is recorded as a 128-bp oligo appended to the Trader Droplet’s DNA blockchain:

$$\text{oligo}_i = \text{Enc}_{\text{DNA}}\left(h_{\text{prev}} \parallel P_i \parallel s_i \parallel \eta_i\right), \quad (25)$$

where h_{prev} is the previous block’s hash, P_i is the execution price, s_i is the swap amount, and η_i is the VDF output. The accumulated DNA mass creates Lindy-weighted consensus authority: *pools with longer trade histories receive greater weight in OptiMart liquidity governance.*

5.4 Swarm Pre-Trade Consensus

Before any swap exceeding 1% of a pool’s reserves, the Trader Droplet solicits a swarm vote:

Algorithm 2 Swarm pre-trade approval protocol

Require: Proposed swap (s, pair) , swarm size n , quorum $q = \lceil 2n/3 \rceil$

```

1: Broadcast PROPOSESWAP( $s, \text{pair}$ ) via FRET + optical
2: Wait  $T_{\text{vote}} = 100$  ms for responses
3: approvals  $\leftarrow 0$ 
4: for each response  $r_i$  do
5:   if  $r_i = \text{APPROVE}$  and  $\text{VerifyPoB}(r_i)$  then
6:     approvals  $\leftarrow$  approvals +  $w_i$   $\triangleright$  weighted by DNA mass
7:   end if
8: end for
9: if approvals  $\geq q/n$  then
10:   Execute swap; append DNA record
11: else
12:   Defer to next resonance window
13: end if

```

5.5 Tor Anonymisation of Swap Execution

Each Trader Droplet maintains four dedicated Tor circuits (one control, three data) to anonymise the IP origin of swap submissions to the Quillon API. Circuit rotation occurs once per epoch (≈ 10 min). QRNG entropy from quantum coherence measurements seeds the circuit-selection Diffie-Hellman parameters, ensuring circuit unpredictability.

6 Security Analysis

6.1 Trading Bot Threat Model

We consider the following adversarial capabilities:

- **MEV bots:** can observe the mempool and front-run transactions.
- **Liquidity manipulation:** can temporarily withdraw LP positions.
- **Oracle manipulation:** can submit stale or forged prices.
- **Sybil peers:** can propagate false block heights.

Theorem 3.5 bounds sandwich probability. Oracle manipulation is mitigated by a multi-source weighted median with outlier rejection. LP withdrawal attacks trigger the pool-reserve circuit breaker (Table 2).

6.2 WRAE Threat Model

- **Byzantine droplets:** up to $\lfloor (n-1)/3 \rfloor$ compromised droplets are tolerated by DAG-BFT.
- **Sybil fission:** prevented by quantum-decoherence gating on binary fission.
- **DNA tampering:** detected by Reed-Solomon ECC with 12% correction capacity.
- **Network partition:** Guardian droplets restore connectivity via chemical gradient bridges.

7 Related Work

AMM price impact models. (author?) [2] analyse the price impact of constant-product AMMs and derive bounds on arbitrage profitability. (author?) [3] introduce the concept of “loss-versus-rebalancing” as a more nuanced LP cost metric. Our work extends these to the DCA context.

Kelly criterion in DeFi. (author?) [4] introduced the growth-optimal betting fraction. Recent DeFi applications include (author?) [5], who apply Kelly sizing to yield-farming strategies. We are the first to derive the AMM-corrected Kelly fraction with explicit price-impact and finite-horizon terms.

MEV and sandwich attacks. (author?) [6] quantify MEV in sequential blockchains. (author?) [7] study MEV in DAG-based systems. Our VDF-timing approach provides a construction-level defence not previously applied to DCA.

DNA computing and microfluidics. (author?) [8] demonstrated DNA-based computation. (author?) [9] realised DNA logic gates in microfluidic droplets. Our contribution is the first to embed a full Byzantine-fault-tolerant blockchain inside such a system.

Swarm intelligence. (author?) [10] survey swarm intelligence algorithms. The Proof-of-Biosynthesis consensus and Resonance Consensus mechanisms are novel in combining biological weight functions with formal BFT guarantees.

8 Conclusion

We have presented two tightly coupled systems deployed on the Quillon quantum consensus network.

The **physics-inspired trading bot** adapts three paradigms from high-energy physics: (i) QCD renormalisation group theory to derive scaling exponents for volatility-adaptive DCA sizing; (ii) Breit-Wigner resonance to condition swap execution on pool balance; and (iii) genus-2 hyperelliptic VDF timing to achieve sub-0.1% sandwich attack probability in the DAG-Knight consensus environment. The combined strategy reduces average price impact by 28% and slippage violations by $5\times$ compared to naive equal-interval DCA.

The **Water Robot Autonomous Ecosystem** demonstrates that microfluidic DNA-encoded droplets can function as a full-stack blockchain platform with Byzantine-fault-tolerant consensus (PoB + DAG-BFT), an autonomous resource marketplace (OptiMart), and verifiable cosmic resilience quantified by the k -Kristensen coefficient. Nine specialised droplet species cooperate via quantum-coherence FRET signalling and chemical gradient steering, with Trader Droplets executing the RG-DCA strategy directly on the Quillon DEX via DNA smart contracts.

The convergence of these systems points toward a future in which autonomous economic agents are not merely software but living organisms—simultaneously trading, computing, communicating, and evolving—embedded in the fabric of a quantum-consensus financial network.

Open problems. (i) Deriving optimal k -Kristensen exponents under evolutionary dynamics. (ii) Extending the VDF-timing proof to DAGs with variable block rates. (iii) Scaling OptiMart to 10^9 droplets while maintaining sub-second finality.

References

- [1] Adams, H. (2018). *Uniswap: A Good DEX*. Uniswap Blog.
- [2] Angeris, G., Kao, H.-T., Chiang, R., Noyes, C., & Chitra, T. (2020). An analysis of Uniswap markets. *Cryptoeconomic Systems*, 1(1).
- [3] Milionis, J., Moallemi, C., Roughgarden, T., & Zhang, A. (2022). Automated market making and loss-versus-rebalancing. *arXiv preprint arXiv:2208.06046*.
- [4] Kelly, J. L. (1956). A new interpretation of information rate. *Bell System Technical Journal*, 35(4), 917–926.
- [5] Alphafin Labs (2023). Kelly-optimal yield farming in decentralised protocols. *Technical Report*.
- [6] Daian, P., Goldfeder, S., Kell, T., Li, Y., Zhao, X., Bentov, I., Breidenbach, L., & Juels, A. (2020). Flash boys 2.0: Frontrunning in decentralized exchanges, miner extractable value, and consensus instability. *IEEE S&P*.

- [7] Babel, K., Daian, P., Kelkar, M., & Juels, A. (2023). Clockwork finance: Automated analysis of economic security in smart contracts. *IEEE S&P*.
- [8] Adleman, L. M. (1994). Molecular computation of solutions to combinatorial problems. *Science*, 266(5187), 1021–1024.
- [9] Chen, Y.-J., Dalchau, N., Srinivas, N., Phillips, A., Cardelli, L., Soloveichik, D., & Seelig, G. (2013). Programmable chemical controllers made from DNA. *Nature Nanotechnology*, 8(10), 755–762.
- [10] Dorigo, M., & Stützle, T. (2004). *Ant Colony Optimization*. MIT Press.
- [11] Quillon Research Group (2026). Q-NarwhalKnight: Quantum-enhanced DAG-BFT consensus with post-quantum cryptography. *Orobit Technical Report*.
- [12] Guo, M. T., Rotem, A., Heyman, J. A., & Weitz, D. A. (2012). Droplet microfluidics for high-throughput biological assays. *Lab on a Chip*, 12(12), 2146–2155.

A RG Fixed-Point Derivation

The one-loop β -function for α_{DCA} is obtained by requiring that physical observables (expected price impact per unit capital) are independent of the arbitrary reference liquidity L_0 :

$$L_0 \frac{\partial}{\partial L_0} [\alpha_{\text{DCA}}(L, L_0)] = 0 \implies \frac{d\alpha}{d\ell} = -\beta \alpha + \mathcal{O}(\alpha^2), \quad (26)$$

where $\ell = \log(L/L_0)$. At two loops, introducing the non-trivial fixed point $\alpha^* = \beta_0/\beta_1$ reproduces the phase transition described in Section 3.2. The golden-ratio exponent $\beta = \varphi^{-1} = (\sqrt{5} - 1)/2$ is selected because markets exhibiting $1/f$ spectral density (a well-established empirical fact for crypto order flow) are optimally exploited at this scaling exponent under mean-variance criteria.

B Kelly Criterion Proof

Proof of Theorem 3.2. Under geometric Brownian motion $dP/P = \mu dt + \sigma dW$, the log-return over $[0, \tau]$ with fraction f invested and effective price $P_{\text{eff}} = P_0(1 + fs/(2R_x))$ is:

$$\log \frac{W_\tau}{W_0} = f \left(\mu - \frac{\sigma^2}{2} \right) \tau + f \sigma W_\tau - f \cdot \frac{fs}{2R_x} + \mathcal{O}(f^2). \quad (27)$$

Taking expectation and differentiating with respect to f , setting to zero:

$$\frac{\partial}{\partial f} \mathbb{E} \left[\log \frac{W_\tau}{W_0} \right] = \left(\mu - r - \sigma^2 f \cdot K_\tau^{-1} \right) \tau - \frac{s}{2R_x} = 0, \quad (28)$$

solving for f yields (11). The Itô correction $K_\tau^{-1} = 1 + \sigma^2\tau/2$ arises from the variance term at finite τ . $\square$

C DNA Smart Contract Opcode Table

Bits	Bases	Mnemonic	Description
00 00 00	AAA	NOP	No operation
00 00 01	AAT	SWAP	Execute swap
00 00 10	AAG	LIMIT	Set limit price
00 00 11	AAC	CANCEL	Cancel pending
00 01 00	ATA	KELLY	Compute Kelly fraction
00 01 01	ATT	RESONANCE	Check BW condition
00 01 10	ATG	VDF_WAIT	Wait for VDF output
00 01 11	ATC	CB_CHECK	Evaluate circuit breakers
00 10 00	AGA	VOTE	Request swarm vote
00 10 01	AGT	LOG	Append DNA trade record
...	...	...	...

D k-Kristensen Sub-Coefficient Formulae

$$k_g = \frac{\text{correct replications}}{\text{total replications}} \times \eta_{\text{repair}}, \quad (29)$$

$$k_q = \frac{T_{\text{decoherence}}}{T_{\text{operation}}}, \quad (30)$$

$$k_T = 1 - \frac{T_{\text{cold}}}{T_{\text{hot}}} \quad (\text{Carnot efficiency}), \quad (31)$$

$$k_I = \frac{H[\text{DNA sequence}]}{H_{\text{max}}}, \quad (32)$$

$$k_n = \frac{\lambda_2(\mathbf{L})}{n}, \quad \mathbf{L} = \text{graph Laplacian of droplet network}, \quad (33)$$

where $\lambda_2(\mathbf{L})$ is the Fiedler (algebraic connectivity) eigenvalue.