

MEGAMAT 950

VIBRATION CONTROL



VIBRATION INSULATION PANEL MADE OF END-OF-LIFE TYRES RUBBER GRANULES AND FIBRES

■ TECHNICAL SPECIFICATION

Anti-vibration material supplied in panels, thickness 12,5/25 mm, made of rubber granules and fibres from End-of-Life Tyres (ELTs) compacted using a polyurethane binder in a hot process. A non-woven, non-stretch synthetic membrane is applied on one side of panel, for added protection; density 950 kg/m³. Panels dimensions are m 1,20 length, m 0,80 width. To be used for static and dynamic loads up to 2 N/mm².



■ APPLICATION AREA

Application fields	Load	Deformation
Static	up to 0,50 N/mm ²	~ 10%
Static and Dynamic	up to 2,00 N/mm ²	~ 30%
Load peaks (short time)	up to 4,00 N/mm ²	~ 50%

■ TECHNICAL DATA

		Tolerance	Standard
Thickness	12,5 - 25 mm	± 2	
Length	1,20 m	± 2%	
Width	0,80 m	± 2%	
Density	650 kg/m ³	± 10%	
Stress at strain 10%	0,50 N/mm ²	± 10%	EN ISO 29470
Static Modulus of Elasticity (Es) - strain 10%	5,00 N/mm ²	± 10%	EN ISO 29470
Dynamic Modulus of Elasticity (Ed) - strain 10%	14,2 N/mm ²	± 10%	
Loss factor (η)	0,137	± 10%	
Thermal conductivity coefficient (λ)	0,090		EN 12668
Inflammability	E		EN 13501-2


MEGAMAT 950

VIBRATION CONTROL




INSTALLATION INSTRUCTIONS FOR MEGAMAT


- 1** Prepare the excavation for the foundations and construct the sub-foundation




- 2** Lay the MEGAMAT panels on the sub-foundation, taking care to fit them together without leaving gaps or cavities along the joins




- 3** Seal the joins between the panels carefully with Stik tape and lay a waterproof protective sheet.




- 4** Prepare and position the formwork and reinforcing bars and construct the reinforced concrete foundation slab.




- 5** In the case of underground floors, construct the perimeter walls in reinforced concrete.



- 6** Glue the MEGAMAT panels along the perimeter walls, taking care to fit them together without leaving gaps or cavities along the joins



- 7** Seal the joins between the panels carefully with Stik tape



- 8** Complete construction of the building



SEE THE REFERENCES > VISIT THE WEBSITE

CONTACT THE TECHNICAL DEPARTMENT FOR MORE INFORMATION



www.isolgamma.com
PRG-MOD. 15 - REV. 4.1 14/07/25 EN

© Isolgamma Srl. The data and images are indicative and can be changed at any time without notice


ISOLGOMMA
SILENCE MAKERS

MEGAMAT 950


VIBRATION CONTROL




LOAD DEFLECTION CURVE



STATIC MODULUS OF ELASTICITY



DYNAMIC MODULUS OF ELASTICITY




MEGAMAT 950

VIBRATION CONTROL



NATURAL FREQUENCY



VIBRATION ISOLATION EFFICIENCY

