Floorplanning

- Course contents:
  - Normalized polish expression for slicing floorplans
  - Sequence pair for general (non-slicing) floorplans
  - Tree based non-slicing floorplans (B*-tree)
  - ILP for general floorplans
  - Modern floorplanning considerations



Motorola's PowerPC™ 604 RISC Microprocessor

Floorplanning/Placement

- Partitioning leads to
  - Blocks with well-defined **areas and shapes** (rigid/hard blocks).
  - Blocks with approximated areas and no particular shapes (flexible/soft blocks).
  - A **netlist** specifying connections between the blocks.
- Objectives
  - Find **locations** for all blocks.
  - Consider shapes of soft block and pin locations of all the blocks.



Floorplanning Problem

- Inputs to the floorplanning problem:
  - A set of blocks, hard or soft.
  - Pin locations of hard blocks.
  - A netlist.
- Objectives: minimize area, reduce wirelength for (critical) nets, maximize routability (minimize congestion), determine shapes of soft blocks



An optimal floorplan, in terms of area



A non–optimal floorplan

Floorplan Examples







PowerPC 604



Pentium 4

Early Layout Decision Methodology

- An IC is a 2-D medium; consider the dimensions of blocks in early stages of the design helps to improve the quality.
- Floorplanning gives early feedback
  - Suggests valuable architectural modifications
  - Estimates the whole chip area
  - Estimates delay and congestion due to wiring
- Floorplanning fits very well in a *top-down* design strategy; the *step-wise refinement* strategy also propagated in software design.
- Floorplanning considers the *flexibility* in the shapes and terminal locations of blocks.

Floorplan Design



- *Modules:* 

- *Area:* $A = xy$
- *Aspect ratio:* $r <= y/x <= s$
- *Rotation:* 
- *Module connectivity*



Slicing Floorplan Structure

- **Rectangular dissection:** Subdivision of a given rectangle by a finite # of horizontal and vertical line segments into a finite # of non-overlapping rectangles.
- **Slicing structure:** a rectangular dissection that can be obtained by repetitively subdividing rectangles horizontally or vertically.
- **Slicing tree:** A binary tree, where each internal node represents a vertical cut line or horizontal cut line, and each leaf a basic rectangle.
- **Skewed slicing tree:** One in which no node and its **right** child are the same.



Floorplan Order

- **Wheel:** The smallest non-slicing floorplans (Wang and Wong, TCAD, Aug. 92).
- **Order of a floorplan:** a slicing floorplan is of order 2.
- **Floorplan tree:** A tree representing the hierarchy of partitioning.



The two possible wheels.



A floorplan of order 5



Corresponding floorplan tree

Slicing Floorplan Design by Simulated Annealing

- Related work
  - Wong & Liu, “A new algorithm for floorplan design,” DAC-86.
    - Considers slicing floorplans.
  - Wong & Liu, “Floorplan design for rectangular and L-shaped modules,” ICCAD'87.
    - Also considers L-shaped modules.
  - Wong, Leong, Liu, *Simulated Annealing for VLSI Design*, pp. 31--71, Kluwer Academic Publishers, 1988.
- Ingredients
  - solution space
  - neighborhood structure
  - cost function
  - annealing schedule

Solution Representation

- An expression $E = e_1\ e_2 \ldots\ e_{2n-1}$, where $e_i \in \{1, 2, \ldots, n, H, V\}$, $1 \le i \le 2n\text{-}1$, is a **Polish expression** of length $2n$-1 iff
  1. every operand j, $1 \le j \le n$, appears exactly once in E;
  2. (**the balloting property**) for every subexpression $E_i = e_1 \ldots e_i$, $1 \le i \le 2n$-1, # operands > # operators.



- Polish expression ↔ Postorder traversal.
- *ijH*: rectangle *i* on bottom of *j*; *ijV*: rectangle *i* on the left of *j*.





$E = 16H2V75VH34HV$

$E = 16+2*75*+34+*$

Postorder traversal of a tree!

Redundant Representation





$E = 123H4VV$

non–skewed!



$E = 123HV4V$

skewed!

Non–skewed cases



..... HH .....



..... VV .....

- **Question:** How to eliminate ambiguous representation?

Normalized Polish Expression

- A Polish expression $E = e_1\ e_2\ \ldots\ e_{2n-1}$ is called **normalized** iff E has no consecutive operators of the same type (H or V).
- Given a **normalized** Polish expression, we can construct a **unique** rectangular slicing structure.





$E = 16H2V75VH34HV$

A normalized Polish expression

Neighborhood Structure

- **Chain:** *HVHVH* … or *VHVHV* …



- **Adjacent:** 1 and 6 are adjacent operands; 2 and 7 are adjacent operands; 5 and *V* are adjacent operand and operator.
- 3 types of moves:
  - *M1* (**Operand Swap**): Swap two adjacent operands.
  - *M2* (**Chain Invert**): Complement some chain (*V* = *H*, *H* = V).
  - *M3* (**Operator/Operand Swap**): Swap two adjacent operand and operator.

Effects of Perturbation



- **Question:** The balloting property holds during the moves?
  - *M1* and *M2* moves are OK.
  - **Check the *M3* moves!** Reject "illegal" *M3* moves.
- **Check *M3* moves:** Assume that *M3* swaps the operand e_i with the operator e_{i+1}, $1 \le i \le k\text{-}1$. Then, the swap will not violate the balloting property iff $2N_{i+1} < i$.
  - N_k: # of operators in the Polish expression $E = e_1\ e_2\ \ldots\ e_k$, $1 \le k \le 2n\text{-}1$

Cost Function

- $\phi = A + \lambda W$.
  - A: area of the smallest rectangle
  - W: overall wiring length
  - λ : user-specified parameter



- $W = \sum_{ij} c_{ij}\, d_{ij}$.
  - c_{ij}: # of connections between blocks i and j.
  - d_{ij}: center-to-center distance between basic rectangles i and j.



Area Computation for Hard Blocks

- Allow rotation









- Wiring cost?
  - Center-to-center interconnection length

Incremental Computation of Cost Function

- Each move leads to only a minor modification of the Polish expression.
- At most **two paths** of the slicing tree need to be updated for each move.



Incremental Computation of Cost Function (cont)



E = 12H34V56VHV **E = 12H34V56HVH**



E = 12H34V56VHV

E = 123H4V56VHV

Annealing Schedule

- Initial solution: 12*V*3*V* … *nV*.



- $T_i = r^i T_0$, i = 1, 2, 3, …; r =0.85.
- At each temperature, try *kn* moves (k = 5-10).
- Terminate the annealing process if
  - # of accepted moves < 5%,
  - temperature is low enough, or
  - run out of time.

Algorithm: Wong-Liu (P, ε, r, k)

```
1 begin
2 E ← 12V3V4V … nV; /* initial solution */
3 Best ← E; T0 ← Δ_avg / ln(P) ; M ← MT ← uphill ← 0; N = kn;
4 repeat
5   MT ← uphill ← reject ← 0;
6   repeat
7     SelectMove(M);
8     Case M of
9     M1: Select two adjacent operands ei and ej; NE ← Swap(E, ei, ej);
10    M2: Select a nonzero length chain C; NE ← Complement(E, C);
11    M3: done ← FALSE;
12       while not (done) do
13          Select two adjacent operand ei and operator ei+1;
14          if (ei-1 ≠ ei+1) and (2 Ni+1 < i) then done ← TRUE;
15       NE ← Swap(E, ei, ei+1);
16    MT ← MT+1; Δcost ← cost(NE) - cost(E);
17    if (Δcost ≤ 0) or (Random < e^(−Δcost/T) )
18     then
19        if (Δcost > 0) then uphill ← uphill + 1;
20        E ← NE;
21        if cost(E) < cost(best) then best ← E;
22     else reject ← reject + 1;
23   until (uphill > N) or (MT > 2N);
24   T ← rT; /* reduce temperature */
25 until (reject/MT > 0.95) or (T < ε) or OutOfTime;
26 end
```

Extension to L-Shaped Modules

- Unary operator *L*: Change an L-shaped figure into a rectangle
- Binary operators V_1, V_2, H_1, H_2: Combine 2 rectangles or L-shaped figures to form a rectangle or an L-shaped figure.
- Can generate non-slicing floorplans.





E = A L B H1 C D V2 L E H2 V1 L

Orientation:



Representation:



(2, 1.5, 3, 1)

Shape Curve for Floorplan Sizing

- A soft (flexible) blocks *b* can have different aspect ratios, but is with a fixed area *A*.
- The shape function of *b* is a hyperbola: $xy = A$, or $y = A/x$, for width *x* and height *y*.
- Very thin blocks are often not interesting and feasible to design
  - Add two straight lines for the constraints on aspect ratios.
  - Aspect ratio: $r \le y/x \le s$.



Shape Curve

- Since a basic block is built from discrete transistors, it is not realistic to assume that the shape function follows the hyperbola continuously.
- In an extreme case, a block is rigid/hard: it can only be rotated and mirrored during floorplanning or placement.



The shape curve of a 2 × 4 hard block.

Shape Curve (cont)

- In general, a *piecewise linear* function can be used to approximate any shape function.
- The points where the function changes its direction, are called the corner (*break) points* of the piecewise linear function.



Feasible Implementations

- Shape curves correspond to different kinds of constraints where the shaded areas are feasible regions.



Vertical Abutment

- Composition by vertical abutment (horizontal cut) ⇒ the addition of shape functions.



Deriving Shapes of Children

- A choice for the minimal shape of a composite block fixes the shapes of its children blocks.



Slicing Floorplan Sizing

- The shape functions of all leaf blocks are given as piecewise linear functions.
- Traverse the slicing tree to compute the shape functions of all composite blocks (bottom-up composition).
- Choose the desired shape of the top-level block
  - Only the corner points of the function need to be evaluated for area minimization.
- Propagate the consequences of the choice down to the leaf blocks (top-down propagation).
- The sizing algorithm runs in polynomial time for slicing floorplans
  - NP-complete for non-slicing floorplans

P*-admissible Solution Space

- **P-admissible** solution space for Problem P (Murata et al., ICCAD-95)
  1. the solution space is finite,
  2. every solution is feasible,
  3. evaluation for each configuration is possible in polynomial time and so is the implementation of the corresponding configuration (P), **and**
  4. the configuration corresponding to the best evaluated solution in the space coincides with an optimal solution of P. (admissible)
- **P*-admissible** solution space (Lin & Chang, DAC-2002)

  5. The relationship between any two blocks is defined in the representation (topological representation).
- Slicing floorplan is **not** P-admissible. Why?
- P*-admissible floorplan representations: **Sequence Pair, BSG, TCG, TCG-S.**

Sequence Pair (SP)

- Murata, Fujiyoshi, Nakatake, Kajitani, "Rectangle-Packing Based Module Placement," ICCAD-95 (also in *The Best of ICCAD*)
- Represent a packing by a pair of module-name sequences (e.g., (*abdecf*, *cbfade*)).
  - Solution space: $(n!)^2$
- Correspond all pairs of the sequences to a P-admissible solution space.
- Search in the P-admissible solution space (by simulated annealing).
  - Swap two nodes only in a sequence
  - Swap two nodes in both sequences





A floorplan



Loci of module b

Relative Module Positions

- A floorplan is a partition of a chip into **rooms**, each containing at most one block.
- **Locus** (right-up, left-down, up-left, down-right)
  1. Take a non-empty room.
  2. Start at the center of the room, walk in two alternating directions to hit the sides of rooms.
  3. Continue until to reach a corner of the chip.
- **Positive locus Γ_+:** Union of right-up locus and left-down locus.
- **Negative locus Γ_-:** Union of up-left locus and down-right locus.



Loci of module b *Positive loci: abdecf* *Negative loci: cbfade*

Geometrical Information

- No pair of positive (negative) loci cross each other, i.e., **loci are linearly ordered**.
- SP uses two sequences (Γ_+, Γ_-) to represent a floorplan.
  - **H-constraint:** (..a..b.., ..a..b..) iff a is on the left of b
  - **V-constraint:** (..a..b..,..b..a..) iff b is below a



Loci of module b



Positive loci: abdecf



Negative loci: cbfade

(Γ_+, Γ_-) = (abdecf, cbfade)

($\square_+$, $\square_-$)-Packing

- For every SP ($\square_+$, $\square_-$), there is a ($\square_+$, $\square_-$) packing.
- **Horizontal constraint graph** $G_H(V, E)$ (similarly for $G_V(V, E)$):
  - V: source s, sink t, n vertices for modules.
  - E: (s, x) and (x, t) for each module x, and (x, y) iff x must be left to y.
  - **Vertex weight:** 0 for s and t, **width** of module x for the other vertices.



Packing for sequence pair: (ubdecf, cbfude)



Horizontal constraint graph (Transitive edges are not shown)



Vertical constraint graph (Transitive edges are not shown)

Cost Evaluation for Sequence Pair (1/3)

- Graph-based packing computation
  - **Optimal** ($\square_+$, $\square_-$)-Packing can be obtained in $O(n^2)$ time by applying a longest path algorithm on a vertex-weighted directed acyclic graph. (Murata et.al., ICCAD-95)
    - G_H and G_V are independent.
    - The X and Y coordinates of each module are the minimum values of the longest path length between s and the corresponding vertex in G_H and G_V, respectively.



Cost Evaluation for Sequence Pair (2/3)

- Graph-based packing computation (cont)
  - Building constraint graph (relative placement computation)
    - $O(n^2)$ time (Murata et.al., ICCAD-95)
    - $O(nlogn)$ time (Lin et.al., ISCAS-2000) : Direct view algorithm
  - Mapping (absolute placement computation)
    - $O(n^2)$ -> $O(n\ logn)$
  - Incremental packing computation
    - $O(\sqrt{n}\ log\sqrt{n}\ )$ (Lin et.al., ECCTD-2001)

Cost Evaluation for Sequence Pair (3/3)

- Non-graph-based packing computation
  - Maximum-weighted common subsequence (Tang & Wong, DATE-2000 and ASP-DAC-2001)
    - Compute block positions
    - Based on computing the longest common subsequence in a pair of weighted sequences
  - Cost evaluation can be done in $O(n \lg \lg n)$ time (ASP-DAC-2001)

Maximum-Weight Common Subsequence (MWCS) (1/6)

- A weighted sequence is a sequence on a given set *S*, and every element in *S* has a weight.
- Example:

  A sequence (4 3 1 6 2 5)

  weight: 4 3 3 2 4 6
- Given 2 weighted sequences *X* and *Y*, a sequence *Z* is a common subsequence of *X* and *Y* if *Z* is a subsequence of both *X* and *Y*.
- Example:

  X=(4 3 1 6 2 5) *Y*=(6 3 5 4 1 2)

  Z=(3 1 2) is a common subsequence

Maximum-Weight Common Subsequence (MWCS) (2/6)

- The length of a common subsequence $Z=(z_1 z_2 \ldots z_n)$ is: $\sum_{i=1}^{n} w(z_i)$
- MWCS is the common subsequence with the maximal length:

$$\max_{Z} \sum_{i} w(z_i)$$

- Example:

X=(4 3 1 6 2 5) Y=(6 3 5 4 1 2)

weight: 2 3 4 6 3 4 6 3 4 2 4 3

(3 1 2) is a MWCS. Its length is 10=3+4+3.

Maximum-Weight Common Subsequence (MWCS) (3/6)



5 paths correspond to
5 comm. subseq. of (X, Y)

4 1 2
3 1 2
3 5
6 2
6 5
weight = width of block

Correspondence with constraint graph G_h

(X, Y)=<4 3 1 6 2 5, 6 3 5 4 1 2>

Maximum-Weight Common Subsequence (MWCS) (4/6)



5 paths correspond to
5 comm. subseq. of (X^R, Y)

6 3 4
6 1
5 4
5 1
5 2
weight = height of block

Correspondence with constraint graph G_v
(X^R, Y)=<5 2 6 1 3 4, 6 3 5 4 1 2>
X^R is the reverse of X

Maximum-Weight Common Subsequence (MWCS) (5/6)



Oblique grid



placement

Seq-Pair (X,Y)=(4 3 1 6 2 5, 6 3 5 4 1 2), weight: blocks' width

Maximum-Weight Common Subsequence (MWCS) (6/6)



Oblique grid



placement

Seq-Pair, (X^R, Y)= (5 2 6 1 3 4, 6 3 5 4 1 2), weights: blocks' height

B*-Tree: Compacted Floorplan Representation

- Chang et. al., "B*-tree: A new representation for non-slicing floorplans," DAC-2k.
  1. Compact modules to left and bottom.
  2. Construct an ordered binary tree (B*-tree).
     - Left child: the lowest, adjacent block on the right ($x_j = x_i + w_i$).
     - Right child: the first block above, with the same x-coordinate ($x_j = x_i$).



B*-tree Packing

- x-coordinates can be determined by the tree structure.
  - Left child: the lowest, adjacent block on the right ($x_j = x_i + w_i$).
  - Right child: the first block above, with the same *x*-coordinate ($x_j = x_i$).
- y-coordinates?



Computing y-coordinates

- Reduce the complexity of computing a y-coordinate to amortized O(1) time. (same as in O-tree)



Contour Data Structure



C = <(0,0), **(0,6), (9,6), (9,0),** (∞,0)>



C = <(0,0), (0,6), (9,6), **(9,8)**, **(15,8), (15,0)**, (∞,0)>



C = <(0,0), **(0,12), (3,12), (3,6),** (9,6), (9,8), (15,8), (15,0), (∞,0)>



C = <(0,0), (0,12), (3,12), **(3,13), (6,13), (6,6),** (9,6), (9,8), (15,8), (15,0), (∞,0)>



C = <(0,0), (0,12), (3,12), (3,13), **(6,13), (12,13), (12,8),** (15,8), (15,0), (∞,0)>



C = <(0,0), **(0,15), (12,15), (12,13),** (12,8), (15,8), (15,0), (∞,0)>

B*-Tree Perturbation

- Op1: rotate a macro
- Op2: move a node to another place
- Op3: swap two nodes



Simulated Annealing Using B*-trees

- The cost function is based on problem requirements.



Pros and Cons

- Advantages
  - Binary tree based, efficient and easy.
  - Flexible to deal with hard, preplaced, soft, and rectilinear modules.
  - Transformation between a tree and its placement takes only linear time (v.s. $O(n^2)$ or $O(n \lg \lg n)$ for sequence pair).
  - Operate only on one B*-tree (v.s. 2 O-trees).
  - Can evaluate area cost incrementally.
  - Smaller solution space: only $O(n!\, 4^n / n^{1.5})$ combinations (v.s. $O((n!)^2)$ for sequence pair).
  - Directly corresponds to multilevel framework for large-scale floorplan designs.
- Disadvantages
  - Representation may change after packing.
  - Less flexible than sequence pair in representation
    - Can represent only compacted placement.

B*-Tree May Change after Packing



For compacted floorplan representations, the representation might change after packing.
The resulting placement might not correspond to the original B*-tree due to the compacting operation during packing.

Coping with Pre-placed Modules

- If there are modules ahead or lower than b_i so that b_i cannot be placed at its fixed position (x^f_i, y^f_i), exchange b_i with the module in $D_i = \{b_j \mid (x_j, y_j) \leq (x^f_i, y^f_i)\}$ that is closest to (x^f_i, y^f_i).
- Incremental area cost update is possible.
  - E.g., the positions of b_0, b_7, b_8, b_{11}, b_9, b_{10}, and b_1 (before b_2 in the DFS order of T) remain unchanged after the exchange since they are in front of b_2 in the DFS order.



b_6 is a preplaced module

Coping with Rectilinear Modules

- Wu, Chang, Chang, "Rectilinear block placement using B*-trees," ICCD-00
- Partition a rectilinear module into rectangular sub-modules.



- Keep **location constraints** for the sub-modules.
  - E.g., Keep the right sub-module as the left child in the B*-tree.
- Align sub-modules, if necessary.
- Treat the sub-modules of a module as a whole during processing.



Coping with Soft Modules (1/2)

- Step1: Change the shape of the inserted soft module.
- Step2: Change the shapes of other soft modules.



Coping with Soft Modules (1/2)

- Step1: Change the shape of the inserted soft module
- Step2: Change the shape of other soft modules



Coping with Soft Modules (2/2)

- Step1: Change the shape of the inserted soft module
- Step2: Change the shapes of other soft modules



Coping with Soft Modules (2/2)

- Step1: Change the shape of the inserted soft module
- Step2: Change the shape of other soft modules



Perturbations & Solutions

- Perturbing B*-trees in simulated annealing
  - Op1: Rotate a module.
  - [Op2: Flip a module.]
  - Op3: Move a module to another place.
  - Op4: Swap two modules.
- ami49: Area = 36.74 mm^2; dead space = 3.53%; CPU time = 0.25 min on SUN Ultra 60 (optimum = 35.445 mm^2).



ami49



Rectangular, L–, and T–shaped modules

Multilevel B*-trees

- Lee, Hsu, Chang, Yang, "Multilevel floorplanning/placement for large-scale modules using B*-trees," DAC-2003.
- Two stages for MB*-tree: clustering followed by declustering.
- Clustering
  - Iteratively groups a set of modules based on area utilization and module connectivity.
  - Constructs a B*-tree to keep the geometric relations for the newly clustered modules.
- Declustering
  - Iteratively ungroups a set of the previously clustered modules (i.e., perform tree expansion)
  - Refines the solution using simulated annealing.



Multilevel B*-tree Example



(a) 7 modules



(b) Cluster 5, 6, 7 into 8 based on area & connectivity density; construct a B*-tree subtree



(c) Cluster 1, 2, 4 into 9; construct a B*-subtree



(d) Cluster 3, 8, 9 into 10; Construct a B*-subtree



(e) Decluster 10 to 3, 8, 9



(f) Refine the solution by moving 8

Multilevel B*-tree Example (cont'd)



(g) Decluster 9 to 1, 2, 4



(h) Refine the solution by moving 2, 3



(i) Decluster 8 to 5, 6, 7



(j) Refine the solution by moving 4

Floorplanning by Mathematical Programming

- Sutanthavibul, Shragowitz, and Rosen, "An analytical approach to floorplan design and optimization," 27th DAC, 1990.
- Notation:
  - w_i, h_i: width and height of module M_i.
  - (x_i, y_i): coordinate of the lower left corner of module M_i.
  - $a_i \le w_i / h_i \le b_i$: aspect ratio w_i / h_i of module M_i. (Note: We defined aspect ratio as h_i / w_i before.)
- Goal: Find a mixed **integer linear programming (ILP)** formulation for the floorplan design.
  - ***Linear*** constraints? Objective function?



Nonoverlap Constraints

- Two modules M_i and M_j are nonoverlap, if at least one of the following linear constraints is satisfied (cases encoded by p_{ij} and q_{ij}):

		p_{ij}	q_{ij}
M_i to the left of M_j:	$x_i + w_i \leq x_j$	0	0
M_i below M_j:	$y_i + h_i \leq y_j$	0	1
M_i to the right of M_j:	$x_i - w_j \geq x_j$	1	0
M_i above M_j:	$y_i - h_j \geq y_j$	1	1

- Let W, H be upper bounds on the floorplan width and height, respectively.
- Introduce two 0, 1 variables p_{ij} and q_{ij} to denote that one of the above inequalities is enforced; e.g., $p_{ij} = 0$, $q_{ij} = 1 \Rightarrow y_i + h_i \leq y_j$ is satisfied

$$
\begin{aligned}
x_i + w_i &\leq x_j + W(p_{ij} + q_{ij}) \\
y_i + h_i &\leq y_j + H(1 + p_{ij} - q_{ij}) \\
x_i - w_j &\geq x_j - W(1 - p_{ij} + q_{ij}) \\
y_i - h_j &\geq y_j - H(2 - p_{ij} - q_{ij})
\end{aligned}
$$





Cost Function & Constraints

- Minimize *Area* = *xy*, **nonlinear!** (*x, y*: width and height of the resulting floorplan)
- How to fix?
  - Fix the width *W* and minimize the height *y*!
- Four types of constraints:
  1. no two modules overlap ($\forall\ i, j$: $1 \le i < j \le n$);
  2. each module is enclosed within a rectangle of width *W* and height *H* ($x_i + w_i \le W$, $y_i + h_i \le H$, $1 \le i \le n$);
  3. $x_i \ge 0$, $y_i \ge 0$, $1 \le i \le n$;
  4. $p_{ij}, q_{ij} \in \{0, 1\}$.
- w_i, h_i are known.

Mixed ILP for Floorplanning

Mixed ILP for the floorplanning problem with rigid, fixed modules.

$$\begin{aligned}
& \min \quad y \\
& \textit{subject to} \\
& x_i + w_i \le W, && 1 \le i \le n && (1)\\
& y_i + h_i \le y, && 1 \le i \le n && (2)\\
& x_i + w_i \le x_j + W(p_{ij} + q_{ij}), && 1 \le i < j \le n && (3)\\
& y_i + h_i \le y_j + H(1 + p_{ij} - q_{ij}), && 1 \le i < j \le n && (4)\\
& x_i - w_j \ge x_j - W(1 - p_{ij} + q_{ij}), && 1 \le i < j \le n && (5)\\
& y_i - h_j \ge y_j - H(2 - p_{ij} - q_{ij}), && 1 \le i < j \le n && (6)\\
& x_i, y_i \ge 0, && 1 \le i \le n && (7)\\
& p_{ij}, q_{ij} \in \{0, 1\}, && 1 \le i < j \le n && (8)
\end{aligned}$$

- Size of the mixed ILP: for *n* modules,
  - # continuous variables: $O(n)$; # integer variables: $O(n^2)$; # linear constraints: $O(n^2)$.
  - Unacceptably huge program for a large *n*! (How to cope with it?)
- Popular LP software: LINDO, lp_solve, etc.

Mixed ILP for Floorplanning (cont)

Mixed ILP for the floorplanning problem: rigid, freely oriented modules.

$$\min \quad y$$

subject to

$$x_i + r_i h_i + (1 - r_i) w_i \leq W, \qquad 1 \leq i \leq n \qquad (9)$$

$$y_i + r_i w_i + (1 - r_i) h_i \leq y, \qquad 1 \leq i \leq n \qquad (10)$$

$$x_i + r_i h_i + (1 - r_i) w_i \leq x_j + M(p_{ij} + q_{ij}), \qquad 1 \leq i < j \leq n \qquad (11)$$

$$y_i + r_i w_i - (1 - r_i) h_i \leq y_j + M(1 + p_{ij} - q_{ij}), \qquad 1 \leq i < j \leq n \qquad (12)$$

$$x_i - r_j h_j + (1 - r_j) w_j \geq x_j - M(1 - p_{ij} + q_{ij}), \qquad 1 \leq i < j \leq n \qquad (13)$$

$$y_i - r_j w_j - (1 - r_j) h_j \geq y_j - M(2 - p_{ij} - q_{ij}), \qquad 1 \leq i < j \leq n \qquad (14)$$

$$x_i, y_i \geq 0, \qquad 1 \leq i \leq n \qquad (15)$$

$$p_{ij}, q_{ij} \in \{0, 1\}, \qquad 1 \leq i < j \leq n \qquad (16)$$

- For each module *i* with free orientation, associate a 0-1 variable r_i:
  - r_i = 0: 0° rotation for module *i*.
  - r_i = 1: 90° rotation for module *i*.
- *M* = max{*W*, *H*}.

Reducing the Size of the Mixed ILP

- Time complexity of a mixed ILP: exponential!
- Recall the large size of the mixed ILP: # variables, # constraints: $O(n^2)$.
  - How to fix it?
- Key: Solve a partial problem at each step
  - successive augmentation
  - Classic cluster-growth greedy approach
  - Repeatedly select subsets of modules and formulate corresponding linear programs, along with additional constraints from previously selected modules
- Questions:
  - How to select next subgroup of modules? □ linear ordering based on connectivity. (cluster growth)
  - How to minimize the # of required variables?



Reducing the Size of the Mixed ILP (cont)

- Size of each successive mixed ILP depends on (1) # of modules in the next group; (2) "size" of the partially constructed floorplan.
- Keys to deal with (2)
  - Minimize the problem size of the partial floorplan.
  - Replace the already placed modules by a set of covering rectangles.
  - # rectangles is usually much smaller than # placed modules.



Interconnect-Centric Floorplanning

- Floorplanning greatly influences interconnect structure





Interconnect Planning

- Pin assignment and routing of global interconnects
- Buffer insertion and sizing
  - Buffer block planning
- Wire sizing



Floorplanning and Interconnect Planning



Interconnect-Centric Floorplanning: ami49 (1/2)



Interconnect-Centric Floorplanning: ami49 (2/2)



Fixed-Outline Floorplanning

- Input
  - Modules, netlist, fixed outline
- Output
  - Module positions, orientations
- Objectives
  - Minimize the half-perimeter wirelength (HPWL)
  - All modules are within the fixed die (fixed-outline constraint) and no overlaps occur between modules



Fixed-Outline Constraint

- Fixed-outline floorplanning is more prevailing in modern VLSI design
- Given the *maximum white-space fraction* Γ and *desired aspect ratio R*,* the outline is defined by

$$H^* = \sqrt{(1+\Gamma)AR^*} \qquad W^* = \sqrt{(1+\Gamma)A/R^*}$$

  - $R^* = H^*/W^*,\ H^*W^* = (1+\Gamma)A$
- Cost for floorplan *F*

$$\Phi(F) = \alpha A + \beta L + (1-\alpha-\beta)(R^*-R)^2$$

A	**Block area**
L	**Wirelength**
R^*	**Fixed-outline aspect ratio**
R	**Current floorplan aspect ratio**

Defer: Fixed-Outline Slicing Floorplan



- Block orientation
- Slice line direction (H/V)
- Left-right or top-bottom relative order

J. Z. Yan, and C. Chu, "DeFer: Deferred Decision Making Enabled Fixed-Outline Floorplanning Algorithm," in IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, pp. 367–381, 2010.

Optimal Slack-Driven Block Shaping Algorithm in Fixed-Outline Floorplanning

ISPD 2012 Best Paper Award
(by J. Z. Yan and C. Chu)

- **Input**
  - n Blocks
    - Area A_i for block i
    - Width bounds $W_i^{\min}$ and $W_i^{\max}$ for block i
    - Height bounds $H_i^{\min}$ and $H_i^{\max}$ for block I
  - Constraint graphs G_h and G_v
  - Fixed-outline region
- **Output**
  - Block coordinates (x_i, y_i), width w_i and height h_i
    - All blocks inside fixed-outline region
    - All blocks without overlaps

Optimal Slack-Driven Block Shaping Algorithm in Fixed-Outline Floorplanning



- G_h, G_v
- Shape of n blocks

horizontal slack

$$s_i^h = \max(0, \Delta_{x_i})$$

vertical slack

$$s_i^v = \max(0, \Delta_{y_i})$$

Optimal Slack-Driven Block Shaping Algorithm in Fixed-Outline Floorplanning

- Horizontal Critical Path (**HCP**)
- Vertical Critical Path (**VCP**)





Length of VCP = Layout height y_{n+1}

Basic Slack-Driven Shaping

- Soft blocks are shaped *iteratively*.
- At each iteration, apply two operations:

  - Globally distribute the total amount of slack to the individual soft block.
- Algorithm stops when there is no identified soft block to shape.
- Layout height is monotonically reducing, and layout width is bouncing, but always within the upper bound.

Summary: Floorplanning (1/3)

- Floorplanning objectives: (1) minimize area, (2) meet timing constraints, (3) maximize routability (minimize congestion), ((4) determine shapes of soft modules)
- Existing representations
  - Slicing: slicing tree (DAC-82), normalized Polished expression (DAC-86)
  - Mosaic: CBL (ICCAD-2k), Q-Sequence (AP-CAS-2k, DATE-02), Twin binary tree (ISPD-01)
  - Compacted: O-tree (DAC-99), B*-tree (DAC-2k), MB*-tree (DAC-03), CS (TVLSI, 2003)
  - General: SP (ICCAD-95), BSG (ICCAD-96), TCG (DAC-01), TCG-S (DAC-02).
- P*-admissible representations: all representations for general floorplans.
- P-admissible, non-P*-admissible representations (for area): all for compacted floorplans.
- What makes a good representation?
  - Easy, effective, efficient, flexible, stable

Summary: Floorplanning (2/3)

- Other issues
  - Soft module: shape curve (NPE, DAC-86), (Integer) linear programming (DAC-90, DAC-2k), stretching range (B*-tree, DAC-2k), Lagrangian relaxation (SP, ISPD-2k)
  - Preplaced module: ASPDAC-98 (BSG), ASPDAC-01 (SP), DAC-2K (B*-tree), ISCAS-01 (B*-tree), DAC-02 (TCG-S)
  - Symmetry module: DAC-99 (SP), ICCAD-02 (B*-tree)
  - Rectilinear module: TCAD-2K (SP), ICCAD-98 (SP), ISPD-98 (SP), ISPD-01 (SP), DATE-02 (TCG), TVLSI-02 (TCG), ICCD-2K (B*-tree), ACM TODAES-03 (B*-tree), ISPD-01 (O-tree)
  - Range constraint: ISPD-99 (NPE), ASPDAC-01 (SP), DAC-02 (TCG-S)
  - Boundary constraint: ASPDAC-01 (SP), DAC-02 (TCG-S), IEE Proc.-02 (B*-tree)
- Since each representation has its pros and cons, so maybe we can
  - Integrate two or more representations to get a better one (e.g., TCG-S, DAC-02)
  - Apply different representations at different stages
- Large-scale module floorplanning/placement (MB*-tree, DAC-03)

Summary: Floorplanning (3/3)

- Performance-driven floorplanning
  - Buffer planning (ICCAD-99, ISPD-2K, DAC-01, ASPDAC-03)
  - Wire planning (ICCAD-99)
  - Power supply planning (ASPDAC-01)
  - Power supply noise-aware floorplanning (ASPDAC-03)
- Fixed-outline floorplanning

2003 MOE IC/CAD Contest: Problem 1

- **Chip Floorplanning with Hard/Soft Macros**



Input files :

[problem1.mac]:

```
.chip_bbox   (100,100)
.macro   A   2000   0.6   1.5
.macro   B   3000   0.8   1.2
.macro   C   3000   0.8   1.5
.macro   D   2000   0.8   0.8   // hard macro
```

[problem1.spc]:

```
.net   N1   A   B   C
```

Output files :

[problem1.rpt]

```
.macro   A   (0, 50) (40, 100)
.macro   B   (40, 50) (100, 100)
.macro   C   (0, 0) (60, 50)
.macro   D   (60, 0) (100, 50)
.mst   110
.area   10000
```

2003 MOE IC/CAD Contest: Problem 3

- **Block and Input/Output Buffer Placement for Skew/Delay Minimization in Flip-chip Design**



2005 MOE IC/CAD Contest Problem 5

- Chip placement for MPW (Multiple Project Wafer)
  - Manufacturing cost minimization in shuttle mask sharing in getting certain amount of prototyping chips
- Needs to decide the floorplan of reticle(s) and cut lines for wafer(s) in order to get less cost
  - Also needs to consider manufacturing technology issue (#metal layers)
- Needs some algorithmic aspects and geometrical thinking
- References:
  - A.B. Kahng et.al., “Multi-Project Reticle Floorplanning and Wafer Dicing”, ISPD 2004
  - Report from previous generation problem (online soon)

Illustrations for MPW



Fig. 1. A Multi-Project Wafer