

THE V4 FIELD MANUAL

SICK OLLIE CREATOR STUDIO + TOOLKIT

4.0.0

**MAKE IT.
KEEP WHAT WORKS.**

A connected workflow for prompts, LoRAs, outfits and images. Start with one generation.
Build a Library you want to return to.

CHOOSE

GENERATE

COMPARE

REUSE

WORKFLOWS FIRST / POWER TOOLS WHEN YOU NEED THEM

FIND YOUR WAY

Start anywhere.

Read pages 4-6 for the core loop. Follow the full path or jump to the task at hand.

Your first five minutes	04
One connected studio	05
Four creative libraries	06
Save something you can use again	07
Review at full size	08
The right actions for the record	09
Choose the model and LoRA	10
Build a controlled LoRA stack	11
Three ways to supply a prompt	12
Make placeholders do the work	13
Set the canvas, then the seed	14
Compare without losing the moment	15
Bring an old image back to work	16
Recover what the image carries	17
Save images with a way back	18
Small controls, shorter workflows	19
Load, Queue or Queue Next?	20

FIND YOUR WAY

Start anywhere.

Read pages 4-6 for the core loop. Follow the full path or jump to the task at hand.

Make the Library worth browsing	21
Review while generation continues	22
Curate a scope with confidence	23
Move a Library, or just a capsule	24
Browse and test your LoRAs	25
Give every checkpoint a fair test	26
From piece to complete Look	27
Forge a log, then curate it	28
Resolve once. Place deliberately.	29
Use the extra sockets when needed	30
Change files with a reviewed plan	31
Clean the intended thing	32
Know where your work lives	33
Upgrade the product, keep your work	34
When something feels wrong	35
Install, import, make something	36

CONTROL FINDER

The final pages provide a workflow-ordered reference to the useful controls covered in the guide.

START HERE

Your first five minutes

Choose → Load → Generate → Compare → Save → Reuse

01 / Choose your engine

Add Loader Core, Prompt Core, Generation Core, Output Core and Preview Core from the ComfyUI node menu. Wire them as shown on the next page. In Loader Core, choose an installed diffusion model. In Generation Core, select its compatible text encoder, VAE and CLIP type. Select settings appropriate to your own model before queueing; the package includes no sample workflow or model weights.

02 / Make one image

Keep Main LoRA disabled for a first base-model check, or enable an installed LoRA and set its strength. Set Prompt Core to Manual and enter a complete description, such as: photo of a woman wearing a cyan rain jacket in a sunlit greenhouse. Choose a modest canvas and queue once. Generation Core sends samples and VAE to Output Core; Output saves and passes images to Preview Core.

03 / Keep the result useful

Press Pin + Compare on a result you want to study. Change one prompt or model setting and generate again. Clear removes the reference. Save to Library preserves the displayed result with available generation information. Open Creative Library from Studio Hub when you want to reuse it.

Start small, then automate

First make one successful image. Then import your own TXT content or a separately supplied Library Pack, try a Template, and test a small preview run. Installed model files are selected locally; they are not bundled.

START HERE

One connected studio

The Library supplies reusable choices. The nodes turn those choices into images.



What travels between systems

LoRA Library → Loader	An installed LoRA or Collection scope
Templates / Prompts → Prompt	Reusable source or resolved prompt text
Wardrobe / Looks / Scenes → Prompt	Outfit A/B/C and Scene values
Metadata → Prompt + Generation	Recovered text and an available seed
Preview / Metadata → Creative Library	An image plus reusable generation information

A useful separation

Generation Core produces latent samples and a VAE. Output Core decodes and saves them in a simple Studio workflow, then supplies the IMAGE used by Preview Core. Image Metadata Core is a separate reuse station.

THE CREATIVE LIBRARY

Four creative libraries

Find the ingredient by what you want to reuse.

TEMPLATES

Formulas with recognized unresolved placeholders.
Example: photo of a woman wearing OUTFIT in SCENE.

PROMPTS

Resolved, token-free text. Example: photo of a woman wearing a cyan rain jacket in a greenhouse.

OUTFITS

Wardrobe holds pieces and styling material. Looks holds complete outfit values ready for an Outfit slot.

SCENES

Location and environment values ready for Prompt Core's Scene component.

HOME

Where the asset lives: its canonical category/subcategory. Move Home changes that location.

COLLECTION

A reusable creative grouping. One asset can participate in multiple Collections without moving.

Open the right workspace

Studio Hub brings together Creative Library, LoRA Library, Outfit Forge and LoRA Organizer. Creative Library manages text and generation assets. LoRA Library manages the visual review of installed model files.

THE CREATIVE LIBRARY

Save something you can use again

An image becomes more valuable when its source survives.

SAVE TO LIBRARY

Capture a displayed generation or a metadata-bearing image as reusable Library material. Available prompt assembly and settings travel with it.

GENERATE PREVIEW

Run existing Library assets through the active Studio workflow to create or replace their review images.

SOURCE / REUSABLE

The portable prompt formula. Keep identity-related placeholders such as NAME and BRAND reusable when the captured data supports them.

THUMBNAIL COMBINATION

The resolved Outfit and Scene combination represented by the image. Choose this when the captured styling is the starting point.

Load with intention

On a Prompt or Template, choose Load and inspect the apply choices. Loading changes the active graph. Available source or captured component information can be applied; missing image metadata cannot be reconstructed by the Library.

Saved Generation Recipes

A Recipe preserves generation state behind saves, image imports and reuse. It is an advanced asset that supports the four creative libraries, rather than another beginner tab to learn.

THE CREATIVE LIBRARY

Review at full size

Click a thumbnail or View. Loading the asset is a separate action.

One stable review session

The large window stays fixed relative to your viewport. Metadata scrolls independently of the image. Left and Right browse the active filtered Home or Collection, including items beyond the current gallery page. Rating changes do not reorder that open session; reopen to adopt a new filter order.

FIT + ZOOM

Fit shows the whole image. – and + range from 50% to 400% of Fit. Click the image to switch Fit / 200% of Fit; scroll to pan. This is not a native-pixel percentage.

RATE + DELETE

Use the stars or keys 1-5. Key 0 clears; clicking the current star rating also clears. Delete Asset or the Delete key opens confirmation, then review continues through survivors.

Copy the useful fields

Prompt/Template records show Final Prompt, Source Prompt, Outfit A/B/C, Scene and a trusted Seed when captured. Copy All includes populated fields with labels; a captured seed of 0 is valid. A missing seed stays unavailable.

No thumbnail yet?

View still opens a useful Inspector. Use Generate Preview to make the first image. Escape or Done closes the Inspector; nested text editors own their typing keys.

THE CREATIVE LIBRARY

The right actions for the record

The Inspector adapts to the kind of asset you opened.

Action sets

Prompt / Template	Load · Queue · Queue Next · Edit · Collections · Generate Preview · Delete Thumbnail
Outfit Look	Load A/B/C · Move Home · Collections · Generate Preview · Delete Thumbnail · Source Recipe when available
Scene	Load Scene · Move Home · Collections · Generate Preview · Delete Thumbnail · Source Recipe when available
Wardrobe	+ Builder · Load A/B/C · Edit · Collections · Generate Preview

Deletion has a specific meaning

Deleting a Prompt/Template archives a source-backed record or deletes an imported record; original source files and saved Recipes remain. Deleting a Look/Scene removes the asset and thumbnail and prevents silent reconstruction from old sources; saved Recipe text remains. Deleting Wardrobe removes the piece, thumbnail and relationships while preserving saved Look text.

Thumbnail maintenance is separate

Delete Thumbnail removes the review image while retaining the asset. Wardrobe thumbnail deletion is available through bulk curation, not a dedicated Inspector button. Prompt/Template card-level Preview and Delete Thumb buttons are retired.

THE CORE NODES

Choose the model and LoRA

Loader Core controls the model stack and the Main LoRA testing pool.

Use these controls first

Click Diffusion model, choose Main LoRA, set Enabled and Strength, then choose Folder scope. The scope browser also includes LoRA Collections. LIB opens LoRA Library in that current scope. The output model feeds Generation Core; `clean_name`, `main_trigger` and `main_folder` are reusable strings.

MODEL AFTER GENERATE

Fixed, Increment, Decrement, Randomize and Shuffle advance the diffusion selector independently.

MAIN LORA AFTER GENERATE

The Testing section advances the Main LoRA within its filtered pool. Include subfolders expands physical scope. Skip None avoids the empty choice.

Narrow a testing pool

Use Epoch, Library filter and Sort before a run. Sort supports Name, Most used, Least used and Recently used. The Main row shows availability and use information. Review buttons assign Favorite, Keep, Retest or Reject directly from the node.

Leave Advanced for later

Advanced reveals Loop cycle and Off name. Click Clean name to choose the naming cleanup. The trigger row copies the phrase; the pencil edits it, and info opens model details. Secondary LoRAs are covered next.

THE CORE NODES

Build a controlled LoRA stack

Use Main for the variable you are testing; add secondary influences deliberately.

Add only what you need

Choose Add Secondary LoRA and select an installed model. The stack supports up to ten selected secondary LoRAs. Each row has its own Enabled switch, Strength, model browser, trigger copy, trigger edit, information and remove action.

MODEL APPLICATION

Enabled secondary entries join the model stack. Adjust strength on the row. Removing a row changes the workflow stack; it does not delete the LoRA file.

TRIGGER WORDS

Secondary trigger copy/edit controls use the shared trigger resolver, but Prompt Core's main_trigger connection carries the Main LoRA phrase. Secondary phrases are not automatically assembled into that socket.

A repeatable comparison

Keep secondary strengths fixed while cycling Main LoRA. Hold seed, dimensions and prompt steady for a useful comparison. Generation Core's live shelf shows the actual applied Main and enabled secondary models, even when dropdowns have already advanced.

Model information dependency

The Studio Loader uses rgthree-comfy's model information services. Its secondary stack itself is drawn by Studio. If the Loader interface fails to initialize, check that dependency before changing model files.

THE CORE NODES

Three ways to supply a prompt

Prompt Core assembles the text that reaches Generation Core.

Prompt Source

Manual	Type or edit a local draft. Click the source text area to open its editor.
Prompt Input	Use the connected manual_prompt_input STRING socket, often Final Prompt or Source Prompt from Image Metadata Core.
Prompt Log	Select a log and line; choose how its index advances after queueing.

A wire can stay attached

Switch back to Manual without disconnecting Prompt Input. The incoming value is remembered separately and does not overwrite your Manual draft. Select Prompt Input when you want to use it again.

Components have their own sources

Outfit A/B/C and Scene each choose a Manual value or an Outfit / Scene log. Collection-backed sources appear in the same browser. Manual components remain fixed; log components use their selected mode and index.

Inputs and output

The useful first connections are main_trigger from Loader and optional manual_prompt_input from Metadata. final_prompt connects to Generation Core’s positive_text. Source selection and component placement are independent decisions.

THE CORE NODES

Make placeholders do the work

Write a formula, then control where each component is placed.

Placement behavior

Auto	Outfit/Scene: replace its placeholder if found, otherwise append. Trigger: replace TRIGGER if found, otherwise prepend.
Placeholder	Insert only where the matching token occurs. A missing token means no placement.
Beginning / End	Remove matching placeholder occurrences and place the value at the chosen edge.
Off	Remove the matching placeholder and do not insert its value.

Use exact tokens

The default component aliases include OUTFIT / OUTFIT_A, OUTFIT_B, OUTFIT_C and SCENE. NAME is a substitution slot. The configurable ITEM slot can be renamed BRAND. Matching is case-sensitive and accepts supported bare or braced aliases at token boundaries; ordinary lowercase prose is not a token.

Affixes participate too

Enabled Prefix and Suffix join the source before component resolution. Their Outfit/Scene placeholders resolve and activate the relevant log progression. NAME and ITEM substitutions can then resolve inside inserted component values.

Keep the advanced layer explicit

Creative Library recognizes additional portable tokens, including LOCATION, TRIGGER and specialty tokens listed in the reference. Recognition makes a Template; it does not create a dedicated resolver for every word. Configure a slot or edit unsupported values before generation. Advanced contains separator and optional regex cleanup.

THE CORE NODES

Set the canvas, then the seed

Generation Core samples the image and reports what actually ran.

First controls

Choose compatible Text encoder and VAE files. Set Resolution to Preset for Aspect + Megapixels, or Custom for Width + Height; the swap control reverses custom dimensions. Start with Batch 1 and the model’s appropriate sampling settings. Sampler, Scheduler, Steps, CFG, Denoise and Shift are editable rows.

Seed choices

Random each run	Set -1 for a fresh random seed on each execution.
New fixed random	Choose one new random seed and hold it for comparisons.
Use last queued	Reuse the last seed recorded by the node. Click the seed-copy row to copy the recorded seed.
seed_input	A connected INT overrides the widget for the run. A connected -1 still randomizes.

Read the live shelf

The applied LoRA monitor reflects execution state, including enabled secondary LoRAs. With a direct Loader connection it follows that Loader. The shelf may differ from selectors that have advanced for the next run.

Connections

Loader model + Prompt final_prompt enter Generation. samples and vae leave it for Output Core or a compatible decode path. Advanced CLIP type/device and external conditioning belong in the reference workflow.

THE CORE NODES

Compare without losing the moment

Preview Core keeps the reference beside the live result.

NORMAL PREVIEW

Review the incoming IMAGE. FIT, BG and Background Color change presentation, not the saved generation itself.

PIN + COMPARE

Capture the currently displayed image and immediately open it beside the live Preview. Generate another result to compare.

Clear the reference

Clear removes the pinned image and returns the node to normal width. Use it when the comparison is finished or when starting another visual question.

Save the displayed result

Save to Library sends the verified shown image with available prompt assembly and generation state into Creative Library. It is the current name of the reusable-save action. Separate Pin, Compare, Recipe and Library Thumb actions are not the v4 toolbar.

A better comparison habit

Change one influential setting at a time: LoRA strength, one phrase, seed or dimensions. Pin a useful baseline, generate the change and decide what to save. The three primary actions are Pin + Compare, Clear and Save to Library.

THE CORE NODES

Bring an old image back to work

Image Metadata Core is the bridge from an image to a new generation.

Inspect before applying

Load an image file. Read Final Prompt, Source Prompt, seed and the available resolved Outfit A/B/C and Scene values. Copy individual fields or the full report. A truly connected IMAGE input takes precedence over a manually chosen file; disconnect it when you want to inspect files independently.

Two useful workflows

Recreate / modify	Metadata final_prompt or source_prompt → Prompt manual_prompt_input. Select Prompt Input. Metadata seed → Generation seed_input. Apply available component values as needed.
Build reusable Library material	Load image → inspect recovered fields → Save to Library. The loaded image can become the preview.

FINAL PROMPT

Start from the resolved text used by that generation. Avoid adding the same components or trigger again.

SOURCE PROMPT

Start from a recoverable reusable formula. Restore its component values or choose new ones before generating.

Respect the graph direction

Keep Metadata independent of the output path when feeding its text/seed back into generation. Wiring the new result back into that same Metadata node creates a graph cycle. Keep Metadata separate when using its outputs for reuse.

THE CORE NODES

Recover what the image carries

Available fields depend on the source image and how it was saved.

Metadata sources

Native SICK OLLIE data	Can preserve source and final prompt, assembly values, models and resolved generation information.
ComfyUI prompt / workflow data	Can recover recognized node settings and prompt values; arbitrary custom workflows may provide less.
Common parameters metadata	Can recover conventional prompt, seed and generation fields when present.
No embedded metadata	The picture remains viewable. Prompt text, seed and missing component values cannot be inferred exactly from pixels.

Queued images remain valid

Loading another file or clearing the visible image is designed to preserve imports already queued. Temporary source files are retired later rather than removed underneath pending work.

More outputs when you need them

The node provides images, final_prompt, source_prompt, seed, generation_settings, models, resolved_inputs, full_report, metadata_json and has_metadata. Use the structured or report outputs only when another workflow needs them.

Reproduction is conditional

A matching seed alone does not reproduce an image. Model files, LoRAs, conditioning, dimensions and sampling settings also matter. Output metadata toggles determine which information survives saving.

THE CORE NODES

Save images with a way back

Output Core controls destination, file naming and metadata.

Start with Output root

Choose a folder beneath ComfyUI output. Connect samples + vae from Generation Core and Output decodes them. If an images input is connected, that IMAGE takes priority. Output returns images for Preview.

Practical controls

Subfolder recipe	Combine literal text with up to four variables and a delimiter.
Filename recipe	Combine literal text with up to six variables and a delimiter.
Format / Quality / Counter digits	PNG, JPG or WebP; quality affects JPG/WebP, while PNG ignores it. Counter digits control numbering.
Prompt / Workflow / Civitai metadata	Choose which prompt, reloadable workflow and common parameters information to embed.

Use the context that already exists

Output reads connected Studio context for naming and metadata. Resolved input rows can be clicked to copy. The latest saved path helps locate the result without reconstructing a filename.

Keep round-tripping practical

PNG with metadata enabled is a useful starting point for reuse. There is no standalone public Strip Triggers switch in this endpoint: manage trigger placement in Prompt Core and inspect already resolved text before reusing it.

LIBRARY POWER TOOLS

Small controls, shorter workflows

These are worth learning even if you used them in v3.

Click the value, not just the obvious button

Prompt assembly chips	Outfit/Scene chips open placement. TRIGGER opens Trigger Builder.
Placeholder labels	Edit the configured token itself, including the ITEM / BRAND label.
Local values	Click a displayed value to open its editor.
Connected values	Click to pulse the supplying node instead of editing its output here.
Resolved prompt / output rows	Copy the assembled prompt or resolved output information directly.
Loader trigger row	Copy the trigger; use its pencil for a saved override and info for details.

Read color and status together

Prompt tokens are color-coded. Assembly status distinguishes used values, unplaced placeholders, missing sources and disabled placement. A displayed value can be present without being used: check the placement status before queueing.

Open Advanced only with a purpose

Loader hides loop/off-name controls; Prompt hides separator and cleanup; Generation hides CLIP type/device. These controls are available without making the first run a settings survey. Text editors support Ctrl/Cmd+Enter to save where shown.

LIBRARY POWER TOOLS

Load, Queue or Queue Next?

Choose whether you want to change the canvas or submit a job.

Intent → action

Load	Intentionally applies the asset to the active Studio workflow.
Queue	Submits a generation for the asset, then restores the visible working state.
Queue Next	Places a Prompt/Template at the front of pending queue work. It does not interrupt the currently running generation.

Progression happens around queueing

Fixed holds a selection. Increment and Decrement walk the active pool. Randomize selects randomly; Shuffle uses the pool’s shuffle state. Model and Main LoRA controls are independent. Prompt and component log modes act on relevant active streams; Manual values stay fixed.

Keep batches understandable

Prompt batches have a 400-item safety limit. Use multiple passes for larger scopes. Generate Previews and LoRA Yearbook use sequential capture and wait for earlier ComfyUI queue work before arming thumbnail collection.

Run state comes back

Automated runs temporarily route outputs under output/Sick Ollie Yearbooks/Creative Library or output/Sick Ollie Yearbooks/LoRA Library. Original node settings and Output paths are restored when a run completes or stops. Verify interruption behavior in Desktop before an unattended production run.

LIBRARY POWER TOOLS

Make the Library worth browsing

Generate Previews gives existing assets a consistent visual test.

Choose a small scope first

Open Generate Previews from the Library. Choose selected items, the current filtered results, a Home or Collection, selected sections or the complete Creative Library. Templates, Prompts, Wardrobe, Outfit Looks and Scenes participate in one scope workflow.

GENERATION SIZE

Creative Library defaults to 800 × 1000. Fast and larger presets remain available, with custom sizing where offered. Scenes turn the selected dimensions into landscape orientation.

STORED PREVIEW

Compact WebP preserves aspect ratio and up to 2048 px on the longest edge, within a 512 KiB budget. Small originals are not enlarged; complex images may be reduced to meet the budget.

Follow the run

The run generates and captures assets sequentially, restoring temporary state afterward. Open Theater for live review. Closing Theater does not stop generation; use the run's stop control to end it.

Existing previews do not change themselves

Regenerate or replace an older thumbnail from a larger source to gain detail. Encoding respects EXIF orientation and replaces files atomically; failed replacement preserves the previous valid image. LoRA Yearbook has its own size choices.

LIBRARY POWER TOOLS

Review while generation continues

Theater is a live review environment with its own history.

LIVE Follows the newest completed thumbnail automatically. Run progress remains visible.	FROZEN Browse earlier completed images with Left/Right while the underlying run continues. Return to Live to follow new results.
--	--

Two review systems

Creative Library Theater	1-5 assigns stars. X toggles Reject. Use its rating controls to clear a selected rating; Inspector additionally has key 0.
LoRA Theater	F or 1 = Favorite. L or 2 = Like (stored Keep). R or 3 = Retest. X = Reject. Choosing the same review state again clears it.
Both	Space toggles Live/Frozen. Left/Right browse history. Escape closes Theater. Fit / Fill / Actual control image display.

Close the window, keep the run

Theater can be closed without stopping Yearbook or Generate Previews. Reopen it during an active run using Theater. Its history belongs to that run; the persistent asset rating or review state belongs to the Library.

Use the correct meaning of a rating

LoRA review states describe a model’s testing status. Creative Library stars describe reusable creative assets. They are separate systems with different shortcuts; do not read LoRA key 3 as three stars.

LIBRARY POWER TOOLS

Curate a scope with confidence

Search first. Check the selection. Then apply the operation.

Narrow the result set

Use Home or Collection navigation, text search, ratings, placeholder filters and the available facets. Prompt/Template source-log navigation retains Original Log order when available. A filter changes what you are browsing; it does not move assets.

Select Multiple

Multi-select exposes the bulk actions relevant to that asset kind: Collection membership, organization, Builder operations, thumbnail deletion/regeneration or record deletion. Read whether an action targets selected cards, current filtered results or a wider scope.

MOVE HOME

Change an asset's canonical location. Use the appropriate Home editor or bulk organization controls.

COLLECT

Add creative group membership without moving the asset. Deleting a Collection removes the group, not its member assets.

Review before broad deletion

Inspector is best for one-at-a-time decisions; bulk controls are best for a deliberate scope. Source-backed and imported records can have different delete behavior. Purge and orphan cleanup are separate maintenance tools covered later.

LIBRARY POWER TOOLS

Move a Library, or just a capsule

Library Menu → Library Pack is the portable-content entry point.

Choose the smallest useful export

Starter / Share Pack	A shareable creative selection.
Wardrobe & Looks	Reusable clothing material and complete outfits.
Current Scope	The active tab, Home, Collection and filters.
Full Backup	A broad Creative Library backup.
Custom	Select the libraries, organization and optional thumbnails you want.

Import deliberately

Choose Import Library Pack, inspect its contents, then select what to merge. Required linked dependencies remain automatic. Unselected and unrelated local content is not deleted. Reimporting a known pack can reconcile organization supplied by that pack while preserving locally owned review, previews and organization.

TXT is still useful

Import an existing prompt log when text is your source. Mixed lines are routed to Templates or Prompts according to recognized unresolved placeholders. Managed copies can preserve source-log provenance and order; originals are not rewritten by the import.

A pack is not a model install

The .soslibrary file moves Library content, not installed diffusion models or LoRA weights. Full Backup describes Creative Library scope; preserve the user-data folder and input logs too when backing up the whole installation.

LORA LIBRARY

Browse and test your LoRAs

LoRA Library is the review workbench for installed model files.

Find the model in context

Use the searchable nested folder sidebar, review filters and model search. Open details for trigger evidence, thumbnail provenance, usage history and Civitai information. Fill from Civitai can supply missing references; optional online lookup needs a working connection.

PHYSICAL FOLDER

A real directory of LoRA files. Scan LoRA folders scans configured roots; Scan current folder targets a selected physical subtree.

LORA COLLECTION

A virtual testing group across folders. Multi-select to manage membership. Choose a physical folder before scanning; scanning is unavailable in a Collection.

Send a choice back to Studio

Load LoRA selects it in Loader Core with fixed progression. Per-card Queue uses the active workflow. Queue Current View submits the visible filtered set in order or shuffled. Loader's Folder scope can select a Collection, and LIB carries that scope back here.

Library vs Organizer

LoRA Library browses, tests, reviews, queues, thumbnails and groups models. LoRA Organizer plans and performs filesystem naming, moves and cleanup. Choose Organizer only when you intend to change files on disk.

LORA LIBRARY

Give every checkpoint a fair test

LoRA Yearbook runs a controlled visual comparison.

Set the comparison

Filter to the intended LoRAs, then open Yearbook run. Set the shared prompt, LoRA strength, dimensions and seed. A fixed seed makes comparisons easier to interpret. The LoRA Yearbook dialog has its own presets and defaults, independent of Creative Library’s 800 × 1000 default.

Choose thumbnail policy and order

Fill missing	Generate entries that lack the requested thumbnail coverage.
Standardize non-Yearbook	Fill missing and replace automatic sources while protecting custom images and existing Yearbook thumbnails.
Replacement options	Read the selected thumbnail action before starting a broader overwrite.
Incremental / ordered / shuffled	Use recognized epoch/checkpoint families in numeric low-to-high progression, preserve filtered view order, or shuffle.

Watch the run in Theater

Follow each newly completed image or freeze on a checkpoint worth reviewing. Favorite, Like/Keep, Retest and Reject write the LoRA’s real review state. Closing Theater leaves Yearbook running.

Scope is the safety rail

Yearbook waits for earlier queue work before capture. Original Loader, Prompt, Generation and Output values return at the end. Start with a small family to verify your comparison settings and output path before a long run.

OUTFITS

From piece to complete Look

Wardrobe Piece → Outfit Builder → Outfit Look → Prompt Core

WARDROBE Reusable pieces, sets and styling material. Keep garment identity here; vary its attributes in Builder.	LOOK A complete outfit value. Save a finished assembly here when you want to load the same combination again.
--	---

Per-piece Builder attributes

Color / Pattern	Choose color and surface pattern independently.
Cut / Fit / Material	Refine silhouette and construction substance.
Wear	Add condition or wear details.
Graphic / Text	Add graphic wording, including portable NAME or BRAND placeholders where needed.

Build or load directly

Add pieces, tune their inline/custom values, reorder them and copy, load or save the resulting outfit. Direct Wardrobe Load A/B/C sets a Manual Outfit value. Loading a Look switches that slot back to its managed Prompt Log source behavior.

Collections are live sources

Wardrobe Collections and Look Collections can both supply Outfit A/B/C pools. Scene Collections supply Scene. Fixed, Increment, Decrement, Randomize and Shuffle use the selected Collection members without making duplicate TXT master logs; renaming the Collection keeps its stable source identity.

OUTFITS

Forge a log, then curate it

Outfit Forge is an optional local beta tool for complete Looks.

Start with a concrete brief

Open Studio Hub → Outfit Forge. Enter Theme, then choose Line count, Seed, Coverage, Complexity and Wearability. Inspect Understood and Not represented. Recognized garments, colors and materials constrain generation; the beta interpreter cannot represent every concept.

A useful working sequence

Forge Outfit Log	Build a deterministic log from the full brief and seed. New Seed explores a different set.
Edit and reforge	Edit one line, duplicate it, remove it or regenerate only that entry. Search filters the draft.
Audit	Constraint Fidelity checks enforced constraints. Brief Coverage identifies unrepresented terms. Structural checks flag repetition and duplicates.
Publish	Copy, Download .TXT, or Export to Outfit Looks into a category/subcategory.

Optional refinements

Advanced controls add Required, Avoid and vocabulary banks. Theme constraints take precedence over optional banks. Coverage changes exposure/layering; Complexity changes detail density; Wearability 1–2 permits experimental construction, while 3–5 stays more plausible.

Know what is saved

Drafts and edits autosave in this browser. Download or publish a result you want to keep across browsers. Forge uses local structured generation rather than an external language model. Its published outputs are complete Looks, not Wardrobe Pieces.

ADVANCED / REFERENCE

Resolve once. Place deliberately.

Loader chooses the phrase; Prompt Core chooses its position.

1 / Exact LoRA override

2 / Epoch-family override

3 / Automatic discovery

First available match → resolved Main trigger → Prompt Core placement

Persistent override scopes

Use the Loader trigger pencil and choose THIS LoRA ONLY or MATCHING EPOCH FAMILY. A safe family changes only the numeric token after epoch/ep; the remaining filename and parent folder must match, case-insensitively. New matching epoch files inherit that family rule.

Automatic fallback

Without an override, Loader tries explicit embedded activation metadata, then training-tag evidence, then Civitai sidecar / exact-hash fallback. It rejects model titles as activation phrases and does not auto-inject an unsafe long or weighted Civitai recipe.

Place it in Prompt Core

Connect Main trigger and open the TRIGGER assembly chip. Auto replaces TRIGGER or prepends when absent. Placeholder only replaces an existing token. Beginning/End removes token occurrences and inserts at that edge. Off removes the token and inserts nothing. The default placement is Off.

Follow the model as it changes

Prompt Core can save or clear the active LoRA override. A local pin is scoped to its LoRA so it does not follow an unrelated model. Disabled or zero-strength Main LoRA output is suppressed; manually baked trigger text remains ordinary prompt text. Secondary phrases require their own deliberate placement.

Use the extra sockets when needed

Extend the Studio workflow without losing track of what overrides what.

External conditioning

Generation Core accepts optional `positive_conditioning` and `negative_conditioning`. Connected positive conditioning overrides its internal positive-text encoding; an unconnected negative uses the normal empty fallback. The Conditioning status rows report which path is active. Use compatible external conditioning for the model and workflow you are building.

CLIP type and device

Advanced reveals CLIP type and device selection. The correct encoder family depends on the installed model. The node’s initial settings are not universal generation defaults.

Library-recognized portable tokens

Primary	NAME · OUTFIT · OUTFIT_A · OUTFIT_B · OUTFIT_C · BRAND · ITEM · SCENE · TRIGGER
Additional portable vocabulary	LOCATION · RARE_EVENT · LIGHT_SOURCE · ANALOG_CAPTURE_STYLE · PRACTICAL_OUTER_LAYER · SMALL_STYLING_DETAILS · NATURAL_SURFACE

Recognition vs resolution

Creative Library uses recognized token presence to classify Templates. Prompt Core resolves its configured component, name, item and trigger slots. Additional portable vocabulary needs deliberate editing or slot configuration; the Library does not invent missing values. Use exact case and inspect the resolved prompt.

ADVANCED / REFERENCE

Change files with a reviewed plan

LoRA Organizer is the filesystem tool, separate from LoRA Library.

Scan → review → apply

Choose the LoRA library root, set naming and Base / Category / Creator organization rules, then Scan Folder. Inspect proposed names and destinations. Select only intended Ready items and use Apply Selected. Scanning itself does not move files; Stop Scan cancels planning.

Keep model families together

The organizer handles related sidecars, bounds mutation paths to the selected root and avoids clobbering destination files. Reprocess existing subfolders is a deliberate option for reorganizing an existing layout; start from the real root rather than a nested organized category.

DUPLICATES / ORPHANS

Find Exact Duplicates uses exact identity checks. Find Orphans / Empty Folders proposes cleanup. Review the selected files before confirming OS Trash / Recycle Bin operations.

UNDO LAST

Operation manifests support undo for applicable changes. OS Trash recovery belongs to the operating system; undo and recoverable Trash are not substitutes for a separate backup.

Other controls

Browse chooses a root; Copy Info and Open Civitai help inspect the selected record. Settings controls organizer preferences and optional online lookup credentials. A cancelled scan publishes no partial mutation plan. Do not treat Library Purge as filesystem organization.

ADVANCED / REFERENCE

Clean the intended thing

Use disposable test data when learning destructive maintenance.

Maintenance choices

Delete Thumbnail	Remove an asset’s preview while retaining its reusable text record.
Delete Asset	Remove or archive a Library record according to its type; inspect the confirmation.
Clean Orphan Thumbnails	Run a reference scan and review files that no live Library record uses.
Creative Library Purge	Choose sections or the entire Library; read the itemized warning and typed confirmation.
LoRA catalog maintenance	Clearing thumbnails affects caches. Purge + rebuild resets the selected LoRA index/review/history data and rescans files; it does not delete LoRA weights.

Back up the right scope

Export a Library Pack for portable creative assets. For installation-level recovery, also copy the user-data directory, input logs and any model files you plan to reorganize. A pack is not a complete filesystem backup.

Legacy recoverability

Retired Workshop data remains recoverable until explicitly purged. Deleting a Collection removes membership, not its assets. The Organizer is the separate tool for confirmed model-file moves and cleanup.

Know where your work lives

Normal extension replacement should leave user-owned content intact.

Default locations

Extension	ComfyUI/custom_nodes/ComfyUI-SickOllie/
Catalog and user data	ComfyUI/user/SickOllie/; the catalog is solo_catalog.sqlite3. Actual user root follows ComfyUI configuration.
Creative previews	creative_library_previews/ beside the catalog. Compatible older preview folders are migrated conservatively.
Prompt / component logs	ComfyUI/input/SickOllieLogs/ with prompts/, outfits/ and scenes/ categories. Generated Library logs use Creative Library subfolders.
Generated images	ComfyUI/output/ beneath the Output Core path or dedicated Yearbook run roots.
Forge drafts / UI preferences	Browser local storage; export important drafts for portability.

Migration boundaries

Old generated Recipe Library log references map to canonical Creative Library references. Managed preview files move to the canonical store when safe; unknown or conflicting files are preserved. Internal schema numbers and compatibility identifiers are independent of the v4 product version.

Nonstandard installations

The backend follows ComfyUI’s configured user and input directories. If no user directory is available, the catalog code has an extension-local data fallback. Inspect the actual installation path before replacing a folder; never discard a data folder just because it is beside code.

ADVANCED / REFERENCE

Upgrade the product, keep your work

v4 keeps deliberate compatibility while giving new users one clear starting point.

Studio and Classic

Build a current Studio graph using the map near the beginning of this manual, or open your existing workflow. v4 includes no bundled sample workflows, starter logs or old manuals. Classic node IDs remain registered, and legacy Preview nodes migrate to Studio Preview through compatibility handling.

Retained maintenance compatibility

Older workflows containing Log Organizer can still open. That legacy tool is not promoted in the primary Studio Hub. Its historical name and internal engine versions are compatibility identifiers, not the v4 public release label.

The current product language

Use Templates, Prompts, Outfits and Scenes; Home and Collection; Generate Previews in Creative Library; Yearbook in LoRA Library; and Library Pack for .soslibrary. Saved Generation Recipes remain available behind reuse. Separate Wardrobe Pack and Workshop-first navigation are retired.

Before updating

Back up ComfyUI user data and SickOllieLogs. Close ComfyUI, replace only the extension folder, restart fully and hard-refresh the frontend. Open a copied workflow first, reselect missing local files and verify one generation before continuing production.

ADVANCED / REFERENCE

When something feels wrong

Check the selected source and active scope before rebuilding anything.

Symptom → first check

Typing stops or a modal seems hidden	Close the active dialog and refocus its field. The Studio focus guard addresses stale canvas capture; if it recurs, record the dialog, steps and console error.
Manual text is not used	Check Prompt Source. Prompt Input and Prompt Log are separate choices.
Outfit / Scene does not change	Check Manual vs log source, placement, token spelling and the stream’s After Generate mode.
Unexpected trigger words	Check Loader override scope, Prompt Trigger placement and trigger text already baked into the source.
Missing preview / older detail	Open View, inspect available metadata and regenerate from a larger source if appropriate.
Collection not available / wrong results	Confirm the asset type, active scope and actual members; reopen the relevant source browser after editing.
Loader UI does not initialize	Confirm rgthree-comfy is installed, restart ComfyUI and hard-refresh.
Unexpected metadata image	Check the optional IMAGE connection; a connected image source takes priority.

A useful bug report

Include Toolkit version 4.0.0, ComfyUI version, the node or Library area, exact reproduction steps, console traceback and a minimal workflow without private data. Separate an automated-test result from what happened in your Desktop session.

START / UPDATE

Install, import, make something

A clean starting point for new users and returning v3 users.

Install v4

Use a compatible ComfyUI installation with the LiteGraph canvas and Python 3.10+. Install rgthree-comfy for Loader's shared model-information services. Place the single ComfyUI-SickOllie folder in custom_nodes, avoiding a double-nested folder. Restart ComfyUI, then hard-refresh the browser.

Choose your local model files

Build the five-Core graph shown in this manual, select Diffusion model and compatible encoder/VAE files, and inspect the model-specific sampling settings. The package does not bundle generation model weights.

Import your Library content

This release ships with an empty Library and no bundled starter content. When you have a separately supplied .soslibrary pack, open Studio Hub → Creative Library → Library Menu → Library Pack → Import Library Pack and inspect its contents. Install selected sections and thumbnails deliberately. You can also import your own TXT logs. Updates do not silently replace your Library.

Your next useful experiment

Load a Template, choose one Outfit and one Scene, fix the seed and generate. Pin + Compare, change one component and generate again. Save the stronger result. You have completed the whole Studio loop.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Diffusion model / Weight / p. 10

Choose installed diffusion model and weight representation.

Model After generate / p. 10

Cycle diffusion models independently through Fixed, Increment, Decrement, Randomize or Shuffle.

Folder scope and Include subfolders / p. 10

Limit the Main LoRA pool to a physical directory with optional descendants.

LoRA Collection scope / p. 10

Use a virtual LoRA group without moving model files.

LIB scope jump / p. 10

Open LoRA Library in the active physical folder or Collection.

Main LoRA / Enabled / Strength / p. 10

Select the primary LoRA, disable it, or adjust its influence.

Epoch filter / p. 10

Narrow eligible checkpoint files before cycling.

Favorite / Keep / Retest / Reject / p. 10

Review the active LoRA directly on the node.

Library filter and usage sorting / p. 10

Browse by review state, name, frequency, or recency of use.

Clean name click / p. 10

Choose a cleanup mode for portable identity and output naming.

Main After generate / Skip None / p. 10

Advance through the selected Main LoRA pool.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Advanced Loop cycle / Off name / p. 10

Control end-of-pool looping and the disabled-LoRA name.

Dynamic secondary stack / p. 11

Add up to ten secondary LoRAs with independent enable, strength, copy, edit, info and remove controls.

Automatic trigger discovery / p. 29

Read explicit embedded evidence, training tags and safe Civitai fallback; model titles are not activation phrases.

Trigger copy and info / p. 29

Click the trigger value to copy; info opens model details.

Exact persistent trigger override / p. 29

Save a durable activation phrase for one LoRA.

Matching epoch family override / p. 29

Vary only the epoch/ep numeric token in the same folder; future matching files inherit the rule.

Exact > family > automatic priority / p. 29

Resolve a predictable effective trigger without overwriting more specific choices.

Disabled Main trigger suppression / p. 29

An inactive or zero-strength Main LoRA supplies no live trigger.

Manual / Prompt Input / Prompt Log / p. 12

Keep a prompt wire attached while choosing a separate Manual draft or a log.

Prompt Input socket / p. 16

Receive Final Prompt or Source Prompt from Image Metadata Core.

Manual Outfit A/B/C and Scene / p. 12

Type fixed component values independently of the main prompt source.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Collection-backed component logs / p. 27

Choose Wardrobe, Looks or Scene Collections as live pools with stable identities.

Outfit A/B/C / Scene placement / p. 13

Choose Auto, Placeholder, Beginning, End or Off per component.

NAME / configurable ITEM or BRAND / p. 13

Edit the placeholder label and replacement value; configure ITEM to BRAND when needed.

Colored placeholder rendering / p. 19

Use token colors to read the assembly; substitution remains case-sensitive.

Clickable assembly status chips / p. 19

Click component chips for placement; click TRIGGER for Trigger Builder.

Clickable placeholder / configuration values / p. 19

Edit tokens and local values directly on dashboard rows.

Linked value source pulse / p. 19

Click a connected value to highlight the supplying node.

Prefix / Suffix toggle and editor / p. 13

Add reusable affixes with independent toggles, including connected text sources.

Affix placeholder resolution and progression / p. 13

Resolve components across prefix, source and suffix, and advance used log streams.

Log browser / line index / recovery / p. 12

Browse source logs, choose a line and recover missing log references.

Fixed / Increment / Decrement / Randomize / Shuffle / p. 20

Advance active log streams after queueing; Manual components remain fixed.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Resolved prompt copy / p. 19

Copy the complete assembled text rather than reconstructing it.

Advanced separator and cleanup / p. 13

Tune text joining and optional regex cleanup only when necessary.

Trigger Builder and placement / p. 29

Follow Loader or choose a candidate; placement controls actual insertion.

Save / clear active LoRA override / p. 29

Persist an override from Prompt Core and return to Loader resolution when cleared.

Text encoder / VAE / p. 14

Select local files compatible with the diffusion model.

External positive / negative conditioning / p. 30

Use supplied conditioning; positive overrides internal text encoding, negative otherwise uses an empty fallback.

Preset / custom dimensions / swap / batch / p. 14

Choose aspect and megapixels or exact dimensions; swap width and height in Custom.

Sampler / Scheduler / Steps / CFG / Denoise / Shift / p. 14

Control sampling using settings appropriate to the selected model.

Random / fixed / last queued seed / copy / p. 14

Randomize each run, pick one fixed random seed, reuse the last queued seed, or copy it.

seed_input / p. 16

An external INT overrides the seed widget for that run; -1 randomizes.

Live applied LoRA shelf / p. 14

See LoRAs actually applied, associated with the connected Loader when available.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Advanced CLIP type and device / p. 30

Change encoding family or device placement only when required.

Latents + VAE or IMAGE saving / p. 18

Decode samples internally or save connected images, which take priority.

Output root / filename / subfolder recipes / p. 18

Combine literal text and variables into traceable output paths.

PNG / JPG / WebP / quality / counter / p. 18

Select a file format and naming counter; PNG ignores lossy quality.

Prompt / Workflow / Civitai metadata toggles / p. 18

Choose which generation records accompany saved images.

Resolved input copy / saved path / p. 19

Copy resolved values from the output dashboard.

Fit / Background / Background color / p. 15

Choose image fitting and background presentation.

Pin + Compare / p. 15

Capture the displayed result and open it beside the live preview in one action.

Clear comparison / p. 15

Remove the reference and restore the normal preview width.

Save to Library / p. 7

Save the verified displayed image and available generation state for reuse.

Image upload / clear / optional IMAGE / p. 16

Inspect a chosen file; a genuinely connected image input takes precedence.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Final / Source prompt / seed outputs / p. 16

Recover prompt text, seed, settings, models, components and reports when metadata exists.

Individual copy fields / full report / p. 16

Copy available seed, Outfit A/B/C, Scene and prompt data directly.

Save to Library / p. 7

Save normalized displayed metadata and its loaded image into Creative Library.

Queued source lifetime / p. 16

Previously queued imports survive subsequent image loading and clearing.

Templates / Prompts / Outfits / Scenes / p. 6

Browse reusable formulas, resolved prompts, outfit material and locations in four primary areas.

Home vs Collection / p. 6

Home is the canonical location; Collections group assets without moving them.

Template classification / p. 13

Recognized unresolved portable tokens classify an asset as a Template.

TXT import / mixed routing / Original Log / p. 24

Split mixed logs line by line while retaining managed source provenance and order.

Search / facets / placeholder / rating filters / p. 23

Narrow the view before reviewing or running scoped operations.

Source / Reusable vs Thumbnail Combination / p. 7

Choose portable source text or the captured resolved component combination.

Load into active workflow / p. 7

Apply selected text and available metadata deliberately to the current Studio graph.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Queue / Queue Next / p. 20

Submit an asset and restore visible state; Queue Next fronts pending work, not the running job.

400-item Prompt batch limit / p. 20

Process large Prompt batches in separate passes.

Saved Generation Recipes / p. 7

Preserve generation-state assets behind reuse, metadata import and portable packs.

Thumbnail / View / no-thumbnail entry / p. 8

Open review without loading the record into the active workflow.

Fixed large frame / independent panes / p. 8

Review within a viewport-bounded frame with independently scrolling metadata.

Scope snapshot / Left / Right / p. 8

Browse the active filtered set without rating changes reordering the session.

Fit / 50%-400% of fit / image toggle / p. 8

Zoom relative to Fit; image click switches Fit and 200% of fit.

Stars / keys 1-5 / 0 / p. 8

Rate persistently; 0 clears, and clicking the current star rating clears too.

Delete Asset / Delete key / p. 8

Confirm type-specific record deletion and continue to the next surviving item.

Metadata platter / Copy All / p. 8

Copy only available fields; a trusted captured seed of zero remains valid.

Prompt / Template actions / p. 8

Load, Queue, Queue Next, Edit, Collections, Generate Preview and Delete Thumbnail.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Look / Scene actions / p. 8

Load a component, Move Home, manage Collections, preview, or inspect an available source Recipe.

Wardrobe actions / p. 8

Add to Builder, Load A/B/C, Edit, Collections or Generate Preview; thumbnail deletion is a bulk workflow.

Unified scopes across five asset kinds / p. 21

Choose selected items, filtered results, Homes, Collections, sections or the whole Creative Library.

Sequential capture / queue-safe start / p. 21

Wait for existing queue work, then generate and capture each planned asset in sequence.

Default 800 x 1000 / presets / custom / p. 21

Use Fast, larger presets or custom dimensions; Scene runs use landscape orientation.

2048 px / 512 KiB / WebP / atomic / p. 21

Preserve aspect and EXIF orientation, avoid upscaling and retain the old preview if replacement fails.

Live / Frozen / history / run progress / p. 22

Follow completed previews or browse past frames while generation continues.

Fit / Fill / Actual / p. 22

Choose how the review image fills the Theater surface.

1-5 stars / Reject / keyboard / p. 22

Use 1-5 for stars, X for Reject, Space for Live/Frozen and arrows for history.

Close / reopen without stopping run / p. 22

Review can close independently of the underlying preview run.

Select Multiple / bulk curation / p. 23

Use applicable bulk Collection, Home, Builder, thumbnail and deletion actions.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Library Menu / Purge / Clean Orphan Thumbnails / p. 32

Inspect destructive scopes and remove only previews not referenced by live records.

One .soslibrary format / presets / p. 24

Use Starter / Share Pack, Wardrobe & Looks, Current Scope, Full Backup or Custom.

Selective import preview / merge / p. 24

Review and select content; merge without deleting unrelated local assets.

Pack reimport reconciliation / p. 24

Reconcile pack-supplied organization while preserving user-owned review and organization state.

Content-free distribution / p. 36

v4 ships without starter logs, sample workflows, bundled Library Packs or old manuals. Import a separately supplied Library Pack deliberately.

Wardrobe vs Looks / p. 27

Keep reusable pieces and complete outfit values distinct within Outfits.

Outfit Builder assembly / p. 27

Combine and reorder pieces, copy the result, load an Outfit slot or save a Look.

Color / Pattern / Cut-Fit / Material / Wear / Graphic-Text / p. 27

Tune per-piece attributes inline rather than duplicating color variants in Wardrobe.

Direct Wardrobe Load A/B/C / p. 27

Load a piece as a Manual Outfit value; loading a Look returns the slot to log behavior.

Local deterministic beta generation / p. 28

Generate complete Outfit Look logs from recognized themes without an external language model.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Theme / count / seed / three sliders / p. 28

Set coverage, complexity and wearability, then inspect how the brief was interpreted.

Optional refinements / required / avoided / p. 28

Refine generation through editable vocabulary and phrase constraints.

Edit / duplicate / remove / reforge / search / autosave / p. 28

Curate a browser-saved draft without regenerating every line.

Audit / Constraint Fidelity / Brief Coverage / p. 28

Distinguish structural diversity, enforced constraints and unrepresented brief terms.

Copy / TXT / Export to Outfit Looks / p. 28

Publish complete Looks into a chosen category/subcategory or keep an editable log.

Nested folders / scoped scans / p. 25

Scan configured physical roots or one subtree; Collection scopes cannot scan files.

Collections / multi-select membership / p. 25

Group LoRAs across folders and feed the group into Loader or Yearbook.

Card Queue / Queue Current View / p. 25

Queue LoRAs with current workflow settings in visible order or shuffled.

Reviews / filters / usage history / p. 25

Review model quality, usage and provenance independently of Creative Library stars.

Thumbnail sources / Civitai fill / detail / p. 25

Inspect model information and populate missing visual references.

Comparison prompt / strength / dimensions / seed / p. 26

Run consistent LoRA tests with temporary comparison settings.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Epoch/checkpoint numeric progression / p. 26

Test detected training families from low to high; ordered and shuffled alternatives remain.

Fill missing / standardize / replacement policies / p. 26

Choose which thumbnail sources may be replaced before starting.

Live/Frozen / history / Fit-Fill-Actual / progress / p. 22

Browse the active Yearbook run while generation continues.

Favorite / Like / Retest / Reject / keys / p. 22

F or 1 Favorite; L or 2 Like/Keep; R or 3 Retest; X Reject; Space toggles Live.

Dedicated output roots / restored state / p. 20

Route runs under Sick Ollie Yearbooks/LoRA Library or Creative Library and restore original settings afterward.

Scan / plan / Apply Selected / Undo Last / p. 31

Preview filesystem changes before applying; undo uses operation manifests.

Exact duplicates / Orphans / native Trash / p. 31

Review cleanup candidates before recoverable OS Trash operations.

Source-root safety / sidecars / no-clobber moves / p. 31

Keep moves inside the chosen root and preserve model-sidecar relationships.

CONTROL FINDER

Every useful control

Quick reference. The page number leads back to the relevant workflow.

Focused tool navigation / p. 6

Open Creative Library, LoRA Library, Outfit Forge or LoRA Organizer from the Studio hub.

Classic IDs and legacy Preview migration / p. 34

Keep Classic workflows and migrate retired preview nodes without changing user data.

Legacy Log Organizer remains registered / p. 34

Older workflow nodes remain usable; the tool is not a primary Hub destination.

Canonical log / preview path migration / p. 33

Read compatible old references and move managed previews into a shared canonical store.

Input focus / modal stacking / press feedback / p. 35

Recover Studio-owned typing focus and provide consistent button feedback on supported devices.