

Problem Chosen
REPLACE ME
WITH PROBELM

2020
MCM/ICM
Summary Sheet

Team Control Number
REPLACE ME
WITH TEAM
NUMBER

Use this template to begin typing the first page (summary page) of your electronic report. This template uses a 12-point Times New Roman font. Submit your paper as an Adobe PDF electronic file (e.g. 1111111.pdf), typed in English, with a readable font of at least 12-point type.

Do not include the name of your school, advisor, or team members on this or any page.

Papers must be within the page limit specified in the problem statement.

Be sure to change the control number and problem choice above.

You may delete these instructions as you begin to type your report here.

**Follow us @COMAPMath on Twitter or COMAPCHINAOFFICIAL on Weibo for
the
most up to date contest information.**

Kingdom Built on a Pile of Sand:Slow and Steady

Contents

1	Introduction	1
1.1	Problem Background	1
1.2	Our Work	2
2	Assumptions & Nomenclature	2
2.1	Assumptions	2
2.2	Nomenclature	2
3	Modeling Under Waves and Tides	2
3.1	Shape of the Slope: Mohr-Coulomb Criterion	2
3.2	Top View Shape	3
3.3	Calculating Results	3
3.4	Simulating Results	3
4	Modeling Under Rain	3
5	Determine the Best Sand-to-water Proportion	3
6	Other Ways to Make Our Sand Castle Last Longer	3
7	Sensitivity Analysis	3




Figure 1: Water Bridge Between Sand Particle

1 Introduction

1.1 Problem Background

Sunshine, clear blue sea and golden color sand always seem to leave people in a happy state of mind. And a beach is where these three are combined, drawing people all around towards it. Sand, the granular matter formed by constant brushing of flowing water, however, can react with water in a different way, despite the fact that people refer to it as non-stable or unreliable. On a beach, where the already formed granular sand and the rise and fall of sea wave lies together, a new buff can be added to our flowing friend, a wetted state.

Magically but not randomly, sand gets sticky when combined with water, due to the most obvious physical theorem: surface tension and atmosphere pressure. From previous people's work, we've know that this buff comes from the water bridge formed between sand particles, which can significantly cluster together during the increasing water-sand portion[1]–[3]. Kudroli and Arshad has visualized the bridge between sand like Figure 1.

And that's the magic that glue our favorite sand castle together, which is one of the most entertainment for enthusiastic beach goers. However, being built near the water that melts mud and our wet sand, all sand castles have to face the fate that they'll g et too wet to hold its own weight and the impact from sea waves. That's because the water bridge has another property of clustering together[3]. When you throw a pile of sand into water, they behave just as when they're completely dry, melting down like fluid. Thus beach castle builder might want to make their sand castle last longer than those build arbitrarily than others, which is also the purpose of this article.

1.2 Our Work

Normally people will sculpt their kingdom from a pile of tedious wet sand. To simplify the model and grasp main threads, we'll focus our research on this single, nondescriptive mound of wetted sand.

2 Assumptions & Nomenclature

2.1 Assumptions

2.2 Nomenclature

3 Modeling Under Waves and Tides

The 3-dimensional shape constructing problem is divided into two subproblems. We first establish the model using the **Mohr-Coulomb Criterion** to decide the shape of the slope. We then construct another model with a modified version of **Cellular Automata** to determine the best shape viewed from the top,...

3.1 Shape of the Slope: Mohr-Coulomb Criterion

We begin by determining the Side shape of the sand castle foundation. Before Approaching the problem, we will briefly address the property of sand as a granular media.

In our assumptions, sand particle are considered as a simplified model of identical tiny spheres. If we zoom in to observe a pile of wet sand, there are the so-called liquid bridges formed between sand particles.

Various water contents produce different liquid bridge distributions, which will influence the properties of sand.

Table 1: States of Sand

Liquid Content	State	Description	left for future use
No	Dry	000	000
Small	Pendular	000	000
Middle	Funicular	000	000
Almost saturated	capillary	000	000
More	Slurry	000	000

When the wave hits the foundation, the surface area is in slurry state and there exists no cohesive interaction between the particles, which makes it very hard, if not impossible, to prevent sand loss. Nevertheless, collapses after the wave resides can cause more harm to the foundation, which can be avoided by alternating the shape.

For dry sand, the failure criterion is given in terms of the shear stress τ , the normal compressible stress σ and the internal friction μ as

$$\tau > \mu\sigma$$

This is simply the friction formula with different notations. Now we consider a sandpile with a normal adhesive stress s_A across every plane, in addition to the stress caused by weight. The equation(1) is then modified as

$$\tau > \mu(\sigma + s_A)$$

This criterion is the so-called **Mohr-Coulumb criterion**. The stress resulting from the weight above the plane is shown in figure (1). Denote τ_f and μ_f as the shear stress and normal compressible stress at the failure plane, they can be written as

$$\tau_f = \rho g D \sin \theta_c \quad \text{and} \quad \sigma_f = \rho g D \cos \theta_c$$

where θ_c is the critical angle, D is the height of the sandpile and ρ is the density of sand. Therefore, to solve for θ_c is to solve the equation

$$\mu = \tan \theta_c(D) \left(1 + \frac{s_A}{\rho g D \cos \theta_c(D)} \right)$$

The only unknown factor is s_A , the adhesive stress across the plane. According to (Thomas C.H and Alex J.L -fix later)'s study, the value of s_A is determined by water content and there are three regimes as a function of the added-fluid volume. We now focus only on the state where the water content is close to saturated.

3.2 Top View Shape

3.3 Calculating Results

3.4 Simulating Results

4 Modeling Under Rain

5 Determine the Best Sand-to-water Proportion

6 Other Ways to Make Our Sand Castle Last Longer

7 Sensitivity Analysis

This is a test figure. Remember to delete me.




Figure 2: A Windows Terminal.

This is a test figure. Remember to delete me.




Figure 3: A Windows Terminal.

This is some example text¹.

¹Hello footnote

I'm referring to footnote 1.

List of Figures

1	Water Bridge Between Sand Particle	1
2	A Windows Terminal.	4
3	A Windows Terminal.	4

List of Tables

1	States of Sand	2
---	--------------------------	---

List of Listings

References

- [1] M. Pakpour, M. Habibi, P. Møller, and D. Bonn, “How to construct the perfect sandcastle,” *Scientific reports*, vol. 2, no. 1, pp. 1–3, 2012.
- [2] N. Mitarai and F. Nori, “Wet granular materials,” *Advances in Physics*, vol. 55, no. 1-2, pp. 1–45, 2006.
- [3] A. Kudrolli, “Sticky sand,” *Nature materials*, vol. 7, no. 3, pp. 174–175, 2008.