


Power for IoT

USB Type C Power Delivery




Flexible, robust solution for power
and interconnect

Wireless Charging



Enabling Wirelessly Charging the
World

USB Power Delivery and Type-C™



Flexible, robust
solution for power
and interconnect

Type-C & USB-PD
Architecture
Features

ST products for
Type-C & USB-PD




Type-C & USB-PD
Solution





USB Type-C Overview

USB Power Delivery specification introduces USB Type-C receptacle, plug and cable; they provide a smaller, thinner and more robust alternative to existing USB interconnect. Main features are:

- Enable new and exciting host and device form-factors where size, industrial design and style are important parameters
- Work seamlessly with existing USB host and device silicon solutions
- Enhance ease of use for connecting USB devices with a focus on minimizing user confusion for plug and cable orientation



USB Type-C with Power Delivery



New USB Type-C receptacle, plug and cable;
a smaller, thinner and more robust alternative to existing USB interconnect

Enables new and exciting host and device form-factors where size,
industrial design and style are important parameters

Work seamlessly with existing USB host and device silicon solutions

Enhances ease of use for connecting USB devices
Focus on minimizing user confusion for plug and cable orientation

The Re-Evolution of USB

USB has evolved from a data interface capable of supplying limited power to a primary provider of *power* with a data interface



Power
Delivery

More **Power** with USB Power Delivery (100W)



Type-C

More **Flexibility** with a new reversible USB-C connector



Alternate
Mode

More **Protocols**
(Display Port, HDMI, VGA, Ethernet...)



USB IF

More Speed with USB 3.1 (10 Gbit/s)






USB Type-C: More Power Options

Mode of Operation	Nominal Voltage	Maximum Current	Notes
USB 2.0	5 V	500 mA	Default current, based on definitions in the base specifications
USB 3.1	5 V	900 mA	
USB BC 1.2	5 V	Up to 1.5 A	Legacy charging
USB Type-C @ 1.5 A	5 V	1.5 A	Supports high power devices
USB Type-C @ 3.0 A	5 V	3 A	Supports higher power devices
USB PD	Configurable up to 20 V	Configurable up to 5 A	Directional control and power level management

USB Type-C Power Rules



USB Type-C™ Pin Outs Functions

Enhance ease of use

Receptacle



A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	V _{BUS}	CC1	D+	D-	SBU1	V _{BUS}	RX2-	RX2+	GND
GND	RX1+	RX1-	V _{BUS}	SBU2	D-	D+	CC2	V _{BUS}	TX2-	TX2+	GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

Two pins on the USB Type-C receptacle, CC1 and CC2, are used in the discovery, configuration and management of connections across the USB Type-C cable

Plug



A12	A11	A10	A9	A8	A7	A6	A5	A4	A3	A2	A1
GND	RX2+	RX2-	V _{BUS}	SBU1	D-	D+	CC	V _{BUS}	TX1-	TX1+	GND
GND	TX2+	TX2-	V _{BUS}	V _{CONN}			SBU2	V _{BUS}	RX1-	RX1+	GND
B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12

On a standard USB Type-C cable, only a single CC wire within each plug is connected through the cable to establish signal orientation. The other CC pin is repurposed as V_{CONN} for powering electronics
Also, only one set of USB 2.0 D+/D- wires are implemented

High Speed Data Path
(RX for USB 3.1, or reconfigured in Alternate Mode)

High Speed Data Path
(TX for USB 3.1, or reconfigured in Alternate Mode)

USB 2.0 Interface

Cable Bus Power
(from 5V up to 20V)


Sideband use

Cable Ground


Configuration Channel

Architecture

Architecture and key words



USB Type-C CC Connections



- Detect attach/detach of USB ports, e.g. a DFP to a UFP
- **Resolve cable orientation and twist connections** to establish USB data bus routing
- Establish DFP and UFP roles between two attached ports
- Discover and configure VBUS
- USB Power Delivery Communication


USB PD Stack & Policy

Policies

System Policy Manager (system wide) is optional. It monitors and controls System Policy between various Providers and Consumers connected via USB.

Device Policy Manager (one per Provider or Consumer) provides mechanisms to monitor and control the USB-PD within a particular Provider or Consumer. It enables local policies to be enforced across the system by communication with the System Policy Manager.

Policy Engine (one per Source or Sink Port) interacts directly with the Device Policy Manager in order to determine the present local policy to be enforced.



Protocol Layer

The **Protocol Layer** forms the messages used to communicate information between a pair of ports. It receives inputs from the Policy Engine indicating which messages to send and indicates the responses back to the Policy Engine.


Physical Layer

It is responsible for sending and receiving messages across either the V_{BUS} or CC wire. It consists of a transceiver that superimposes a signal (BFSK on V_{BUS} or BMC on CC) on the wire.

It is responsible for managing data on the wire and for collision avoidance and detects errors in the messages using a CRC.

ST Products for USB Type-C PD

ST Chipset: A flexible offer in the USB Type-C PD ecosystem



Scalable offer for USB-PD controller and USB Type-C interface: from STM32 general purpose MCU to hard-coded solution to fit different use cases and power ratings


Large product portfolio for protection and filtering covering all the application needs

Highly secure solution using STSAFE secure element family for strong authentication needs




Power Management

A complete offer to “lean in” USB PD Ecosystem




Profile 1-2-3

Power source building blocks



- It covers profile 1-2-3 from 5W to 45W
- High Efficiency
- Low EMI design: intelligent Jitter for EMI suppression

Primary side controller: Adapters up to 45W



e.s. available

HV	1	VDD
NC	2	GD
FB	3	GND
ZCD	4	SENSE



SO8


Features

- Proprietary Constant current output regulation (CC) with no opto-coupler
- 700V embedded HV start-up circuit
- Quasi-resonant (QR) Zero Voltage Switching (ZVS) operation
- Valley skipping at medium-light load and advanced burst mode operation at no-load for under 10mW consumption
- Accurate adjustable output OVP

- Low part count. BOM reduction thanks to an extensive features integration
- Exceeding 5 stars: No-Load power < 10mW
 - HV start-up zero power consumption
 - Advanced burst-mode operation
- Flexibility: suitable for adapters from 5W to 40W
- High Efficiency
- Low EMI design: intelligent jitter for EMI suppression


Profile 4, 5

Power source building blocks



L6563H

Transition mode PFC controller



Datasheet : available on www.st.com

INV	1	Vcc
COMP	2	GD
MULT	3	GND
CS	4	ZCD
VFF	5	RUN
TBO	6	PWM_STOP
PFC_OK	7	N.C.
PWM_LATCH	8	HVS



SO16

- Low steady state ripple and current distortion with limited under- or overshoot of the pre-regulator's output thanks to new input voltage feed-forward implementation
- Reduced THD of the current
- High reliability thanks to a full set of protections
- HV start-up significantly reduces consumption compared to standard discrete circuit solutions
- Facilitated cooperation with cascaded DC-DC converter thanks to several power management & housekeeping functions


Features

- 700V High Voltage Start-up circuit
- Fast bidirectional input voltage feed-forward
- Adjustable OVP
- AC Brownout Detection
- Tracking boost function
- Inductor saturation protection
- Proprietary THD optimizer circuit
- Interface for cascaded converters
- -600mA/+800mA gate driver

L6699

High power adapters 90W to 250W



Series-resonant half-bridge topology



Features

- Self adjusting adaptive dead time
- Anti-capacitive mode protection
- Two-level OCP: Frequency shift and Immediate shutdown
- Safe-start procedure
- Burst-mode operation at light load
- Brown-out protection
- Interface with PFC controller

Datasheet : available on www.st.com



SO16N

- High efficiency:
 - Reduced internal consumption ($Iq=1mA$)
 - Adaptive dead time allows design optimization to achieve ZVS with lower magnetizing current
- Improved reliability and lifetime thanks to anti-capacitive protection and smooth start-up circuit
- Reduced audible noise when entering burst-mode operation thanks to smooth restart feature

USB-PD

Power MOSFET product families

800V-1500V

K5

600V-650V

M2

M6

Price/Performance

Premium efficiency

40-120V

F7

Flyback


Flyback/PFC/LLC

Synch Rec




VHV Power MOSFETs

Flyback Architecture



Outstanding Form Factor



STL8N80K5

800V, 950mOhm, 13nC
PowerFLAT5x6

Features

- Unmatched $R_{DS(on)}$ at very high BVDSS - 800-950V-1050V
- Ultra-Low Q_G and high switching speed
- Extremely low thermal resistance
- High quality & reliability


Benefits

- Lower on-state conduction losses
- Best switching losses
- High efficiency with lower design complexity
- Ultra small Form factor

Product range example

Part Number	B_{Vdss}	$R_{DS(on)}$	I_D
STB13N80K5	800V	0.45Ω	12A
STD8N80K5	800V	0.95Ω	6A
STD9N80K5	800V	0.90Ω	7A

Power MOSFET PFC & LLC architecture



Product range example

PFC	V_{DSS}	$R_{DS(on)}$	I_D
STF24N60M2	600V	0.190Ω	18A
STF25N60M2-EP	600V	0.188Ω	18A
STF20N60M2-EP	600V	0.278Ω	13A

PFC
Performance

LLC	V_{DSS}	$R_{DS(on)}$	I_D
STF9N60M2	600V	0.750Ω	5.5A
STF15N60M2-EP	600V	0.378Ω	11A
STF11N60M2-EP (e.s.available)	600V	0.595Ω	8.0A

LLC
Performance

LLC	V_{DSS}	$R_{DS(on)}$	I_D
STF9N60M6	600V	0.750Ω	ES April '16
STF10N60M6	600V	0.600Ω	ES April '16
STF13N60M6	600V	0.380Ω	ES April '16

LLC
Premium

Features

- Up to 30% lower Q_G vs main competition (equivalent die size)
- 400 – 700V BV_{DSS} rated
- Back-to-Back G-S Zener protected

Benefits

- Reduced switching losses
- Enhanced immunity vs ESD & V_{gs} spikes
- Technologies dedicated to specific topology

Product range example




STL24N60M2

600V, 210mΩ, 28nC
PowerFLAT8x8

Power MOSFETs

Synchronous rectification



Part Number	Voltage	Ron	Current
STL260N4LF7	40V	<1.1mΩ	5.5A
STL200N45LF7	40V	<1.8mΩ	11A

Features


- Very low $R_{DS(on)}$
- Proper C_{OSS}
- Low V_{SD} and Q_{RR} with soft recovery body-drain diode
- LL Vth

Benefits

- Efficiency improvement due to low conduction losses and static and dynamic diode ones, minimized switching noise and V_{ds} spike at turn OFF
- Easy driving features

Protections

A complete offer to “lean in” USB PD Ecosystem




Protections ESD/CMF/ECMF


High flexibility for the Designers needs to find best compatibilities



- Robustness: Surge capability up to 25kV and low clamping
- Flexibility & Integration: Single or multi lines products
- Transparency: High bandwidth for high speed signals




- High quality of protection
- Unique filtering shape capabilities
- Serial Interface: USB2.0/3.0, MIPI, DP, HDMI
- Filters radiated noise and limits antenna de-sense.



- High quality of protection
- High integration: 1mm² / 2 differential lines
- Serial Interface: USB2.0/3.0, MIPI, DP, HDMI
- Filters radiated noise and limits antenna de-sense


Type-C and USB PD Controller

A complete offer to “lean in” USB PD Ecosystem



Controller & Interface

Offering flexible and scalable solutions for designers



USB Type-C™ and USB PD Controller

STUSB Family: from USB Type-C Interface to 100% HW Power Delivery Controllers

STUSB1600

USB Type-C interface

STUSB1602

USB Type-C controller
with PD PHY
and BCM driver

STUSB47

Power Delivery controller
Provider only



**USB
Type-C**



**Power
Delivery**



**Alternate
Mode**

Up to 15W


**15W
to
100W**

**5W
to
100W**



USB-PD Provider Solution

- AC/DC Multi-output 45W Converter
 - Based on STCH02 QR controller
 - Multiple Output voltages (5V, 9V, 12V)
- STUSB4700 hard coded controller
 - to interface with USB-C connector
 - to handle the USB Power Delivery protocol
 - No software, better reliability




ST 45W Adapter for ST USB-PD


29

Board Layout: dimensions: L=3.47in, W=1.42in, H=0.95in

Top view



Bottom view



AC Input

FERD20H100S
STF10LN80K5

HF XFRM*

Bulk Cap 68uF, 400V

Control Board with STUSB4700 and TS391

Connection for Captive Cable: Vbus, GND, CC line

Opto

STCH02

Stripline Conn for Control Board

DSCH Switch

Load Switch

*RM10 Core Replaced EFD20



USB PD 2.0 Vs. USB PD 3.0

30



USB 3.0 ensures full compatibility with respect to USB 2.0 and requires some additional optional and mandatory features

New mandatory features in USB PD 3.0	Enables
Battery status data message (Required for systems with batteries)	Reporting of the battery state of charge
Battery capabilities extended message (Required for systems with batteries)	Reporting of the battery design capacity and last full charge capacity
Tighter control on communication to the cable (Required)	Only the V _{CONN} source to communicate to the cable plug e-marker
Source-coordinated collision avoidance (Required)	A more robust mechanism to avoid collisions caused when both source and sink want to send messages beyond the typical power negotiation. USB PD 2.0 has a collision-avoidance mechanism, but with the many new optional messages that may be sent in USB PD 3.0 a more robust method was needed
Not supported control message (Required)	A way to inform a port partner that a particular message is not supported. This is meant to help in the future as USB PD 3.0 expands to include more options and features.

- The voltages required by the new “Power Rules” are 5V, 9V, 15V, and 20V.
- USB PD 3.0 new features are not necessary in all application
- A simple Source device may not need USB PD 3.0 new features


Efficiency: 120VAC Input Voltage

- Power measured at output capacitor
- Tested at 5V and 15V; Load current swept from 0.1A to 3A
- ST Nucleo USB-PD board connected as a host
- Input Power Measured with Yokogawa WT200
- Output current and Voltage measured with Fluke True RMS Digital Multimeters
- Efficiency measured at room temperature after 20 min operation at full power
- No cable drop compensation




Efficiency: 230VAC Input Voltage

- Power measured at output capacitor
- Tested at 5V and 15V; Load current swept from 0.1A to 3A
- ST Nucleo USB-PD board connected as a host
- Input Power Measured with Yokogawa WT200
- Output current and Voltage measured with Fluke True RMS Digital Multimeters
- Efficiency measured at room temperature after 20 min operation at full power



USB-PD Dual Role Solution

MCU + Analog Front-End overview




- STM32 Embedded Software Solution + STUSB1602 AFE
 - Provide Flexibility
 - Possibility to customize the software
- Hardware : Entry level Cortex-M0 based STM32F0 microcontroller series with simple discrete Analog Front End PHY
- Embedded Software : USB-C & PD Middleware

Best device for 2 ports management : STM32F051 in 48 pin package
Best device for 1 port management : STM32F051/31 in 20/32 pin package

MCU Overview

STM32F0 HW resources





- Transmission uses : **TIM14, SPI1, DMA, GPIO**
- Reception uses : **TIM3, DMA, 1 comparator**
- TIM2** is used to time-schedule tasks
- Embedded **ADC** to detect device on the CC bus and perform power measurements
- CRC** to evaluate message's CRC
- Standard GP I/Os to control Vconn, Load switch, Vbus discharge switch, Vout selection (primary feedback...)

Project	Flash Memory	RAM Memory
Provider only	25.5 kB	4.4 kB
Provider only (RTOS)	29.0 kB	7.3 kB
Provider/Consumer DRP (RTOS)	30.2 kB	7.3 kB

USB-PD Interface

STUSB16xx



Features


- Dual Role Type-C Interface with BMC
- Dual role capability
- Configurable start-up profiles
- 600mA VCONN
- 120uA Idle current measured
- Interface with external MCU through I²C+Interrupt
- Integrated Voltage monitoring
- Integrated V_{BUS} discharge path
- Accessory support
- Dual Power supply:
 - V_{SYS} = 3.3V,
 - V_{DD} [4.6V; 22V] (from V_{BUS})

Benefits

- Low Pin count
- Integrated BMC transceiver
- Simple, Robust
- Configurable, Flexible
- Optimized for Portable applications
- P2P with STUSB4x


X-NUCLEO-USBPDM1

- USB-C Power Delivery expansion board with two USB Type-C connectors for two port management
- Main features:
 - Two Dual Role Port
 - Dedicated Power Connector to interface with external Power Supply board providing different profiles (up to 20V and 5A) and V_{CONN}
 - On-board Power management able to provide internal needed voltages from V_{BUS}
 - Six debug LEDs
 - USB 2.0 interface capability available on one port
 - Compatible with STM32 Nucleo boards
 - Equipped with ST morpho connectors




X-NUCLEO-USBPDM1

Board details



ST Enables The Wireless Charging World



Dual Mode TRx



Consumer



Automotive




Wearable





Dual Mode TRx

Multi Mode Qi/Airfuel Wireless Power Receiver with Transmitter Function



Plug and play solution certified with Qi 1.2 15W and Airfuel Inductive 5W standards

Wireless Power Receiver with Transmitter Function

Firmware customization available



CES Demo: Dual Mode TRx

Wireless power reference design: plug and play

Rx & Tx: STWLC33



Receiver: STWLC33



Receiver: Qi and Airfuel Inductive Standards
5V fixed output Voltage – up to 5W (due to phone limitation)

Transmitter: Qi based
Transmitted Power up to 3W

PCB Dimension 15x25mm
Coil Rx-Tx - TDK WR424245-13K2-G


5V fixed output voltage
Li-Ion direct battery charging Option

Space saving solution: 6x10mm - 1mm total thickness (PCB + BOM)
Coil Rx – TDK WR303050-15F5-G

Max Output Power: 3W
Output Leakage: <1uA



STWLC33 - Receiver

Multi Mode Qi/Airfuel 15W Wireless Power Receiver with Tx function



STWLC33 - Receiver


Measurement Results





Wearable Solution

Wireless charging reference design – 1 Watt wireless delivery



5 V USB powered TX and configurable output voltage
5 V or direct charging mode on RX

Active presence detection, FOD, Li-Ion battery supported


Firmware customization available



Wearable Solution

Wireless power reference design – 1 Watt wireless delivery

Transmitter STWBC-WA




USB as power source
5 V input, up to 0.5 A

Smart standby
Automatic receiver recognition
FOD for increased safety

Minimal BOM thanks to half bridge
architecture

Configurable via API for application
customization via GUI

Receiver: STWLCO4





Consumer Solution

Wireless charging reference design: plug and play



Plug and play solution certified with Qi and PMA standards

Energy friendly with smart standby, safe with FOD

Firmware customization available, supports different battery chemistry and direct charging



Consumer Solution

Wireless power reference design: plug and play

STWBC: Transmitter




Ubiquitous: 5 V USB powered

Plug and play: Qi 1.2 LP certified (5 W)

Smart Standby: 3 mW consumption with FOD

Flexible: customizable via GUI or software API

Receiver: STWLC03



Energy friendly: Integrated high-performance buck converter and synchronous rectifier

Plug and play: certification with Qi (5 W) and PMA standards (7.5 W)

Safe: enables safe operation with advanced FOD

Flexible: supports different battery chemistry and direct charging





Automotive Solution

Wireless charging is part of the convergence of smartphones and vehicles



Multi-coil providing a large charging area

Qi-certified solutions with foreign-object detection

ESD protections, low EMI, smart standby

NFC coexistence

Transmitter: STWBC-MC and ASTWBC AEC-Q100
Grade 2




Automotive Solution

Wireless charging is part of the convergence of smartphones and vehicles

STWBC-MC transmitter controlling flyback, half bridge, coil selectors, Qi protocol and FOD


- **Power rate**
 - 5 W typical on RX side
- **Qi standard support**
 - Qi 1.2.1 certification ongoing
- **Wireless Charging Features**
 - Wide charging area: 3 coils support
 - Low EMI: fixed frequency switching
 - Safe: foreign object detection also during stand-by
 - Dynamic voltage adaptation: support variable Vin between 5V to 15V
- **Solution features**
 - 2 layers PCB
 - Turn key or customization contacting ST
- **Products:**
 - STWBC-MC and ASTWBC with AEC-Q100 grade 2 (- 40 ÷ 105 °C) qualification ongoing





Wireless Power

Available now!



Further information and full design support available at: www.st.com

