

# Advanced Programming Concepts with C++ CSI2372 – Fall 2017

Jochen Lang  
EECS, University of Ottawa  
Canada

Université d'Ottawa | University of Ottawa



uOttawa

L'Université canadienne  
Canada's university



[uOttawa.ca](http://uOttawa.ca)

# This Lecture

## No reinventing the wheel

- STL
  - Sequential container adapters, Ch. 9.6
    - `queue`, `priority_queue`, `stack`
  - Associative containers, Ch. 11
    - `map`, `set`, `multimap`, `multiset`
    - C++11 `unordered_map`, `unordered_set`,  
`unordered_multimap`, `unordered_multiset`
  - Generic algorithms, Ch. 10

# Sequential Container Adapters

- **Idea**
  - Have a container behave like something else
- **Two headers**
  - Both `queue` and `priority_queue` are defined in:  
`<queue>`
  - `Stack` is defined in `<stack>`
- **Construction**
  - Default constructor creates an empty default container
  - Both `queue` and `stack` adapt `deque` by default
  - `priority_queue` adapts a `vector` by default

# Adapting a Different Container


- In the construction a different container may be specified to be adapted
- Template parameter needs to be specified

```
#include <queue>
#include <stack>
using std::vector;
using std::priority_queue;
using std::stack;
// Construction by a vector of 100 elements all = 1
vector<int> iVec( 100, 1);
// Copy the vector as a basis for priority_queue - default
priority_queue<int> pq( iVec.begin(), iVec.end() );
// Copy the vector as a basis for stack - non-default
stack<int, vector<int> > iStack( iVec );
```

# Some Methods


- **Stack operation**

- Placing an element onto the stack `push(element)`
- Returning the top element `top()`
- Removing but not returning the top element `pop()`



- **Queue operation**

- Placing an element into the queue `push(element)`
- Returning the front element `front()`
- Returning the back element `back()`
- Removing but not returning the front element `pop()`



# Associative Containers

- **Idea**
  - Store elements in the container based on a key
- **Need to pair up a key and a value**
  - The header `<utility>` defines a type `pair`
  - Pair holds public data members `first` and `second`
  - Default construction or with two initializers

key	value
<code>first</code>	<code>second</code>

# Some Operations on Pairs

- **Constructors**

- Default construction `pair<T1,T2> p`
- Construction with initialization  
`pair<T1,T2> p( v1, v2 )`
- Making a new pair with inferring types from arguments  
`make_pair( v1, v2 )`

- **Comparison**

- **LessThan Comparable:** `p1 < p2` defined as `p1.first < p2.first || (!(p1.first < p2.first) && !(p1.first > p2.first) && p1.second < p2.second)`
- **Equality Comparable:** `p1 == p2` is true if `p1.first == p2.first && p1.second == p2.second`

# Map Type

- **Sorted collection of key-value pairs with unique keys**
  - Commonly red-black trees are used for implementation
- **Construction**
  - Default construction `map<K, V> KVmap`
  - Copy construction `map<K, V> KVmap( oMap )`
  - Copy a range of pairs  
`map<K, V> KVmap( iterA, iterB )`
- **Types in map**
  - **Key** `map<K, V>::key_type`
  - **Value** `map<K, V>::mapped_type`
  - **Pair** `map<K, V>::value_type`



# Constraints on keys

- Strict weak ordering (in mathematical notation)

$$\neg (k1 < k1)$$

$$k1 < k2 < k3 \Rightarrow k1 < k3$$

$$\neg (k1 < k2 \ \& \ k2 < k1)$$

- Map container uses `operator<` by default
- Keys in maps are `const`

# Map Construction

- **Default constructor**
  - empty map
- **Range constructor**
  - as with sequential containers, takes two iterators
- **Copy constructor**
  - copies each element (as with sequential containers)
- **Initializer list constructor (C++11)**
  - as with sequential containers but here with pairs

```
#include <map>
// map with string as a key and int as value
map<string, int> siMap = {{"Smith, John", 31245},
                        {"Doe, Jane", 245876},
                        {"Scott, Stephen", 34411}};
```

# Inserting and Removing Elements from

**a** map

- **Inserting**

- Will not insert the pair if key is already in map
- Single pair `KVmap.insert(p)`
- With hint where to start the search  
`KVmap.insert(iter, p)`
- Range of pairs `KVmap.insert(iterA, iterB)`

- **Removing**

- By key `KVmap.erase(k)`
- At iterator `KVmap.erase(iter)`
- Range of pairs `KVmap.erase(iterA, iterB)`

# Test if Map contains Key and Map Subscripting

- Count the occurrences of a key `KVmap.count(k)`
  - Note: always 0 or 1 in map
- Return an iterator to the pair with the key `KVmap.find(k)`
- **Subscripting**
  - Subscripting access the value `KVmap[k] = v`
  - *If key is not in map subscripting will add it!*

## Example: Insertion into a Map

```
#include <map>
// map with string as a key and int as value
map<string, int> siMap{{"Smith, John", 31245},
                     {"Doe, Jane", 245876},
                     {"Scott, Stephen", 34411}};
siMap["Sobey, Anna"] = 89554; // Add another entry
siMap["Doe, Jane"] = 2; // Update value for existing key
// duplicate key - no insertion
siMap.insert(make_pair("Doe, Jane", 1));
// insert pairs in other map - types must match
map<string, int> oMap;
oMap.insert( siMap.begin(), siMap.end() );
auto iter ← oMap.find("Doe, Jane");
if ( iter != siMap.end() ) {
    cout << iter->first << " val: " << iter->second << endl;
    siMap.erase( iter );
}
```

map<string, int>::iterator

# Iterating over a Map

- Similar to sequential container
- Element is a pair and iterator dereference yields a pair

```
#include <map>
map<string, int> siMap; // map with string as a key
// loop over the elements
for ( auto iter = siMap.cbegin();  
      iter != siMap.cend(); ++iter ) {  
    cout << "Key: " << iter->first << endl;  
    cout << "Value: " << iter->second << endl;  
}  
for (auto si:siMap) { // use range loop  
    cout << "Key: " << si.first << endl;  
    cout << "Value: " << si.second << endl;  
}
```

`map <string, int>::  
 const_iterator`

# Multiple Entries `Multimap`

- **Key can be inserted multiple times**
  - Occurrences of a key `Mmap.count(k)`
    - May return 0 or a positive integer in `multimap`
  - Iterator to the first pair with the key `Mmap.find(k)`
  - Identical keys are sorted by the order they were inserted
- **Dealing with multiple entries**
  - Multiple entries with the same key are stored in sequence
    - First entry with a key `Mmap.lower_bound(k)`
    - Last entry with a key `Mmap.upper_bound(k)`
    - Get the pair of first and last `Mmap.equal_range(k)`

## **Sets:** `set` **and** `multiset`

- **Sets are ordered containers like maps but the key and value are the same**
  - Because key are const, elements can only be read accessed
    - `iterator` **and** `const_iterator` are const
  - Set operations are not part of set
    - generic algorithms are available for mathematical set operations



# Unordered Maps (Hash Maps)


- STL map and multi\_map are tree maps
  - I.e., by using a balanced binary tree (e.g., AVL tree)
  - Insertion, removal, find all take  $O(\log n)$  time
- A hash-map may perform better with a good hash function if load factor is not too high
  - A hash-map is in `<unordered_map>` (C++11)
    - `unordered_map` **and** `unordered_multimap`
  - A hash-set is in `<unordered_set>` (C++11)
    - `unordered_set` **and** `unordered_multiset`
- Note: Type `hash_map` is not part of the STL but used to be provided by many compilers, e.g., gcc or Visual Studio in a namespace `ext` or `stdext`

# Unordered Containers

- Most operations on unordered containers are the same as for the corresponding associative based on a tree implementation
- **But**
  - No ordering constraints
  - Key is replaced by hash value
    - Unordered container use `==` (instead of `<` for map)
    - Library supplies hash functions for built-in types and some STL types through `hash<key_type>`
  - Functions to control the set up of the hash table (use of buckets)

# Unordered Containers use a Hashtable with Buckets

- Some functions to manage the buckets and to access elements in a bucket
  - `hmap.bucket_count()`, `hmap.bucket_size()`, `hmap_bucket(key)`
  - `hmap.load_factor()`, `hmap.rehash(min_no_buckets)`, `hmap.reserve(num_elements)`



# Hashing Keys

- May use own type as key in an unordered container

```
#include <unordered_map>
std::unordered_map<Id, string> hMap;
```

- Need to define both an equality operator for the key class and a hashing function
  - Equality operator

```
struct Id {
    std::string d_name;
    int d_id;
    // define the equal operator
    bool operator==(const Id& _oId ) const {
        return (d_id == _oId.d_id && d_name == _oId.d_name);
    }
};
```

# Hash Function

- Directly defining a hash function
  - Here relying on the built-in hash for string

```
struct Id { ...  
    size_t operator()( const Id& _id ) const {  
        return (std::hash<std::string>() (_id.d_name) ^  
                std::hash<int>() (_id.d_id)<<1); }    };
```

- Or
  - By specializing the template `hash<key_type>`

```
namespace std {  
    template <> struct hash<Id> {  
        size_t operator()( const Id& _id ) const {  
            return (std::hash<std::string>() (_id.d_name) ^  
                    std::hash<int>() (_id.d_id)>>1);  
        }  
    }; } // end of namespace
```

# Generic Algorithms

- Algorithms are not part of any container class
  - Unlike Java
- Algorithms also work on other types
  - Types must conform to the STL convention
  - Many work with built-in arrays
- Algorithms work solely with iterators
  - no insertion or removal into a container by the algorithm but change of value or change of element position
  - indirect insertion through an insertion iterator (inserter)

# Modifying Elements

- **Example: `fill_n`**
  - fills `n` elements of a container with a value
    - Remember `std` algorithms do not create new elements
      - elements must already exist

```
const vector<string>::size_type sz = 10;  
vector<string> sVec( sz, "abc" );  
  
std::fill_n( sVec.begin() + 3, 4, string("xyz") );
```

# Copying Elements

- **Example: copy**
  - copies elements from a source container to a sequential destination container
  - Remember std algorithms do not create new elements
    - elements must already exist

```
std::vector<std::pair<string,int> > siVec;  
map<string, int> siMap{{"Smith, John", 31245},  
                      {"Doe, Jane", 245876},  
                      {"Scott, Stephen", 34411}};  
siVec.resize(siMap.size());  
std::copy( siMap.begin(), siMap.end(), siVec.begin());  
for ( const auto& si:siVec ) {  
    cout << "Key: " << si.first << endl;  
    cout << "Value: " << si.second << endl;  
}
```



# Deleting Elements

- **Example: unique**
  - sorts a container such that there are no consecutive duplicates at the beginning of the container
  - returns an iterator to where no duplicates regions ends
    - Remember std algorithms do not delete elements
      - elements must be deleted separately

```
const vector<string>::size_type sz = 10;
vector<string> sVec( sz, "abc" );
std::fill_n( sVec.begin() + 3, 4, string("xyz"));

vector<string>::iterator lastU =
    std::unique( iVec.begin(), iVec.end());
```

# Sorting

- **Some generic sorting algorithms**
  - Range between random access iterators
    - `sort( iterA, iterB )`
    - `stable_sort( iterA, iterB )`
  - Additionally if range satisfies heap property
    - `sort_heap( iterA, iterB )`

# Algorithms Related to Sorting

- **Turn a range between random access iterators into a heap**

```
make_heap( iterA, iterB)
```

- **Merge two sorted ranges between input iterator**

```
merge( iterA1, iterB1,  
       iterA2, iterB2, outIter )
```

- **Partition a range between forward iterators**

```
partition( iterA, iterB, predicate )
```

# Searching

- **Minimum and maximum in range of forward iterators**
  - `min_element( iterA, iterB )`
  - `max_element( iterA, iterB )`
- **The nth element in range of random access iterators**
  - `nth_element( iterA, iterN, iterB )`
- **Find an element equals a value in range of input iterators**
  - `find( iterA, iterB, val )`
  - With binary search:  
`binary_search(iterA, iterB, val )`

# Next

## No more Memory leaks

- **Smart pointers and data management**
  - Textbook (Lippman): Chapters 12, 12.1-12.2
  - Smart pointers
  - C++11 smart pointer library types
  - Move constructor and move assignments