














| Tag name   | Description   |
|--|---|
| <!-- -->   | This tag is used to apply comment in an HTML document.  |
| <!DOCTYPE>   | This tag is used to specify the version of HTML   |
| <b>A</b>   |   |
| <a>  | It is termed as anchor tag and it creates a hyperlink or link.  |
| <abbr>   | It defines an abbreviation for a phrase or longer word.   |
| <acronym>  | It defines acronym for a word. <b>(Not supported in HTML5)</b>  |
| <address>  | It defines the author's contact information of the HTML article   |
| <applet>   | It defines an embedded Java applet. <b>(Not supported in HTML5)</b>   |
| <area>   | It defines the area of an image map.  |
| <article>   | It defines the self-contained content.  |
| <aside>     | It defines content aside from main content. Mainly represented as sidebar.  |
| <audio>     | It is used to embed sound content in HTML document.   |
| <b>B</b>   |   |
| <b>  | It is used to make a text bold.   |
| <base>   | This tag defines the base URL for all relative URL within the document.   |
| <basefont>   | This tag is used to set default font, size and color for all elements of document. <b>(Not supported in HTML5)</b>                    |
| <bdi>     | This tag is used to provide isolation for that part of text which may be formatted in different directions from its surrounding text. |
| <bdo>  | It is used to override the current text direction.  |
| <big>  | This tag is used to make font size one level larger than its surrounding content. <b>(Not supported in HTML5)</b>                     |
| <blockquote>   | It is used to define a content which is taken from another source.  |
| <body>   | It is used to define the body section of an HTML document.  |
| <br>   | It is used to apply single line break.  |
| <button>   | It is used to represent a clickable button  |
| <b>C</b>   |   |
| <canvas>  | It is used to provide a graphics space within a web document.   |
| <caption>  | It is used to define a caption for a table.   |
| <center>   | It is used to align the content in center. <b>(Not supported in HTML5)</b>  |
| <cite>   | It is used to define the title of the work, book, website, etc.   |
| <code>   | It is used to display a part of programming code in an HTML document.   |

|  |   |
|--|---|
| <col>  | It defines a column within a table which represent common properties of columns and used with the <colgroup> element. |
| <colgroup>   | It is used to define group of columns in a table.   |
| <b>D</b>   |   |
| <data>          | It is used to link the content with the machine-readable translation.   |
| <datalist>      | It is used to provide a predefined list for input option.   |
| <dd>   | It is used to provide definition/description of a term in description list.   |
| <del>  | It defines a text which has been deleted from the document.   |
| <details>       | It defines additional details which user can either view or hide.   |
| <dfn>  | It is used to indicate a term which is defined within a sentence/phrase.  |
| <dialog>        | It defines a dialog box or other interactive components.  |
| <dir>  | It is used as container for directory list of files. <b>(Not supported in HTML5)</b>                                  |
| <div>  | It defines a division or section within HTML document.  |
| <dl>   | It is used to define a description list.  |
| <dt>   | It is used to define a term in description list.  |
| <b>E</b>   |   |
| <em>   | It is used to emphasis the content applied within this element.   |
| <embed>       | It is used as embedded container for external file/application/media, etc.  |
| <b>F</b>   |   |
| <fieldset>   | It is used to group related elements/labels within a web form.  |
| <figcaption>  | It is used to add a caption or explanation for the <figure> element.  |
| <figure>      | It is used to define the self-contained content, and s mostly refer as single unit.                                   |
| <font>   | It defines the font, size, color, and face for the content. <b>(Not supported in HTML5)</b>                           |
| <footer>      | It defines the footer section of a webpage.   |
| <form>   | It is used to define an HTML form.  |
| <frame>  | It defines a particular area of webpage which can contain another HTML file. <b>(Not supported in HTML5)</b>          |
| <frameset>   | It defines group of Frames. <b>(Not supported in HTML5)</b>   |
| <b>H</b>   |   |
| <h1> to <h6>   | It defines headings for an HTML document from level 1 to level 6.   |
| <head>   | It defines the head section of an HTML document.  |
| <header>      | It defines the header of a section or webpage.  |

|  |   |
|--|---|
| <code>&lt;hr&gt;</code>  | It is used to apply thematic break between paragraph-level elements.  |
| <code>&lt;html&gt;</code>  | It represents root of an HTML document.   |
| <b>I</b>   |   |
| <code>&lt;i&gt;</code>   | It is used to represent a text in some different voice.   |
| <code>&lt;iframe&gt;</code>  | It defines an inline frame which can embed other content.   |
| <code>&lt;img&gt;</code>   | It is used to insert an image within an HTML document.  |
| <code>&lt;input&gt;</code>   | It defines an input field within an HTML form.  |
| <code>&lt;ins&gt;</code>   | It represent text that has been inserted within an HTML document.   |
| <code>&lt;isindex&gt;</code>   | It is used to display search string for current document. <b>(Not supported in HTML5)</b>   |
| <b>K</b>   |   |
| <code>&lt;kbd&gt;</code>   | It is used to define keyboard input.  |
| <b>L</b>   |   |
| <code>&lt;label&gt;</code>   | It defines a text label for the input field of form.  |
| <code>&lt;legend&gt;</code>  | It defines a caption for content of <code>&lt;fieldset&gt;</code>   |
| <code>&lt;li&gt;</code>  | It is used to represent items in list.  |
| <code>&lt;link&gt;</code>  | It represents a relationship between current document and an external resource.   |
| <b>M</b>   |   |
| <code>&lt;main&gt;</code>   | It represents the main content of an HTML document.   |
| <code>&lt;map&gt;</code>   | It defines an image map with active areas.  |
| <code>&lt;mark&gt;</code>   | It represents a highlighted text.   |
| <code>&lt;marquee&gt;</code>   | It is used to insert the scrolling text or an image either horizontally or vertically. <b>(Not supported in HTML5)</b>                                |
| <code>&lt;menu&gt;</code>  | It is used for creating a menu list of commands.  |
| <code>&lt;meta&gt;</code>  | It defines metadata of an HTML document.  |
| <code>&lt;meter&gt;</code>  | It defines scalar measurement with known range or fractional value.   |
| <b>N</b>   |   |
| <code>&lt;nav&gt;</code>    | It represents section of page to represent navigation links.  |
| <code>&lt;noframes&gt;</code>  | It provides alternate content to represent in browser which does not support the <code>&lt;frame&gt;</code> elements. <b>(Not supported in HTML5)</b> |
| <code>&lt;noscript&gt;</code>  | It provides an alternative content if a script type is not supported in browser.  |
| <b>O</b>   |   |
| <code>&lt;object&gt;</code>  | It is used to embed an object in HTML file.   |

|  |   |
|--|---|
| <code>&lt;ol&gt;</code>  | It defines an ordered list of items.  |
| <code>&lt;optgroup&gt;</code>  | It is used to group the options of a drop-down list.  |
| <code>&lt;option&gt;</code>  | It is used to define options or items in a drop-down list.  |
| <code>&lt;output&gt;</code>     | It is used as container element which can show result of a calculation.   |
| <b>P</b>   |   |
| <code>&lt;p&gt;</code>   | It represents a paragraph in an HTML document.  |
| <code>&lt;param&gt;</code>   | It defines parameter for an <code>&lt;object&gt;</code> element   |
| <code>&lt;picture&gt;</code>    | It defines more than one source element and one image element.  |
| <code>&lt;pre&gt;</code>   | It defines preformatted text in an HTML document.   |
| <code>&lt;progress&gt;</code>   | It defines the progress of a task within HTML document.   |
| <b>Q</b>   |   |
| <code>&lt;q&gt;</code>   | It defines short inline quotation.  |
| <b>R</b>   |   |
| <code>&lt;rp&gt;</code>         | It defines an alternative content if browser does not supports ruby annotations.  |
| <code>&lt;rt&gt;</code>  | It defines explanations and pronunciations in ruby annotations.   |
| <code>&lt;ruby&gt;</code>  | It is used to represent ruby annotations.   |
| <b>S</b>   |   |
| <code>&lt;s&gt;</code>   | It render text which is no longer correct or relevant.  |
| <code>&lt;samp&gt;</code>  | It is used to represent sample output of a computer program.  |
| <code>&lt;script&gt;</code>  | It is used to declare the JavaScript within HTML document.  |
| <code>&lt;section&gt;</code>  | It defines a generic section for a document.  |
| <code>&lt;select&gt;</code>  | It represents a control which provides a menu of options.   |
| <code>&lt;small&gt;</code>   | It is used to make text font one size smaller than document?s base font size.   |
| <code>&lt;source&gt;</code>   | It defines multiple media recourses for different media element such as <code>&lt;picture&gt;</code> , <code>&lt;video&gt;</code> , and <code>&lt;audio&gt;</code> element. |
| <code>&lt;span&gt;</code>  | It is used for styling and grouping inline.   |
| <code>&lt;strike&gt;</code>  | It is used to render strike through the text. <b>(Not supported in HTML5)</b>   |
| <code>&lt;strong&gt;</code>  | It is used to define important text.  |
| <code>&lt;style&gt;</code>   | It is used to contain style information for an HTML document.   |
| <code>&lt;sub&gt;</code>   | It defines a text which displays as a subscript text.   |
| <code>&lt;summary&gt;</code>  | It defines summary which can be used with <code>&lt;details&gt;</code> tag.   |
| <code>&lt;sup&gt;</code>   | It defines a text which represent as superscript text.  |

|  |  |
|--|--|
| <code>&lt;svg&gt;</code>   | It is used as container of SVG (Scalable Vector Graphics).   |
| <b>T</b>   |  |
| <code>&lt;table&gt;</code>   | It is used to present data in tabular form or to create a table within HTML document.  |
| <code>&lt;tbody&gt;</code>   | It represents the body content of an HTML table and used along with <code>&lt;thead&gt;</code> and <code>&lt;tfoot&gt;</code> .  |
| <code>&lt;td&gt;</code>  | It is used to define cells of an HTML table which contains table data  |
| <code>&lt;template&gt;</code>  | It is used to contain the client side content which will not display at time of page load and may render later using JavaScript. |
| <code>&lt;textarea&gt;</code>  | It is used to define multiple line input, such as comment, feedback, and review, etc.  |
| <code>&lt;tfoot&gt;</code>   | It defines the footer content of an HTML table.  |
| <code>&lt;th&gt;</code>  | It defines the head cell of an HTML table.   |
| <code>&lt;thead&gt;</code>   | It defines the header of an HTML table. It is used along with <code>&lt;tbody&gt;</code> and <code>&lt;tfoot&gt;</code> tags.    |
| <code>&lt;time&gt;</code>     | It is used to define data/time within an HTML document.  |
| <code>&lt;title&gt;</code>   | It defines the title or name of an HTML document.  |
| <code>&lt;tr&gt;</code>  | It defines the row cells in an HTML table  |
| <code>&lt;track&gt;</code>   | It is used to define text tracks for <code>&lt;audio&gt;</code> and <code>&lt;video&gt;</code> elements.                         |
| <code>&lt;tt&gt;</code>  | It is used to define teletype text. <b>(Not supported in HTML5)</b>  |
| <b>U</b>   |  |
| <code>&lt;u&gt;</code>   | It is used to render enclosed text with an underline.  |
| <code>&lt;ul&gt;</code>  | It defines unordered list of items.  |
| <b>V</b>   |  |
| <code>&lt;var&gt;</code>   | It defines variable name used in mathematical or programming context.  |
| <code>&lt;video&gt;</code>  | It is used to embed a video content with an HTML document  |
| <b>W</b>   |  |
| <code>&lt;wbr&gt;</code>    | It defines a position within text where break line is possible.  |