

Fabric Lifecycle Agents — what belongs to what

Read a column top to bottom to see everything involved in one domain, from Microsoft's know-how down to the client's files. **Read a row across** to see one layer for every domain. Precedence when rules conflict: **Client > Firm rules > Microsoft**. Adding a domain = adding a column: one orchestrator, one rules file, evals; Microsoft's part is already in vendor/.

	SEMANTIC MODEL domain	REPORT domain	SHARED by every domain
MICROSOFT how things are done · vendored, pinned, never edited	vendor/.../semantic-model-authoring/ TMDL, MCP, Direct Lake, deploy, refresh	vendor/.../powerbi-report-planning/ - design/ -authoring/ -management/ PBIR files, visuals, validate, publish	vendor/.../common/ Fabric REST + auth recipes both domains use
FIRM · ENTRY POINT the orchestrator · what a consultant invokes · routing only, no rules	skills/semantic-model/SKILL.md /semantic-model ...	skills/report/SKILL.md /report ...	skills/engagement-workflow/ phases, gates, templates — both domains follow it
FIRM · RULES what good looks like · the firm's standards	skills/standards/semantic-model.md MOD-* modelling rules · DAX-* rules · RLS patterns	skills/standards/report.md RPT-* rules · review checklist · theme	skills/standards/SKILL.md index + the ONE table of overrides of Microsoft naming.yaml · bpa-rules.json — machine-checkable subset
FIRM · WORKERS subagents the orchestrator delegates to	agents/modeler.md builds TMDL	— the report orchestrator authors PBIR itself	agents/reviewer.md · agents/report-reviewer.md · agents/deployer.md read-only reviewers write the review that gates deploy; deployer needs a passing review + prod token
FIRM · GUARDRAILS enforcement · runs whether or not the agent read the rules	scripts/lint-tmdl.py hook blocks Modeling-MCP writes (MOD-00); lints TMDL after every edit	scripts/check-report-bindings.py hook blocks .pbix writes (RPT-00); checks report bindings after every edit	hooks/pre-tool-use.sh · hooks/post-edit-tmdl.sh block writes to vendor/ · block prod deploy without today's token
CLIENT what's different this time · lives in the client's repo on a real engagement	clients/<code>/models/<Model>.SemanticModel/ the TMDL model · spec.md · reviews/<Model>-* .md	clients/<code>/models/<Report>.Report/ the PBIR report · _brief-report-spec.md · reviews/<Report>-report-* .md	clients/<code>/engagement.yaml · overrides.md · glossary.md config · CO-* exceptions to firm rules · business terms
PLUMBING packaging, CI, tests	evals/scenarios/001-006 · fixtures/bad-model/	evals/scenarios/007-009 · fixtures/bad-report/	.claude-plugin/ · .github/workflows/ · commands/ · scripts/sync-upstream.sh install · weekly upstream sync, evals on PR, release on tag · /new-engagement /review /sync-upstream

Orchestrator = the SKILL.md a consultant invokes; it loads the other rows in precedence order and delegates to workers.

Rules = prose the agent reads. **Guardrails** = scripts that run regardless.

Handoff model → report = the commit sha recorded in a passing model review.