



## Denis Shevchenko

- ✓ Haskell Developer at IOHK
- ✓ Co-founder of ruHaskell
- ✓ Code since 2005

 @dshevchenko\_biz



August 2019

# A practical introduction to **FP** in Python

**FP?**

FP — **rewrite** your code!

# OOP's **for**

```
names = ['David', 'Karen', 'Ruben']  
secrets = []  
for i in range(len(names)):  
    secrets.append(hash(names[i]))
```

# FP's **map**

```
names = ['David', 'Karen', 'Ruben']  
secrets = map(hash, names)
```

**rethink**

FP — ~~rewrite~~ your code!

```
def inc():  
    global a  
    a += 1
```

```
def check():  
    if a > 12:  
        print("Enough!")
```



```
a = 3
```

```
inc()
```


```
check()
```


```
def inc(a):  
    return(a + 1)
```

```
def check(a):  
    if a > 12:  
        return "Enough!"
```

```
print(check(inc(3)))
```

**Compose** your functions





```
from infix import shift_infix as infix
```

```
@infix
```

```
def then(f, g):
```

```
    return lambda x: g(f(x))
```

do = inc <<then>> check



do = inc <<then>> check

do\_all = do <<then>> **print**

```
do = inc <<then>> check
```

```
do_all = do <<then>> print
```

```
...
```

```
do_all(3)
```

Use **fair** constants

PI = 3.14159265

...

```
def calcCircLength(r: float) -> float:  
    return 2 * PI * r
```

```
import cmath
```

```
...
```

```
def circle_length(r: float) -> float:  
    return 2 * cmath.pi * r
```

```
import cmath
```

```
cmath.pi = 3.129 # Bad joke!
```

```
def circle_length(r: float) -> float:  
    return 2 * cmath.pi * r
```

```
def pi() -> float:  
    return 3.14159265
```

...

```
def circle_length(r: float) -> float:  
    return 2 * pi() * r
```

**Math?!**




$$M = (S, \bullet, e)$$

I  $S = \{...\}$

II  $\bullet = S \times S \rightarrow S$

III  $\exists e \in S : e \bullet a = a \bullet e = a$



```
https_prefix = "https://"
base_url     = "istc.am"
secure_url   = https_prefix + base_url
```

```
https_prefix = "https://"
base_url      = "istc.am"
secure_url    = https_prefix + base_url
```

**Monoid — idea!**

```
https_prefix = "https://"
base_url     = "istc.am"
secure_url   = https_prefix + base_url
```

Take **existent**, create **new**.

So...

- I **Compose** your functions
- II Use **fair** constants
- III Don't be **afraid** of math



What's **next**?

«A practical introduction  
to functional programming»

[bit.do/fpPython](https://bit.do/fpPython)

Thank you!

**Questions?**