

Problem: Procedural To-Do List

Write a Java program that manages a simple to-do list.

Your program should allow the user to store up to 5 tasks. Each task should contain:

- a unique integer ID
- a description
- a completion status

When a new task is created, it should automatically receive the next available ID. New tasks should begin as incomplete.

The program should support the following operations:

1. Add a new task using a description.
2. Display all incomplete tasks.
3. Mark a task as complete using its task ID.
4. Remove a task using its task ID.
5. Report whether an operation succeeded or failed.

If the task list is full, the program should not add another task.

If the user attempts to complete or remove a task that does not exist, the operation should fail.

If the user attempts to complete a task that is already complete, the operation should also fail.

For this version, solve the problem procedurally. Do not create `Task`, `TaskList`, or `TaskManager` classes.

You may use arrays, variables, loops, conditionals, and static methods.

For example, you may represent the task data using parallel arrays such as:

```
String[] descriptions = new String[5];
boolean[] completed = new boolean[5];
int[] taskIds = new int[5];
```

Your program should demonstrate the following sequence:

- Add five tasks.
- Attempt to add a sixth task.
- Display all incomplete tasks.
- Complete one task.
- Display the incomplete tasks again.
- Remove one task.
- Display the incomplete tasks again.

After completing the procedural version, consider how the program could be redesigned using objects so that related data and behavior are grouped together.