

## 64663 HLX

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets




### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Technical data

General Product Information

Product number (Americas)	54259
Product name (Americas)	EVD 64663 HLX 400W 36V 40/CS 1/SKU
Family brand	XENOPHOT (HLX)
Lamp type	HLX
ANSI code	EVD
LIF code	A1/239
Global order reference	64663 HLX

Electrical Data

Nominal wattage	400 W
Nominal voltage	36.0 V
Type of current	AC

Photometric Data

Nominal luminous flux	16200 lm
Illuminated field	9.3*4.9 mm <sup>2</sup>
Color temperature	3250 K
Color rendering index Ra	100
Light center length (LCL)	36.0 mm
Light center length (LCL) - (in)	1.404 in

Physical Attributes & Dimensions

Lamp base	G6.35
Diameter (in)	0.630 in
Diameter	15.0 mm
Length	60.0 mm
Product weight	5.50 g

Operating Conditions

Burning position	s90
------------------	-----

Lifetime Data

Nominal lifetime	50 hr
------------------	-------

Environmental & Regulatory Information

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300006741
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300006741	OSRH6466340	8327826	4739434	-
4050300006741	OSRH6466340	-	4739434	-

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006741	64663 HLX	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm <sup>3</sup>	2.00 g
4050300890937	64663 HLX	Shipping carton box 40	143 mm x 107 mm x 121 mm	1.86 dm <sup>3</sup>	386.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.