

64502 150 W 230 V

Halogen (> $130\ V$) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift





Product datasheet

Technical data

General Product Information

ANSI code	-
Global order reference	64502


Electrical Data

Nominal wattage	150 W
Nominal voltage	230 V

Photometric Data

Nominal luminous flux	4000 lm
Useful luminous flux (Фuse)	3675 lm
Φuse value refers to luminous flux	360
Illuminated field	13.0*1.9 mm²
Color temperature	3200 K
Correlated color temperature CCT	3232 K
Chromaticity coordinate x	0.422
Chromaticity coordinate y	0.400
Color rendering index Ra	100

Physical Attributes & Dimensions



Lamp base	GX6.35-20
Diameter	18.0 mm
Length	55.0 mm
Product weight	6.50 g

Operating Conditions

Burning position	Any

Product datasheet

Dimmable	Yes	
Lifetime Data		
Nominal lifetime	50 hr	

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4008321746054 4052899080751 405289936325			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899080751	64502 150 W 230 V	Folding carton box 1	33 mm x 37 mm x 71 mm	0.09 dm³	14.00 g
4052899080768	64502 150 W 230 V	Shipping carton box 20	205 mm x 142 mm x 76 mm	2.21 dm³	335.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.