

64515 300 W 230 V

Halogen (> 130 V) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets




Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift



Technical data

General Product Information

Product number (Americas)	54768
Product name (Americas)	64515 300W 230V 20/CS 1/SKU
Lamp type	SINGLE END
ANSI code	-
Product remark	With quartz pinch technology
Global order reference	64515


Electrical Data

Nominal wattage	300 W
Nominal voltage	230 V
Nominal current	1.3 A
Type of current	AC

Photometric Data

Nominal luminous flux	9600 lm
Useful luminous flux (Φ_{use})	10035 lm
Φ_{use} value refers to luminous flux	360
Illuminated field	9.8*12.5 mm ²
Color temperature	3300 K
Correlated color temperature CCT	3458 K
Chromaticity coordinate x	0.408
Chromaticity coordinate y	0.393
Color rendering index Ra	100
Light center length (LCL) - (in)	1.053 in

Physical Attributes & Dimensions



Product datasheet

Lamp base	GX6.35
Diameter (in)	0.728 in
Diameter	18.5 mm
Length	53.0 mm
Product weight	6.50 g

Operating Conditions

Burning position	s90
Dimmable	Yes

Lifetime Data

Nominal lifetime	15 hr
------------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321098696 4008321746153
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321746153	64515 300 W 230 V	Folding carton box 1	33 mm x 37 mm x 71 mm	0.09 dm ³	14.00 g
4008321746160	64515 300 W 230 V	Shipping carton box 20	194 mm x 139 mm x 84 mm	2.27 dm ³	342.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.