

# 64505 200 W 230 V

Halogen (>  $130\ V$ ) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift





## Product datasheet

### Technical data

### **General Product Information**

ANSI code	-
Product remark	With quartz pinch technology
Global order reference	64505


### **Electrical Data**

Nominal wattage	200 W
Nominal voltage	230 V

### **Photometric Data**

Nominal luminous flux	5100 lm
Useful luminous flux (Фuse)	5795 lm
Φuse value refers to luminous flux	360
Illuminated field	9.6*12.5 mm²
Color temperature	3200 K
Correlated color temperature CCT	3300 K
Chromaticity coordinate x	0.418
Chromaticity coordinate y	0.398
Color rendering index Ra	100

## **Physical Attributes & Dimensions**



Lamp base	GX6.35
Diameter	18.5 mm
Length	53.0 mm
Product weight	6.50 g

## **Operating Conditions**

## Product datasheet

Burning position	s90
Dimmable	Yes

### **Lifetime Data**

	_
Nominal lifetime	25 hr

## **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
<b>Primary article identifier</b> 4008321098436   4008321746078			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321746078	64505 200 W 230 V	Folding carton box 1	33 mm x 37 mm x 71 mm	0.09 dm <sup>3</sup>	14.00 g
4008321746085	64505 200 W 230 V	Shipping carton box 20	205 mm x 142 mm x 76 mm	2.21 dm³	335.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.