

64275 AX

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets



Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Technical data

General Product Information

Product number (Americas)	54258
Product name (Americas)	64275 AX 35W 6V 40/CS 1/SKU
ANSI code	-
LIF code	M/137
Global order reference	64275


Electrical Data

Nominal wattage	35 W
Nominal voltage	6 V
Type of current	AC

Photometric Data

Nominal luminous flux	755 lm
Illuminated field	1.3*1.6 mm²
Color temperature	3350 K
Color rendering index Ra	100
Light center length (LCL)	26.0 mm
Light center length (LCL) - (in)	1.014 in

Physical Attributes & Dimensions



Lamp base	G4
Diameter (in)	0.354 in
Diameter	9 mm
Length	35.0 mm
Product weight	2.50 g

Product datasheet

Operating Conditions

Burning position	Any
------------------	-----

Lifetime Data

Nominal lifetime	25 hr
------------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300258690
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300258690	OSRH6427540	-	-	-
4050300258690	OSRH6427540	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300258690	64275 AX	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm ³	4.50 g
4050300890913	64275 AX	Shipping carton box 40	122 mm x 109 mm x 152 mm	2.02 dm ³	405.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.