

# 64515 300 W 240 V

Halogen (>  $130\ V$ ) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift





# Product datasheet

### Technical data

### **General Product Information**

ANSI code	-	
Product remark	With quartz pinch technology	
Global order reference	64515	


### **Electrical Data**

Nominal wattage	300 W
Nominal voltage	240 V

### **Photometric Data**

Nominal luminous flux	8900 lm
Useful luminous flux (Φuse)	9685 lm
Φuse value refers to luminous flux	360
Illuminated field	10.0*12.5 mm²
Color temperature	3350 K
Correlated color temperature CCT	3400 K
Chromaticity coordinate x	0.412
Chromaticity coordinate y	0.395
Color rendering index Ra	100

# **Physical Attributes & Dimensions**



Lamp base	GX6.35
Diameter	18.5 mm
Length	53.0 mm
Product weight	6.50 g

# **Operating Conditions**

# Product datasheet

Burning position	s90
Dimmable	Yes

### **Lifetime Data**

Nominal lifetime	15 hr

# **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
imary article identifier 4008321746177			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321746177	64515 300 W 240 V	Folding carton box 1	32 mm x 37 mm x 71 mm	0.09 dm <sup>3</sup>	13.00 g
4008321746184	64515 300 W 240 V	Shipping carton box 20	194 mm x 139 mm x 84 mm	2.27 dm <sup>3</sup>	338.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.