

## 64672 500 W 240 V

Halogen (> 130 V) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets




### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift



Technical data

General Product Information

Product number (Americas)	54964
Product name (Americas)	64672 M40 500W 240V 12/CS 1/SKU
Lamp type	SINGLE ENDED
ANSI code	-
Global order reference	64672


Electrical Data

Nominal wattage	500 W
Nominal voltage	240 V

Photometric Data

Nominal luminous flux	8500 lm
Useful luminous flux ( $\Phi_{use}$ )	7405 lm
$\Phi_{use}$ value refers to luminous flux	360
Illuminated field	12.0*11.0 mm <sup>2</sup>
Color temperature	2900 K
Correlated color temperature CCT	2842 K
Chromaticity coordinate x	0.449
Chromaticity coordinate y	0.408
Color rendering index Ra	100

Physical Attributes & Dimensions



Lamp base	GY9.5
Diameter (in)	0.830 in
Diameter	22.0 mm
Length	89.9 mm

Product datasheet

Product weight	20.00 g
----------------	---------

Operating Conditions

Burning position	Any
Dimmable	Yes

Lifetime Data

Nominal lifetime	2000 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321098535
Energy efficiency class	G
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321098535	64672 500 W 240 V	Folding carton box 1	- x - x -		
4008321098542	64672 500 W 240 V	Shipping carton box 12	178 mm x 137 mm x 152 mm	3.71 dm <sup>3</sup>	720.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.