
swd conn
J6
Conn_01x05_Pin
GND
+3.3V
swclk
swdio
swrst
TODO: rewire to SWD standard
R1
10k
C1
100n
R3
10k
R2
10k
MCK_EXT
C5
12pF
Y1
32768kHz
C4
12pF
R15
2.2k
R14
2.2k
scl
sda
BT1
3.3V
PWR_FLAG
L1
10uH
C2
1uF
C3
100n
VDDA
C67
10n
C68
10n
U100
AP1117-33
VI
VO
C7
10uF
C8
10uF
+VDC
FIXME: использовать инвертор чтобы избежать одновременного включения
U1
STM32F411CEU6
NRST
BOOT0
PH0
PH1
PC13
PC14
PC15
PB0
PB1
PB2
PB3
PB4
PB5
PB6
PB7
PB8
PB9
PB10
PB12
PB13
PB14
PB15
VCAP1
VBAT
VDD
VSS
VSSA
PA0
PA1
PA2
PA3
PA4
PA5
PA6
PA7
PA8
PA9
PA10
PA11
PA12
PA13
PA14
PA15
LED
mck
SCLK
MISO
MOSI
scl
KEY_DAH
KEY_DIT
usb_dm
usb_dp
swdio
swclk
enc_a
displ_DC
displ_CS
displ_RESET
enc_b
sda
reset
QSE_EN
QSD_EN
filter_sel1
filter_sel2
displ_LED
ws
ck
sdi
sdo
C6
4.7uF
ESR: <1 Ohm
Keyboard
keyb
Файл: keyboard.kicad_sch
Codec
sdr_i
sdr_q
{i2s}
{i2c}
VOUTR+
VOUTR−
VOUTL+
VOUTL−
Файл: codec.kicad_sch
RF Processing
filter_selector1
filter_selector2
QSE_EN
QSD_EN
SDR_I
SDR_Q
R+
R−
L+
L−
swr_fwd
swr_rvs
phase0
phase1
Файл: rf_processing.kicad_sch
{spi}
Programmable Clock Generator
{i2c}
f0
f1
f2
MCK_EXT
Файл: clock_gen.kicad_sch
U4
AT24CS64-SSHM
SDA
SCL
WP
VCC
A0
A1
A2
Power supply
usb_dp
usb_dm
power_5VD
gnd
Файл: power.kicad_sch
Display ILI9341
D/C
SCK
CS
RESET
LED
VCC
T_OUT
T_IN
T_CS
T_IRQ
T_CLK
Файл: display.kicad_sch
SW6
RotaryEncoder
enc_a
enc_b
AudioJack5
J5
Telegraph key
KEY_DIT
KEY_DAH
Sheet: /
File: main.kicad_sch
Title:
Size: A4
Date:
Rev:
KiCad E.D.A. kicad 7.0.9+dfsg-1
Id: 1/13



Sheet: /Codec/		
File: codec.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 2/13



Sheet: /Programmable Clock Generator/
File: clock_gen.kicad_sch

Title:

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 3/13



Sheet: /Keyboard/		
File: keyboard.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 4/13



1 VCC 5V/3.3V power input
2 GND Ground
3 CS LCD chip select signal, low level enable
4 RESET LCD reset signal, low level reset
5 DC/RS LCD register / data selection signal,
high level: register, low level: data

6 SDI(MOSI) SPI bus write data signal
7 SCK SPI bus clock signal
8 LED Backlight control, high level lighting,
if not controlled, connect 3.3V always bright

9 SDO(MISO) SPI bus read data signal, if you do not need to the read function, you can not connect it
(The following is the touch screen signal line wiring, if you do not need to touch function or the module itself does not have touch function, you can not connect them)
10 T_CLK Touch SPI bus clock signal
11 T_CS Touch screen chip select signal, low level enable
12 T_DIN Touch SPI bus input
13 T_DO Touch SPI bus output
14 T_IRQ Touch screen interrupt signal, low level when touch is detected

Sheet: /Display ILI9341/
File: display.kicad_sch

Title: 2.8inch SPI Module ILI9341 SKU:MSP2807

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 5/13



Sheet: /Power supply/		
File: power.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 6/13









Sheet: /RF Processing/Filter selector/Filters/
File: filters.kicad_sch

Title:

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 8/13



Sheet: /RF Processing/Filter selector/ File: filter_selector.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 9/13



Sheet: /RF Processing/		
File: rf_processing.kicad_sch		
Title:		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg−1		Id: 10/13

Based on Selenite Lite SDR HF Transceiver by Dmitrii Rudnev

TODO:
Вопрос:
Нужны ли разделительные конденсаторы
(C46 и прочие) на большую ёмкость?

TODO: Необходимость этих резисторов и их номинал под вопросом



Phases:

0	1	2	3
L−	R−	R+	L+
L+	R+	R−	L−

Sheet: /RF Processing/Modulator/
File: modulator.kicad_sch

Title: Quadrature Sampling Exciter (QSE)

Size: A4	Date:	Rev:
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 11/13

Double Balanced "Tayloe" Detector (by Dan Tayloe)



Sheet: /RF Processing/Mixer (Detector)/		
File: mixer.kicad_sch		
Title: Balanced quadrature sampling detector (QSD)		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 12/13

"Stockton bridge"
from (tr)uSDX RF board



Sheet: /RF Processing/Power SWR Bridge/
File: power_swr_bridge.kicad_sch

Title:

Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 13/13

Based on AE9RB Peaberry SDR V2 circuit



Sheet: /RF Processing/Power Amplifier/		
File: transmitter.kicad_sch		
Title: Transmitter, Power Amplifier		
Size: A4	Date:	**Rev:**
KiCad E.D.A. kicad 7.0.9+dfsg-1		Id: 14/13