Tier 1 Troubleshooting Procedure for Epic Client-Side Errors

Course-specific procedure

Production rule: Follow the health system's approved Epic, identity, endpoint, security, downtime, and escalation procedures. This course procedure does not grant configuration authority.

1 | Intake and Patient-Care Impact

- Capture the exact symptom/error text, time first observed, affected workflow, user role, device/workstation, and one-user vs. multi-user scope.
- If the issue blocks time-sensitive care, invoke the organization's clinical downtime or operational escalation path in parallel when required.
- Do not copy unnecessary patient information into learner notes or warm-transfer messages.

2 | Classify Before Acting

Stage	Tier 1 Checks	Stop/Escalate When
A | Client launch/session	Confirm scope; identify the configured authentication/client path; review available client/session/service-health evidence; perform only the authorized recovery action.	Repeated or multi-user failures; known service incident; security/risk signal; or failure after the single authorized recovery action.
B | Chart access	Confirm the client/session is functioning; compare organization-provided identity prerequisites and Epic-side access evidence separately.	Epic access/build/security configuration is missing or inconsistent; privileged change is required.
C | Print path	Confirm request generation; inspect Epic output-management/EPS evidence where supplied; then downstream Windows queue/printer where used.	Shared output service, EPS, multi-user impact, or no authorized local action.
D | Identity-related symptom	Verify requester per the organization procedure; inspect identity evidence available to the role.	Conditional Access/MFA/security remediation, account block/session revocation, or other privileged action is required.

3 | Resolution Test

- Re-test the exact clinician workflow that failed.
- Record the successful signal, not only the action performed.
- If unresolved, stop repeating the same action and create a warm-transfer summary with observed evidence and one requested next action.
- Route by the failed layer, not because the ticket contains the word Epic.

LC6 Case-Specific Decision Aid

Evidence	Interpretation for TH-2026-0907-01
Epic client launches; session authenticated	Client launch/session failure is not supported by this evidence.
Organization-specific Entra prerequisite present	Identity prerequisite is satisfied for this synthetic deployment; this does not prove Epic chart authorization.
Mock Epic access artifact shows expected chart-access assignment missing	Route to Epic application/analyst owner; do not modify Epic security/build at Tier 1.

Official Reference Anchors

- **HHS HIPAA Security Rule summary:** https://www.hhs.gov/hipaa/for-professionals/security/laws-regulations/index.html
- **Microsoft Entra group management:** https://learn.microsoft.com/en-us/entra/fundamentals/how-to-manage-groups

Epic-specific note: Epic customer build, security, client, and support procedures are organization-specific. The health system's approved Epic reference and Epic-provided customer documentation remain authoritative.