

**Audit Access Expires Mar 19, 2020**

You lose all access to this course, including your progress, on Mar 19, 2020.

Assessment Part 1: String Processing Part 3

In this part of the assessment, you will answer several multiple choice questions that review the concepts of string processing. You can answer these questions without using R, although you may find it helpful to experiment with commands in your console.

In the second part of the assessment on the next page, you will import a real dataset and use string processing to clean it for analysis. This will require you to write code in R.

Want even more practice with regular expressions? Complete the lessons and exercises in the [RegexOne](#) online interactive tutorial!

Question 1

0/1 point (graded)

```
s <- c("5'10", "6'1\"", "5'8inches", "5'7.5")
tab <- data.frame(x = s)
```

If you use the extract code from our video, the decimal point is dropped. What modification of the code would allow you to put the decimals in a third column called "decimal"?



```
extract(data = tab, col = x, into = c("feet", "inches", "decimal"),
regex = "\\d'\\d{1,2}\\d{0,1}?"
```



```
extract(data = tab, col = x, into = c("feet", "inches", "decimal"),
regex = "\\d'\\d{1,2}\\d{0,1}"
```



```
extract(data = tab, col = x, into = c("feet", "inches", "decimal"),
regex = "\\d'\\d{1,2}\\d{0,1}?"
```



```
extract(data = tab, col = x, into = c("feet", "inches", "decimal"),
regex = "\\d'\\d{1,2}\\d{0,1}?"
```



Answer

Incorrect:

Try again. This regex pattern would only extract feet, inches and decimals for strings that have a decimal point. You need an extra character to tell regex that the decimal is optional.

Submit

You have used 2 of 2 attempts

Answers are displayed within the problem

Question 2

0.5/1 point (graded)

You have the following data frame, `schedule` :

```
>schedule
  day      staff
Monday Mandy, Chris and Laura
Tuesday Steve, Ruth and Frank
```

You want to turn this into a more useful data frame.

Which two commands would properly split the text in the "staff" column into each individual name? Select ALL that apply.

☒ `str_split(schedule$staff, ",|and")`

☐ `str_split(schedule$staff, ", | and ")` ✓

☒ `str_split(schedule$staff, "\\s|\\sand\\s")` *

☐ `str_split(schedule$staff, "\\s?(,|and)\\s?")`



Answer

Incorrect:

Try again. This regex splits the string either at a comma or at an "and" - which splits Mandy into "M" and "y". This regex command is the same as the one above, except that the spaces are written as `\\s`, but it's not the only one.

Submit

You have used 2 of 2 attempts

i Answers are displayed within the problem

Question 3

1/1 point (graded)

You have the following data frame, `schedule` :

```
> schedule
  day      staff
Monday Mandy, Chris and Laura
Tuesday Steve, Ruth and Frank
```

What code would successfully turn your "Schedule" table into the following tidy table?

```
> tidy
  day      staff
<chr> <chr>
Monday Mandy
Monday Chris
Monday Laura
Tuesday Steve
Tuesday Ruth
Tuesday Frank
```



```
tidy <- schedule %>%  
  mutate(staff = str_split(staff, ", | and ")) %>%  
  unnest()
```



```
tidy <- separate(schedule, staff, into = c("s1", "s2", "s3"), sep = ",") %>%  
  gather(key = s, value = staff, s1:s3)
```



```
tidy <- schedule %>%  
  mutate(staff = str_split(staff, ", | and ", simplify = TRUE)) %>%  
  unnest()
```



Answer

Correct:

The mutate command creates a column "staff". Each row in the "staff" column is a character vector of length three, with the names of each staff member. We unnest this character vector using the unnest() function from tidyr.

Submit

You have used 2 of 2 attempts

i Answers are displayed within the problem

Question 4

0/1 point (graded)

Using the gapminder data, you want to recode countries longer than 12 letters in the region "Middle Africa" to their abbreviations in a new column, "country_short". Which code would accomplish this?



```
dat <- gapminder %>% filter(region == "Middle Africa") %>%
  mutate(recode(country,
    "Central African Republic" = "CAR",
    "Congo, Dem. Rep." = "DRC",
    "Equatorial Guinea" = "Eq. Guinea"))
```



```
dat <- gapminder %>% filter(region == "Middle Africa") %>%
  mutate(country_short = recode(country,
    c("Central African Republic", "Congo, Dem. Rep.", "Equatorial Guinea"),
    c("CAR", "DRC", "Eq. Guinea")))
```



```
dat <- gapminder %>% filter(region == "Middle Africa") %>%
  mutate(country = recode(country,
    "Central African Republic" = "CAR",
    "Congo, Dem. Rep." = "DRC",
    "Equatorial Guinea" = "Eq. Guinea"))
```



```
dat <- gapminder %>% filter(region == "Middle Africa") %>%
  mutate(country_short = recode(country,
    "Central African Republic" = "CAR",
    "Congo, Dem. Rep." = "DRC",
    "Equatorial Guinea" = "Eq. Guinea"))
```



Answer

Incorrect:

Try again. We want to create new column called "country_short", not overwrite our existing country column.

Submit

You have used 2 of 2 attempts

Answers are displayed within the problem