ARRANGE J10,J11 & J12
IN A JUMPER BLOCK
J12 J13 J14

JUMPER ONE
J11

FOR JUMPER J11 TAP YX
ADDRESS = BASE + 8*X

JUMPER BLOCK ABOVE SELECTS
ONE OF FOUR 64 I/O ADDRESS BLOCKS

```
     J12 J13 J14
A6   0   0---0
A7   0   0---0   =   0x00-0x3F

     J12 J13 J14
A6   0---0   0
A7   0   0---0   =   0x40-0x7F

     J12 J13 J14
A6   0   0---0
A7   0---0   0   =   0x80-0xBF

     J12 J13 J14
A6   0---0   0
A7   0---0   0   =   0xC0-0xFF
```

JUMPER ABOVE SELECTS ONE 8 ADDRESS
BLOCK FROM THE 64 SELECTED

THE 16550 UART USE ONE 8 ADDRESS BLOCK

JUMPER IF USING TYPE 1
UART INTERRUPTS
J16

J17 FTDI POWER INPUT

J10

FTDI HEADER

1.8432 MHz

MOUNTING HOLES

H1 H2 H3 H4 H5 H6

POWER

Sheet: /
File: RC2014Backplane-wUART.kicad_sch

Title: RC2014 BACKPLANE WITH 16550 UART

Size: B	Date: 2025-11-20	**Rev: 1**
KiCad E.D.A. 9.0.6		Id: 1/1