國立臺北科技大學
資訊工程系碩士班

碩士學位論文

# 基於沙盒系統之程式評測應用

# Online Judge System based on Sandbox System

研究生：黃漢軒

指導教授：郭忠義博士

中華民國一百一十二年七月

# 國立臺北科技大學

## 資訊工程系碩士班

## 碩士學位論文

# 基於沙盒系統之程式評測應用

# Online Judge System based on Sandbox System

研究生：黃漢軒

指導教授：郭忠義博士

中華民國一百一十二年七月

## 「學位論文口試委員會審定書」掃描檔

審定書填寫方式以系所規定為準，但檢附在電子論文內的掃描檔須具備以下條件：

1. 含指導教授、口試委員及系所主管的完整簽名。
2. 口試委員人數正確，碩士口試委員至少 3 人、博士口試委員至少 5 人。
3. 若此頁有論文題目，題目應和書背、封面、書名頁、摘要頁的題目相符。
4. 此頁有無浮水印皆可。

審定書不用頁碼

# 摘要

關鍵詞：(請自己填)

摘要為論文或報告的精簡概要, 其目的是透過簡短的敘述使讀者大致瞭解整篇報告的內容。摘要的內容通常須包括問題的描述以及所得到的結果, 但以不超過 500 字或一頁為原則, 且不得有參考文獻或引用圖表等。以中文撰寫之論文除中文摘要外，得於中文摘要後另附英文摘要。標題使用 20pt 粗標楷體並於上、下方各空一行（1.5 倍行高，字型 12pt 空行）後鍵入摘要內容。摘要頁須編頁碼（小寫羅馬數字表示頁碼)。

TAIPEI TECH

# ABSTRACT

Keyword: (Fill it)

Start writing abstract from here. Start writing abstract from here. Start writing abstract from here. Start writing abstract from here. Start writing abstract from here. Start writing abstract from here. Start writing abstract from here. Start writing abstract from here.

TAIPEI TECH

# 誌謝

所有對於研究提供協助之人或機構，作者都可在誌謝中表達感謝之意。

TAIPEI TECH

# 目錄


摘要 . . . . . i

ABSTRACT . . . . . ii

誌謝 . . . . . iii

目錄 . . . . . iv

圖目錄 . . . . . v

表目錄 . . . . . vi

第一章　緒論（大標） . . . . . 1

1.1　研究動機與背景（小標） . . . . . 1

1.1.1　研究背景 (小小標) . . . . . 1

第二章　若標題太長，則可以分成兩行排列的形式撰寫 . . . . . 5

2.1　名詞定義（小標） . . . . . 5

2.2　模型說明（小標） . . . . . 5

2.3　VMSH: Hypervisor-agnostic Guest Overlays for VMs . . . . . 6

2.3.1　System Architecture . . . . . 6

第三章　Experiment and Result . . . . . 8

3.1　Functional Validation and Generality . . . . . 8

3.1.1　PCI Device Discovery and Initialization . . . . . 8

3.1.2　Block I/O and Filesystem Validation . . . . . 8

3.1.3　Cloud Hypervisor Validation . . . . . 8

參考文獻 . . . . . 11


TAIPEI TECH

# 圖目錄


1.1 Cool train station . . . . . 2

1.2 “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” 2

1.3 Cool train station . . . . . 3

1.4 Cool train station . . . . . 4

2.1 Cool train station . . . . . 5

2.2 System architecture of vmsh. vmsh establishes devices in the guest through side-loading a kernel library. The block device supports the overlay root file system, and the console device handles the I/O of the spawned process. Numbers 1–4 correspond to the four-step workflow. (Adapted from [2]) . . . . . 6

3.1 dmesg log of PCI device discovery and BAR assignment (QEMU) . . . . . 8

3.2 dmesg log of VirtIO negotiation completion (QEMU) . . . . . 8

3.3 Guest userspace query of the vdb device . . . . . 8

3.4 Block I/O read/write and data integrity test (QEMU) . . . . . 9

3.5 ext4 filesystem mount test (QEMU) . . . . . 9

3.6 Data integrity test (Cloud Hypervisor) . . . . . 9

3.7 ext4 filesystem mount test (Cloud Hypervisor) . . . . . 10


TAIPEI TECH

# 表目錄

1.1 表格範例標題 . . . . . 1
1.2 表格範例標題 . . . . . 3

2.1 表格範例標題 . . . . . 5
2.2 Host machine specifications . . . . . 7

TAIPEI TECH

# 第一章　緒論（大標）

## 1.1　研究動機與背景（小標）

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a} \tag{1.1}$$

### 1.1.1　研究背景 (小小標)

背景內文背景內文背景內文背景內文, 背景內文背景內文背景內文背景內文背景內文背景內文，如表 1.1 所示。

表 1.1: 表格範例標題

| Protocol | $P$ | $CS_1$ | $CS_2$ | $RG$ |
|---|---|---|---|---|
| SD | $O(1), O(1)$, N/A | $O(n-t), O(1)$, N/A | $O(n-t), O(1)$, N/A | $O(1), O(n), O(n)$ |
| MSSMul | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |
| MSSAdd | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | N/A, N/A, N/A | $O(1), O(n), O(n)$ |
| SC | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |

#### 1.1.1.1　研究動機 (小小標)

$$(1+x)^n = 1 + \frac{nx}{1!} + \frac{n(n-1)x^2}{2!} \tag{1.2}$$

動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機。

動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機。動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機。動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，如圖 1.1、圖 1.2 所示。

動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機。




圖 1.1: Cool train station

圖 1.2: “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station” “Cool train station”

圖 1.3: Cool train station

表 1.2: 表格範例標題

| Protocol | $P$ | $CS_1$ | $CS_2$ | $RG$ |
|---|---|---|---|---|
| MSSMul | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |
| MSSAdd | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | N/A, N/A, N/A | $O(1), O(n), O(n)$ |
| SC | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |
| MSSMul | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |
| MSSAdd | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | N/A, N/A, N/A | $O(1), O(n), O(n)$ |
| SC | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |

動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機。

動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機。

動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。動機動機動機動機動機，動機動機動機動機動機動機動機動機動機動機動機動機動機動機，動機動機動機動機動機動機動機動機動機。



圖 1.4: Cool train station

# 第二章　若標題太長，則可以分成兩行排列的形式撰寫

## 2.1　名詞定義（小標）

定義定義定義定義定義定義 [1]，定義定義定義定義，定義定義定義定義定義定義定義定義定義定義，定義定義。

表 2.1: 表格範例標題

| Protocol | $P$ | $CS_1$ | $CS_2$ | $RG$ |
|---|---|---|---|---|
| MSSMul | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |
| SC | $O(1), O(1)$, N/A | $O(n-t), O(n), O(1)$ | $O(n-t), O(n)$, N/A | $O(1), O(n), O(n)$ |

## 2.2　模型說明（小標）

說明說明說明說明，說明說明說明說明說明說明說明說明說明說明說明說明說明說明，說明說明說明說明說明說明說明說明說明。

圖 2.1: Cool train station

## 2.3 VMSH: Hypervisor-agnostic Guest Overlays for VMs

### 2.3.1 System Architecture

As an independent host process, vmsh runs alongside the hypervisor on the same host machine. vmsh does not modify the hypervisor's source code, nor does it rely on any management API provided by the hypervisor. Instead, vmsh completes all operations externally through ptrace and the underlying KVM API. Figure 2.2 presents the system architecture of vmsh (adapted from [2] Figure 2), whose workflow can be divided into the following four steps:




圖 2.2: System architecture of vmsh. vmsh establishes devices in the guest through side-loading a kernel library. The block device supports the overlay root file system, and the console device handles the I/O of the spawned process. Numbers 1–4 correspond to the four-step workflow. (Adapted from [2])

All experiments in this study were conducted on the same physical host machine, whose

hardware and operating system specifications are listed in Table 2.2.

表 2.2: Host machine specifications

| Item | Specification |
|---|---|
| CPU | Intel Core i7-11700 @ 2.50GHz (8 cores, 16 threads) |
| Memory | 48 GB DDR4 |
| Storage | ADATA SX8200PNP 480GB NVMe SSD |
| OS | Ubuntu 22.04 LTS (kernel 5.15.0) |

TAIPEI TECH

# 第三章　Experiment and Result

## 3.1　Functional Validation and Generality

### 3.1.1　PCI Device Discovery and Initialization

```
[root@qemu-microvm:~]# dmesg | tail -25
[   47.007513] stage1: detected linux version 6.3.6
[   47.007514] stage1: using PCI transport (EXPERIMENTAL)
[   47.007514] stage1: [EXPERIMENTAL] triggering PCI bus rescan
[   47.009020] pci 0000:00:0a.0: [1af4:1042] type 00 class 0x010000
[   47.009710] pci 0000:00:0a.0: reg 0x10: [mem 0x00000000-0x00000fff]
[   47.010314] pci 0000:00:0a.0: reg 0x18: [mem 0x00000000-0x00000fff]
[   47.010921] pci 0000:00:0a.0: reg 0x20: [mem 0x00000000-0x00000fff]
[   47.011512] pci 0000:00:0a.0: reg 0x30: [mem 0x00000000-0x000007ff pref]
[   47.021659] resource: avoiding allocation from e820 entry [mem 0x0009fc00-0x000fffff]
[   47.021663] pci 0000:00:0a.0: BAR 0: assigned [mem 0x20000000-0x20000fff]
[   47.021777] resource: avoiding allocation from e820 entry [mem 0x0009fc00-0x000fffff]
[   47.021779] pci 0000:00:0a.0: BAR 2: assigned [mem 0x20001000-0x20001fff]
[   47.021897] resource: avoiding allocation from e820 entry [mem 0x0009fc00-0x000fffff]
[   47.021898] pci 0000:00:0a.0: BAR 4: assigned [mem 0x20002000-0x20002fff]
[   47.022007] resource: avoiding allocation from e820 entry [mem 0x0009fc00-0x000fffff]
[   47.022008] pci 0000:00:0a.0: BAR 6: assigned [mem 0x20003000-0x200037ff pref]
[   47.022869] virtio-pci 0000:00:0a.0: enabling device (0000 -> 0002)
```

圖 3.1: dmesg log of PCI device discovery and BAR assignment (QEMU)

```
[   47.052456] virtio_blk virtio2: [vdb] 131072 512-byte logical blocks (67.1 MB/64.0 MiB)
```

圖 3.2: dmesg log of VirtIO negotiation completion (QEMU)

```
[root@qemu-microvm:~]# ls /dev/vd*
/dev/vda  /dev/vdb

[root@qemu-microvm:~]# cat /sys/block/vdb/size
131072
```

圖 3.3: Guest userspace query of the vdb device

### 3.1.2　Block I/O and Filesystem Validation

### 3.1.3　Cloud Hypervisor Validation

```
[root@qemu-microvm:~]# dd if=/dev/vdb of=/dev/null bs=4k count=1
1+0 records in
1+0 records out
4096 bytes (4.1 kB, 4.0 KiB) copied, 0.00445993 s, 918 kB/s

[root@qemu-microvm:~]# dd if=/dev/zero of=/dev/vdb bs=4k count=1
1+0 records in
1+0 records out
4096 bytes (4.1 kB, 4.0 KiB) copied, 0.00578631 s, 708 kB/s

[root@qemu-microvm:~]# echo "VMSH_TEST_DATA" | dd of=/dev/vdb bs=512 count=1
0+1 records in
0+1 records out
15 bytes copied, 0.0124918 s, 1.2 kB/s

[root@qemu-microvm:~]# dd if=/dev/vdb bs=512 count=1 | head -c 20
1+0 records in
1+0 records out
VMSH_TEST_DATA
512 bytes copied, 0.00840111 s, 60.9 kB/s
```

圖 3.4: Block I/O read/write and data integrity test (QEMU)

```
[root@qemu-microvm:~]# lsblk
NAME
    MAJ:MIN RM   SIZE RO TYPE MOUNTPOINTS
fd0   2:0    1     4K  0 disk
sr0  11:0    1  1024M  0 rom
vda 254:0    0 267.5M  1 disk /nix/store
                               /
vdb 254:16   0    10M  0 disk

[root@qemu-microvm:~]# mkdir -p /tmp/mnt

[root@qemu-microvm:~]# mount /dev/vdb /tmp/mnt

[root@qemu-microvm:~]# ls /tmp/mnt
bin  dev  etc  lost+found  nix  proc  sys  tmp  var

[root@qemu-microvm:~]# umount /tmp/mnt
```

圖 3.5: ext4 filesystem mount test (QEMU)

```
[root@qemu-microvm:~]# echo "VMSH_CH_TEST_2026" | dd of=/dev/vdb bs=512 count=1
0+1 records in
0+1 records out
18 bytes copied, 0.00511157 s, 3.5 kB/s

[root@qemu-microvm:~]# dd if=/dev/vdb bs=512 count=1 | head -c 20
1+0 records in
1+0 records out
VMSH_CH_TEST_2026
512 bytes copied, 0.00541082 s, 94.6 kB/s
```

圖 3.6: Data integrity test (Cloud Hypervisor)

```
[root@qemu-microvm:~]# lsblk
NAME
    MAJ:MIN RM   SIZE RO TYPE MOUNTPOINTS
vda 254:0    0 267.5M  1 disk /nix/store
                              /
vdb 254:16   0    10M  0 disk

[root@qemu-microvm:~]# mkdir -p /tmp/mnt

[root@qemu-microvm:~]# mount /dev/vdb /tmp/mnt

[root@qemu-microvm:~]# ls /tmp/mnt
bin  dev  etc  lost+found  nix  proc  sys  tmp  var

[root@qemu-microvm:~]# umount /tmp/mnt

[root@qemu-microvm:~]# ls /tmp/mnt
```

圖 3.7: ext4 filesystem mount test (Cloud Hypervisor)

# 參考文獻


[1] Leslie Lamport. *LaTeX: a Document Preparation System*. 2nd ed. Massachusetts: Addison Wesley, 1994.

[2] Jörg Thalheim et al. “vmsh: Hypervisor-agnostic Guest Overlays for VMs”. In: *Proceedings of the Seventeenth European Conference on Computer Systems (EuroSys ’22)*. Rennes, France: ACM, 2022, pp. 678–693.


TAIPEI TECH