


Student News



Save lives. Be a better engineer.
The UNSW Engineering World Health Summer Institute in Cambodia and Uganda is happening in 2019.

Applications close Tuesday 31st July.
Apply now: <http://unsw.to/EWHAPP2019>

 engineeringworldhealth

 **Musculoskeletal Modelling in Physical Rehabilitation**

Lauren Kark (lauren.kark@unsw.edu.au)

Never Stand Still Faculty of Engineering Graduate School of Biomedical Engineering

Aims and Objectives

This lecture aims to:

- Introduce musculoskeletal modelling in physical rehabilitation

Following this lecture you should be able to:


- Describe the anatomy of the ankle
- Discuss the biomechanics of the ankle
- Describe the ways in which the ankle can be injured
- List current methods for preventing ankle injuries
- Develop design criteria for an optimal ankle brace
- Discuss how musculoskeletal modelling can be used to assess the efficacy of new designs of medical technology associated with human movement

does what it's meant to.



Graduate School of Biomedical Engineering

Introduction



Graduate School of Biomedical Engineering


Today

1. Anatomy
2. Injuries
3. Mechanics of Injuries
4. Prevention
5. Musculoskeletal modelling















Graduate School of Biomedical Engineering

Anatomy



Graduate School of Biomedical Engineering






Ankle Sprains (IV)

Mechanical Properties: Stress, Strain and Young's Modulus

$$F \Rightarrow \sigma = \frac{F}{A_0}$$

$$l \Rightarrow \epsilon = \frac{\Delta l}{l_0}$$


$$E = \frac{\sigma}{\epsilon} \quad \left\{ \begin{array}{l} \text{only in} \\ \text{linear} \\ \text{section} \end{array} \right.$$



Graduate School of Biomedical Engineering

Ankle Sprains (V)

Mechanical Properties: Stress-Strain Diagram




Graduate School of Biomedical Engineering

Example (I)

The ATFL has an original cross-sectional area of 10mm^2 and an original length of 15mm (made up numbers!). For each of the groups shown in the stress-strain diagram on the right, calculate:

- Young's modulus
- Length at yield 10MPa .



Control:

$$E = \frac{\sigma}{\epsilon} = \frac{25-5}{0.038-0.012} = 769\text{ MPa}$$

@ 10MPa : $\epsilon = 0.02 = \frac{\Delta l}{l_0} = \frac{\Delta l}{15}$

$$\Rightarrow \Delta l = (0.02)(15) = 0.3\text{mm}$$



$$l_f = l_0 + \Delta l = 15.3\text{mm}$$



Graduate School of Biomedical Engineering

Example (II)




Graduate School of Biomedical Engineering

Viscoelasticity



Graduate School of Biomedical Engineering

Break (~2mins)



Graduate School of Biomedical Engineering

Ankle Sprains (IV)

Risk Factors

- Previous or existing ankle injury (biggest factor)
- Lack of strength and stability in the ankle
- Lack of, or extreme, flexibility in the ankle
- Poor balance
- Acceleration or deceleration (sudden change in direction)
- Increasing age

http://sma.org.au/wp-content/uploads/2011/01/719-SMA-InjuryBrochure-ankle_web.pdf



Graduate School of Biomedical Engineering

Ankle Sprains (V)

Prevention

- Balance training
- Ankle strengthening
- Flexibility
- Adequate preparation
- Taping and bracing



Graduate School of Biomedical Engineering

Taping and Braces

Taping		Braces	
Pros	Cons	Pros	Cons
Customisable	Cost	Reusable	
Less bulky	Qualified person	Cost	
Proprioception	Lost effectiveness*	Easy to apply	
		ROM restriction	
		Better prevention	

* Taping support declines by 40 – 50% within 5 – 20 minutes of activity (Paris et al., 1995)



Graduate School of Biomedical Engineering

Ankle Braces (I)

Types



http://www.braceup.com/ankle_01.htm



Graduate School of Biomedical Engineering

Ankle Braces (II)

Design Requirements for Hinged Braces

ENGINEERING FUNCTIONAL AESTHETIC




Graduate School of Biomedical Engineering

Musculoskeletal Modelling (I)




Graduate School of Biomedical Engineering

Musculoskeletal Modelling (II)



Musculoskeletal Modelling (III)

Ankle Inversion Angle




Musculoskeletal Modelling (IV)



Musculoskeletal Modelling (V)

Comparison of Inversion Angles



Musculoskeletal Modelling (VI)

- Your job in the tutorial this week is to design the optimal ankle brace!
- Two types of braces: passive and active (challenge)
- Minimum passive design requirements:
 - Prevent ankle injury (inversion angle < 25°)
 - Minimal stiffness, for maximal comfort
- Minimum active design requirements:
 - As for passive, but also:
 - Smallest torque required for smallest motor
 - Minimal active time for maximal battery life
- Don't forget to include any other design criteria you think important.

Good luck! Have fun!



Thank you!

Questions?

Never Stand Still

Faculty of Engineering

Graduate School of Biomedical Engineering